



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

SPECfp®_rate2006 = 39.7

NovaScale B280 (Intel Xeon processor 5150,2.66GHz)

SPECfp_rate_base2006 = 39.1

CPU2006 license: 20


Test date: Dec-2006

Test sponsor: Bull SAS

Hardware Availability: Jan-2007

Tested by: Bull SAS

Software Availability: Dec-2006



Hardware

CPU Name: Intel Xeon 5150
CPU Characteristics: 2.66 GHz, 4MB L2, 1333MHz bus
CPU MHz: 2660
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
CPU(s) orderable: 1 to 2 chips
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 4 MB I+D on chip per chip

Software

Operating System: Windows Server 2003 Enterprise Edition (32 bits)
Service Pack1
Compiler: Intel C++ Compiler for IA32 version 9.1
Package ID W_CC_C_9.1.033 Build no 20061103Z
Intel Fortran Compiler for IA32 version 9.1
Package ID W_FC_C_9.1.033 Build no 20061103Z
Microsoft Visual Studio .NET 2003 (lib & linker)
Auto Parallel: No
File System: NTFS
System State: Default

Continued on next page

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

SPECfp_rate2006 = 39.7

NovaScale B280 (Intel Xeon processor 5150,2.66GHz)

SPECfp_rate_base2006 = 39.1

CPU2006 license: 20

Test date: Dec-2006

Test sponsor: Bull SAS

Hardware Availability: Jan-2007

Tested by: Bull SAS

Software Availability: Dec-2006

L3 Cache:	None	Base Pointers:	32-bit
Other Cache:	None	Peak Pointers:	32-bit
Memory:	8 GB (1GB DIMMx8, FB-DIMM PC2-5300F ECC CL5)	Other Software:	MicroQuill SmartHeap Library 8.0 (shlw32M.lib)
Disk Subsystem:	73 GB SAS, 10000RPM		
Other Hardware:	None		

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	4	1648	33.0	1651	32.9	1656	32.8	4	1665	32.6	1656	32.8	1657	32.8
416.gamess	4	1247	62.8	1246	62.8	1247	62.8	4	1251	62.6	1251	62.6	1251	62.6
433.milc	4	1809	20.3	1813	20.3	1812	20.3	4	1813	20.3	1812	20.3	1813	20.3
434.zeusmp	4	817	44.5	818	44.5	817	44.6	4	854	42.6	873	41.7	849	42.9
435.gromacs	4	471	60.6	470	60.8	470	60.7	4	467	61.1	467	61.1	467	61.2
436.cactusADM	4	965	49.5	969	49.3	969	49.3	4	979	48.8	980	48.8	980	48.8
437.leslie3d	4	1577	23.8	1577	23.8	1577	23.8	4	1576	23.9	1587	23.7	1579	23.8
444.namd	4	595	53.9	594	54.0	594	54.0	4	586	54.7	585	54.8	585	54.8
447.dealII	4	722	63.4	728	62.9	748	61.2	4	688	66.5	685	66.8	668	68.5
450.soplex	4	1303	25.6	1217	27.4	1217	27.4	4	1281	26.0	1202	27.7	1201	27.8
453.povray	4	281	75.7	281	75.8	281	75.8	4	222	96.0	221	96.2	221	96.2
454.calculix	4	712	46.3	696	47.4	715	46.1	4	693	47.6	692	47.7	684	48.2
459.GemsFDTD	4	1948	21.8	1958	21.7	1950	21.8	4	1956	21.7	1973	21.5	1970	21.5
465.tonto	4	1083	36.3	1084	36.3	1109	35.5	4	1088	36.2	1091	36.1	1088	36.2
470.lbm	4	2775	19.8	2797	19.7	2798	19.6	4	2778	19.8	2803	19.6	2802	19.6
481.wrf	4	1086	41.1	1080	41.4	1082	41.3	4	1099	40.6	1096	40.8	1095	40.8
482.sphinx3	4	1881	41.5	1870	41.7	1878	41.5	4	1922	40.6	1911	40.8	1920	40.6

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Base Compiler Invocation

C benchmarks:

 icl -Qvc7.1 -Qc99

C++ benchmarks:

 icl -Qvc7.1

Fortran benchmarks:

 ifort

Benchmarks using both Fortran and C:

 icl -Qvc7.1 -Qc99 ifort



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale B280 (Intel Xeon processor 5150,2.66GHz)

SPECfp_rate2006 = 39.7

SPECfp_rate_base2006 = 39.1

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Dec-2006

Hardware Availability: Jan-2007

Software Availability: Dec-2006

Base Portability Flags

```
436.cactusADM: -Qlowercase /assume:underscore  
444.namd: -TP  
447.dealII: -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG  
             -DBOOST_NO_INTRINSIC_WCHAR_T  
453.povray: -DSPEC_CPU_WINDOWS_ICL  
454.calculix: -DSPEC_CPU_NOZMODIFIER -Qlowercase  
481.wrf: -DSPEC_CPU_WINDOWS_ICL
```

Base Optimization Flags

C benchmarks:

```
-fast /F9500000000 shlw32m.lib           -link /FORCE:MULTIPLE
```

C++ benchmarks:

```
-fast -Qcxx_features /F9500000000 shlw32m.lib  
      -link /FORCE:MULTIPLE
```

Fortran benchmarks:

```
-fast /F9500000000           -link /FORCE:MULTIPLE
```

Benchmarks using both Fortran and C:

```
-fast /F9500000000           -link /FORCE:MULTIPLE
```

Peak Compiler Invocation

C benchmarks:

```
icl -Qvc7.1 -Qc99
```

C++ benchmarks:

```
icl -Qvc7.1
```

Fortran benchmarks:

```
ifort
```

Benchmarks using both Fortran and C:

```
icl -Qvc7.1 -Qc99 ifort
```

Peak Portability Flags

```
436.cactusADM: -Qlowercase /assume:underscore  
444.namd: -TP  
447.dealII: -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG  
             -DBOOST_NO_INTRINSIC_WCHAR_T
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale B280 (Intel Xeon processor 5150,2.66GHz)

SPECfp_rate2006 = 39.7

SPECfp_rate_base2006 = 39.1

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Dec-2006

Hardware Availability: Jan-2007

Software Availability: Dec-2006

Peak Portability Flags (Continued)

453.povray: -DSPEC_CPU_WINDOWS_ICL
454.calculix: -DSPEC_CPU_NOZMODIFIER -Qlowercase
481.wrf: -DSPEC_CPU_WINDOWS_ICL

Peak Optimization Flags

C benchmarks:

```
-Qprof_gen(pass 1) -Qprof_use(pass 2) -fast /F9500000000 shlw32m.lib  
-link /FORCE:MULTIPLE
```

C++ benchmarks:

```
-Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qcxx_features  
/F9500000000 shlw32m.lib -link /FORCE:MULTIPLE
```

Fortran benchmarks:

```
-Qprof_gen(pass 1) -Qprof_use(pass 2) -fast /F9500000000  
-link /FORCE:MULTIPLE
```

Benchmarks using both Fortran and C:

```
-Qprof_gen(pass 1) -Qprof_use(pass 2) -fast /F9500000000  
-link /FORCE:MULTIPLE
```

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/flags.20090715.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/flags.20090715.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.

Report generated on Tue Jul 22 10:51:51 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 21 February 2007.