



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale B280 (Intel Xeon processor E5320,1.86GHz)

SPECfp®_rate2006 = 41.7

SPECfp_rate_base2006 = 40.9

CPU2006 license: 20


Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Feb-2007

Hardware Availability: Jan-2007

Software Availability: Dec-2006



Hardware

CPU Name: Intel Xeon E5320
 CPU Characteristics: 1.86 GHz, 8MB L2, 1066MHz bus
 CPU MHz: 1860
 FPU: Integrated
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
 CPU(s) orderable: 1 to 2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 8 MB I+D on chip per chip, 4 MB shared / 2 cores

Continued on next page

Software

Operating System: Windows Server 2003 Enterprise Edition (32 bits) Service Pack1
 Compiler: Intel C++ Compiler for IA32 version 9.1 Package ID W_CC_C_9.1.033 Build no 20061103Z
 Intel Fortran Compiler for IA32 version 9.1 Package ID W_FC_C_9.1.033 Build no 20061103Z
 Microsoft Visual Studio .NET 2003 (lib & linker)
 Auto Parallel: No
 File System: NTFS
 System State: Default

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale B280 (Intel Xeon processor E5320,1.86GHz)

SPECfp_rate2006 = 41.7

SPECfp_rate_base2006 = 40.9

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Feb-2007

Hardware Availability: Jan-2007

Software Availability: Dec-2006

L3 Cache: None
Other Cache: None
Memory: 8 GB (1GB DIMMx8, FB-DIMM PC2-5300F ECC CL5)
Disk Subsystem: 73 GB SAS, 10000RPM
Other Hardware: None

Base Pointers: 32-bit
Peak Pointers: 32-bit
Other Software: MicroQuill SmartHeap Library 8.0 (shIW32M.lib)

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	8	4319	25.2	4312	25.2	4317	25.2	8	4329	25.1	4319	25.2	4319	25.2
416.gamess	8	1784	87.8	1785	87.8	1785	87.7	8	1789	87.6	1789	87.5	1788	87.6
433.milc	8	4945	14.9	4943	14.9	4953	14.8	8	4956	14.8	4941	14.9	4950	14.8
434.zeusmp	8	1475	49.4	1488	48.9	1479	49.2	8	1504	48.4	1500	48.5	1509	48.3
435.gromacs	8	675	84.6	675	84.6	675	84.7	8	670	85.2	670	85.3	670	85.2
436.cactusADM	8	1748	54.7	1748	54.7	1752	54.6	8	1758	54.4	1753	54.5	1755	54.5
437.leslie3d	8	4050	18.6	4048	18.6	4052	18.6	8	4048	18.6	4052	18.6	4051	18.6
444.namd	8	854	75.2	853	75.2	854	75.2	8	841	76.3	840	76.4	841	76.3
447.dealII	8	1118	81.9	1110	82.5	1083	84.5	8	1012	90.4	1015	90.2	1028	89.0
450.soplex	8	3023	22.1	3025	22.1	3031	22.0	8	2978	22.4	2965	22.5	2969	22.5
453.povray	8	403	106	402	106	403	106	8	317	134	317	134	317	134
454.calculix	8	1004	65.8	1003	65.8	1003	65.8	8	989	66.8	1005	65.7	997	66.2
459.GemsFDTD	8	5146	16.5	5143	16.5	5150	16.5	8	5153	16.5	5164	16.4	5162	16.4
465.tonto	8	1819	43.3	1771	44.5	1809	43.5	8	1827	43.1	1821	43.2	1791	44.0
470.lbm	8	5414	20.3	5411	20.3	5405	20.3	8	5409	20.3	5403	20.3	5410	20.3
481.wrf	8	2482	36.0	2471	36.2	2495	35.8	8	2490	35.9	2492	35.9	2474	36.1
482.sphinx3	8	4264	36.6	4253	36.7	4275	36.5	8	4429	35.2	4414	35.3	4423	35.3

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Base Compiler Invocation

C benchmarks:

icl -Qvc7.1 -Qc99

C++ benchmarks:

icl -Qvc7.1

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icl -Qvc7.1 -Qc99 ifort



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale B280 (Intel Xeon processor E5320,1.86GHz)

SPECfp_rate2006 = 41.7

SPECfp_rate_base2006 = 40.9

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: Feb-2007
Hardware Availability: Jan-2007
Software Availability: Dec-2006

Base Portability Flags

436.cactusADM: -Qlowercase /assume:underscore
444.namd: -TP
447.dealII: -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG
-DBOOST_NO_INTRINSIC_WCHAR_T
453.povray: -DSPEC_CPU_WINDOWS_ICL
454.calculix: -DSPEC_CPU_NOZMODIFIER -Qlowercase
481.wrf: -DSPEC_CPU_WINDOWS_ICL

Base Optimization Flags

C benchmarks:
-fast /F950000000 shlw32m.lib -link /FORCE:MULTIPLE

C++ benchmarks:
-fast -Qcxx_features /F950000000 shlw32m.lib
-link /FORCE:MULTIPLE

Fortran benchmarks:
-fast /F950000000 -link /FORCE:MULTIPLE

Benchmarks using both Fortran and C:
-fast /F950000000 -link /FORCE:MULTIPLE

Peak Compiler Invocation

C benchmarks:
icl -Qvc7.1 -Qc99

C++ benchmarks:
icl -Qvc7.1

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icl -Qvc7.1 -Qc99 ifort

Peak Portability Flags

436.cactusADM: -Qlowercase /assume:underscore
444.namd: -TP
447.dealII: -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG
-DBOOST_NO_INTRINSIC_WCHAR_T

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale B280 (Intel Xeon processor E5320,1.86GHz)

SPECfp_rate2006 = 41.7

SPECfp_rate_base2006 = 40.9

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: Feb-2007
Hardware Availability: Jan-2007
Software Availability: Dec-2006

Peak Portability Flags (Continued)

453.povray: -DSPEC_CPU_WINDOWS_ICL
454.calculix: -DSPEC_CPU_NOZMODIFIER -Qlowercase
481.wrf: -DSPEC_CPU_WINDOWS_ICL

Peak Optimization Flags

C benchmarks:

-Qprof_gen(pass 1) -Qprof_use(pass 2) -fast /F950000000 shlw32m.lib
-link /FORCE:MULTIPLE

C++ benchmarks:

-Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qcxx_features
/F950000000 shlw32m.lib -link /FORCE:MULTIPLE

Fortran benchmarks:

-Qprof_gen(pass 1) -Qprof_use(pass 2) -fast /F950000000
-link /FORCE:MULTIPLE

Benchmarks using both Fortran and C:

-Qprof_gen(pass 1) -Qprof_use(pass 2) -fast /F950000000
-link /FORCE:MULTIPLE

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/flags.20090714.00.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/flags.20090714.00.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 10:39:40 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 6 March 2007.