



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Dell Inc.

PowerEdge 2950 (Intel Xeon processor E5310, 1.60 GHz)

SPECfp®\_rate2006 = Not Run

SPECfp\_rate\_base2006 = 41.8

CPU2006 license: 55


Test sponsor: Dell Inc.

Tested by: Dell Inc.

Test date: Mar-2007

Hardware Availability: Dec-2006

Software Availability: Nov-2006



### Hardware

CPU Name: Intel Xeon E5310  
 CPU Characteristics: 1066 MHz Bus Speed  
 CPU MHz: 1600  
 FPU: Integrated  
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip  
 CPU(s) orderable: 1,2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 8 MB I+D on chip per chip, 4 MB shared / 2 cores

Continued on next page

### Software

Operating System: SuSE Linux Enterprise Server 10 EM64T kernel 2.6.16.21-0.8-smp  
 Compiler: Intel C++ Compiler for Intel EM64T-based applications, Version 9.1  
 Package ID l\_cc\_c\_9.1.045 Build no 20061101  
 Intel Fortran Compiler for Intel EM64T-based applications, Version 9.1  
 Package ID l\_fc\_c\_9.1.040 Build no 20061101  
 Auto Parallel: No

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Dell Inc.

PowerEdge 2950 (Intel Xeon processor E5310, 1.60 GHz)

SPECfp\_rate2006 = Not Run

SPECfp\_rate\_base2006 = 41.8

CPU2006 license: 55

Test sponsor: Dell Inc.

Tested by: Dell Inc.

Test date: Mar-2007

Hardware Availability: Dec-2006

Software Availability: Nov-2006

L3 Cache: None  
Other Cache: None  
Memory: 16 GB (8 x 2 GB 667MHz CL5 DDR2 FB-DIMM SDRAM)  
Disk Subsystem: 1 x 73 GB SAS 15k RPM  
Other Hardware: None

File System: ext2  
System State: Multi-user run level 3  
Base Pointers: 64-bit  
Peak Pointers: Not Applicable  
Other Software: None

## Results Table

Benchmark	Base								Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio		
410.bwaves	8	4299	25.3	4298	25.3	<u>4299</u>	<u>25.3</u>									
416.gamess	8	1788	87.6	1790	87.5	<u>1789</u>	<u>87.6</u>									
433.milc	8	3050	24.1	3051	24.1	<u>3050</u>	<u>24.1</u>									
434.zeusmp	8	<u>1609</u>	<u>45.2</u>	1619	45.0	1605	45.3									
435.gromacs	8	771	74.1	776	73.6	<u>771</u>	<u>74.1</u>									
436.cactusADM	8	1844	51.8	1841	51.9	<u>1843</u>	<u>51.9</u>									
437.leslie3d	8	4027	18.7	<u>4034</u>	<u>18.6</u>	4049	18.6									
444.namd	8	<u>961</u>	<u>66.8</u>	960	66.8	961	66.8									
447.dealII	8	<u>1073</u>	<u>85.3</u>	1074	85.2	1061	86.2									
450.soplex	8	2620	25.5	<u>2621</u>	<u>25.5</u>	2626	25.4									
453.povray	8	470	90.5	<u>474</u>	<u>89.7</u>	474	89.7									
454.calculix	8	1061	62.2	<u>1056</u>	<u>62.5</u>	1055	62.6									
459.GemsFDTD	8	4506	18.8	<u>4507</u>	<u>18.8</u>	4507	18.8									
465.tonto	8	1517	51.9	<u>1522</u>	<u>51.7</u>	1525	51.6									
470.lbm	8	5727	19.2	5729	19.2	<u>5728</u>	<u>19.2</u>									
481.wrf	8	<u>2548</u>	<u>35.1</u>	2555	35.0	2548	35.1									
482.sphinx3	8	4033	38.7	4029	38.7	<u>4030</u>	<u>38.7</u>									

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Platform Notes

Hardware Prefetcher disabled in BIOS  
Adjacent Cache Line Prefetch disabled in BIOS  
"ulimit -s unlimited" set

## Base Compiler Invocation

C benchmarks:  
icc

C++ benchmarks:  
icpc

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Dell Inc.**

PowerEdge 2950 (Intel Xeon processor E5310, 1.60 GHz)

**SPECfp\_rate2006 = Not Run**

**SPECfp\_rate\_base2006 = 41.8**

**CPU2006 license:** 55

**Test sponsor:** Dell Inc.

**Tested by:** Dell Inc.

**Test date:** Mar-2007

**Hardware Availability:** Dec-2006

**Software Availability:** Nov-2006

## Base Compiler Invocation (Continued)

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

## Base Portability Flags

```

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

```

## Base Optimization Flags

C benchmarks:

-fast

C++ benchmarks:

-fast

Fortran benchmarks:

-fast

Benchmarks using both Fortran and C:

-fast

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/dell-ic91-flags.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/dell-ic91-flags.xml>



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Dell Inc.**

PowerEdge 2950 (Intel Xeon processor E5310, 1.60 GHz)

**SPECfp\_rate2006 = Not Run**

**SPECfp\_rate\_base2006 = 41.8**

**CPU2006 license:** 55

**Test sponsor:** Dell Inc.

**Tested by:** Dell Inc.

**Test date:** Mar-2007

**Hardware Availability:** Dec-2006

**Software Availability:** Nov-2006

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.  
Report generated on Tue Jul 22 11:56:17 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 17 April 2007.