



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY BX620 S3, Intel Xeon processor 5130, 2.0 GHz

SPECfp®_rate2006 = 37.2

SPECfp_rate_base2006 = 36.1

CPU2006 license: 22


Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Apr-2007

Hardware Availability: Jul-2006

Software Availability: Feb-2007



Hardware

CPU Name: Intel Xeon 5130
 CPU Characteristics: 1333 MHz system bus
 CPU MHz: 2000
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1,2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 4 MB I+D on chip per chip

Continued on next page

Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 10, Kernel 2.6.16.21-0.8-smp on an x86_64
 Compiler: Intel C++ Compiler for IA32/EM64T application, Version 9.1 - Build 20070215, Package-ID: l_cc_p_9.1.047
 Intel Fortran Compiler for IA32/EM64T application, Version 9.1 - Build 20070215, Package ID: l_fc_p_9.1.043
 Auto Parallel: No
 File System: ext2

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY BX620 S3, Intel Xeon processor 5130, 2.0 GHz

SPECfp_rate2006 = 37.2

SPECfp_rate_base2006 = 36.1

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Apr-2007

Hardware Availability: Jul-2006

Software Availability: Feb-2007

L3 Cache: None
Other Cache: None
Memory: 8 GB (8x1 GB DDR2 PC2-5300F, 2 rank, CAS 5-5-5, with ECC)
Disk Subsystem: SAS (36GB 10000 rpm)
Other Hardware: None

System State: Multiuser, Runlevel 3
Base Pointers: 64-bit
Peak Pointers: 32/64-bit
Other Software: None

Results Table

Benchmark	Base								Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio		
410.bwaves	4	1680	32.4	1673	32.5	1674	32.5	4	1680	32.4	1673	32.5	1674	32.5		
416.gamess	4	1435	54.6	1435	54.6	1437	54.5	4	1435	54.6	1435	54.6	1437	54.5		
433.milc	4	1710	21.5	1709	21.5	1708	21.5	4	1791	20.5	1791	20.5	1791	20.5		
434.zeusmp	4	930	39.1	925	39.3	946	38.5	4	934	39.0	934	39.0	931	39.1		
435.gromacs	4	588	48.5	589	48.5	593	48.2	4	574	49.7	574	49.8	573	49.8		
436.cactusADM	4	1032	46.3	1033	46.3	1038	46.0	4	1032	46.3	1033	46.3	1038	46.0		
437.leslie3d	4	1631	23.1	1624	23.1	1631	23.1	4	1631	23.1	1624	23.1	1631	23.1		
444.namd	4	765	41.9	765	41.9	766	41.9	4	765	41.9	765	41.9	766	41.9		
447.dealII	4	735	62.2	702	65.2	708	64.6	4	684	66.9	697	65.7	686	66.7		
450.soplex	4	1248	26.7	1246	26.8	1251	26.7	4	1163	28.7	1167	28.6	1161	28.7		
453.povray	4	389	54.7	388	54.8	388	54.8	4	295	72.1	311	68.4	295	72.2		
454.calculix	4	791	41.7	783	42.1	791	41.7	4	774	42.6	773	42.7	774	42.7		
459.GemsFDTD	4	1987	21.4	2004	21.2	2005	21.2	4	1987	21.4	2004	21.2	2005	21.2		
465.tonto	4	991	39.7	988	39.8	999	39.4	4	958	41.1	960	41.0	959	41.0		
470.lbm	4	2929	18.8	2932	18.7	2930	18.8	4	2760	19.9	2760	19.9	2759	19.9		
481.wrf	4	1137	39.3	1135	39.4	1135	39.4	4	1137	39.3	1135	39.4	1135	39.4		
482.sphinx3	4	2080	37.5	2086	37.4	2081	37.5	4	1939	40.2	1952	39.9	1936	40.3		

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
'/usr/bin/taskset' used to bind processes to CPUs

General Notes

The system bus runs at 1333 MHz

All binaries were built with 64-bit Intel compiler except:
433.milc, 434.zeusmp, 450.soplex, 470.lbm and 482.sphinx3 in peak were built with 32-bit Intel compiler by changing the path for include and library files.

For information about Fujitsu Siemens Computers in your country please see:

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY BX620 S3, Intel Xeon processor 5130, 2.0 GHz

SPECfp_rate2006 = 37.2

SPECfp_rate_base2006 = 36.1

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Apr-2007

Hardware Availability: Jul-2006

Software Availability: Feb-2007

General Notes (Continued)

<http://www.fujitsu-siemens.com/countries>

Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

Base Portability Flags

```

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

```

Base Optimization Flags

C benchmarks:

-fast

C++ benchmarks:

-fast

Fortran benchmarks:

-fast

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY BX620 S3, Intel Xeon processor 5130, 2.0 GHz

SPECfp_rate2006 = 37.2

SPECfp_rate_base2006 = 36.1

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Apr-2007

Hardware Availability: Jul-2006

Software Availability: Feb-2007

Base Optimization Flags (Continued)

Benchmarks using both Fortran and C:

-fast

Peak Compiler Invocation

C benchmarks:

```
/opt/intel/cc/9.1.047/bin/icc -I/opt/intel/cc/9.1.047/include
-L/opt/intel/cc/9.1.047/lib
```

C++ benchmarks (except as noted below):

icpc

```
450.soplex: /opt/intel/cc/9.1.047/bin/icpc
-I/opt/intel/cc/9.1.047/include -L/opt/intel/cc/9.1.047/lib
```

Fortran benchmarks (except as noted below):

ifort

```
434.zeusmp: /opt/intel/fc/9.1.043/bin/ifort
-I/opt/intel/fc/9.1.043/include -L/opt/intel/fc/9.1.043/lib
```

Benchmarks using both Fortran and C:

icc ifort

Peak Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
```

Peak Optimization Flags

C benchmarks:

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY BX620 S3, Intel Xeon processor 5130, 2.0 GHz

SPECfp_rate2006 = 37.2

SPECfp_rate_base2006 = 36.1

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Apr-2007

Hardware Availability: Jul-2006

Software Availability: Feb-2007

Peak Optimization Flags (Continued)

433.milc: -prof_gen(pass 1) -prof_use(pass 2) -fast

470.lbm: Same as 433.milc

482.sphinx3: -fast

C++ benchmarks:

444.namd: basepeak = yes

447.dealII: -prof_gen(pass 1) -prof_use(pass 2) -fast

450.soplex: Same as 447.dealII

453.povray: Same as 447.dealII

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: basepeak = yes

434.zeusmp: -fast

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

465.tonto: -prof_gen(pass 1) -prof_use(pass 2) -fast

Benchmarks using both Fortran and C:

435.gromacs: -prof_gen(pass 1) -prof_use(pass 2) -fast

436.cactusADM: basepeak = yes

454.calculix: Same as 435.gromacs

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at

http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.09.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.09.xml



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY BX620 S3, Intel Xeon processor 5130, 2.0 GHz

SPECfp_rate2006 = 37.2

SPECfp_rate_base2006 = 36.1

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Apr-2007

Hardware Availability: Jul-2006

Software Availability: Feb-2007

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 12:13:46 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 15 May 2007.