



SPEC[®] CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale 3045
(1.6GHz/18MB Dual-Core Intel Itanium 2)

SPECfp[®]_rate2006 = 82.2

SPECfp_rate_base2006 = 80.8

CPU2006 license: 20


Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Apr-2007

Hardware Availability: Oct-2006

Software Availability: Nov-2006



Hardware

CPU Name: Dual-Core Intel Itanium 2 9040
 CPU Characteristics: 1.6GHz/18MB, 533MHz FSB
 CPU MHz: 1600
 FPU: Integrated
 CPU(s) enabled: 8 cores, 4 chips, 2 cores/chip
 CPU(s) orderable: 1-4 chips
 Primary Cache: 16 KB I + 16 KB D on chip per core
 Secondary Cache: 1 MB I + 256 KB D on chip per core

Continued on next page

Software

Operating System: Red Hat Enterprise Linux AS release 4 (Update 4)
 Compiler: Intel C++ Compiler 9.1 for Linux (Build 20061105)
 Intel Fortran Compiler 9.1 for Linux (Build 20061105)
 Auto Parallel: No
 File System: ext3
 System State: Multi-user

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale 3045
(1.6GHz/18MB Dual-Core Intel Itanium 2)

SPECfp_rate2006 = 82.2

SPECfp_rate_base2006 = 80.8

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Apr-2007

Hardware Availability: Oct-2006

Software Availability: Nov-2006

L3 Cache: 9 MB I+D on chip per core
Other Cache: None
Memory: 64 GB (32x2GB DIMMs)
Disk Subsystem: 2x73 GB 15K RPM SAS
Other Hardware: None

Base Pointers: 64-bit
Peak Pointers: 64-bit
Other Software: None

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	8	1692	64.3	1694	64.2	1714	63.4	8	1692	64.3	1694	64.2	1714	63.4
416.gamess	8	2125	73.7	2125	73.7	2124	73.7	8	2054	76.2	2054	76.3	2055	76.2
433.milc	8	2022	36.3	2012	36.5	1958	37.5	8	1920	38.2	1906	38.5	1899	38.7
434.zeusmp	8	927	78.5	932	78.1	927	78.5	8	927	78.5	932	78.1	927	78.5
435.gromacs	8	539	106	539	106	539	106	8	510	112	511	112	513	111
436.cactusADM	8	524	183	532	180	529	181	8	524	183	532	180	529	181
437.leslie3d	8	1401	53.7	1401	53.7	1406	53.5	8	1401	53.7	1401	53.7	1406	53.5
444.namd	8	352	183	352	182	351	183	8	311	206	311	206	311	206
447.dealII	8	971	94.3	968	94.5	966	94.7	8	962	95.1	962	95.1	961	95.2
450.soplex	8	1410	47.3	1409	47.4	1429	46.7	8	1393	47.9	1401	47.6	1403	47.5
453.povray	8	571	74.5	570	74.7	573	74.3	8	508	83.8	508	83.8	508	83.8
454.calculix	8	582	113	582	113	580	114	8	568	116	570	116	570	116
459.GemsFDTD	8	1935	43.9	1930	44.0	1932	43.9	8	1935	43.9	1930	44.0	1932	43.9
465.tonto	8	936	84.1	932	84.4	931	84.6	8	936	84.1	932	84.4	931	84.6
470.lbm	8	1682	65.4	1774	62.0	1699	64.7	8	1737	63.3	1727	63.6	1695	64.8
481.wrf	8	1101	81.1	1088	82.1	1100	81.2	8	1101	81.1	1088	82.1	1100	81.2
482.sphinx3	8	1168	133	1085	144	1089	143	8	1133	138	1346	116	1224	127

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

stacksize set to unlimited prior to run

Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale 3045
(1.6GHz/18MB Dual-Core Intel Itanium 2)

SPECfp_rate2006 = 82.2

SPECfp_rate_base2006 = 80.8

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: Apr-2007
Hardware Availability: Oct-2006
Software Availability: Nov-2006

Base Compiler Invocation (Continued)

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX -DSPEC_CPU_CASE_FLAG
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:
-fast -IPF_fp_relaxed -ansi-alias
C++ benchmarks:
-fast -IPF_fp_relaxed -ansi-alias
Fortran benchmarks:
-fast -IPF_fp_relaxed
Benchmarks using both Fortran and C:
-fast -IPF_fp_relaxed -ansi-alias

Peak Compiler Invocation

C benchmarks:
icc

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale 3045
(1.6GHz/18MB Dual-Core Intel Itanium 2)

SPECfp_rate2006 = 82.2

SPECfp_rate_base2006 = 80.8

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: Apr-2007
Hardware Availability: Oct-2006
Software Availability: Nov-2006

Peak Compiler Invocation (Continued)

C++ benchmarks:
icpc

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

433.milc: -fast -IPF_fp_relaxed -ansi-alias -fno-alias

470.lbm: -prof_gen(pass 1) -prof_use(pass 2) -fast -IPF_fp_relaxed
-ansi-alias

482.sphinx3: Same as 470.lbm

C++ benchmarks:

444.namd: -prof_gen(pass 1) -prof_use(pass 2) -fast -IPF_fp_relaxed
-no-prefetch -fno-alias

447.dealII: -fast -IPF_fp_relaxed -ansi-alias -no-alias-args

450.soplex: -fast -IPF_fp_relaxed -ansi-alias -inline-factor=150

453.povray: -prof_gen(pass 1) -prof_use(pass 2) -fast -IPF_fp_relaxed
-ansi-alias

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -fast -IPF_fp_relaxed -inline-factor=150

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale 3045
(1.6GHz/18MB Dual-Core Intel Itanium 2)

SPECfp_rate2006 = 82.2

SPECfp_rate_base2006 = 80.8

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: Apr-2007
Hardware Availability: Oct-2006
Software Availability: Nov-2006

Peak Optimization Flags (Continued)

459.GemsFDTD: basepeak = yes

465.tonto: basepeak = yes

Benchmarks using both Fortran and C:

435.gromacs: -prof_gen(pass 1) -prof_use(pass 2) -fast -IPF_fp_relaxed
-fno-alias -inline-factor=150

436.cactusADM: basepeak = yes

454.calculix: -fast -IPF_fp_relaxed -fno-alias

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at

http://www.spec.org/cpu2006/flags/IA64_Intel91_flags.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/cpu2006/flags/IA64_Intel91_flags.xml

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 12:14:22 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 15 May 2007.