



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/120Ri-2
(Intel Xeon processor 5140)

SPECint_rate2006 = 51.6

SPECint_rate_base2006 = 48.3

CPU2006 license: 9006


Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Jun-2007

Hardware Availability: May-2007

Software Availability: Jun-2007



Hardware

CPU Name: Intel Xeon 5140
CPU Characteristics: 2.33 GHz, 4MB L2, 1333MHz bus
CPU MHz: 2333
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
CPU(s) orderable: 1,2 chips
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 4 MB I+D on chip per chip
L3 Cache: None
Other Cache: None
Memory: 8 GB (4x2 GB DDR2 5300F, 2 rank, CL5-5-5, ECC)
Disk Subsystem: 1x73.2 GB SAS, 15000RPM
Other Hardware: None

Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 10, Kernel 2.6.16.21-0.8-smp for x86_64
Compiler: Intel C++ Compiler for IA32/EM64T application, Version 10.0 - Build 20070426 Package ID: l_cc_p_10.0.023
Auto Parallel: No
File System: ext2
System State: Multiuser, Runlevel 3
Base Pointers: 32-bit
Peak Pointers: 32/64-bit
Other Software: MicroQuill SmartHeap library 8.1 binutils-2.17.tar.gz, Version 2.17



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/120Ri-2
(Intel Xeon processor 5140)

SPECint_rate2006 = 51.6

SPECint_rate_base2006 = 48.3

CPU2006 license: 9006

Test date: Jun-2007

Test sponsor: NEC Corporation

Hardware Availability: May-2007

Tested by: NEC Corporation

Software Availability: Jun-2007

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	647	60.4	647	60.4	647	60.4	4	543	71.9	541	72.2	544	71.9
401.bzip2	4	1033	37.4	1026	37.6	1031	37.4	4	983	39.3	988	39.1	994	38.8
403.gcc	4	760	42.4	756	42.6	758	42.5	4	760	42.4	756	42.6	758	42.5
429.mcf	4	828	44.1	828	44.1	829	44.0	4	852	42.8	853	42.7	851	42.9
445.gobmk	4	699	60.0	699	60.0	698	60.1	4	640	65.5	639	65.7	639	65.7
456.hammer	4	768	48.6	767	48.6	767	48.6	4	605	61.7	603	61.8	605	61.7
458.sjeng	4	901	53.7	902	53.7	905	53.5	4	805	60.1	810	59.7	808	59.9
462.libquantum	4	2028	40.9	2021	41.0	2026	40.9	4	1991	41.6	1989	41.7	1991	41.6
464.h264ref	4	944	93.7	944	93.8	944	93.7	4	896	98.8	895	98.9	894	99.0
471.omnetpp	4	840	29.8	840	29.8	840	29.7	4	816	30.7	816	30.6	817	30.6
473.astar	4	792	35.5	792	35.4	793	35.4	4	740	37.9	740	37.9	741	37.9
483.xalancbmk	4	460	60.0	459	60.1	460	60.0	4	460	60.0	459	60.1	460	60.0

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
'/usr/bin/taskset' used to bind processes to CPUs

General Notes

All benchmarks compiled in 32-bit mode except 401.bzip2 and 456.hammer,
for peak, are compiled in 64-bit mode

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32

462.libquantum: -DSPEC_CPU_LINUX

483.xalancbmk: -DSPEC_CPU_LINUX



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/120Ri-2
(Intel Xeon processor 5140)

SPECint_rate2006 = 51.6

SPECint_rate_base2006 = 48.3

CPU2006 license: 9006

Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Jun-2007

Hardware Availability: May-2007

Software Availability: Jun-2007

Base Optimization Flags

C benchmarks:
-fast

C++ benchmarks:
-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs
-L/opt/SmartHeap_8.1/lib -lsmartheap

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):

icc

401.bzip2: /opt/intel/cce/10.0.023/bin/icc

456.hmmr: /opt/intel/cce/10.0.023/bin/icc

C++ benchmarks:

icpc

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
401.bzip2: -DSPEC_CPU_LP64
456.hmmr: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -fast -ansi-alias
-prefetch

401.bzip2: -L/opt/intel/cce/10.0.023/lib -I/opt/intel/cce/10.0.023/include
-prof-gen(pass 1) -prof-use(pass 2) -fast

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/120Ri-2
(Intel Xeon processor 5140)

SPECint_rate2006 = 51.6

SPECint_rate_base2006 = 48.3

CPU2006 license: 9006

Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Jun-2007

Hardware Availability: May-2007

Software Availability: Jun-2007

Peak Optimization Flags (Continued)

403.gcc: basepeak = yes

429.mcf: -fast -prefetch

445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xT -O2 -ipo
-no-prec_div -ansi-alias

456.hmmr: -L/opt/intel/cce/10.0.023/lib -I/opt/intel/cce/10.0.023/include
-prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-ansi-alias

458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4

462.libquantum: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -Obo
-prefetch -opt-streaming-stores always

464.h264ref: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-ansi-alias

C++ benchmarks:

471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo
-no-prec_div -ansi-alias -Wl,-z,muldefs
-L/opt/SmartHeap_8.1/lib -lsmartheap

473.astar: Same as 471.omnetpp

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/NEC-ic10-linux-flags.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/NEC-ic10-linux-flags.xml>



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/120Ri-2
(Intel Xeon processor 5140)

SPECint_rate2006 = 51.6

SPECint_rate_base2006 = 48.3

CPU2006 license: 9006

Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Jun-2007

Hardware Availability: May-2007

Software Availability: Jun-2007

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.

Report generated on Tue Jul 22 13:22:45 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 24 July 2007.