



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUS Computer International

(Test Sponsor: Intel Corporation)

SPECfp®_rate2006 = 28.4

ASUS P5K3 motherboard (Intel Core 2 Duo E6750)

SPECfp_rate_base2006 = 27.7

CPU2006 license: 13


Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Jul-2007

Hardware Availability: Jul-2007

Software Availability: Aug-2006



Hardware

CPU Name: Intel Core 2 Duo E6750
CPU Characteristics: 2.66 GHz, 1333 MHz bus
CPU MHz: 2666
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1 chip
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 4 MB I+D on chip per chip

Software

Operating System: Windows Vista32 Ultimate
Compiler: Intel C++ Compiler for IA32 version 10.0
Build 20070426 Package ID: W_CC_P_10.0.025
Intel Fortran Compiler for IA32 version 10.0
Build 20070426 Package ID: W_FC_P_10.0.025
Microsoft Visual Studio .Net 2003 (for libraries)
Auto Parallel: No
File System: NTFS
System State: Default

Continued on next page

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUS Computer International

(Test Sponsor: Intel Corporation)

SPECfp_rate2006 = 28.4

ASUS P5K3 motherboard (Intel Core 2 Duo E6750)

SPECfp_rate_base2006 = 27.7

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Jul-2007

Hardware Availability: Jul-2007

Software Availability: Aug-2006

L3 Cache:	None	Base Pointers:	32-bit
Other Cache:	None	Peak Pointers:	32-bit
Memory:	2 GB (2x1GB ELPIDA PC3-8500U-7-00-BP DDR3-1066 7-7-7-20)	Other Software:	SmartHeap Library Version 8.0 from http://www.microquill.com/
Disk Subsystem:	Seagate ST320620AS 320GB Barracuda 7200.10 NCQ SATA II		
Other Hardware:	None		

Results Table

Benchmark	Base								Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	2	869	31.3	866	31.4	866	31.4	2	866	31.4	866	31.4	866	31.4		
416.gamess	2	1357	28.9	1358	28.8	1357	28.9	2	1342	29.2	1342	29.2	1342	29.2		
433.milc	2	926	19.8	926	19.8	926	19.8	2	918	20.0	917	20.0	917	20.0		
434.zeusmp	2	599	30.4	598	30.5	599	30.4	2	565	32.2	563	32.3	563	32.3		
435.gromacs	2	466	30.6	467	30.6	466	30.6	2	457	31.2	457	31.2	458	31.2		
436.cactusADM	2	686	34.9	685	34.9	686	34.8	2	686	34.9	685	34.9	686	34.8		
437.leslie3d	2	869	21.6	868	21.7	867	21.7	2	867	21.7	866	21.7	865	21.7		
444.namd	2	581	27.6	582	27.6	581	27.6	2	580	27.7	580	27.7	580	27.7		
447.dealII	2	635	36.1	634	36.1	634	36.1	2	571	40.1	571	40.1	572	40.0		
450.soplex	2	700	23.8	699	23.9	700	23.8	2	705	23.7	706	23.6	704	23.7		
453.povray	2	279	38.1	279	38.1	279	38.2	2	218	48.8	218	48.9	217	48.9		
454.calculix	2	682	24.2	683	24.2	683	24.1	2	685	24.1	682	24.2	685	24.1		
459.GemsFDTD	2	1113	19.1	1112	19.1	1112	19.1	2	1113	19.1	1112	19.1	1112	19.1		
465.tonto	2	719	27.4	718	27.4	718	27.4	2	706	27.9	705	27.9	709	27.8		
470.lbm	2	1433	19.2	1432	19.2	1432	19.2	2	1454	18.9	1453	18.9	1453	18.9		
481.wrf	2	684	32.7	684	32.7	683	32.7	2	683	32.7	683	32.7	685	32.6		
482.sphinx3	2	1088	35.8	1093	35.7	1089	35.8	2	1076	36.2	1080	36.1	1078	36.2		

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

Tested systems can be used with Shin-G ATX case, Antec NeoPower 480W power supply
Product description located as of 7/2007:

<http://usa.asus.com/products.aspx?l1=3&l2=11&l3=534&l4=0&model=1645&modelmenu=1>

The system bus runs at 1333 MHz

System has a discrete gfx card - Asus EN8800GTX/HTDP/768M w/ nVidia 8800GTX

Binaries were built on Windows XP Professional SP2 with 4GB of RAM and /3GB boot switch
The start command with the /affinity switch was used to bind processes to cores



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUS Computer International
(Test Sponsor: Intel Corporation)

SPECfp_rate2006 = 28.4

ASUS P5K3 motherboard (Intel Core 2 Duo E6750)

SPECfp_rate_base2006 = 27.7

CPU2006 license: 13

Test date: Jul-2007

Test sponsor: Intel Corporation

Hardware Availability: Jul-2007

Tested by: Intel Corporation

Software Availability: Aug-2006

Base Compiler Invocation

C benchmarks:

```
icl -Qvc7.1 -Qc99
```

C++ benchmarks:

```
icl -Qvc7.1
```

Fortran benchmarks:

```
ifort
```

Benchmarks using both Fortran and C:

```
icl -Qvc7.1 -Qc99 ifort
```

Base Portability Flags

436.cactusADM: -Qlowercase /assume:underscore

444.namd: -TP

447.dealII: -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG
-DBOOST_NO_INTRINSIC_WCHAR_T

453.povray: -DSPEC_CPU_WINDOWS_ICL

454.calculix: -DSPEC_CPU_NOZMODIFIER -Qlowercase

481.wrf: -DSPEC_CPU_WINDOWS_ICL

Base Optimization Flags

C benchmarks:

```
-fast /F9500000000 shlw32m.lib -link /FORCE:MULTIPLE
```

C++ benchmarks:

```
-fast -Qcxx_features /F9500000000 shlw32m.lib  
-link /FORCE:MULTIPLE
```

Fortran benchmarks:

```
-fast /F9500000000
```

Benchmarks using both Fortran and C:

```
-fast /F9500000000
```

Peak Compiler Invocation

C benchmarks:

```
icl -Qvc7.1 -Qc99
```

C++ benchmarks:

```
icl -Qvc7.1
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUS Computer International

(Test Sponsor: Intel Corporation)

SPECfp_rate2006 = 28.4

ASUS P5K3 motherboard (Intel Core 2 Duo E6750)

SPECfp_rate_base2006 = 27.7

CPU2006 license: 13

Test date: Jul-2007

Test sponsor: Intel Corporation

Hardware Availability: Jul-2007

Tested by: Intel Corporation

Software Availability: Aug-2006

Peak Compiler Invocation (Continued)

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icl -Qvc7.1 -Qc99 ifort

Peak Portability Flags

```
436.cactusADM: -Qlowercase /assume:underscore
 444.namd: -TP
 447.dealII: -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG
             -DBOOST_NO_INTRINSIC_WCHAR_T
 453.povray: -DSPEC_CPU_WINDOWS_ICL
 454.calculix: -DSPEC_CPU_NOZMODIFIER -Qlowercase
 481.wrf: -DSPEC_CPU_WINDOWS_ICL
```

Peak Optimization Flags

C benchmarks:

```
433.milc: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qunroll2 -Oa
           /F95000000000 shlw32m.lib           -link /FORCE:MULTIPLE
 470.lbm: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qunroll2
          -Qscalar-rep- -Qprefetch /F95000000000 shlw32m.lib
          -link /FORCE:MULTIPLE
 482.sphinx3: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qunroll2
              /F95000000000 shlw32m.lib           -link /FORCE:MULTIPLE
```

C++ benchmarks:

```
444.namd: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Oa
           -Qcxx_features /F95000000000 shlw32m.lib
           -link /FORCE:MULTIPLE
 447.dealII: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qprefetch
             -Qcxx_features /F95000000000 shlw32m.lib
             -link /FORCE:MULTIPLE
 450.soplex: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qcxx_features
              /F95000000000 shlw32m.lib           -link /FORCE:MULTIPLE
 453.povray: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qansi-alias
              -Qcxx_features /F95000000000 shlw32m.lib
              -link /FORCE:MULTIPLE
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUS Computer International

(Test Sponsor: Intel Corporation)

SPECfp_rate2006 = 28.4

ASUS P5K3 motherboard (Intel Core 2 Duo E6750)

SPECfp_rate_base2006 = 27.7

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Jul-2007

Hardware Availability: Jul-2007

Software Availability: Aug-2006

Peak Optimization Flags (Continued)

Fortran benchmarks:

410.bwaves: -fast /F950000000

416.gamess: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qunroll12 -Ob0
-Qansi-alias -Qscalar-rep- /F950000000

434.zeusmp: -Qprof_gen(pass 1) -Qprof_use(pass 2) -QxT -O2 -Qprec_div-
-Qunroll10 -Qscalar-rep- /F950000000

437.leslie3d: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast /F950000000

459.GemsFDTD: basepeak = yes

465.tonto: Same as 437.leslie3d

Benchmarks using both Fortran and C:

435.gromacs: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Oa
/F950000000

436.cactusADM: basepeak = yes

454.calculix: -fast /F950000000

481.wrf: Same as 454.calculix

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.42.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.42.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.

Report generated on Tue Jul 22 12:55:07 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 8 August 2007.