



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**HITACHI**

BladeSymphony BS1000 (Intel Xeon X5355)


**SPECint\_rate2006 = 86.4**

CPU2006 license: 872

Test date: Jul-2007

Hardware Availability: Jan-2007

Software Availability: Jun-2007



**SPECint\_rate\_base2006 = 83.5**

**SPECint\_rate2006 = 86.4**

## Hardware

CPU Name: Intel Xeon X5355  
CPU Characteristics: 1333 MHz system bus  
CPU MHz: 2666  
FPU: Integrated  
CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip  
CPU(s) orderable: 1, 2 chips  
Primary Cache: 32 KB I + 32 KB D on chip per core  
Secondary Cache: 8 MB I+D on chip per chip, 4 MB shared / 2 cores  
L3 Cache: None  
Other Cache: None  
Memory: 16 GB(8 x 2 GB PC2-5300F CAS 5-5-5)  
Disk Subsystem: 2 x 73 GB 10000rpm SAS  
Other Hardware: None

## Software

Operating System: Microsoft Windows Server 2003 R2, Enterprise x64 Edition  
Compiler: Intel C++ Compiler for IA32 version 10.0 Build 20070426  
Auto Parallel: Microsoft Visual Studio .Net 2003 (for libraries)  
File System: No  
System State: NTFS  
Base Pointers: Default  
Peak Pointers: 32-bit  
Other Software: 32-bit  
SmartHeap Library, Version 8.0



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

HITACHI

SPECint rate2006 = 86.4

## BladeSymphony BS1000 (Intel Xeon X5355)

SPECint\_rate\_base2006 = 83.5

CPU2006 license: 872

**Test date:** Jul-2007

**Test sponsor:** HITACHI

### **Hardware Availability:** Jan-2007

**Tested by:** HITACHI

### **Software Availability:** Jun-2007

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	8	664	118	548	143	<b>548</b>	<b>143</b>	8	<b>483</b>	<b>162</b>	484	162	481	162
401.bzip2	8	1009	76.5	<b>1012</b>	<b>76.3</b>	1013	76.2	8	982	78.6	<b>986</b>	<b>78.3</b>	987	78.2
403.gcc	8	<b>2015</b>	<b>32.0</b>	2036	31.6	1958	32.9	8	<b>1949</b>	<b>33.0</b>	1948	33.1	2006	32.1
429.mcf	8	1166	62.6	<b>1164</b>	<b>62.7</b>	1163	62.7	8	1166	62.6	<b>1164</b>	<b>62.7</b>	1163	62.7
445.gobmk	8	<b>627</b>	<b>134</b>	627	134	626	134	8	<b>573</b>	147	<b>573</b>	<b>146</b>	576	146
456.hammer	8	675	111	675	111	<b>675</b>	<b>111</b>	8	669	112	<b>670</b>	<b>111</b>	670	111
458.sjeng	8	<b>792</b>	<b>122</b>	792	122	791	122	8	<b>723</b>	134	724	134	<b>723</b>	<b>134</b>
462.libquantum	8	3442	48.2	3448	48.1	<b>3445</b>	<b>48.1</b>	8	3442	48.2	3448	48.1	<b>3445</b>	<b>48.1</b>
464.h264ref	8	835	212	836	212	<b>835</b>	<b>212</b>	8	818	216	816	217	<b>817</b>	<b>217</b>
471.omnetpp	8	1093	45.7	1103	45.3	<b>1103</b>	<b>45.3</b>	8	<b>1082</b>	<b>46.2</b>	1073	46.6	1083	46.2
473.astar	8	<b>868</b>	<b>64.7</b>	866	64.9	868	64.7	8	<b>868</b>	<b>64.7</b>	866	64.9	868	64.7
483.xalancbmk	8	571	96.7	<b>571</b>	<b>96.8</b>	570	96.8	8	<b>571</b>	96.7	<b>571</b>	<b>96.8</b>	570	96.8

Results appear in the order in which they were run. **Bold underlined** text indicates a median measurement.

## Base Compiler Invocation

C benchmarks:  
  icl -Qvc7.1 -Qc9

## C++ benchmarks:

## Base Portability Flags

403.gcc: -DSPEC\_CPU\_WIN32  
464.h264ref: -DSPEC\_CPU\_NO\_INTTYPES -DWIN32

## Base Optimization Flags

C benchmarks:  
-fast /F512000000 shlw32m.lib

-link /FORCE:MULTIPLE

```
C++ benchmarks:  
    -fast -Qcxx_features /F512000000 shlw32m.lib  
          -link /FORCE:MULTIPLE
```



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

HITACHI

BladeSymphony BS1000 (Intel Xeon X5355)

**SPECint\_rate2006 = 86.4**

CPU2006 license: 872

Test sponsor: HITACHI

Tested by: HITACHI

Test date: Jul-2007

Hardware Availability: Jan-2007

Software Availability: Jun-2007

## Base Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

## Peak Compiler Invocation

C benchmarks:

icl -Qvc7.1 -Qc99

C++ benchmarks:

icl -Qvc7.1

## Peak Portability Flags

403.gcc: -DSPEC\_CPU\_WIN32

464.h264ref: -DSPEC\_CPU\_NO\_INTTYPES -DWIN32

## Peak Optimization Flags

C benchmarks:

400.perlbench: ONESTEP -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -fast  
/F512000000 shlw32m.lib -link /FORCE:MULTIPLE

401.bzip2: Same as 400.perlbench

403.gcc: Same as 400.perlbench

429.mcf: basepeak = yes

445.gobmk: -Qprof\_gen(pass 1) -Qprof\_use(pass 2) -fast /F512000000  
shlw32m.lib -link /FORCE:MULTIPLE

456.hmmer: Same as 400.perlbench

458.sjeng: Same as 400.perlbench

462.libquantum: basepeak = yes

464.h264ref: Same as 400.perlbench

C++ benchmarks:

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

HITACHI

BladeSymphony BS1000 (Intel Xeon X5355)

**SPECint\_rate2006 = 86.4**

CPU2006 license: 872

Test sponsor: HITACHI

Tested by: HITACHI

Test date: Jul-2007

Hardware Availability: Jan-2007

Software Availability: Jun-2007

## Peak Optimization Flags (Continued)

```
471.omnetpp: ONESTEP -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast  
-Qcxx_features /F512000000 shlw32m.lib  
-link /FORCE:MULTIPLE
```

```
473.astar: basepeak = yes
```

```
483.xalancbmk: basepeak = yes
```

## Peak Other Flags

C benchmarks:

```
403.gcc: -Dalloca=_alloca
```

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/ic100.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/ic100.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.1.

Report generated on Tue Jul 22 12:25:53 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 21 August 2007.