



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

ProLiant DL580 G4  
(3.2 GHz, Intel Xeon processor 7130M)

**SPECint\_rate2006 = 23.6**

**SPECint\_rate\_base2006 = 21.9**

CPU2006 license: 3


Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

Test date: Jul-2007

Hardware Availability: Aug-2006

Software Availability: May-2007



### Hardware

CPU Name: Intel Xeon 7130M  
CPU Characteristics: 3.2 GHz, 800 MHz system bus  
CPU MHz: 3200  
FPU: Integrated  
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip, 2 threads/core  
CPU(s) orderable: 1,2,4 chips  
Primary Cache: 12 K micro-ops I + 16 KB D on chip per core  
Secondary Cache: 1 MB I+D on chip per core  
L3 Cache: 8 MB I+D on chip per chip  
Other Cache: None  
Memory: 32 GB (16x2 GB PC2-3200R)  
Disk Subsystem: 1x72 GB 15 K SAS  
Other Hardware: None

### Software

Operating System: SuSE Linux Enterprise Server 10 (x86\_64)  
Compiler: Intel C++ Compiler for IA32/EM64T applications, Version 10.0 Build 20070426 Package ID: l\_cc\_p\_10.0.023  
Auto Parallel: No  
File System: ext2  
System State: Multi-user run level 3  
Base Pointers: 32-bit  
Peak Pointers: 32/64-bit  
Other Software: MicroQuill SmartHeap 8.1 libraries



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

ProLiant DL580 G4  
(3.2 GHz, Intel Xeon processor 7130M)

**SPECint\_rate2006 = 23.6**

**SPECint\_rate\_base2006 = 21.9**

CPU2006 license: 3

Test date: Jul-2007

Test sponsor: Hewlett-Packard Company

Hardware Availability: Aug-2006

Tested by: Hewlett-Packard Company

Software Availability: May-2007

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	1739	22.5	1789	21.8	<b>1741</b>	<b>22.4</b>	4	1527	25.6	<b>1536</b>	<b>25.4</b>	1563	25.0
401.bzip2	4	2050	18.8	<b>2059</b>	<b>18.7</b>	2071	18.6	4	1925	20.1	1911	20.2	<b>1915</b>	<b>20.2</b>
403.gcc	4	1343	24.0	<b>1345</b>	<b>23.9</b>	1351	23.8	4	1343	24.0	<b>1345</b>	<b>23.9</b>	1351	23.8
429.mcf	4	1467	24.9	<b>1468</b>	<b>24.9</b>	1470	24.8	4	1463	24.9	1459	25.0	<b>1463</b>	<b>24.9</b>
445.gobmk	4	2052	20.4	<b>2096</b>	<b>20.0</b>	2116	19.8	4	<b>1901</b>	<b>22.1</b>	1902	22.1	1855	22.6
456.hammer	4	2266	16.5	<b>2266</b>	<b>16.5</b>	2262	16.5	4	<b>1656</b>	<b>22.5</b>	1655	22.6	1658	22.5
458.sjeng	4	<b>2947</b>	<b>16.4</b>	3002	16.1	2946	16.4	4	<b>2622</b>	<b>18.5</b>	2687	18.0	2605	18.6
462.libquantum	4	3037	27.3	3020	27.4	<b>3021</b>	<b>27.4</b>	4	3023	27.4	<b>3022</b>	<b>27.4</b>	3022	27.4
464.h264ref	4	<b>2282</b>	<b>38.8</b>	2286	38.7	2280	38.8	4	<b>2144</b>	<b>41.3</b>	2143	41.3	2146	41.3
471.omnetpp	4	<b>1645</b>	<b>15.2</b>	1643	15.2	1658	15.1	4	<b>1514</b>	<b>16.5</b>	1514	16.5	1514	16.5
473.astar	4	1420	19.8	<b>1420</b>	<b>19.8</b>	1418	19.8	4	<b>1376</b>	<b>20.4</b>	1376	20.4	1382	20.3
483.xalancbmk	4	<b>1006</b>	<b>27.4</b>	1007	27.4	1006	27.4	4	<b>1006</b>	<b>27.4</b>	1007	27.4	1006	27.4

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run

## Platform Notes

BIOS configuration:  
Power Regulator Disabled  
Adjacent Sector Prefetch Enabled  
Hardware Prefetcher Enabled  
Hyper-Threading Technology Enabled

## Base Compiler Invocation

C benchmarks:  
icc

C++ benchmarks:  
icpc

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32

462.libquantum: -DSPEC\_CPU\_LINUX

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

ProLiant DL580 G4  
(3.2 GHz, Intel Xeon processor 7130M)

**SPECint\_rate2006 = 23.6**

**SPECint\_rate\_base2006 = 21.9**

CPU2006 license: 3

Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

Test date: Jul-2007

Hardware Availability: Aug-2006

Software Availability: May-2007

## Base Portability Flags (Continued)

483.xalancbmk: -DSPEC\_CPU\_LINUX

## Base Optimization Flags

C benchmarks:

-xP -ipo -O3 -static -no-prec-div

C++ benchmarks:

-xP -ipo -O3 -no-prec-div -Wl,-z,muldefs  
-L/cpu2006.1.0/SmartHeap\_8.1/lib -lsmartheap

## Base Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

## Peak Compiler Invocation

C benchmarks (except as noted below):

icc

401.bzip2: /opt/intel/cce/10.0.023/bin/icc  
-L/opt/intel/cce/10.0.023/lib  
-I/opt/intel/cce/10.0.023/include

456.hmmr: /opt/intel/cce/10.0.023/bin/icc  
-L/opt/intel/cce/10.0.023/lib  
-I/opt/intel/cce/10.0.023/include

C++ benchmarks:

icpc

## Peak Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32

401.bzip2: -DSPEC\_CPU\_LP64

456.hmmr: -DSPEC\_CPU\_LP64

462.libquantum: -DSPEC\_CPU\_LINUX

483.xalancbmk: -DSPEC\_CPU\_LINUX



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

ProLiant DL580 G4  
(3.2 GHz, Intel Xeon processor 7130M)

**SPECint\_rate2006 = 23.6**

**SPECint\_rate\_base2006 = 21.9**

**CPU2006 license:** 3

**Test sponsor:** Hewlett-Packard Company

**Tested by:** Hewlett-Packard Company

**Test date:** Jul-2007

**Hardware Availability:** Aug-2006

**Software Availability:** May-2007

## Peak Optimization Flags

C benchmarks:

400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -xP -ipo -O3  
-no-prec-div -ansi-alias -prefetch

401.bzip2: -prof-gen(pass 1) -prof-use(pass 2) -xP -ipo -O3  
-no-prec-div

403.gcc: basepeak = yes

429.mcf: -xP -ipo -O3 -static -no-prec-div -prefetch  
-L/cpu2006.1.0/SmartHeap\_8.1/lib -lsmartheap

445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xP -O2 -ipo  
-no-prec\_div -ansi-alias

456.hmmr: -prof-gen(pass 1) -prof-use(pass 2) -xP -ipo -O3 -static  
-no-prec-div -unroll2 -ansi-alias

458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -xP -ipo -O3 -static  
-no-prec-div -unroll4

462.libquantum: Same as 458.sjeng

464.h264ref: Same as 456.hmmr

C++ benchmarks:

471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xP -O3 -ipo  
-no-prec\_div -ansi-alias -Wl,-z,muldefs  
-L/cpu2006.1.0/SmartHeap\_8.1/lib -lsmartheap

473.astar: Same as 471.omnetpp

483.xalancbmk: basepeak = yes

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

The flags file that was used to format this result can be browsed at  
<http://www.spec.org/cpu2006/flags/hp-ic10-flags.20090714.03.html>

You can also download the XML flags source by saving the following link:  
<http://www.spec.org/cpu2006/flags/hp-ic10-flags.20090714.03.xml>



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

ProLiant DL580 G4  
(3.2 GHz, Intel Xeon processor 7130M)

**SPECint\_rate2006 = 23.6**

**SPECint\_rate\_base2006 = 21.9**

**CPU2006 license:** 3

**Test date:** Jul-2007

**Test sponsor:** Hewlett-Packard Company

**Hardware Availability:** Aug-2006

**Tested by:** Hewlett-Packard Company

**Software Availability:** May-2007

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.

Report generated on Tue Jul 22 12:24:49 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 21 August 2007.