



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant BL465c
(3.0GHz AMD Opteron 2222)

SPECfp®2006 = 15.1

SPECfp_base2006 = 14.8

CPU2006 license: 3


Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

Test date: Aug-2007

Hardware Availability: Sep-2007

Software Availability: Oct-2007



SPECfp_base2006 = 14.8

SPECfp2006 = 15.1

Hardware

CPU Name: AMD Opteron 2222
CPU Characteristics:
CPU MHz: 3000
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1,2 chips
Primary Cache: 64 KB I + 64 KB D on chip per core
Secondary Cache: 1 MB I+D on chip per core

Software

Operating System: SuSE Linux Enterprise Server 10 (x86_64) SP1
Compiler: kernel 2.6.16.46-0.12-smp
The Portland Group (PGI)
PGI pgf90 7.1-0 Fortran Compiler
File System: PGI pgcc 7.1-0 C Compiler
System State: PGI pgCC 7.1-0 C++ Compiler
Auto Parallel: No
File System: ext2
System State: Multi-user, run level 3

Continued on next page

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant BL465c
(3.0GHz AMD Opteron 2222)

SPECfp2006 = 15.1

SPECfp_base2006 = 14.8

CPU2006 license: 3

Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

Test date: Aug-2007

L3 Cache: None
Other Cache: None
Memory: 16 GB (4x4 GB, PC2-5300P CL5)
Disk Subsystem: 1x72 GB 10 K SAS
Other Hardware: None

Base Pointers: 64-bit
Peak Pointers: 64-bit
Other Software: none

Hardware Availability: Sep-2007
Software Availability: Oct-2007

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	663	20.5	664	20.5	664	20.5	637	21.4	636	21.4	636	21.4
416.gamess	1225	16.0	1228	15.9	1226	16.0	1206	16.2	1211	16.2	1207	16.2
433.milc	692	13.3	679	13.5	669	13.7	644	14.3	645	14.2	646	14.2
434.zeusmp	659	13.8	660	13.8	660	13.8	659	13.8	660	13.8	660	13.8
435.gromacs	549	13.0	548	13.0	548	13.0	454	15.7	455	15.7	455	15.7
436.cactusADM	906	13.2	908	13.2	907	13.2	906	13.2	908	13.2	907	13.2
437.leslie3d	718	13.1	717	13.1	719	13.1	718	13.1	717	13.1	719	13.1
444.namd	562	14.3	560	14.3	560	14.3	556	14.4	554	14.5	553	14.5
447.dealII	733	15.6	733	15.6	731	15.6	733	15.6	733	15.6	731	15.6
450.soplex	707	11.8	708	11.8	706	11.8	707	11.8	708	11.8	706	11.8
453.povray	304	17.5	304	17.5	305	17.4	306	17.4	305	17.5	304	17.5
454.calculix	558	14.8	556	14.8	556	14.8	558	14.8	556	14.8	556	14.8
459.GemsFDTD	813	13.1	812	13.1	818	13.0	813	13.1	812	13.1	818	13.0
465.tonto	653	15.1	651	15.1	652	15.1	635	15.5	640	15.4	640	15.4
470.lbm	805	17.1	830	16.6	864	15.9	867	15.9	868	15.8	869	15.8
481.wrf	687	16.3	686	16.3	684	16.3	666	16.8	668	16.7	668	16.7
482.sphinx3	1201	16.2	1203	16.2	1203	16.2	1201	16.2	1203	16.2	1203	16.2

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

Environment stack size set to 'unlimited'
ulimit -l set to 1048576
Set vm.nr_hugepages=1024 in /etc/sysctl.conf
mount -t hugetlbfs nodev /mnt/hugepages

Base Compiler Invocation

C benchmarks:
 pgcc

C++ benchmarks:
 pgcpp

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant BL465c
(3.0GHz AMD Opteron 2222)

SPECfp2006 =

15.1

SPECfp_base2006 =

14.8

CPU2006 license: 3

Test date:

Aug-2007

Test sponsor: Hewlett-Packard Company

Hardware Availability:

Sep-2007

Tested by: Hewlett-Packard Company

Software Availability:

Oct-2007

Base Compiler Invocation (Continued)

Fortran benchmarks:

pgf95

Benchmarks using both Fortran and C:

pgcc pgf95

Base Portability Flags

```

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
    433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -Mnomain
436.cactusADM: -DSPEC_CPU_LP64 -Mnomain
    437.leslie3d: -DSPEC_CPU_LP64
        444.namd: -DSPEC_CPU_LP64
        447.dealII: -DSPEC_CPU_LP64
    450.soplex: -DSPEC_CPU_LP64
    453.povray: -DSPEC_CPU_LP64
    454.calculix: -DSPEC_CPU_LP64 -Mnomain
459.GemsFDTD: -DSPEC_CPU_LP64
    465.tonto: -DSPEC_CPU_LP64
    470.lbm: -DSPEC_CPU_LP64
    481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

```

Base Optimization Flags

C benchmarks:

```
-fast -Mipa=fast -Mipa=inline -Mfprelaxed -Msmartralloc=huge:8
-typ k8-64 -Bstatic_pgi
```

C++ benchmarks:

```
-fast -Mipa=fast -Mipa=inline -Mfprelaxed -Msmartralloc=huge:8
--zc_eh -typ k8-64 -Bstatic_pgi
```

Fortran benchmarks:

```
-fast -Mipa=fast -Mipa=inline -Mfprelaxed -Msmartralloc=huge:8
-typ k8-64 -Bstatic_pgi
```

Benchmarks using both Fortran and C:

```
-fast -Mipa=fast -Mipa=inline -Mfprelaxed -Msmartralloc=huge:8
-typ k8-64 -Bstatic_pgi
```



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant BL465c
(3.0GHz AMD Opteron 2222)

SPECfp2006 = 15.1

SPECfp_base2006 = 14.8

CPU2006 license: 3

Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

Test date: Aug-2007

Hardware Availability: Sep-2007

Software Availability: Oct-2007

Base Other Flags

C benchmarks:

-w

C++ benchmarks:

-w

Fortran benchmarks:

-w

Benchmarks using both Fortran and C:

-w

Peak Compiler Invocation

C benchmarks:

pgcc

C++ benchmarks:

pgcpp

Fortran benchmarks:

pgf95

Benchmarks using both Fortran and C:

pgcc pgf95

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

```
433.milc: -Mpfi(pass 1) -Mipa=fast(pass 2) -Mipa=inline(pass 2)
           -Mipa=noarg(pass 2) -Mpfo(pass 2) -fast -O4 -Mdse
           -Mfprelaxed -Msmartralloc=huge:8 -tp k8-64 -Bstatic_pgi
```

```
470.lbm: -fast -Mfprelaxed -Msmartralloc=huge:8 -Mipa=fast
           -Mipa=noarg -tp k8-64 -Bstatic_pgi
```

```
482.sphinx3: basepeak = yes
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant BL465c
(3.0GHz AMD Opteron 2222)

SPECfp2006 =

15.1

SPECfp_base2006 =

14.8

CPU2006 license: 3

Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

Test date:

Aug-2007

Hardware Availability: Sep-2007

Software Availability: Oct-2007

Peak Optimization Flags (Continued)

C++ benchmarks:

```
444.namd: -Mpfi(pass 1) -Mpfo(pass 2) -Mipa=fast(pass 2)
           -Mipa=inline(pass 2) -fast -O4 -Mfprelaxed
           -Msmaralloc=huge:32 --zc_eh -tp k8-64 -Bstatic_pgi
```

```
447.dealII: basepeak = yes
```

```
450.soplex: basepeak = yes
```

```
453.povray: -fast -Mfprelaxed -Msmaralloc=huge:32 -Mipa=fast
            -Mipa=inline --zc_eh -tp k8-64 -Bstatic_pgi
```

Fortran benchmarks:

```
410.bwaves: -fast -Mipa=fast -Mipa=inline -Mfprelaxed -Msmaralloc
            -tp k8-64 -Bstatic_pgi
```

```
416.gamess: -fast -Mipa=fast -Mipa=inline -Mfprelaxed -Mvect=noaltcode
            -Msmaralloc=huge:64 -tp k8-64 -Bstatic_pgi
```

```
434.zeusmp: basepeak = yes
```

```
437.leslie3d: basepeak = yes
```

```
459.GemsFDTD: basepeak = yes
```

```
465.tonto: -fast -Mfprelaxed -Msmaralloc=huge:128 -Mipa=fast
            -Mipa=inline -Mvect=noaltcode -tp k8-64 -Bstatic_pgi
```

Benchmarks using both Fortran and C:

```
435.gromacs: -fast -O4 -Mipa=fast -Mipa=inline -Mfprelaxed
              -Msmaralloc=huge:16 -tp k8-64 -Mfpapprox=rsqrt
              -Bstatic_pgi
```

```
436.cactusADM: basepeak = yes
```

```
454.calculix: basepeak = yes
```

```
481.wrf: -fast -Mfprelaxed -Msmaralloc=huge:32 -Mvect=noaltcode
          -tp k8-64 -Bstatic_pgi
```

Peak Other Flags

C benchmarks:

-w

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant BL465c
(3.0GHz AMD Opteron 2222)

SPECfp2006 = 15.1

SPECfp_base2006 = 14.8

CPU2006 license: 3

Test sponsor: Hewlett-Packard Company

Tested by: Hewlett-Packard Company

Test date: Aug-2007

Hardware Availability: Sep-2007

Software Availability: Oct-2007

Peak Other Flags (Continued)

C++ benchmarks:

-w

Fortran benchmarks:

-w

Benchmarks using both Fortran and C:

-w

The flags file that was used to format this result can be browsed at

http://www.spec.org/cpu2006/flags/hp-pgi710_flags.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/cpu2006/flags/hp-pgi710_flags.xml

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.

Report generated on Tue Jul 22 13:28:18 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 19 September 2007.