



# SPEC<sup>®</sup> CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

**SPECint<sup>®</sup>\_rate2006 = 29.3**

ProLiant DL385 G2  
(3.0 GHz AMD Opteron 2222)

**SPECint\_rate\_base2006 = 27.1**

CPU2006 license: 3


Test date: Aug-2007

Test sponsor: Hewlett-Packard Company

Hardware Availability: Sep-2007

Tested by: Hewlett-Packard Company

Software Availability: Oct-2007



### Hardware

CPU Name: AMD Opteron 2222  
 CPU Characteristics:  
 CPU MHz: 3000  
 FPU: Integrated  
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip  
 CPU(s) orderable: 1,2 chips  
 Primary Cache: 64 KB I + 64 KB D on chip per core  
 Secondary Cache: 1 MB I+D on chip per core  
 L3 Cache: None  
 Other Cache: None  
 Memory: 16 GB (4x4 GB, PC2-5300P CL5)  
 Disk Subsystem: 1x72 GB 10 K SAS  
 Other Hardware: None

### Software

Operating System: SuSE Linux Enterprise Server 10 (x86\_64) SP1  
 kernel 2.6.16.46-0.12-smp  
 Compiler: The Portland Group (PGI)  
 PGI pgcc 7.1-0 C Compiler  
 PGI pgCC 7.1-0 C++ Compiler  
 Auto Parallel: No  
 File System: ext2  
 System State: Multi-user, run level 3  
 Base Pointers: 32/64-bit  
 Peak Pointers: 32/64-bit  
 Other Software: SmartHeap 8.0 32-bit Library for Linux



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

SPECint\_rate2006 = 29.3

ProLiant DL385 G2  
(3.0 GHz AMD Opteron 2222)

SPECint\_rate\_base2006 = 27.1

CPU2006 license: 3

Test date: Aug-2007

Test sponsor: Hewlett-Packard Company

Hardware Availability: Sep-2007

Tested by: Hewlett-Packard Company

Software Availability: Oct-2007

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	2	<b>760</b>	<b>25.7</b>	760	25.7	759	25.7	2	<b>607</b>	<b>32.2</b>	607	32.2	608	32.2
401.bzip2	2	904	21.4	<b>904</b>	<b>21.4</b>	904	21.3	2	885	21.8	<b>887</b>	<b>21.8</b>	887	21.7
403.gcc	2	<b>895</b>	<b>18.0</b>	901	17.9	892	18.1	2	715	22.5	<b>718</b>	<b>22.4</b>	719	22.4
429.mcf	2	790	23.1	788	23.2	<b>789</b>	<b>23.1</b>	2	590	30.9	589	30.9	<b>590</b>	<b>30.9</b>
445.gobmk	2	702	29.9	703	29.9	<b>702</b>	<b>29.9</b>	2	653	32.1	652	32.2	<b>652</b>	<b>32.2</b>
456.hmmer	2	475	39.2	478	39.0	<b>476</b>	<b>39.2</b>	2	448	41.7	456	40.9	<b>449</b>	<b>41.6</b>
458.sjeng	2	839	28.8	840	28.8	<b>839</b>	<b>28.8</b>	2	810	29.9	809	29.9	<b>810</b>	<b>29.9</b>
462.libquantum	2	927	44.7	921	45.0	<b>927</b>	<b>44.7</b>	2	927	44.7	921	45.0	<b>927</b>	<b>44.7</b>
464.h264ref	2	<b>1023</b>	<b>43.3</b>	1046	42.3	1022	43.3	2	<b>1023</b>	<b>43.3</b>	1046	42.3	1022	43.3
471.omnetpp	2	669	18.7	<b>671</b>	<b>18.6</b>	673	18.6	2	669	18.7	<b>671</b>	<b>18.6</b>	673	18.6
473.astar	2	702	20.0	<b>705</b>	<b>19.9</b>	706	19.9	2	702	20.0	<b>705</b>	<b>19.9</b>	706	19.9
483.xalancbmk	2	477	28.9	<b>478</b>	<b>28.8</b>	479	28.8	2	475	29.1	<b>476</b>	<b>29.0</b>	477	29.0

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

```
Environment stack size set to 'unlimited'
ulimit -l set to 1048576
'numactl' was used to bind copies to the cores
Set vm/nr_hugepages=1024 in /etc/sysctl.conf
mount -t hugetlbfs nodev /mnt/hugepages
```

## Base Compiler Invocation

C benchmarks:  
pgcc

C++ benchmarks:  
pgcpp

## Base Portability Flags

```
400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
403.gcc: -DSPEC_CPU_LP64
429.mcf: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
```

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECint\_rate2006 = 29.3

ProLiant DL385 G2  
(3.0 GHz AMD Opteron 2222)

SPECint\_rate\_base2006 = 27.1

CPU2006 license: 3

Test date: Aug-2007

Test sponsor: Hewlett-Packard Company

Hardware Availability: Sep-2007

Tested by: Hewlett-Packard Company

Software Availability: Oct-2007

## Base Portability Flags (Continued)

462.libquantum: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX  
464.h264ref: -DSPEC\_CPU\_LP64  
483.xalancbmk: -DSPEC\_CPU\_LINUX

## Base Optimization Flags

C benchmarks:

-fast -Mipa=fast -Mipa=inline -Mipa=noarg -Mfprelaxed  
-Msmartalloc=huge:64 -tp k8-64 -Bstatic\_pgi

C++ benchmarks:

-fastsse -Mipa=fast -Mipa=inline -Mfprelaxed -Msmartalloc --zc\_eh  
-tp k8-32 -Bstatic\_pgi -lsmarheap

## Base Other Flags

C benchmarks:

-w

C++ benchmarks:

-w -L/proj/qa/smarheap/SmartHeap\_8/lib

## Peak Compiler Invocation

C benchmarks:

pgcc

C++ benchmarks:

pgcpp

## Peak Portability Flags

400.perlbench: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX\_X64  
401.bzip2: -DSPEC\_CPU\_LP64  
445.gobmk: -DSPEC\_CPU\_LP64  
456.hmmer: -DSPEC\_CPU\_LP64  
458.sjeng: -DSPEC\_CPU\_LP64  
462.libquantum: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX  
464.h264ref: -DSPEC\_CPU\_LP64  
483.xalancbmk: -DSPEC\_CPU\_LINUX



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Hewlett-Packard Company**

**SPECint\_rate2006 = 29.3**

ProLiant DL385 G2  
(3.0 GHz AMD Opteron 2222)

**SPECint\_rate\_base2006 = 27.1**

**CPU2006 license:** 3

**Test date:** Aug-2007

**Test sponsor:** Hewlett-Packard Company

**Hardware Availability:** Sep-2007

**Tested by:** Hewlett-Packard Company

**Software Availability:** Oct-2007

## Peak Optimization Flags

C benchmarks:

400.perlbench: -Mpfi(pass 1) -Mpfo(pass 2) -Mipa=inline(pass 2) -fast  
-O4 -Mfprelaxed -Msmartalloc=huge:8 -Mnounroll -tp k8-64  
-Bstatic\_pgi

401.bzip2: -Mpfi(pass 1) -Mpfo(pass 2) -fast -O4  
-Msmartalloc=huge:64 -tp k8-64 -Bstatic\_pgi

403.gcc: -fastsse -Mfprelaxed -Msmartalloc=huge:32 -Mipa=fast  
-Mipa=inline -tp k8-32 -Bstatic\_pgi

429.mcf: -fastsse -Mipa=fast -Mipa=inline -Msmartalloc=huge:16  
-tp k8-32 -Bstatic\_pgi

445.gobmk: -Mpfi(pass 1) -Mpfo(pass 2) -Mipa=fast(pass 2) -fast -O4  
-Msmartalloc=huge:32 -Mfprelaxed -Mnovect -tp k8-64  
-Bstatic\_pgi

456.hmmer: -fast -Msmartalloc=huge:32 -Mfprelaxed -Msafeptr  
-Mipa=const -Mipa=ptr -Mipa=arg -tp k8-64 -Bstatic\_pgi

458.sjeng: -Mpfi(pass 1) -Mipa=fast(pass 2) -Mipa=inline(pass 2)  
-Mipa=noarg(pass 2) -Mpfo(pass 2) -fast  
-Msmartalloc=huge:32 -Mfprelaxed -tp k8-64 -Bstatic\_pgi

462.libquantum: basepeak = yes

464.h264ref: basepeak = yes

C++ benchmarks:

471.omnetpp: basepeak = yes

473.astar: basepeak = yes

483.xalancbmk: -fastsse -O4 -Mipa=fast -Mipa=inline -Mfprelaxed  
-Msmartalloc --zc\_eh -tp k8-32 -Bstatic\_pgi -lsmartheap

## Peak Other Flags

C benchmarks:

-w

C++ benchmarks:

-w -L/proj/qa/smartheap/SmartHeap\_8/lib



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Hewlett-Packard Company**

**SPECint\_rate2006 = 29.3**

ProLiant DL385 G2  
(3.0 GHz AMD Opteron 2222)

**SPECint\_rate\_base2006 = 27.1**

**CPU2006 license:** 3

**Test date:** Aug-2007

**Test sponsor:** Hewlett-Packard Company

**Hardware Availability:** Sep-2007

**Tested by:** Hewlett-Packard Company

**Software Availability:** Oct-2007

The flags file that was used to format this result can be browsed at

[http://www.spec.org/cpu2006/flags/hp-pgi710\\_flags.html](http://www.spec.org/cpu2006/flags/hp-pgi710_flags.html)

You can also download the XML flags source by saving the following link:

[http://www.spec.org/cpu2006/flags/hp-pgi710\\_flags.xml](http://www.spec.org/cpu2006/flags/hp-pgi710_flags.xml)

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.  
Report generated on Tue Jul 22 12:38:53 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 18 September 2007.