



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp®_rate2006 = 35.0

PowerEdge 860 (Intel Xeon X3210, 2.13 GHz)

SPECfp_rate_base2006 = 33.1

CPU2006 license: 55


Test date: Aug-2007

Test sponsor: Dell Inc.

Hardware Availability: Jan-2007

Tested by: Dell Inc.

Software Availability: Nov-2007



Hardware

CPU Name: Intel Xeon X3210
 CPU Characteristics: 1066MHz system bus
 CPU MHz: 2133
 FPU: Integrated
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip
 CPU(s) orderable: 1 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 8 MB I+D on chip per chip, 4 MB shared / 2 cores

Continued on next page

Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 10
 Compiler: Intel C++ and Fortran Compiler for Linux32 and Linux64 version 10.1 Build 20070725
 Auto Parallel: No
 File System: ReiserFS
 System State: Multi-user, run level 3
 Base Pointers: 32/64-bit
 Peak Pointers: 32/64-bit

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp_rate2006 = 35.0

PowerEdge 860 (Intel Xeon X3210, 2.13 GHz)

SPECfp_rate_base2006 = 33.1

CPU2006 license: 55

Test date: Aug-2007

Test sponsor: Dell Inc.

Hardware Availability: Jan-2007

Tested by: Dell Inc.

Software Availability: Nov-2007

L3 Cache: None
Other Cache: None
Memory: 8 GB (4x2 GB 667 Mhz DIMM)
Disk Subsystem: 1 x 73 GB SAS 10k RPM
Other Hardware: None

Other Software: SmartHeap library V8.1

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	4	2240	24.3	2187	24.9	<u>2233</u>	<u>24.3</u>	4	2239	24.3	2209	24.6	<u>2214</u>	<u>24.5</u>
416.gamess	4	<u>1301</u>	<u>60.2</u>	1301	60.2	1300	60.3	4	<u>1281</u>	<u>61.1</u>	1281	61.2	1283	61.1
433.milc	4	1905	19.3	1870	19.6	<u>1889</u>	<u>19.4</u>	4	1892	19.4	1858	19.8	<u>1870</u>	<u>19.6</u>
434.zeusmp	4	1003	36.3	<u>994</u>	<u>36.6</u>	988	36.8	4	<u>978</u>	<u>37.2</u>	957	38.0	992	36.7
435.gromacs	4	551	51.9	<u>550</u>	<u>51.9</u>	550	51.9	4	542	52.7	<u>543</u>	<u>52.6</u>	543	52.6
436.cactusADM	4	<u>1143</u>	<u>41.8</u>	1147	41.7	1143	41.8	4	1068	44.8	<u>1040</u>	<u>46.0</u>	1039	46.0
437.leslie3d	4	2365	15.9	<u>2322</u>	<u>16.2</u>	2317	16.2	4	2322	16.2	<u>2299</u>	<u>16.4</u>	2271	16.6
444.namd	4	709	45.2	720	44.6	<u>709</u>	<u>45.2</u>	4	705	45.5	706	45.4	<u>706</u>	<u>45.5</u>
447.dealII	4	<u>684</u>	<u>66.9</u>	682	67.1	687	66.6	4	642	71.3	638	71.8	<u>639</u>	<u>71.6</u>
450.soplex	4	1564	21.3	1557	21.4	<u>1561</u>	<u>21.4</u>	4	1443	23.1	<u>1415</u>	<u>23.6</u>	1413	23.6
453.povray	4	<u>314</u>	<u>67.8</u>	314	67.9	317	67.2	4	<u>265</u>	<u>80.3</u>	264	80.5	265	80.3
454.calculix	4	755	43.7	757	43.6	<u>755</u>	<u>43.7</u>	4	540	61.1	<u>540</u>	<u>61.1</u>	537	61.5
459.GemsFDTD	4	2718	15.6	<u>2737</u>	<u>15.5</u>	2738	15.5	4	2705	15.7	2752	15.4	<u>2733</u>	<u>15.5</u>
465.tonto	4	925	42.5	921	42.7	<u>923</u>	<u>42.6</u>	4	912	43.1	<u>906</u>	<u>43.5</u>	896	44.0
470.lbm	4	3741	14.7	<u>3766</u>	<u>14.6</u>	3775	14.6	4	3606	15.2	3671	15.0	<u>3630</u>	<u>15.1</u>
481.wrf	4	1528	29.2	1510	29.6	<u>1516</u>	<u>29.5</u>	4	1513	29.5	<u>1512</u>	<u>29.6</u>	1511	29.6
482.sphinx3	4	2256	34.6	<u>2252</u>	<u>34.6</u>	2243	34.8	4	2130	36.6	<u>2127</u>	<u>36.7</u>	2127	36.7

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

OMP_NUM_THREADS set to number of cores
KMP_STACK_SIZE set to 64M
KMP_AFFINITY set to physical,0

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
'/usr/bin/taskset' used to bind processes to CPUs



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp_rate2006 = 35.0

PowerEdge 860 (Intel Xeon X3210, 2.13 GHz)

SPECfp_rate_base2006 = 33.1

CPU2006 license: 55

Test date: Aug-2007

Test sponsor: Dell Inc.

Hardware Availability: Jan-2007

Tested by: Dell Inc.

Software Availability: Nov-2007

Platform Notes

BIOS Settings:

Adjacent Cache Line Prefetch = Disabled (default Enabled)

Hardware Prefetcher = Disabled (default Enabled)

Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:

-fast

C++ benchmarks:

-fast

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp_rate2006 = 35.0

PowerEdge 860 (Intel Xeon X3210, 2.13 GHz)

SPECfp_rate_base2006 = 33.1

CPU2006 license: 55

Test date: Aug-2007

Test sponsor: Dell Inc.

Hardware Availability: Jan-2007

Tested by: Dell Inc.

Software Availability: Nov-2007

Base Optimization Flags (Continued)

Fortran benchmarks:

-fast

Benchmarks using both Fortran and C:

-fast

Peak Compiler Invocation

C benchmarks (except as noted below):

/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/bin/icc
-L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/lib
-I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/include

433.milc: icc

C++ benchmarks (except as noted below):

icpc

450.soplex: /home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/bin/icpc
-L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/lib
-I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/include

Fortran benchmarks (except as noted below):

ifort

437.leslie3d: /home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/bin/ifort
-L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/lib
-I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/include

Benchmarks using both Fortran and C:

icc ifort

Peak Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp_rate2006 = 35.0

PowerEdge 860 (Intel Xeon X3210, 2.13 GHz)

SPECfp_rate_base2006 = 33.1

CPU2006 license: 55

Test date: Aug-2007

Test sponsor: Dell Inc.

Hardware Availability: Jan-2007

Tested by: Dell Inc.

Software Availability: Nov-2007

Peak Portability Flags (Continued)

465.tonto: -DSPEC_CPU_LP64

481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

433.milc: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32

470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-scalar-rep- -prefetch -opt-malloc-options=3

482.sphinx3: -fast -unroll2

C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast
-opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4
-ansi-alias

Fortran benchmarks:

410.bwaves: -fast -prefetch

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0
-ansi-alias -scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -fast

437.leslie3d: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-opt-malloc-options=3

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0
-prefetch

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -auto

Benchmarks using both Fortran and C:

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp_rate2006 = 35.0

PowerEdge 860 (Intel Xeon X3210, 2.13 GHz)

SPECfp_rate_base2006 = 33.1

CPU2006 license: 55

Test date: Aug-2007

Test sponsor: Dell Inc.

Hardware Availability: Jan-2007

Tested by: Dell Inc.

Software Availability: Nov-2007

Peak Optimization Flags (Continued)

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-prefetch -auto-ilp32

454.calculix: -fast -unroll-aggressive -auto-ilp32

481.wrf: -fast -auto-ilp32

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-FP-intel64-linux-flags.20090714.13.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-FP-intel64-linux-flags.20090714.13.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 13:58:27 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 2 October 2007.