



SPEC[®] CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp[®]_rate2006 = 77.5

PowerEdge 2950 III (Intel Xeon X5460, 3.16 GHz)

SPECfp_rate_base2006 = 69.7

CPU2006 license: 55


Test date: Nov-2007

Test sponsor: Dell Inc.

Hardware Availability: Nov-2007

Tested by: Dell Inc.

Software Availability: Nov-2007



SPECfp_rate2006 = 77.5

SPECfp_rate_base2006 = 69.7

Hardware

CPU Name: Intel Xeon X5460
 CPU Characteristics: 1333 MHz system bus
 CPU MHz: 3166
 FPU: Integrated
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
 CPU(s) orderable: 1,2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores

Continued on next page

Software

Operating System: SUSE Linux Enterprise Server 10 (x86_64) SP1, Kernel 2.6.16.46-0.12-smp
 Compiler: Intel C++ and Fortran Compiler 10.1 for Linux Build 20070913 Package ID: l_cc_p_10.1.008, l_fc_p_10.1.008
 Auto Parallel: Yes
 File System: ReiserFS
 System State: Multi-user, run level 3
 Base Pointers: 64-bit

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp_rate2006 = 77.5

PowerEdge 2950 III (Intel Xeon X5460, 3.16 GHz)

SPECfp_rate_base2006 = 69.7

CPU2006 license: 55

Test date: Nov-2007

Test sponsor: Dell Inc.

Hardware Availability: Nov-2007

Tested by: Dell Inc.

Software Availability: Nov-2007

L3 Cache: None
Other Cache: None
Memory: 16 GB (8x2 GB 667 MHz ECC CL5 FB-DIMM)
Disk Subsystem: 1 x 73 GB SAS 15k RPM
Other Hardware: None

Peak Pointers: 32/64-bit
Other Software: None

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	8	<u>3221</u>	<u>33.8</u>	3221	33.8	3223	33.7	4	1580	34.4	<u>1580</u>	<u>34.4</u>	1579	34.4
416.gamess	8	843	186	<u>843</u>	<u>186</u>	842	186	8	831	188	829	189	<u>831</u>	<u>189</u>
433.milc	8	2341	31.4	<u>2343</u>	<u>31.3</u>	2348	31.3	8	2355	31.2	<u>2348</u>	<u>31.3</u>	2345	31.3
434.zeusmp	8	1036	70.2	1040	70.0	<u>1037</u>	<u>70.2</u>	8	<u>1038</u>	<u>70.1</u>	1039	70.1	1038	70.1
435.gromacs	8	375	152	376	152	<u>376</u>	<u>152</u>	8	363	157	<u>362</u>	<u>158</u>	360	159
436.cactusADM	8	1313	72.8	1303	73.4	<u>1304</u>	<u>73.3</u>	1	<u>117</u>	<u>102</u>	118	102	117	102
437.leslie3d	8	2837	26.5	<u>2836</u>	<u>26.5</u>	2835	26.5	4	<u>1348</u>	<u>27.9</u>	1343	28.0	1350	27.8
444.namd	8	<u>484</u>	<u>133</u>	484	133	484	133	8	480	134	<u>480</u>	<u>134</u>	481	133
447.dealII	8	<u>704</u>	<u>130</u>	675	136	716	128	8	<u>691</u>	<u>132</u>	692	132	689	133
450.soplex	8	1826	36.5	1804	37.0	<u>1804</u>	<u>37.0</u>	8	1622	41.1	<u>1620</u>	<u>41.2</u>	1619	41.2
453.povray	8	<u>198</u>	<u>215</u>	198	215	198	215	8	169	251	172	248	<u>170</u>	<u>250</u>
454.calculix	8	539	122	<u>540</u>	<u>122</u>	545	121	8	<u>398</u>	<u>166</u>	398	166	397	166
459.GemsFDTD	8	3080	27.6	<u>3065</u>	<u>27.7</u>	3060	27.7	8	3065	27.7	3075	27.6	<u>3071</u>	<u>27.6</u>
465.tonto	8	653	121	<u>654</u>	<u>120</u>	655	120	8	<u>642</u>	<u>123</u>	642	123	641	123
470.lbm	8	4120	26.7	<u>4119</u>	<u>26.7</u>	4118	26.7	4	<u>1442</u>	<u>38.1</u>	1440	38.2	1443	38.1
481.wrf	8	1760	50.8	1761	50.7	<u>1760</u>	<u>50.8</u>	8	1771	50.5	1757	50.9	<u>1760</u>	<u>50.8</u>
482.sphinx3	8	2285	68.2	2220	70.2	<u>2237</u>	<u>69.7</u>	4	768	102	750	104	<u>755</u>	<u>103</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

OMP_NUM_THREADS set to number of cores
KMP_STACK_SIZE set to 64M
KMP_AFFINITY set to physical,0

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
'/usr/bin/taskset' used to bind processes to CPUs



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp_rate2006 = 77.5

PowerEdge 2950 III (Intel Xeon X5460, 3.16 GHz)

SPECfp_rate_base2006 = 69.7

CPU2006 license: 55

Test date: Nov-2007

Test sponsor: Dell Inc.

Hardware Availability: Nov-2007

Tested by: Dell Inc.

Software Availability: Nov-2007

Platform Notes

BIOS Settings:

Adjacent Cache Line Prefetch = Disabled (default Enabled)

Hardware Prefetcher = Disabled (default Enabled)

Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
 416.gamess: -DSPEC_CPU_LP64
 433.milc: -DSPEC_CPU_LP64
 434.zeusmp: -DSPEC_CPU_LP64
 435.gromacs: -DSPEC_CPU_LP64 -nofor_main
 436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
 437.leslie3d: -DSPEC_CPU_LP64
 444.namd: -DSPEC_CPU_LP64
 447.dealII: -DSPEC_CPU_LP64
 450.soplex: -DSPEC_CPU_LP64
 453.povray: -DSPEC_CPU_LP64
 454.calculix: -DSPEC_CPU_LP64 -nofor_main
 459.GemsFDTD: -DSPEC_CPU_LP64
 465.tonto: -DSPEC_CPU_LP64
 470.lbm: -DSPEC_CPU_LP64
 481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
 482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:

-fast

C++ benchmarks:

-fast

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp_rate2006 = 77.5

PowerEdge 2950 III (Intel Xeon X5460, 3.16 GHz)

SPECfp_rate_base2006 = 69.7

CPU2006 license: 55

Test date: Nov-2007

Test sponsor: Dell Inc.

Hardware Availability: Nov-2007

Tested by: Dell Inc.

Software Availability: Nov-2007

Base Optimization Flags (Continued)

Fortran benchmarks:

-fast

Benchmarks using both Fortran and C:

-fast

Peak Compiler Invocation

C benchmarks (except as noted below):

/opt/intel/cc/10.1.008/bin/icc -L/opt/intel/cc/10.1.008/lib
-I/opt/intel/cc/10.1.008/include

433.milc: icc

C++ benchmarks (except as noted below):

icpc

450.soplex: /opt/intel/cc/10.1.008/bin/icpc -L/opt/intel/cc/10.1.008/lib
-I/opt/intel/cc/10.1.008/include

Fortran benchmarks (except as noted below):

ifort

437.leslie3d: /opt/intel/fc/10.1.008/bin/ifort -L/opt/intel/fc/10.1.008/lib
-I/opt/intel/fc/10.1.008/include

Benchmarks using both Fortran and C:

icc ifort

Peak Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp_rate2006 = 77.5

PowerEdge 2950 III (Intel Xeon X5460, 3.16 GHz)

SPECfp_rate_base2006 = 69.7

CPU2006 license: 55

Test date: Nov-2007

Test sponsor: Dell Inc.

Hardware Availability: Nov-2007

Tested by: Dell Inc.

Software Availability: Nov-2007

Peak Optimization Flags

C benchmarks:

433.milc: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32

470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-scalar-rep- -prefetch -opt-malloc-options=3

482.sphinx3: -fast -unroll2

C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast
-opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4
-ansi-alias

Fortran benchmarks:

410.bwaves: -fast -prefetch

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0
-ansi-alias -scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -fast

437.leslie3d: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-opt-malloc-options=3

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0
-prefetch

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -auto

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-prefetch -parallel -auto-ilp32

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp_rate2006 = 77.5

PowerEdge 2950 III (Intel Xeon X5460, 3.16 GHz)

SPECfp_rate_base2006 = 69.7

CPU2006 license: 55

Test date: Nov-2007

Test sponsor: Dell Inc.

Hardware Availability: Nov-2007

Tested by: Dell Inc.

Software Availability: Nov-2007

Peak Optimization Flags (Continued)

454.calculix: -fast -unroll-aggressive -auto-ilp32

481.wrf: -fast -auto-ilp32

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-FP-intel64-linux-flags.20090714.11.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-FP-intel64-linux-flags.20090714.11.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 14:36:21 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 27 November 2007.