



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY BX620 S4, Intel Xeon processor X5260,
3.33 GHz

SPECfp®_rate2006 = 56.6

SPECfp_rate_base2006 = 50.6

CPU2006 license: 22


Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Dec-2007

Hardware Availability: Dec-2007

Software Availability: Nov-2007



CPU Name: Intel Xeon X5260
CPU Characteristics: 1333 MHz system bus
CPU MHz: 3333
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
CPU(s) orderable: 1,2 chips
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 6 MB I+D on chip per chip

Hardware

Operating System: SUSE Linux Enterprise Server 10 (x86_64) SP1, Kernel 2.6.16.46-0.12-smp
Compiler: Intel C++ and Fortran Compiler for Linux32 and Linux64 Version 10.1 - Build 20070725
Auto Parallel: Yes
File System: ext2
System State: Multiuser, Runlevel 3
Base Pointers: 64-bit

Software

Continued on next page

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY BX620 S4, Intel Xeon processor X5260,
3.33 GHz

SPECfp_rate2006 = 56.6

SPECfp_rate_base2006 = 50.6

CPU2006 license: 22

Test date: Dec-2007

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: Dec-2007

Tested by: Fujitsu Siemens Computers

Software Availability: Nov-2007

L3 Cache: None
 Other Cache: None
 Memory: 16 GB (8x2 GB PC2-5300F, 2 rank, CAS 5-5-5, with ECC)
 Disk Subsystem: Seagate ST973451SS (SAS, 73GB, 15000rpm)
 Other Hardware: None

Peak Pointers: 32/64-bit
 Other Software: None

Results Table

Benchmark	Base								Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	4	1515	35.9	1521	35.7	1521	35.7	4	1485	36.6	1482	36.7	1482	36.7		
416.gamess	4	800	97.8	801	97.8	801	97.8	4	790	99.2	795	98.5	789	99.2		
433.milc	4	1618	22.7	1586	23.2	1573	23.3	4	1550	23.7	1547	23.7	1542	23.8		
434.zeusmp	4	644	56.6	652	55.8	648	56.1	4	638	57.1	638	57.0	638	57.0		
435.gromacs	4	337	84.7	338	84.6	339	84.2	4	335	85.3	335	85.3	335	85.3		
436.cactusADM	4	865	55.3	852	56.1	863	55.4	1	178	67.1	177	67.4	175	68.3		
437.leslie3d	4	1385	27.1	1379	27.3	1377	27.3	4	1329	28.3	1328	28.3	1328	28.3		
444.namd	4	457	70.1	457	70.2	457	70.2	4	455	70.5	455	70.5	457	70.2		
447.dealII	4	488	93.7	484	94.5	484	94.6	4	459	99.6	457	100	457	100		
450.soplex	4	1059	31.5	1057	31.6	1055	31.6	4	952	35.0	952	35.0	950	35.1		
453.povray	4	194	110	197	108	195	109	4	164	130	164	130	166	129		
454.calculix	4	478	69.1	479	68.9	470	70.2	4	333	99.1	338	97.5	335	98.4		
459.GemsFDTD	4	1648	25.8	1649	25.7	1635	26.0	4	1605	26.4	1602	26.5	1603	26.5		
465.tonto	4	493	79.9	492	80.0	492	80.0	4	476	82.7	477	82.4	476	82.6		
470.lbm	4	2880	19.1	2872	19.1	2870	19.2	2	690	39.8	692	39.7	690	39.8		
481.wrf	4	861	51.9	861	51.9	859	52.0	4	860	52.0	861	51.9	860	52.0		
482.sphinx3	4	1580	49.3	1581	49.3	1595	48.9	4	1436	54.3	1445	54.0	1438	54.2		

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run

General Notes

This result has been produced with binaries provided and compiled by Intel.

All binaries were built with 64-bit Intel compiler except:

437.leslie3d, 450.soplex, 470.lbm and 482.sphinx3 in peak were built with 32-bit Intel compiler by changing the path for include and library files.

For information about Fujitsu Siemens Computers please see:
<http://www.fujitsu-siemens.com>



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY BX620 S4, Intel Xeon processor X5260,
3.33 GHz

SPECfp_rate2006 = 56.6

SPECfp_rate_base2006 = 50.6

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Dec-2007

Hardware Availability: Dec-2007

Software Availability: Nov-2007

Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

Base Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
 433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
 444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
 465.tonto: -DSPEC_CPU_LP64
 470.lbm: -DSPEC_CPU_LP64
 481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64
```

Base Optimization Flags

C benchmarks:

-fast

C++ benchmarks:

-fast

Fortran benchmarks:

-fast

Benchmarks using both Fortran and C:

-fast



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY BX620 S4, Intel Xeon processor X5260,
3.33 GHz

SPECfp_rate2006 = 56.6

SPECfp_rate_base2006 = 50.6

CPU2006 license: 22

Test date: Dec-2007

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: Dec-2007

Tested by: Fujitsu Siemens Computers

Software Availability: Nov-2007

Peak Compiler Invocation

C benchmarks (except as noted below):

```
/home/cmpllr/usr3/alrahate/compilers/icl0.1mainline/20070725/Linux32/bin/icc
-L/home/cmpllr/usr3/alrahate/compilers/icl0.1mainline/20070725/Linux32/lib
-I/home/cmpllr/usr3/alrahate/compilers/icl0.1mainline/20070725/Linux32/include
```

433.milc: icc

C++ benchmarks (except as noted below):

icpc

```
450.soplex: /home/cmpllr/usr3/alrahate/compilers/icl0.1mainline/20070725/Linux32/bin/icpc
-L/home/cmpllr/usr3/alrahate/compilers/icl0.1mainline/20070725/Linux32/lib
-I/home/cmpllr/usr3/alrahate/compilers/icl0.1mainline/20070725/Linux32/include
```

Fortran benchmarks (except as noted below):

ifort

```
437.leslie3d: /home/cmpllr/usr3/alrahate/compilers/icl0.1mainline/20070725/Linux32/bin/ifort
-L/home/cmpllr/usr3/alrahate/compilers/icl0.1mainline/20070725/Linux32/lib
-I/home/cmpllr/usr3/alrahate/compilers/icl0.1mainline/20070725/Linux32/include
```

Benchmarks using both Fortran and C:

icc ifort

Peak Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
    433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
    444.namd: -DSPEC_CPU_LP64
    447.dealII: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
    465.tonto: -DSPEC_CPU_LP64
    481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
```

Peak Optimization Flags

C benchmarks:

```
433.milc: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
    -auto-ilp32
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY BX620 S4, Intel Xeon processor X5260,
3.33 GHz

SPECfp_rate2006 = 56.6

SPECfp_rate_base2006 = 50.6

CPU2006 license: 22

Test date: Dec-2007

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: Dec-2007

Tested by: Fujitsu Siemens Computers

Software Availability: Nov-2007

Peak Optimization Flags (Continued)

470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll12
-scalar-rep- -prefetch -opt-malloc-options=3

482.sphinx3: -fast -unroll12

C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll12
-ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast
-opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll14
-ansi-alias

Fortran benchmarks:

410.bwaves: -fast -prefetch

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll12 -O0
-ansi-alias -scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -fast

437.leslie3d: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-opt-malloc-options=3

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll12 -O0
-prefetch

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll14 -auto

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll12
-prefetch -parallel -auto-ilp32

454.calculix: -fast -unroll-aggressive -auto-ilp32

481.wrf: -fast -auto-ilp32



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY BX620 S4, Intel Xeon processor X5260,
3.33 GHz

SPECfp_rate2006 = 56.6

SPECfp_rate_base2006 = 50.6

CPU2006 license: 22

Test date: Dec-2007

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: Dec-2007

Tested by: Fujitsu Siemens Computers

Software Availability: Nov-2007

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-FP-intel64-linux-flags.20090714.05.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-FP-intel64-linux-flags.20090714.05.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.

Report generated on Tue Jul 22 13:33:08 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 28 December 2007.