



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro Motherboard X7DVA-8

SPECint_rate2006 = 123
SPECint_rate_base2006 = 95.0

CPU2006 license: 001176


Test sponsor: Supermicro

Tested by: Supermicro

Test date: Nov-2007

Hardware Availability: Nov-2007

Software Availability: Nov-2007



Hardware

CPU Name: Intel Xeon E5440
CPU Characteristics: Quad Core, 2.83GHz
CPU MHz: 2833
FPU: Integrated
CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
CPU(s) orderable: 1,2 chips
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores
L3 Cache: None
Other Cache: None
Memory: 12 GB (6 X 2GB ECC PC2-5300, CL5, FBDIMM)
Disk Subsystem: Western Digital WD1600YS-01SHB1 160GB SATA II, 7200RPM
Other Hardware: None

Software

Operating System: SuSE Linux Enterprise Server 10 (x86_64) SP1, kernel 2.6.16.46-0.12-default
Compiler: Intel C++ Compiler for Linux32 and Linux64 version 10.1 Build 20070725
Auto Parallel: Yes
File System: ReiserFS
System State: Multi-user, run level 3
Base Pointers: 32-bit
Peak Pointers: 32/64-bit
Other Software: SmartHeap library V8.1 Binutils 2.17.50.0.15



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro
Motherboard X7DVA-8

SPECint_rate2006 = 123
SPECint_rate_base2006 = 95.0

CPU2006 license: 001176

Test date: Nov-2007

Test sponsor: Supermicro

Hardware Availability: Nov-2007

Tested by: Supermicro

Software Availability: Nov-2007

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	8	548	143	550	142	547	143	8	469	167	465	168	463	169
401.bzip2	8	793	97.3	785	98.4	775	99.6	8	745	104	742	104	733	105
403.gcc	8	734	87.7	731	88.2	727	88.5	8	723	89.1	723	89.0	722	89.2
429.mcf	8	1032	70.7	986	74.0	965	75.6	8	963	75.8	960	76.0	961	75.9
445.gobmk	8	611	137	612	137	607	138	8	569	147	570	147	570	147
456.hammer	8	636	117	633	118	633	118	8	384	194	386	193	386	194
458.sjeng	8	714	136	712	136	713	136	8	657	147	657	147	655	148
462.libquantum	8	5905	28.1	5815	28.5	5765	28.8	1	99.9	207	99.5	208	99.3	209
464.h264ref	8	751	236	753	235	751	236	8	714	248	715	248	714	248
471.omnetpp	8	968	51.6	933	53.6	909	55.0	8	875	57.2	878	57.0	877	57.0
473.astar	8	889	63.2	860	65.3	856	65.6	8	798	70.4	798	70.4	799	70.3
483.xalancbmk	8	488	113	484	114	477	116	8	488	113	484	114	477	116

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

Tested systems can be used with CSE-811S-520 case,
To ensure system stability, a 500W (minimum) ATX power supply
[4-pin (+12V), 8-pin (+12V) and 24-pin are required]

Product description located as of

<http://www.supermicro.com/products/motherboard/Xeon1333/5000V/X7DVA-8.cfm>

The system bus runs at 1333 MHz

The "taskset" command was used to bind benchmark copies to cores
except for 462.libquantum peak

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32

462.libquantum: -DSPEC_CPU_LINUX

483.xalancbmk: -DSPEC_CPU_LINUX



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro
Motherboard X7DVA-8

SPECint_rate2006 = 123

SPECint_rate_base2006 = 95.0

CPU2006 license: 001176

Test date: Nov-2007

Test sponsor: Supermicro

Hardware Availability: Nov-2007

Tested by: Supermicro

Software Availability: Nov-2007

Base Optimization Flags

C benchmarks:

```
-fast -inline-calloc -opt-malloc-options=3
```

C++ benchmarks:

```
-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs  
-L/home/cmplr/usr3/alrahate/cpu2006.1.0/lib -lsmartheap
```

Base Other Flags

C benchmarks:

```
403.gcc: -Dalloca=_alloca
```

Peak Compiler Invocation

C benchmarks (except as noted below):

```
icc
```

```
401.bzip2: /home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/bin/icc  
-L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/lib  
-I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/include
```

```
456.hmmer: /home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/bin/icc  
-L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/lib  
-I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/include
```

C++ benchmarks:

```
icpc
```

Peak Portability Flags

```
400.perlbench: -DSPEC_CPU_LINUX_IA32
```

```
401.bzip2: -DSPEC_CPU_LP64
```

```
456.hmmer: -DSPEC_CPU_LP64
```

```
462.libquantum: -DSPEC_CPU_LINUX
```

```
483.xalancbmk: -DSPEC_CPU_LINUX
```

Peak Optimization Flags

C benchmarks:

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro
Motherboard X7DVA-8

SPECint_rate2006 = 123
SPECint_rate_base2006 = 95.0

CPU2006 license: 001176

Test date: Nov-2007

Test sponsor: Supermicro

Hardware Availability: Nov-2007

Tested by: Supermicro

Software Availability: Nov-2007

Peak Optimization Flags (Continued)

400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -fast -ansi-alias
-prefetch

401.bzip2: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch

403.gcc: -fast -inline-calloc -opt-malloc-options=3

429.mcf: -fast -prefetch

445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xT -O2 -ipo
-no-prec-div -ansi-alias

456.hmmer: -fast -unroll12 -ansi-alias -opt-multi-version-aggressive

458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4

462.libquantum: -fast -unroll14 -O0 -prefetch
-opt-streaming-stores always -vec-guard-write
-opt-malloc-options=3 -parallel -par-runtime-control

464.h264ref: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll12
-ansi-alias

C++ benchmarks:

471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo
-no-prec-div -ansi-alias -opt-ra-region-strategy=block
-Wl,-z,muldefs
-L/home/cmpllr/usr3/alrahate/cpu2006.1.0/lib -lsmartheap

473.astar: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo
-no-prec-div -ansi-alias -opt-ra-region-strategy=routine
-Wl,-z,muldefs
-L/home/cmpllr/usr3/alrahate/cpu2006.1.0/lib -lsmartheap

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-INT-ia32-linux-flags.20090713.00.html>



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro
Motherboard X7DVA-8

SPECint_rate2006 = 123

SPECint_rate_base2006 = 95.0

CPU2006 license: 001176

Test sponsor: Supermicro

Tested by: Supermicro

Test date: Nov-2007

Hardware Availability: Nov-2007

Software Availability: Nov-2007

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-INT-ia32-linux-flags.20090713.00.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.1.

Report generated on Tue Jul 22 16:58:47 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 27 May 2008.