



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R460 E1  
(Intel Xeon E5205, 1.86GHz)

SPECfp®\_rate2006 = 37.9

SPECfp\_rate\_base2006 = 34.2

CPU2006 license: 20


Test sponsor: Bull SAS

Tested by: NEC Corporation

Test date: Feb-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007



**Hardware**

CPU Name: Intel Xeon E5205  
CPU Characteristics: 1.86 GHz, 6 MB L2, 1066 MHz bus  
CPU MHz: 1861  
FPU: Integrated  
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip  
CPU(s) orderable: 1,2 chips  
Primary Cache: 32 KB I + 32 KB D on chip per core  
Secondary Cache: 6 MB I+D on chip per chip

Continued on next page

**Software**

Operating System: SUSE Linux Enterprise Server 10 (x86\_64) SP1, Kernel 2.6.16.46-0.12-smpp  
Compiler: Intel C++ and Fortran Compiler for Linux32 and Linux64 version 10.1 Build 20070913 Package ID: l\_cc\_p\_10.1.008, l\_fc\_p\_10.1.008  
Auto Parallel: Yes  
File System: ext2

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R460 E1  
(Intel Xeon E5205, 1.86GHz)

SPECfp\_rate2006 = 37.9

SPECfp\_rate\_base2006 = 34.2

CPU2006 license: 20  
Test sponsor: Bull SAS  
Tested by: NEC Corporation

Test date: Feb-2008  
Hardware Availability: Jan-2008  
Software Availability: Nov-2007

L3 Cache: None  
Other Cache: None  
Memory: 12 GB (12x1 GB PC2-5300F, 2 rank, CL5-5-5, ECC)  
Disk Subsystem: 1x73.2 GB SAS, 15000RPM  
Other Hardware: None

System State: Run level 3 (multi-user)  
Base Pointers: 64-bit  
Peak Pointers: 32/64-bit  
Other Software: binutils-2.17.tar.gz, Version 2.17

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	4	1889	28.8	1901	28.6	<b><u>1898</u></b>	<b><u>28.6</u></b>	4	1857	29.3	<b><u>1853</u></b>	<b><u>29.3</u></b>	1852	29.4
416.gamess	4	1432	54.7	1437	54.5	<b><u>1432</u></b>	<b><u>54.7</u></b>	4	1415	55.3	1424	55.0	<b><u>1415</u></b>	<b><u>55.3</u></b>
433.milc	4	1958	18.8	1959	18.7	<b><u>1959</u></b>	<b><u>18.7</u></b>	4	1927	19.1	<b><u>1924</u></b>	<b><u>19.1</u></b>	1918	19.1
434.zeusmp	4	978	37.2	<b><u>981</u></b>	<b><u>37.1</u></b>	987	36.9	4	965	37.7	967	37.6	<b><u>965</u></b>	<b><u>37.7</u></b>
435.gromacs	4	606	47.1	<b><u>603</u></b>	<b><u>47.4</u></b>	599	47.7	4	<b><u>595</u></b>	<b><u>48.0</u></b>	594	48.1	597	47.8
436.cactusADM	4	1271	37.6	<b><u>1279</u></b>	<b><u>37.4</u></b>	1279	37.4	1	273	43.8	<b><u>272</u></b>	<b><u>43.9</u></b>	270	44.3
437.leslie3d	4	1745	21.6	1757	21.4	<b><u>1751</u></b>	<b><u>21.5</u></b>	4	1693	22.2	1696	22.2	<b><u>1695</u></b>	<b><u>22.2</u></b>
444.namd	4	814	39.4	813	39.5	<b><u>813</u></b>	<b><u>39.4</u></b>	4	809	39.7	<b><u>808</u></b>	<b><u>39.7</u></b>	807	39.7
447.dealII	4	770	59.4	<b><u>769</u></b>	<b><u>59.5</u></b>	767	59.7	4	<b><u>721</u></b>	<b><u>63.5</u></b>	722	63.4	721	63.5
450.soplex	4	1375	24.3	<b><u>1371</u></b>	<b><u>24.3</u></b>	1370	24.4	4	<b><u>1239</u></b>	<b><u>26.9</u></b>	1247	26.7	1236	27.0
453.povray	4	346	61.6	<b><u>340</u></b>	<b><u>62.6</u></b>	340	62.7	4	290	73.3	296	72.0	<b><u>291</u></b>	<b><u>73.1</u></b>
454.calculix	4	824	40.1	825	40.0	<b><u>825</u></b>	<b><u>40.0</u></b>	4	572	57.7	<b><u>572</u></b>	<b><u>57.7</u></b>	570	57.9
459.GemsFDTD	4	2121	20.0	<b><u>2108</u></b>	<b><u>20.1</u></b>	2083	20.4	4	2011	21.1	<b><u>2009</u></b>	<b><u>21.1</u></b>	2005	21.2
465.tonto	4	819	48.1	810	48.6	<b><u>818</u></b>	<b><u>48.1</u></b>	4	<b><u>796</u></b>	<b><u>49.4</u></b>	795	49.5	797	49.4
470.lbm	4	3866	14.2	<b><u>3851</u></b>	<b><u>14.3</u></b>	3843	14.3	2	<b><u>930</u></b>	<b><u>29.5</u></b>	932	29.5	925	29.7
481.wrf	4	1133	39.5	<b><u>1130</u></b>	<b><u>39.5</u></b>	1129	39.6	4	1133	39.4	<b><u>1133</u></b>	<b><u>39.4</u></b>	1131	39.5
482.sphinx3	4	<b><u>2079</u></b>	<b><u>37.5</u></b>	2081	37.5	2068	37.7	2	1077	36.2	<b><u>1079</u></b>	<b><u>36.1</u></b>	1079	36.1

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run  
'/usr/bin/taskset' used to bind processes to CPUs  
OMP\_NUM\_THREADS set to number of cores

## Platform Notes

Bios settings:  
Intel SpeedStep Technology: Disabled



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R460 E1  
(Intel Xeon E5205,1.86GHz)

SPECfp\_rate2006 = 37.9

SPECfp\_rate\_base2006 = 34.2

**CPU2006 license:** 20  
**Test sponsor:** Bull SAS  
**Tested by:** NEC Corporation

**Test date:** Feb-2008  
**Hardware Availability:** Jan-2008  
**Software Availability:** Nov-2007

### General Notes

All benchmarks compiled in 64-bit mode except 437.leslie3d, 450.soplex, 470.lbm and 482.sphinx3, for peak, are compiled in 32-bit mode

The NEC Express5800/120Rh-1(Intel Xeon Processor E5205), the NEC Express5800/120Rj-2(Intel Xeon Processor E5205), the Bull NovaScale R440 E1 (Intel Xeon E5205,1.86GHz) and the Bull NovaScale R460 E1 (Intel Xeon E5205,1.86GHz) models are electronically equivalent. The results have been measured on a NEC Express5800/120Rj-2(Intel Xeon Processor E5205) model.

### Base Compiler Invocation

C benchmarks:  
icc

C++ benchmarks:  
icpc

Fortran benchmarks:  
ifort

Benchmarks using both Fortran and C:  
icc ifort

### Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.deallI: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R460 E1  
(Intel Xeon E5205, 1.86GHz)

SPECfp\_rate2006 = 37.9

SPECfp\_rate\_base2006 = 34.2

**CPU2006 license:** 20  
**Test sponsor:** Bull SAS  
**Tested by:** NEC Corporation

**Test date:** Feb-2008  
**Hardware Availability:** Jan-2008  
**Software Availability:** Nov-2007

## Base Optimization Flags

C benchmarks:  
-fast

C++ benchmarks:  
-fast

Fortran benchmarks:  
-fast

Benchmarks using both Fortran and C:  
-fast

## Peak Compiler Invocation

C benchmarks (except as noted below):  
/opt/intel/cc/10.1.008/bin/icc -L/opt/intel/cc/10.1.008/lib  
-I/opt/intel/cc/10.1.008/include

433.milc: icc

C++ benchmarks (except as noted below):  
icpc

450.soplex: /opt/intel/cc/10.1.008/bin/icpc -L/opt/intel/cc/10.1.008/lib  
-I/opt/intel/cc/10.1.008/include

Fortran benchmarks (except as noted below):  
ifort

437.leslie3d: /opt/intel/fc/10.1.008/bin/ifort -L/opt/intel/fc/10.1.008/lib  
-I/opt/intel/fc/10.1.008/include

Benchmarks using both Fortran and C:  
icc ifort

## Peak Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R460 E1  
(Intel Xeon E5205, 1.86GHz)

SPECfp\_rate2006 = 37.9

SPECfp\_rate\_base2006 = 34.2

**CPU2006 license:** 20  
**Test sponsor:** Bull SAS  
**Tested by:** NEC Corporation

**Test date:** Feb-2008  
**Hardware Availability:** Jan-2008  
**Software Availability:** Nov-2007

## Peak Portability Flags (Continued)

453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

### C benchmarks:

433.milc: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias  
-auto-ilp32  
470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-scalar-rep- -prefetch -opt-malloc-options=3  
482.sphinx3: -fast -unroll2

### C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias  
-auto-ilp32  
447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-ansi-alias -scalar-rep-  
450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast  
-opt-malloc-options=3  
453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4  
-ansi-alias

### Fortran benchmarks:

410.bwaves: -fast -prefetch  
416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0  
-ansi-alias -scalar-rep-  
434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -fast  
437.leslie3d: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch  
-opt-malloc-options=3  
459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0  
-prefetch

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R460 E1  
(Intel Xeon E5205, 1.86GHz)

SPECfp\_rate2006 = 37.9

SPECfp\_rate\_base2006 = 34.2

**CPU2006 license:** 20  
**Test sponsor:** Bull SAS  
**Tested by:** NEC Corporation

**Test date:** Feb-2008  
**Hardware Availability:** Jan-2008  
**Software Availability:** Nov-2007

## Peak Optimization Flags (Continued)

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -auto

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch  
-auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-prefetch -parallel -auto-ilp32

454.calculix: -fast -unroll-aggressive -auto-ilp32

481.wrf: -fast -auto-ilp32

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/NEC-Intel-ic10.1-FP-intel64-linux-flags.20090713.00.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/NEC-Intel-ic10.1-FP-intel64-linux-flags.20090713.00.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.  
Report generated on Tue Jul 22 18:06:51 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 17 April 2008.