



# SPEC<sup>®</sup> CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R460 E1  
(Intel Xeon X5260,3.33GHz)

SPECfp<sup>®</sup>2006 = 23.6

SPECfp\_base2006 = 20.1

CPU2006 license: 20


Test sponsor: Bull SAS

Tested by: NEC Corporation

Test date: Feb-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007



### Hardware

CPU Name: Intel Xeon X5260  
 CPU Characteristics: 3.33 GHz, 6 MB L2, 1333 MHz bus  
 CPU MHz: 3333  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip  
 CPU(s) orderable: 1,2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 6 MB I+D on chip per chip

Continued on next page

### Software

Operating System: SUSE Linux Enterprise Server 10 (x86\_64) SP1,  
Kernel 2.6.16.46-0.12-smpp  
 Compiler: Intel C++ and Fortran Compiler for Linux32 and  
Linux64  
 version 10.1 Build 20070913 Package ID:  
l\_cc\_p\_10.1.008,  
l\_fc\_p\_10.1.008  
 Auto Parallel: Yes  
 File System: ext2

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R460 E1  
(Intel Xeon X5260,3.33GHz)

SPECfp2006 = 23.6

SPECfp\_base2006 = 20.1

CPU2006 license: 20  
Test sponsor: Bull SAS  
Tested by: NEC Corporation

Test date: Feb-2008  
Hardware Availability: Jan-2008  
Software Availability: Nov-2007

L3 Cache: None  
Other Cache: None  
Memory: 12 GB (12x1 GB PC2-5300F, 2 rank, CL5-5-5, ECC)  
Disk Subsystem: 1x146.5 GB SAS, 15000RPM  
Other Hardware: None

System State: Run level 3 (multi-user)  
Base Pointers: 64-bit  
Peak Pointers: 32/64-bit  
Other Software: binutils-2.17.tar.gz, Version 2.17

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	<b>419</b>	<b>32.4</b>	417	32.6	419	32.4	406	33.5	<b>405</b>	<b>33.6</b>	404	33.6
416.gamess	820	23.9	827	23.7	<b>822</b>	<b>23.8</b>	<b>791</b>	<b>24.8</b>	790	24.8	791	24.8
433.milc	<b>851</b>	<b>10.8</b>	850	10.8	854	10.8	852	10.8	850	10.8	<b>852</b>	<b>10.8</b>
434.zeusmp	<b>534</b>	<b>17.0</b>	535	17.0	534	17.0	555	16.4	<b>554</b>	<b>16.4</b>	554	16.4
435.gromacs	333	21.4	<b>333</b>	<b>21.4</b>	331	21.5	<b>331</b>	<b>21.6</b>	332	21.5	329	21.7
436.cactusADM	331	36.1	336	35.5	<b>334</b>	<b>35.8</b>	<b>182</b>	<b>65.5</b>	182	65.7	182	65.5
437.leslie3d	497	18.9	<b>497</b>	<b>18.9</b>	498	18.9	497	18.9	<b>497</b>	<b>18.9</b>	498	18.9
444.namd	456	17.6	<b>457</b>	<b>17.6</b>	457	17.5	<b>453</b>	<b>17.7</b>	453	17.7	453	17.7
447.dealII	<b>388</b>	<b>29.5</b>	388	29.5	389	29.4	365	31.3	<b>365</b>	<b>31.3</b>	365	31.3
450.soplex	659	12.7	659	12.7	<b>659</b>	<b>12.7</b>	<b>584</b>	<b>14.3</b>	584	14.3	586	14.2
453.povray	192	27.7	<b>192</b>	<b>27.7</b>	191	27.9	161	33.1	161	33.1	<b>161</b>	<b>33.1</b>
454.calculix	468	17.6	469	17.6	<b>468</b>	<b>17.6</b>	319	25.8	<b>320</b>	<b>25.8</b>	320	25.8
459.GemsFDTD	555	19.1	<b>555</b>	<b>19.1</b>	556	19.1	546	19.4	<b>546</b>	<b>19.4</b>	546	19.4
465.tonto	416	23.7	<b>416</b>	<b>23.6</b>	417	23.6	399	24.7	400	24.6	<b>399</b>	<b>24.6</b>
470.lbm	1868	7.36	<b>1870</b>	<b>7.35</b>	1871	7.34	<b>568</b>	<b>24.2</b>	567	24.2	569	24.1
481.wrf	<b>482</b>	<b>23.2</b>	483	23.1	482	23.2	483	23.1	484	23.1	<b>484</b>	<b>23.1</b>
482.sphinx3	680	28.7	674	28.9	<b>679</b>	<b>28.7</b>	645	30.2	<b>648</b>	<b>30.1</b>	659	29.6

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run  
OMP\_NUM\_THREADS set to number of cores

## Platform Notes

Bios settings:  
Intel SpeedStep Technology: Disabled

## General Notes

All benchmarks compiled in 64-bit mode except 450.soplex,  
470.lbm and 482.sphinx3, for peak, are compiled in 32-bit mode

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R460 E1  
(Intel Xeon X5260,3.33GHz)

SPECfp2006 = 23.6

SPECfp\_base2006 = 20.1

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: NEC Corporation

Test date: Feb-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007

## General Notes (Continued)

The NEC Express5800/120Rh-1(Intel Xeon Processor X5260), the NEC Express5800/120Rj-2(Intel Xeon Processor X5260), the Bull NovaScale R440 E1 (Intel Xeon X5260,3.33GHz) and the Bull NovaScale R460 E1 (Intel Xeon X5260,3.33GHz) models are electronically equivalent. The results have been measured on a NEC Express5800/120Rj-2(Intel Xeon Processor X5260) model.

## Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.deall: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:

-fast -parallel

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R460 E1  
(Intel Xeon X5260,3.33GHz)

SPECfp2006 = 23.6

SPECfp\_base2006 = 20.1

CPU2006 license: 20  
Test sponsor: Bull SAS  
Tested by: NEC Corporation

Test date: Feb-2008  
Hardware Availability: Jan-2008  
Software Availability: Nov-2007

## Base Optimization Flags (Continued)

C++ benchmarks:  
-fast -parallel

Fortran benchmarks:  
-fast -parallel

Benchmarks using both Fortran and C:  
-fast -parallel

## Peak Compiler Invocation

C benchmarks (except as noted below):  
/opt/intel/cc/10.1.008/bin/icc -L/opt/intel/cc/10.1.008/lib  
-I/opt/intel/cc/10.1.008/include

433.milc: icc

C++ benchmarks (except as noted below):  
icpc

450.soplex: /opt/intel/cc/10.1.008/bin/icpc -L/opt/intel/cc/10.1.008/lib  
-I/opt/intel/cc/10.1.008/include

Fortran benchmarks:  
ifort

Benchmarks using both Fortran and C:  
icc ifort

## Peak Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R460 E1  
(Intel Xeon X5260,3.33GHz)

SPECfp2006 = 23.6

SPECfp\_base2006 = 20.1

**CPU2006 license:** 20  
**Test sponsor:** Bull SAS  
**Tested by:** NEC Corporation

**Test date:** Feb-2008  
**Hardware Availability:** Jan-2008  
**Software Availability:** Nov-2007

## Peak Optimization Flags

### C benchmarks:

433.milc: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias  
-auto-ilp32

470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-scalar-rep- -prefetch -opt-malloc-options=3

482.sphinx3: -fast -unroll2

### C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias  
-auto-ilp32

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast  
-opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4  
-ansi-alias

### Fortran benchmarks:

410.bwaves: -fast -prefetch -parallel

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0  
-ansi-alias -scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -fast

437.leslie3d: basepeak = yes

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0  
-prefetch -parallel

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -auto

### Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch  
-auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-prefetch -parallel -auto-ilp32

454.calculix: -fast -unroll-aggressive -auto-ilp32

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R460 E1  
(Intel Xeon X5260,3.33GHz)

SPECfp2006 = 23.6

SPECfp\_base2006 = 20.1

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: NEC Corporation

Test date: Feb-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007

## Peak Optimization Flags (Continued)

481.wrf: -fast -parallel -prefetch -auto-ilp32

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/NEC-Intel-ic10.1-FP-intel64-linux-flags.20090713.00.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/NEC-Intel-ic10.1-FP-intel64-linux-flags.20090713.00.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.  
Report generated on Tue Jul 22 18:02:18 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 17 April 2008.