



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R440 E1
(Intel Xeon E5430, 2.66 GHz)

SPECfp®_rate2006 = 39.9

SPECfp_rate_base2006 = 36.7

CPU2006 license: 20


Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: May-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007



Hardware

CPU Name: Intel Xeon E5430
CPU Characteristics: 1333 MHz system bus
CPU MHz: 2666
FPU: Integrated
CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip
CPU(s) orderable: 1,2 chips
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores

Continued on next page

Software

Operating System: SUSE LINUX Enterprise Server 10 SP1
Kernel 2.6.16.46-0.12-smp for x86_64
Compiler: Intel C++ and Fortran Compiler 10.1 for Linux
Build 20070913 Package ID: l_cc_p_10.1.008,
l_fc_p_10.1.008
Auto Parallel: Yes
File System: ext2
System State: Run level 3 (multi-user)
Base Pointers: 64-bit

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R440 E1
(Intel Xeon E5430, 2.66 GHz)

SPECfp_rate2006 = 39.9

SPECfp_rate_base2006 = 36.7

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: May-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007

L3 Cache: None
Other Cache: None
Memory: 16 GB (8x2 GB) FB-DIMM PC2-5300F ECC CL5
Disk Subsystem: 1x73 GB SAS, 15000 RPM
Other Hardware: None

Peak Pointers: 32/64-bit
Other Software: Binutils 2.17.50.0.15

Results Table

Benchmark	Base								Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	4	2525	21.5	<u>2527</u>	<u>21.5</u>	2533	21.5	4	<u>2367</u>	<u>23.0</u>	2366	23.0	2376	22.9		
416.gamess	4	<u>999</u>	<u>78.4</u>	1002	78.2	999	78.4	4	990	79.1	<u>988</u>	<u>79.3</u>	987	79.4		
433.milc	4	<u>2566</u>	<u>14.3</u>	2559	14.3	2572	14.3	4	2543	14.4	<u>2540</u>	<u>14.5</u>	2540	14.5		
434.zeusmp	4	863	42.2	<u>864</u>	<u>42.2</u>	864	42.2	4	830	43.9	<u>835</u>	<u>43.6</u>	835	43.6		
435.gromacs	4	420	67.9	419	68.1	<u>419</u>	<u>68.1</u>	4	415	68.8	<u>416</u>	<u>68.7</u>	419	68.2		
436.cactusADM	4	<u>1014</u>	<u>47.1</u>	1012	47.2	1021	46.8	1	198	60.4	<u>194</u>	<u>61.6</u>	192	62.3		
437.leslie3d	4	2345	16.0	<u>2351</u>	<u>16.0</u>	2354	16.0	4	2101	17.9	<u>2099</u>	<u>17.9</u>	2099	17.9		
444.namd	4	571	56.2	<u>570</u>	<u>56.2</u>	570	56.3	4	<u>566</u>	<u>56.7</u>	566	56.7	566	56.7		
447.dealII	4	553	82.8	551	83.1	<u>551</u>	<u>83.1</u>	4	529	86.4	<u>530</u>	<u>86.4</u>	537	85.2		
450.soplex	4	1590	21.0	<u>1589</u>	<u>21.0</u>	1589	21.0	4	<u>1321</u>	<u>25.3</u>	1318	25.3	1327	25.1		
453.povray	4	237	89.8	<u>238</u>	<u>89.3</u>	243	87.4	4	<u>203</u>	<u>105</u>	203	105	203	105		
454.calculix	4	596	55.3	<u>596</u>	<u>55.4</u>	596	55.4	4	413	80.0	418	79.0	<u>413</u>	<u>79.9</u>		
459.GemsFDTD	4	2794	15.2	2817	15.1	<u>2811</u>	<u>15.1</u>	4	2760	15.4	2750	15.4	<u>2751</u>	<u>15.4</u>		
465.tonto	4	<u>633</u>	<u>62.2</u>	631	62.3	636	61.9	4	615	64.0	<u>618</u>	<u>63.7</u>	619	63.6		
470.lbm	4	<u>3289</u>	<u>16.7</u>	3290	16.7	3288	16.7	4	3220	17.1	3222	17.1	<u>3221</u>	<u>17.1</u>		
481.wrf	4	1365	32.7	1368	32.7	<u>1367</u>	<u>32.7</u>	4	<u>1366</u>	<u>32.7</u>	1363	32.8	1372	32.6		
482.sphinx3	4	<u>2554</u>	<u>30.5</u>	2561	30.4	2550	30.6	4	2376	32.8	2360	33.0	<u>2364</u>	<u>33.0</u>		

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
'/usr/bin/taskset' used to bind processes to CPUs
OMP_NUM_THREADS set to number of cores
KMP_AFFINITY set to physical,0
KMP_STACKSIZE set to 64M

General Notes

All benchmarks compiled in 64-bit mode except 450.soplex, 470.lbm and 482.sphinx3, at peak, are compiled in 32-bit mode
The Bull NovaScale R440 E1 (Intel Xeon E5430, 2.66 GHz) and the Bull NovaScale R460 E1 (Intel Xeon E5430, 2.66 GHz) models are electronically equivalent.
The results have been measured on a Bull NovaScale R460 E1 (Intel Xeon E5430, 2.66 GHz) model.



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R440 E1
(Intel Xeon E5430, 2.66 GHz)

SPECfp_rate2006 = 39.9

SPECfp_rate_base2006 = 36.7

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: May-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007

Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:

-fast

C++ benchmarks:

-fast

Fortran benchmarks:

-fast

Benchmarks using both Fortran and C:

-fast



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R440 E1
(Intel Xeon E5430, 2.66 GHz)

SPECfp_rate2006 = 39.9

SPECfp_rate_base2006 = 36.7

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: May-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007

Peak Compiler Invocation

C benchmarks (except as noted below):

```
/opt/intel/cc/10.1.008/bin/icc -L/opt/intel/cc/10.1.008/lib  
-I/opt/intel/cc/10.1.008/include
```

433.milc: icc

C++ benchmarks (except as noted below):

icpc

```
450.soplex: /opt/intel/cc/10.1.008/bin/icpc -L/opt/intel/cc/10.1.008/lib  
-I/opt/intel/cc/10.1.008/include
```

Fortran benchmarks (except as noted below):

ifort

```
437.leslie3d: /opt/intel/fc/10.1.008/bin/ifort -L/opt/intel/fc/10.1.008/lib  
-I/opt/intel/fc/10.1.008/include
```

Benchmarks using both Fortran and C:

icc ifort

Peak Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64  
416.gamess: -DSPEC_CPU_LP64  
433.milc: -DSPEC_CPU_LP64  
434.zeusmp: -DSPEC_CPU_LP64  
435.gromacs: -DSPEC_CPU_LP64 -nofor_main  
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main  
444.namd: -DSPEC_CPU_LP64  
447.dealII: -DSPEC_CPU_LP64  
453.povray: -DSPEC_CPU_LP64  
454.calculix: -DSPEC_CPU_LP64 -nofor_main  
459.GemsFDTD: -DSPEC_CPU_LP64  
465.tonto: -DSPEC_CPU_LP64  
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
```

Peak Optimization Flags

C benchmarks:

```
433.milc: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias  
-auto-ilp32
```

```
470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-scalar-rep- -prefetch -opt-malloc-options=3
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R440 E1
(Intel Xeon E5430, 2.66 GHz)

SPECfp_rate2006 = 39.9

SPECfp_rate_base2006 = 36.7

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: May-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007

Peak Optimization Flags (Continued)

482.sphinx3: -fast -unroll2

C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast
-opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4
-ansi-alias

Fortran benchmarks:

410.bwaves: -fast -prefetch

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0
-ansi-alias -scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -fast

437.leslie3d: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-opt-malloc-options=3

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0
-prefetch

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -auto

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-prefetch -parallel -auto-ilp32

454.calculix: -fast -unroll-aggressive -auto-ilp32

481.wrf: -fast -auto-ilp32

The flags file that was used to format this result can be browsed at

http://www.spec.org/cpu2006/flags/EM64T_Intel101_fp_flags.20090713.00.html



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R440 E1
(Intel Xeon E5430, 2.66 GHz)

SPECfp_rate2006 = 39.9

SPECfp_rate_base2006 = 36.7

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: May-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007

You can also download the XML flags source by saving the following link:

http://www.spec.org/cpu2006/flags/EM64T_Intel101_fp_flags.20090713.00.xml

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 19:54:42 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 8 July 2008.