



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu Siemens Computers

PRIMERGY RX200 S4, Intel Xeon X5470, 3.33 GHz

**SPECint\_rate2006 = 150**

**SPECint\_rate\_base2006 = 137**

CPU2006 license: 22


Test date: Nov-2008

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: Oct-2008

Tested by: Fujitsu Siemens Computers

Software Availability: Aug-2008



### Hardware

CPU Name: Intel Xeon X5470  
CPU Characteristics: 1333 MHz system bus  
CPU MHz: 3333  
FPU: Integrated  
CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip  
CPU(s) orderable: 1,2 chips  
Primary Cache: 32 KB I + 32 KB D on chip per core  
Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores  
L3 Cache: None  
Other Cache: None  
Memory: 16 GB (8x2 GB PC2-5300F, 2 rank, CL5-5-5, ECC)  
Disk Subsystem: 1x SATA, 80 GB, 7200 rpm  
Other Hardware: None

### Software

Operating System: SUSE Linux Enterprise Server 10 (x86\_64) SP2, Kernel 2.6.16.60-0.21-smp  
Compiler: Intel C++ Compiler 11.0 for Linux Build 20080730 Package ID: l\_cproc\_b\_11.0.042  
Auto Parallel: Yes  
File System: ext3  
System State: Multi-User Run Level 3  
Base Pointers: 32-bit  
Peak Pointers: 32/64-bit  
Other Software: Microquill SmartHeap Library, Version 8.1 Binutils 2.18.50.0.7.20080502



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu Siemens Computers

PRIMERGY RX200 S4, Intel Xeon X5470, 3.33 GHz

**SPECint\_rate2006 = 150**

CPU2006 license: 22

Test date: Nov-2008

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: Oct-2008

Tested by: Fujitsu Siemens Computers

Software Availability: Aug-2008

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	8	<b>445</b>	<b>176</b>	446	175	444	176	8	389	201	383	204	<b>385</b>	<b>203</b>
401.bzip2	8	<b>648</b>	<b>119</b>	652	118	648	119	8	619	125	<b>619</b>	<b>125</b>	615	126
403.gcc	8	<b>628</b>	<b>102</b>	628	103	633	102	8	<b>628</b>	<b>103</b>	627	103	633	102
429.mcf	8	691	106	<b>691</b>	<b>106</b>	690	106	8	709	103	708	103	<b>708</b>	<b>103</b>
445.gobmk	8	<b>498</b>	<b>168</b>	497	169	499	168	8	<b>470</b>	<b>178</b>	471	178	469	179
456.hammer	8	423	176	<b>423</b>	<b>176</b>	423	177	8	332	225	<b>332</b>	<b>225</b>	332	225
458.sjeng	8	562	172	562	172	<b>562</b>	<b>172</b>	8	536	181	536	180	<b>536</b>	<b>180</b>
462.libquantum	8	889	186	888	187	<b>888</b>	<b>187</b>	1	<b>71.7</b>	<b>289</b>	71.7	289	71.9	288
464.h264ref	8	<b>602</b>	<b>294</b>	602	294	603	293	8	574	308	<b>574</b>	<b>309</b>	573	309
471.omnetpp	8	<b>817</b>	<b>61.2</b>	817	61.2	817	61.2	8	<b>806</b>	<b>62.0</b>	806	62.0	809	61.8
473.astar	8	682	82.3	680	82.6	<b>682</b>	<b>82.4</b>	8	<b>615</b>	<b>91.3</b>	613	91.5	616	91.2
483.xalancbmk	8	419	132	<b>420</b>	<b>131</b>	420	131	8	419	132	<b>420</b>	<b>131</b>	420	131

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Compiler Invocation Notes

All binaries were built with 32-bit mode except:  
401.bzip2 and 456.hammer in peak were built with 64-bit mode.

## Submit Notes

The config file option 'submit' was used.

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run  
OMP\_NUM\_THREADS set to number of cores (default)  
KMP\_AFFINITY set to "physical,0"  
KMP\_STACKSIZE set to 64M

## Platform Notes

BIOS configuration:  
Adjacent Sector Prefetch = Disable  
Memory Throttling = Enable

## General Notes

taskset has been used to bind processes to cores except  
for 462.libquantum peak

For information about Fujitsu Siemens Computers please see:  
Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu Siemens Computers

PRIMERGY RX200 S4, Intel Xeon X5470, 3.33 GHz

**SPECint\_rate2006 = 150**

CPU2006 license: 22

**Test date:** Nov-2008

**Test sponsor:** Fujitsu Siemens Computers

**Hardware Availability:** Oct-2008

**Tested by:** Fujitsu Siemens Computers

**Software Availability:** Aug-2008

## General Notes (Continued)

<http://www.fujitsu-siemens.com>

## Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32

462.libquantum: -DSPEC\_CPU\_LINUX

483.xalancbmk: -DSPEC\_CPU\_LINUX

## Base Optimization Flags

C benchmarks:

-xSSE4.1 -ipo -O3 -no-prec-div -static -inline-calloc  
-opt-malloc-options=3 -opt-prefetch

C++ benchmarks:

-xSSE4.1 -ipo -O3 -no-prec-div -opt-prefetch -Wl,-z,muldefs  
-L/spec/cpu2006.1.1/lib -lsmartheap

## Base Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

## Peak Compiler Invocation

C benchmarks (except as noted below):

icc

401.bzip2: /opt/intel/Compiler/11.0/042/bin/intel64/icc  
-L/opt/intel/Compiler/11.0/042/ipp/em64t/lib  
-I/opt/intel/Compiler/11.0/042/ipp/em64t/include

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu Siemens Computers

PRIMERGY RX200 S4, Intel Xeon X5470, 3.33 GHz

**SPECint\_rate2006 = 150**

CPU2006 license: 22

Test date: Nov-2008

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: Oct-2008

Tested by: Fujitsu Siemens Computers

Software Availability: Aug-2008

## Peak Compiler Invocation (Continued)

```
456.hmmer: /opt/intel/Compiler/11.0/042/bin/intel64/icc  
          -L/opt/intel/Compiler/11.0/042/ipp/em64t/lib  
          -I/opt/intel/Compiler/11.0/042/ipp/em64t/include
```

C++ benchmarks:

```
icpc
```

## Peak Portability Flags

```
400.perlbench: -DSPEC_CPU_LINUX_IA32  
401.bzip2: -DSPEC_CPU_LP64  
456.hmmer: -DSPEC_CPU_LP64  
462.libquantum: -DSPEC_CPU_LINUX  
483.xalancbmk: -DSPEC_CPU_LINUX
```

## Peak Optimization Flags

C benchmarks:

```
400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3  
              -no-prec-div -static -ansi-alias -opt-prefetch  
  
401.bzip2: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3  
              -no-prec-div -static -opt-prefetch -ansi-alias  
  
403.gcc: -xSSE4.1 -ipo -O3 -no-prec-div -static -inline-calloc  
          -opt-malloc-options=3  
  
429.mcf: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3  
          -no-prec-div -static -opt-prefetch  
  
445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -O2 -ipo  
            -no-prec-div -ansi-alias  
  
456.hmmer: -xSSE4.1 -ipo -O3 -no-prec-div -static -unroll12  
            -ansi-alias  
  
458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3  
            -no-prec-div -static -unroll14  
  
462.libquantum: -xSSE4.1 -ipo -O3 -no-prec-div -static  
                -opt-malloc-options=3 -parallel -par-runtime-control  
                -opt-prefetch  
  
464.h264ref: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3  
              -no-prec-div -static -unroll12 -ansi-alias
```

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu Siemens Computers

PRIMERGY RX200 S4, Intel Xeon X5470, 3.33 GHz

**SPECint\_rate2006 = 150**

**CPU2006 license:** 22

**Test date:** Nov-2008

**Test sponsor:** Fujitsu Siemens Computers

**Hardware Availability:** Oct-2008

**Tested by:** Fujitsu Siemens Computers

**Software Availability:** Aug-2008

**SPECint\_rate\_base2006 = 137**

## Peak Optimization Flags (Continued)

C++ benchmarks:

```
471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3  
           -no-prec-div -ansi-alias -opt-ra-region-strategy=block  
           -Wl,-z,muldefs -L/spec/cpu2006.1.1/lib -lsmartheap
```

```
473.astar: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3  
           -no-prec-div -ansi-alias -opt-ra-region-strategy=routine  
           -Wl,-z,muldefs -L/spec/cpu2006.1.1/lib -lsmartheap
```

```
483.xalancbmk: basepeak = yes
```

## Peak Other Flags

C benchmarks:

```
403.gcc: -Dalloca=_alloca
```

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-int-linux64-revD.20090714.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-int-linux64-revD.20090714.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.

Report generated on Tue Jul 22 19:33:16 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 16 September 2008.