



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale B260
(Intel Xeon E5440, 2.83 GHz)

SPECfp®_rate2006 = 66.2

SPECfp_rate_base2006 = 58.6

CPU2006 license: 20


Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Sep-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007



SPECfp_rate_base2006 = 58.6

SPECfp_rate2006 = 66.2

Hardware

CPU Name: Intel Xeon E5440
CPU Characteristics: 1333 MHz system bus
CPU MHz: 2833
FPU: Integrated
CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
CPU(s) orderable: 1,2 chips
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores

Software

Operating System: SUSE LINUX Enterprise Server 10 (x86_64) SP1
Compiler: Intel C++ and Fortran Compiler 10.1 for Linux
Build 20070913 Package ID: l_cc_p_10.1.008,
l_fc_p_10.1.008
Auto Parallel: Yes
File System: ext2
System State: Run level 3 (multi-user)
Base Pointers: 64-bit

Continued on next page

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale B260
(Intel Xeon E5440, 2.83 GHz)

SPECfp_rate2006 = 66.2

SPECfp_rate_base2006 = 58.6

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Sep-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007

L3 Cache: None
Other Cache: None
Memory: 16 GB (4x4 GB) FB-DIMM PC2-5300F ECC CL5
Disk Subsystem: 1x73 GB SAS, 15000 RPM
Other Hardware: None

Peak Pointers: 32/64-bit
Other Software: Binutils 2.17.50.0.15

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	8	3250	33.5	3277	33.2	<u>3277</u>	<u>33.2</u>	4	1605	33.9	1631	33.3	<u>1611</u>	<u>33.7</u>
416.gamess	8	<u>939</u>	<u>167</u>	938	167	940	167	8	926	169	928	169	<u>927</u>	<u>169</u>
433.milc	8	3529	20.8	<u>3529</u>	<u>20.8</u>	3518	20.9	8	<u>3490</u>	<u>21.0</u>	3489	21.0	3497	21.0
434.zeusmp	8	1159	62.8	<u>1150</u>	<u>63.3</u>	1142	63.8	8	1139	63.9	<u>1140</u>	<u>63.9</u>	1153	63.2
435.gromacs	8	400	143	<u>401</u>	<u>142</u>	404	141	8	395	145	403	142	<u>396</u>	<u>144</u>
436.cactusADM	8	1437	66.5	<u>1439</u>	<u>66.4</u>	1441	66.3	1	129	92.8	<u>129</u>	<u>93.0</u>	128	93.4
437.leslie3d	8	3321	22.6	<u>3253</u>	<u>23.1</u>	3252	23.1	4	<u>1521</u>	<u>24.7</u>	1521	24.7	1520	24.7
444.namd	8	536	120	<u>536</u>	<u>120</u>	543	118	8	<u>533</u>	<u>120</u>	533	120	540	119
447.dealII	8	677	135	673	136	<u>676</u>	<u>135</u>	8	675	136	<u>657</u>	<u>139</u>	654	140
450.soplex	8	2123	31.4	<u>2123</u>	<u>31.4</u>	2125	31.4	8	<u>1949</u>	<u>34.2</u>	1945	34.3	1950	34.2
453.povray	8	<u>227</u>	<u>188</u>	227	187	224	190	8	<u>191</u>	<u>223</u>	191	223	191	222
454.calculix	8	581	114	<u>578</u>	<u>114</u>	575	115	8	<u>422</u>	<u>156</u>	421	157	428	154
459.GemsFDTD	8	4278	19.8	<u>4280</u>	<u>19.8</u>	4281	19.8	8	4239	20.0	<u>4242</u>	<u>20.0</u>	4247	20.0
465.tonto	8	809	97.3	824	95.5	<u>820</u>	<u>96.0</u>	8	<u>802</u>	<u>98.2</u>	828	95.1	791	99.6
470.lbm	8	7360	14.9	<u>7357</u>	<u>14.9</u>	7356	14.9	4	2406	22.8	<u>2412</u>	<u>22.8</u>	2414	22.8
481.wrf	8	2119	42.2	2112	42.3	<u>2114</u>	<u>42.3</u>	8	<u>2114</u>	<u>42.3</u>	2115	42.3	2111	42.3
482.sphinx3	8	2904	53.7	2893	53.9	<u>2899</u>	<u>53.8</u>	4	830	93.9	841	92.7	<u>841</u>	<u>92.7</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The config file option 'submit' was used.

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
 '/usr/bin/taskset' used to bind processes to CPUs
 OMP_NUM_THREADS set to number of cores
 KMP_AFFINITY set to physical,0
 KMP_STACKSIZE set to 64M



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale B260
(Intel Xeon E5440, 2.83 GHz)

SPECfp_rate2006 = 66.2

SPECfp_rate_base2006 = 58.6

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Sep-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007

General Notes

All benchmarks compiled in 64-bit mode except 437.leslie3d, 450.soplex, 470.lbm and 482.sphinx3, at peak, are compiled in 32-bit mode

Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:

-fast

C++ benchmarks:

-fast

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale B260
(Intel Xeon E5440, 2.83 GHz)

SPECfp_rate2006 = 66.2

SPECfp_rate_base2006 = 58.6

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Sep-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007

Base Optimization Flags (Continued)

Fortran benchmarks:

-fast

Benchmarks using both Fortran and C:

-fast

Peak Compiler Invocation

C benchmarks (except as noted below):

/opt/intel/cc/10.1.008/bin/icc -L/opt/intel/cc/10.1.008/lib
-I/opt/intel/cc/10.1.008/include

433.milc: icc

C++ benchmarks (except as noted below):

icpc

450.soplex: /opt/intel/cc/10.1.008/bin/icpc -L/opt/intel/cc/10.1.008/lib
-I/opt/intel/cc/10.1.008/include

Fortran benchmarks (except as noted below):

ifort

437.leslie3d: /opt/intel/fc/10.1.008/bin/ifort -L/opt/intel/fc/10.1.008/lib
-I/opt/intel/fc/10.1.008/include

Benchmarks using both Fortran and C:

icc ifort

Peak Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale B260
(Intel Xeon E5440, 2.83 GHz)

SPECfp_rate2006 = 66.2

SPECfp_rate_base2006 = 58.6

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Sep-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007

Peak Optimization Flags

C benchmarks:

433.milc: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32

470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-scalar-rep- -prefetch -opt-malloc-options=3

482.sphinx3: -fast -unroll2

C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast
-opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4
-ansi-alias

Fortran benchmarks:

410.bwaves: -fast -prefetch

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -O0
-ansi-alias -scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -fast

437.leslie3d: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-opt-malloc-options=3

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -O0
-prefetch

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -auto

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-prefetch -parallel -auto-ilp32

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale B260
(Intel Xeon E5440, 2.83 GHz)

SPECfp_rate2006 = 66.2

SPECfp_rate_base2006 = 58.6

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Sep-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007

Peak Optimization Flags (Continued)

454.calculix: -fast -unroll-aggressive -auto-ilp32

481.wrf: -fast -auto-ilp32

The flags file that was used to format this result can be browsed at

http://www.spec.org/cpu2006/flags/EM64T_Intel101_fp_flags.20090713.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/cpu2006/flags/EM64T_Intel101_fp_flags.20090713.xml

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.

Report generated on Tue Jul 22 18:42:13 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 30 September 2008.