



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale B260
(Intel Xeon E5430, 2.66 GHz)

SPECfp[®]_rate2006 = 64.6

SPECfp_rate_base2006 = 57.3

CPU2006 license: 20


Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Sep-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007



SPECfp_rate_base2006 = 57.3

SPECfp_rate2006 = 64.6

Hardware

CPU Name: Intel Xeon E5430
CPU Characteristics: 1333 MHz system bus
CPU MHz: 2666
FPU: Integrated
CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
CPU(s) orderable: 1,2 chips
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores

Software

Operating System: SUSE LINUX Enterprise Server 10 (x86_64) SP1
Compiler: Intel C++ and Fortran Compiler 10.1 for Linux
Build 20070913 Package ID: l_cc_p_10.1.008,
l_fc_p_10.1.008
Auto Parallel: Yes
File System: ext2
System State: Run level 3 (multi-user)
Base Pointers: 64-bit

Continued on next page

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale B260
(Intel Xeon E5430, 2.66 GHz)

SPECfp_rate2006 = 64.6

SPECfp_rate_base2006 = 57.3

CPU2006 license: 20

Test date: Sep-2008

Test sponsor: Bull SAS

Hardware Availability: Jan-2008

Tested by: Bull SAS

Software Availability: Nov-2007

L3 Cache: None
Other Cache: None
Memory: 16 GB (4x4 GB) FB-DIMM PC2-5300F ECC CL5
Disk Subsystem: 1x73 GB SAS, 15000 RPM
Other Hardware: None

Peak Pointers: 32/64-bit
Other Software: Binutils 2.17.50.0.15

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	8	3257	33.4	3294	33.0	<u>3274</u>	<u>33.2</u>	4	1602	33.9	<u>1605</u>	<u>33.9</u>	1622	33.5
416.gamess	8	997	157	1000	157	<u>998</u>	<u>157</u>	8	993	158	984	159	<u>985</u>	<u>159</u>
433.milc	8	3541	20.7	3524	20.8	<u>3526</u>	<u>20.8</u>	8	<u>3492</u>	<u>21.0</u>	3489	21.1	3501	21.0
434.zeusmp	8	<u>1160</u>	<u>62.8</u>	1149	63.4	1163	62.6	8	<u>1149</u>	<u>63.4</u>	1159	62.8	1139	63.9
435.gromacs	8	427	134	<u>424</u>	<u>135</u>	423	135	8	<u>418</u>	<u>137</u>	424	135	418	137
436.cactusADM	8	1454	65.7	1439	66.4	<u>1440</u>	<u>66.4</u>	1	131	91.2	132	90.5	<u>131</u>	<u>91.2</u>
437.leslie3d	8	3262	23.1	<u>3255</u>	<u>23.1</u>	3250	23.1	4	<u>1512</u>	<u>24.9</u>	1508	24.9	1523	24.7
444.namd	8	573	112	<u>569</u>	<u>113</u>	569	113	8	574	112	<u>566</u>	<u>113</u>	565	114
447.dealII	8	700	131	693	132	<u>697</u>	<u>131</u>	8	669	137	<u>675</u>	<u>136</u>	718	127
450.soplex	8	2139	31.2	2124	31.4	<u>2128</u>	<u>31.4</u>	8	1950	34.2	<u>1949</u>	<u>34.2</u>	1946	34.3
453.povray	8	<u>241</u>	<u>177</u>	241	177	239	178	8	203	210	<u>203</u>	<u>210</u>	206	206
454.calculix	8	607	109	<u>607</u>	<u>109</u>	610	108	8	437	151	445	148	<u>442</u>	<u>149</u>
459.GemsFDTD	8	4274	19.9	4269	19.9	<u>4270</u>	<u>19.9</u>	8	<u>4231</u>	<u>20.1</u>	4225	20.1	4235	20.0
465.tonto	8	848	92.8	<u>852</u>	<u>92.3</u>	868	90.6	8	867	90.8	<u>840</u>	<u>93.7</u>	813	96.8
470.lbm	8	7356	14.9	<u>7356</u>	<u>14.9</u>	7354	14.9	4	2414	22.8	<u>2415</u>	<u>22.8</u>	2421	22.7
481.wrf	8	2115	42.3	<u>2113</u>	<u>42.3</u>	2113	42.3	8	<u>2109</u>	<u>42.4</u>	2111	42.3	2107	42.4
482.sphinx3	8	2883	54.1	<u>2890</u>	<u>53.9</u>	2895	53.9	4	871	89.6	867	90.0	<u>867</u>	<u>89.9</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The config file option 'submit' was used.
taskset was used to bind processes to cores except
for 436.cactusADM peak

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
OMP_NUM_THREADS set to number of cores
KMP_AFFINITY set to physical,0
KMP_STACKSIZE set to 64M



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale B260
(Intel Xeon E5430, 2.66 GHz)

SPECfp_rate2006 = 64.6

SPECfp_rate_base2006 = 57.3

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Sep-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007

Platform Notes

BIOS configuration:

Hardware Prefetcher Enabled

Adjacent Cache-Line Prefetch Disabled

General Notes

All benchmarks compiled in 64-bit mode except 437.leslie3d, 450.soplex, 470.lbm and 482.sphinx3, at peak, are compiled in 32-bit mode

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale B260
(Intel Xeon E5430, 2.66 GHz)

SPECfp_rate2006 = 64.6

SPECfp_rate_base2006 = 57.3

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Sep-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007

Base Optimization Flags

C benchmarks:
-fast

C++ benchmarks:
-fast

Fortran benchmarks:
-fast

Benchmarks using both Fortran and C:
-fast

Peak Compiler Invocation

C benchmarks (except as noted below):

```
/opt/intel/cc/10.1.008/bin/icc -L/opt/intel/cc/10.1.008/lib  
-I/opt/intel/cc/10.1.008/include
```

433.milc: icc

C++ benchmarks (except as noted below):

```
icpc
```

```
450.soplex: /opt/intel/cc/10.1.008/bin/icpc -L/opt/intel/cc/10.1.008/lib  
-I/opt/intel/cc/10.1.008/include
```

Fortran benchmarks (except as noted below):

```
ifort
```

```
437.leslie3d: /opt/intel/fc/10.1.008/bin/ifort -L/opt/intel/fc/10.1.008/lib  
-I/opt/intel/fc/10.1.008/include
```

Benchmarks using both Fortran and C:

```
icc ifort
```

Peak Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64  
416.gamess: -DSPEC_CPU_LP64  
    433.milc: -DSPEC_CPU_LP64  
434.zeusmp: -DSPEC_CPU_LP64  
435.gromacs: -DSPEC_CPU_LP64 -nofor_main  
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main  
    444.namd: -DSPEC_CPU_LP64  
447.dealII: -DSPEC_CPU_LP64
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale B260
(Intel Xeon E5430, 2.66 GHz)

SPECfp_rate2006 = 64.6

SPECfp_rate_base2006 = 57.3

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Sep-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007

Peak Portability Flags (Continued)

```
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
```

Peak Optimization Flags

C benchmarks:

```
433.milc: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
           -auto-ilp32

470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
          -scalar-rep -prefetch -opt-malloc-options=3

482.sphinx3: -fast -unroll2
```

C++ benchmarks:

```
444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
           -auto-ilp32

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
            -ansi-alias -scalar-rep

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast
            -opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4
            -ansi-alias
```

Fortran benchmarks:

```
410.bwaves: -fast -prefetch

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -O0
            -ansi-alias -scalar-rep

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -fast

437.leslie3d: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
              -opt-malloc-options=3

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -O0
               -prefetch
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale B260
(Intel Xeon E5430, 2.66 GHz)

SPECfp_rate2006 = 64.6

SPECfp_rate_base2006 = 57.3

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Sep-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007

Peak Optimization Flags (Continued)

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll14 -auto

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll12
-prefetch -parallel -auto-ilp32

454.calculix: -fast -unroll-aggressive -auto-ilp32

481.wrf: -fast -auto-ilp32

The flags file that was used to format this result can be browsed at

http://www.spec.org/cpu2006/flags/EM64T_Intel101_fp_flags.20090713.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/cpu2006/flags/EM64T_Intel101_fp_flags.20090713.xml

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.

Report generated on Tue Jul 22 20:30:01 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 29 October 2008.