



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ACTION S.A.

SPECfp®_rate2006 = 64.8

ACTINA SOLAR 220 X2 (Intel Xeon E5405, 2.0 GHz)

SPECfp_rate_base2006 = 59.7

CPU2006 license: 9008


Test sponsor: ACTION S.A.

Tested by: ACTION S.A.

Test date: Dec-2008

Hardware Availability: Sep-2008

Software Availability: Nov-2008



Hardware

CPU Name: Intel Xeon E5405
 CPU Characteristics: 1333 MHz System Bus
 CPU MHz: 2000
 FPU: Integrated
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
 CPU(s) orderable: 1,2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores

Continued on next page

Software

Operating System: SuSE Linux Enterprise Server 10 (x86_64) with SP2, kernel 2.6.16.60-0.21-smp
 Compiler: Intel C++ and Fortran Compiler 11.0 for Linux Build 20080730 Package ID: l_cproc_b_11.0.042, l_fproc_b_11.0.042
 Auto Parallel: Yes
 File System: ReiserFS
 System State: Run level 3 (multi-user)
 Base Pointers: 64-bit

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ACTION S.A.

SPECfp_rate2006 = 64.8

ACTINA SOLAR 220 X2 (Intel Xeon E5405, 2.0 GHz)

SPECfp_rate_base2006 = 59.7

CPU2006 license: 9008

Test date: Dec-2008

Test sponsor: ACTION S.A.

Hardware Availability: Sep-2008

Tested by: ACTION S.A.

Software Availability: Nov-2008

L3 Cache: None
Other Cache: None
Memory: 16 GB (8x2 GB, PC2-5300, CL 5-5-5, FB ECC)
Disk Subsystem: 500 GB SATA, 7200 RPM
Other Hardware: None

Peak Pointers: 32/64-bit
Other Software: Binutils 2.18.50.0.7.20080502

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	8	3214	33.8	<u>3212</u>	<u>33.8</u>	3211	33.9	4	1598	34.0	<u>1599</u>	<u>34.0</u>	1599	34.0
416.gamess	8	1315	119	1317	119	<u>1316</u>	<u>119</u>	8	1291	121	1296	121	<u>1293</u>	<u>121</u>
433.milc	8	2511	29.2	<u>2512</u>	<u>29.2</u>	2512	29.2	8	2508	29.3	2509	29.3	<u>2509</u>	<u>29.3</u>
434.zeusmp	8	1060	68.7	<u>1074</u>	<u>67.8</u>	1078	67.6	8	1029	70.7	<u>1040</u>	<u>70.0</u>	1043	69.8
435.gromacs	8	544	105	543	105	<u>543</u>	<u>105</u>	8	<u>541</u>	<u>106</u>	540	106	547	104
436.cactusADM	8	<u>1240</u>	<u>77.1</u>	1243	76.9	1239	77.2	1	135	88.5	<u>135</u>	<u>88.3</u>	135	88.2
437.leslie3d	8	2528	29.7	<u>2525</u>	<u>29.8</u>	2523	29.8	4	<u>1172</u>	<u>32.1</u>	1168	32.2	1176	32.0
444.namd	8	<u>737</u>	<u>87.0</u>	745	86.1	737	87.0	8	742	86.4	<u>742</u>	<u>86.5</u>	742	86.5
447.dealII	8	832	110	781	117	<u>825</u>	<u>111</u>	8	749	122	741	123	<u>748</u>	<u>122</u>
450.soplex	8	2066	32.3	<u>2067</u>	<u>32.3</u>	2068	32.3	8	1870	35.7	1861	35.8	<u>1863</u>	<u>35.8</u>
453.povray	8	326	131	<u>326</u>	<u>131</u>	330	129	8	273	156	274	156	<u>273</u>	<u>156</u>
454.calculix	8	542	122	548	120	<u>545</u>	<u>121</u>	8	537	123	540	122	<u>537</u>	<u>123</u>
459.GemsFDTD	8	3362	25.3	<u>3359</u>	<u>25.3</u>	3357	25.3	8	<u>3403</u>	<u>24.9</u>	3419	24.8	3393	25.0
465.tonto	8	855	92.1	<u>847</u>	<u>93.0</u>	846	93.0	8	791	99.6	<u>787</u>	<u>100</u>	787	100
470.lbm	8	4084	26.9	<u>4083</u>	<u>26.9</u>	4082	26.9	4	<u>1479</u>	<u>37.2</u>	1479	37.2	1480	37.1
481.wrf	8	1792	49.9	1805	49.5	<u>1803</u>	<u>49.6</u>	8	1792	49.9	1805	49.5	<u>1803</u>	<u>49.6</u>
482.sphinx3	8	<u>2995</u>	<u>52.1</u>	3005	51.9	2979	52.3	4	<u>1050</u>	<u>74.2</u>	1055	73.9	1050	74.3

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The config file option 'submit' was used.

General Notes

Taskset was used to bind processes to cores except for 436.cactusADM peak
OMP_NUM_THREADS set to number of processors
KMP_AFFINITY set to "physical,0"
KMP_STACKSIZE set to 64M



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ACTION S.A.

SPECfp_rate2006 = 64.8

ACTINA SOLAR 220 X2 (Intel Xeon E5405, 2.0 GHz)

SPECfp_rate_base2006 = 59.7

CPU2006 license: 9008

Test date: Dec-2008

Test sponsor: ACTION S.A.

Hardware Availability: Sep-2008

Tested by: ACTION S.A.

Software Availability: Nov-2008

Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.lelie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:

-xSSE4.1 -ipo -O3 -no-prec-div -static -opt-prefetch

C++ benchmarks:

-xSSE4.1 -ipo -O3 -no-prec-div -static -opt-prefetch

Fortran benchmarks:

-xSSE4.1 -ipo -O3 -no-prec-div -static -opt-prefetch

Benchmarks using both Fortran and C:

-xSSE4.1 -ipo -O3 -no-prec-div -static -opt-prefetch



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ACTION S.A.

SPECfp_rate2006 = 64.8

ACTINA SOLAR 220 X2 (Intel Xeon E5405, 2.0 GHz)

SPECfp_rate_base2006 = 59.7

CPU2006 license: 9008

Test date: Dec-2008

Test sponsor: ACTION S.A.

Hardware Availability: Sep-2008

Tested by: ACTION S.A.

Software Availability: Nov-2008

Peak Compiler Invocation

C benchmarks (except as noted below):

icc

```
482.sphinx3: /opt/intel/Compiler/11.0/042/bin/ia32/icc
             -L/opt/intel/Compiler/11.0/042/ipp/ia32/lib
             -I/opt/intel/Compiler/11.0/042/ipp/ia32/include
```

C++ benchmarks (except as noted below):

icpc

```
450.soplex: /opt/intel/Compiler/11.0/042/bin/ia32/icpc
            -L/opt/intel/Compiler/11.0/042/ipp/ia32/lib
            -I/opt/intel/Compiler/11.0/042/ipp/ia32/include
```

Fortran benchmarks (except as noted below):

ifort

```
437.leslie3d: /opt/intel/Compiler/11.0/042/bin/ia32/ifort
              -L/opt/intel/Compiler/11.0/042/ipp/ia32/lib
              -I/opt/intel/Compiler/11.0/042/ipp/ia32/include
```

Benchmarks using both Fortran and C:

icc ifort

Peak Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
444.namd: -DSPEC_CPU_LP64
447.deallI: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
```

Peak Optimization Flags

C benchmarks:

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ACTION S.A.

SPECfp_rate2006 = 64.8

ACTINA SOLAR 220 X2 (Intel Xeon E5405, 2.0 GHz)

SPECfp_rate_base2006 = 59.7

CPU2006 license: 9008

Test date: Dec-2008

Test sponsor: ACTION S.A.

Hardware Availability: Sep-2008

Tested by: ACTION S.A.

Software Availability: Nov-2008

Peak Optimization Flags (Continued)

433.milc: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -fno-alias

470.lbm: -xSSE4.1 -ipo -O3 -no-prec-div -static -opt-prefetch
-auto-ilp32

482.sphinx3: -xSSE4.1 -ipo -O3 -no-prec-div -static -unroll2

C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -fno-alias -auto-ilp32

447.dealIII: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -unroll2 -ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: -xSSE4.1 -ipo -O3 -no-prec-div -static -opt-prefetch

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -unroll2 -Ob0 -ansi-alias
-scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static

437.leslie3d: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -opt-malloc-options=3 -opt-prefetch

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -unroll2 -Ob0 -opt-prefetch

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -unroll4 -auto

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -opt-prefetch -auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3
-no-prec-div -static -unroll2 -opt-prefetch -parallel
-auto-ilp32

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ACTION S.A.

SPECfp_rate2006 = 64.8

ACTINA SOLAR 220 X2 (Intel Xeon E5405, 2.0 GHz)

SPECfp_rate_base2006 = 59.7

CPU2006 license: 9008

Test date: Dec-2008

Test sponsor: ACTION S.A.

Hardware Availability: Sep-2008

Tested by: ACTION S.A.

Software Availability: Nov-2008

Peak Optimization Flags (Continued)

454.calculix: -xSSE4.1 -ipo -O3 -no-prec-div -static -auto-ilp32

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-fp-linux64-revA.20090713.02.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-fp-linux64-revA.20090713.02.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Tue Jul 22 21:33:37 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 24 December 2008.