



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

SPECint®_rate2006 = 33.4

PRIMERGY RX100 S5, Intel Pentium E5200, 2.50 GHz

SPECint_rate_base2006 = 31.4

CPU2006 license: 19


Test date: Mar-2009

Test sponsor: Fujitsu

Hardware Availability: Apr-2009

Tested by: Fujitsu

Software Availability: Nov-2008



SPECint_rate_base2006 = 31.4

SPECint_rate2006 = 33.4

Hardware

CPU Name: Intel Pentium E5200
CPU Characteristics: 800 MHz system bus
CPU MHz: 2500
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1 chip
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 2 MB I+D on chip per chip
L3 Cache: None
Other Cache: None
Memory: 8 GB (4x2 GB PC2-6400E, 2 rank, CL6-6-6, ECC)
Disk Subsystem: 1 x SATA, 250 GB, 7200 rpm
Other Hardware: None

Software

Operating System: SUSE Linux Enterprise Server 10 (x86_64) SP2, Kernel 2.6.16.60-0.21-smp
Compiler: Intel C++ Compiler 11.0 for Linux Build 20080930 Package ID: l_cproc_p_11.0.066
Auto Parallel: No
File System: ext3
System State: Multi-User Run Level 3
Base Pointers: 32-bit
Peak Pointers: 32/64-bit
Other Software: Microquill SmartHeap V8.1 Binutils 2.18.50.0.7.20080502



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

SPECint_rate2006 = 33.4

PRIMERGY RX100 S5, Intel Pentium E5200, 2.50 GHz

SPECint_rate_base2006 = 31.4

CPU2006 license: 19

Test date: Mar-2009

Test sponsor: Fujitsu

Hardware Availability: Apr-2009

Tested by: Fujitsu

Software Availability: Nov-2008

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	2	575	34.0	573	34.1	574	34.1	2	487	40.1	488	40.0	489	40.0
401.bzip2	2	1017	19.0	1018	19.0	1016	19.0	2	981	19.7	974	19.8	979	19.7
403.gcc	2	666	24.2	669	24.1	630	25.6	2	655	24.6	639	25.2	684	23.5
429.mcf	2	526	34.7	530	34.4	530	34.4	2	529	34.5	531	34.4	523	34.8
445.gobmk	2	640	32.8	640	32.8	640	32.8	2	602	34.9	602	34.8	602	34.8
456.hammer	2	578	32.3	579	32.2	578	32.3	2	470	39.7	469	39.8	469	39.8
458.sjeng	2	732	33.1	727	33.3	729	33.2	2	704	34.4	702	34.5	702	34.5
462.libquantum	2	533	77.7	532	77.9	533	77.8	2	533	77.7	532	77.9	533	77.8
464.h264ref	2	833	53.2	836	53.0	835	53.0	2	816	54.2	809	54.7	814	54.4
471.omnetpp	2	662	18.9	662	18.9	662	18.9	2	614	20.4	615	20.3	614	20.4
473.astar	2	775	18.1	775	18.1	775	18.1	2	698	20.1	695	20.2	697	20.1
483.xalancbmk	2	401	34.4	402	34.4	401	34.4	2	401	34.4	402	34.4	401	34.4

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The config file option 'submit' was used.
taskset has been used to bind processes to cores

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run

General Notes

For information about Fujitsu please visit: <http://www.fujitsu.com>

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

PRIMERGY RX100 S5, Intel Pentium E5200, 2.50 GHz

CPU2006 license: 19

Test sponsor: Fujitsu

Tested by: Fujitsu

SPECint_rate2006 = 33.4

SPECint_rate_base2006 = 31.4

Test date: Mar-2009

Hardware Availability: Apr-2009

Software Availability: Nov-2008

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:

-xSSSE3 -ipo -O3 -no-prec-div -static -inline-calloc
-opt-malloc-options=3 -opt-prefetch

C++ benchmarks:

-xSSSE3 -ipo -O3 -no-prec-div -opt-prefetch -Wl,-z,muldefs
-L/spec/cpu2006.1.1/lib -lsmartheap

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):

icc

401.bzip2: /opt/intel/Compiler/11.0/066/bin/intel64/icc

456.hmmr: /opt/intel/Compiler/11.0/066/bin/intel64/icc

C++ benchmarks:

icpc

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
401.bzip2: -DSPEC_CPU_LP64
456.hmmr: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

PRIMERGY RX100 S5, Intel Pentium E5200, 2.50 GHz

CPU2006 license: 19

Test sponsor: Fujitsu

Tested by: Fujitsu

SPECint_rate2006 = 33.4

SPECint_rate_base2006 = 31.4

Test date: Mar-2009

Hardware Availability: Apr-2009

Software Availability: Nov-2008

Peak Optimization Flags

C benchmarks:

```
400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -xSSSE3 -ipo -O3  
                -no-prec-div -static -ansi-alias -opt-prefetch  
  
401.bzip2: -prof-gen(pass 1) -prof-use(pass 2) -xSSSE3 -ipo -O3  
                -no-prec-div -static -opt-prefetch -ansi-alias  
  
403.gcc: -xSSSE3 -ipo -O3 -no-prec-div -static -inline-calloc  
                -opt-malloc-options=3  
  
429.mcf: -prof-gen(pass 1) -prof-use(pass 2) -xSSSE3 -ipo -O3  
                -no-prec-div -static -opt-prefetch  
  
445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xSSSE3 -O2 -ipo  
                -no-prec-div -ansi-alias  
  
456.hmmr: -xSSSE3 -ipo -O3 -no-prec-div -static -unroll2  
                -ansi-alias  
  
458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -xSSSE3 -ipo -O3  
                -no-prec-div -static -unroll4  
  
462.libquantum: basepeak = yes  
  
464.h264ref: -prof-gen(pass 1) -prof-use(pass 2) -xSSSE3 -ipo -O3  
                -no-prec-div -static -unroll2 -ansi-alias
```

C++ benchmarks:

```
471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xSSSE3 -ipo -O3  
                -no-prec-div -ansi-alias -opt-ra-region-strategy=block  
                -Wl,-z,muldefs -L/spec/cpu2006.1.1/lib -lsmartheap  
  
473.astar: -prof-gen(pass 1) -prof-use(pass 2) -xSSSE3 -ipo -O3  
                -no-prec-div -ansi-alias -opt-ra-region-strategy=routine  
                -Wl,-z,muldefs -L/spec/cpu2006.1.1/lib -lsmartheap  
  
483.xalancbmk: basepeak = yes
```

Peak Other Flags

C benchmarks:

```
403.gcc: -Dalloca=_alloca
```



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

SPECint_rate2006 = 33.4

PRIMERGY RX100 S5, Intel Pentium E5200, 2.50 GHz

SPECint_rate_base2006 = 31.4

CPU2006 license: 19

Test date: Mar-2009

Test sponsor: Fujitsu

Hardware Availability: Apr-2009

Tested by: Fujitsu

Software Availability: Nov-2008

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-int-linux64-revA.20090710.03.html>
<http://www.spec.org/cpu2006/flags/Intel-Linux64-Platform.20090710.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-int-linux64-revA.20090710.03.xml>
<http://www.spec.org/cpu2006/flags/Intel-Linux64-Platform.20090710.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.

Report generated on Wed Jul 23 00:48:19 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 23 April 2009.