



SPEC[®] CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp[®]_rate2006 = 383

Intel QSSC-S4R (Intel Xeon E7530, 1.86 GHz)

SPECfp_rate_base2006 = 371

CPU2006 license: 13


Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Mar-2010

Hardware Availability: Mar-2010

Software Availability: Jan-2010



Hardware

CPU Name: Intel Xeon E7530
 CPU Characteristics: Intel Turbo Boost Technology up to 2.13 GHz
 CPU MHz: 1866
 FPU: Integrated
 CPU(s) enabled: 24 cores, 4 chips, 6 cores/chip, 2 threads/core
 CPU(s) orderable: 1,2,4 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

Software

Operating System: SuSe Linux Enterprise Server 11
 Kernel 2.6.27.19-5 on x86_64
 Compiler: Intel C++ and Fortran Professional Compiler for IA32 and Intel 64, Version 11.1
 Build 20091130 Package ID: l_cproc_p_11.1.064, l_cprof_p_11.1.064
 Auto Parallel: No
 File System: ext3
 System State: Run level 3 (multi-user)

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp_rate2006 = 383

Intel QSSC-S4R (Intel Xeon E7530, 1.86 GHz)

SPECfp_rate_base2006 = 371

CPU2006 license: 13

Test date: Mar-2010

Test sponsor: Intel Corporation

Hardware Availability: Mar-2010

Tested by: Intel Corporation

Software Availability: Jan-2010

L3 Cache: 12 MB I+D on chip per chip
 Other Cache: None
 Memory: 256 GB (64x 4GB Quad-Rank DDR3-1066, ECC, CL9)
 Disk Subsystem: 146 GB SAS, 10000RPM
 Other Hardware: None

Base Pointers: 64-bit
 Peak Pointers: 32/64-bit
 Other Software: None

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	48	1784	366	<u>1788</u>	<u>365</u>	1790	364	24	870	375	<u>867</u>	<u>376</u>	865	377
416.gamess	48	2602	361	2585	364	<u>2592</u>	<u>363</u>	48	2584	364	2661	353	<u>2588</u>	<u>363</u>
433.milc	48	1034	426	1032	427	<u>1033</u>	<u>427</u>	48	1032	427	<u>1031</u>	<u>428</u>	1031	428
434.zeusmp	48	1127	387	1122	389	<u>1126</u>	<u>388</u>	48	1127	387	1122	389	<u>1126</u>	<u>388</u>
435.gromacs	48	<u>985</u>	<u>348</u>	986	348	982	349	48	967	354	<u>968</u>	<u>354</u>	974	352
436.cactusADM	48	1409	407	1413	406	<u>1410</u>	<u>407</u>	48	1409	407	1413	406	<u>1410</u>	<u>407</u>
437.leslie3d	48	<u>1703</u>	<u>265</u>	1703	265	1705	265	24	<u>837</u>	<u>270</u>	837	270	839	269
444.namd	48	<u>1150</u>	<u>335</u>	1147	336	1150	335	48	1121	343	<u>1119</u>	<u>344</u>	1116	345
447.dealII	48	905	606	895	614	<u>902</u>	<u>609</u>	48	905	606	895	614	<u>902</u>	<u>609</u>
450.soplex	48	<u>1371</u>	<u>292</u>	1372	292	1371	292	48	1293	310	1291	310	<u>1292</u>	<u>310</u>
453.povray	48	519	492	522	489	<u>520</u>	<u>491</u>	48	431	592	<u>433</u>	<u>590</u>	434	589
454.calculix	48	921	430	<u>921</u>	<u>430</u>	922	429	48	921	430	<u>921</u>	<u>430</u>	922	429
459.GemsFDTD	48	<u>2082</u>	<u>245</u>	2096	243	2063	247	48	<u>2082</u>	<u>245</u>	2096	243	2063	247
465.tonto	48	1106	427	<u>1108</u>	<u>426</u>	1111	425	48	1030	458	1035	456	<u>1033</u>	<u>457</u>
470.lbm	48	2749	240	2745	240	<u>2748</u>	<u>240</u>	24	<u>1297</u>	<u>254</u>	1297	254	1298	254
481.wrf	48	1117	480	1125	477	<u>1123</u>	<u>477</u>	48	1117	480	1125	477	<u>1123</u>	<u>477</u>
482.sphinx3	48	2403	389	<u>2404</u>	<u>389</u>	2407	389	48	2261	414	2266	413	<u>2264</u>	<u>413</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The config file option 'submit' was used.
numactl was used to bind copies to the cores

Base Compiler Invocation

C benchmarks:
 icc -m64

C++ benchmarks:
 icpc -m64

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp_rate2006 = 383

Intel QSSC-S4R (Intel Xeon E7530, 1.86 GHz)

SPECfp_rate_base2006 = 371

CPU2006 license: 13

Test date: Mar-2010

Test sponsor: Intel Corporation

Hardware Availability: Mar-2010

Tested by: Intel Corporation

Software Availability: Jan-2010

Base Compiler Invocation (Continued)

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
 416.gamess: -DSPEC_CPU_LP64
 433.milc: -DSPEC_CPU_LP64
 434.zeusmp: -DSPEC_CPU_LP64
 435.gromacs: -DSPEC_CPU_LP64 -nofor_main
 436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
 437.leslie3d: -DSPEC_CPU_LP64
 444.namd: -DSPEC_CPU_LP64
 447.dealII: -DSPEC_CPU_LP64
 450.soplex: -DSPEC_CPU_LP64
 453.povray: -DSPEC_CPU_LP64
 454.calculix: -DSPEC_CPU_LP64 -nofor_main
 459.GemsFDTD: -DSPEC_CPU_LP64
 465.tonto: -DSPEC_CPU_LP64
 470.lbm: -DSPEC_CPU_LP64
 481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
 482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static

C++ benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static

Fortran benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static

Benchmarks using both Fortran and C:

-xSSE4.2 -ipo -O3 -no-prec-div -static

Peak Compiler Invocation

C benchmarks (except as noted below):

icc -m64

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp_rate2006 = 383

Intel QSSC-S4R (Intel Xeon E7530, 1.86 GHz)

SPECfp_rate_base2006 = 371

CPU2006 license: 13

Test date: Mar-2010

Test sponsor: Intel Corporation

Hardware Availability: Mar-2010

Tested by: Intel Corporation

Software Availability: Jan-2010

Peak Compiler Invocation (Continued)

482.sphinx3: `icc -m32`

C++ benchmarks (except as noted below):

`icpc -m64`

450.soplex: `icpc -m32`

Fortran benchmarks:

`ifort -m64`

Benchmarks using both Fortran and C:

`icc -m64 ifort -m64`

Peak Portability Flags

410.bwaves: `-DSPEC_CPU_LP64`
 416.gamess: `-DSPEC_CPU_LP64`
 433.milc: `-DSPEC_CPU_LP64`
 434.zeusmp: `-DSPEC_CPU_LP64`
 435.gromacs: `-DSPEC_CPU_LP64 -nofor_main`
 436.cactusADM: `-DSPEC_CPU_LP64 -nofor_main`
 437.leslie3d: `-DSPEC_CPU_LP64`
 444.namd: `-DSPEC_CPU_LP64`
 447.dealII: `-DSPEC_CPU_LP64`
 453.povray: `-DSPEC_CPU_LP64`
 454.calculix: `-DSPEC_CPU_LP64 -nofor_main`
 459.GemsFDTD: `-DSPEC_CPU_LP64`
 465.tonto: `-DSPEC_CPU_LP64`
 470.lbm: `-DSPEC_CPU_LP64`
 481.wrf: `-DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX`

Peak Optimization Flags

C benchmarks:

433.milc: `-xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2) -fno-alias -opt-prefetch`

470.lbm: `-xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2) -opt-malloc-options=3 -ansi-alias -auto-ilp32`

482.sphinx3: `-xSSE4.2 -ipo -O3 -no-prec-div -static -unroll2`

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp_rate2006 = 383

Intel QSSC-S4R (Intel Xeon E7530, 1.86 GHz)

SPECfp_rate_base2006 = 371

CPU2006 license: 13

Test date: Mar-2010

Test sponsor: Intel Corporation

Hardware Availability: Mar-2010

Tested by: Intel Corporation

Software Availability: Jan-2010

Peak Optimization Flags (Continued)

C++ benchmarks:

444.namd: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
-fno-alias -auto-ilp32

447.dealIII: basepeak = yes

450.soplex: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
-opt-malloc-options=3

453.povray: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
-unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: -xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch

416.gamess: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
-unroll2 -Ob0 -ansi-alias -scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: -xSSE4.2 -ipo -O3 -no-prec-div -static

459.GemsFDTD: basepeak = yes

465.tonto: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
-unroll4 -auto -inline-calloc -opt-malloc-options=3

Benchmarks using both Fortran and C:

435.gromacs: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
-opt-prefetch -auto-ilp32

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.1-linux64-revG.html>



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp_rate2006 = 383

Intel QSSC-S4R (Intel Xeon E7530, 1.86 GHz)

SPECfp_rate_base2006 = 371

CPU2006 license: 13

Test date: Mar-2010

Test sponsor: Intel Corporation

Hardware Availability: Mar-2010

Tested by: Intel Corporation

Software Availability: Jan-2010

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic11.1-linux64-revG.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Wed Jul 23 08:08:39 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 4 May 2010.