



# SPEC<sup>®</sup> CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp<sup>®</sup>\_rate2006 = 232

PowerEdge R610 (Intel Xeon X5650, 2.66 GHz)

SPECfp\_rate\_base2006 = 224

CPU2006 license: 55


Test date: Apr-2010

Test sponsor: Dell Inc.

Hardware Availability: Mar-2010

Tested by: Dell Inc.

Software Availability: Dec-2009



### Hardware

CPU Name: Intel Xeon X5650  
 CPU Characteristics: Intel Turbo Boost Technology up to 3.06 GHz  
 CPU MHz: 2667  
 FPU: Integrated  
 CPU(s) enabled: 12 cores, 2 chips, 6 cores/chip, 2 threads/core  
 CPU(s) orderable: 1,2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

### Software

Operating System: SUSE Linux Enterprise Server 11 (x86\_64), Kernel 2.6.27.19-5-smp  
 Compiler: Intel C++ and Fortran Professional Compiler for IA32 and Intel 64, Version 11.1 Build 20091130 Package ID: l\_cproc\_p\_11.1.064, l\_cprof\_p\_11.1.064  
 Auto Parallel: No  
 File System: ext3  
 System State: Run level 3 (multi-user)

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp\_rate2006 = 232

PowerEdge R610 (Intel Xeon X5650, 2.66 GHz)

SPECfp\_rate\_base2006 = 224

CPU2006 license: 55

Test date: Apr-2010

Test sponsor: Dell Inc.

Hardware Availability: Mar-2010

Tested by: Dell Inc.

Software Availability: Dec-2009

L3 Cache: 12 MB I+D on chip per chip  
Other Cache: None  
Memory: 48 GB (12 x 4 GB DDR3-1333 DR RDIMM)  
Disk Subsystem: 1 x 146 GB 15000 RPM SAS  
Other Hardware: None

Base Pointers: 64-bit  
Peak Pointers: 32/64-bit  
Other Software: Binutils 2.18.50.0.7.20080502

## Results Table

| Benchmark     | Base   |                    |                   |                    |                   |                    |                   |        | Peak              |                   |                    |                   |                    |                   |  |  |
|---------------|--------|--------------------|-------------------|--------------------|-------------------|--------------------|-------------------|--------|-------------------|-------------------|--------------------|-------------------|--------------------|-------------------|--|--|
|               | Copies | Seconds            | Ratio             | Seconds            | Ratio             | Seconds            | Ratio             | Copies | Seconds           | Ratio             | Seconds            | Ratio             | Seconds            | Ratio             |  |  |
| 410.bwaves    | 24     | 1720               | 190               | <b><u>1681</u></b> | <b><u>194</u></b> | 1681               | 194               | 12     | <b><u>830</u></b> | <b><u>197</u></b> | 826                | 197               | 830                | 196               |  |  |
| 416.gamess    | 24     | 1830               | 257               | 1869               | 251               | <b><u>1843</u></b> | <b><u>255</u></b> | 12     | <b><u>896</u></b> | <b><u>262</u></b> | 896                | 262               | 897                | 262               |  |  |
| 433.milc      | 24     | 1017               | 217               | <b><u>1017</u></b> | <b><u>217</u></b> | 1018               | 216               | 24     | 1018              | 216               | 1019               | 216               | <b><u>1018</u></b> | <b><u>216</u></b> |  |  |
| 434.zeusmp    | 24     | <b><u>763</u></b>  | <b><u>286</u></b> | 764                | 286               | 763                | 286               | 24     | <b><u>763</u></b> | <b><u>286</u></b> | 764                | 286               | 763                | 286               |  |  |
| 435.gromacs   | 24     | 695                | 247               | <b><u>695</u></b>  | <b><u>247</u></b> | 694                | 247               | 24     | <b><u>682</u></b> | <b><u>251</u></b> | 681                | 251               | 685                | 250               |  |  |
| 436.cactusADM | 24     | <b><u>954</u></b>  | <b><u>301</u></b> | 950                | 302               | 955                | 300               | 24     | <b><u>954</u></b> | <b><u>301</u></b> | 950                | 302               | 955                | 300               |  |  |
| 437.leslie3d  | 24     | 1700               | 133               | <b><u>1700</u></b> | <b><u>133</u></b> | 1700               | 133               | 12     | <b><u>822</u></b> | <b><u>137</u></b> | 822                | 137               | 823                | 137               |  |  |
| 444.namd      | 24     | 815                | 236               | <b><u>817</u></b>  | <b><u>236</u></b> | 822                | 234               | 24     | 798               | 241               | <b><u>797</u></b>  | <b><u>242</u></b> | 794                | 242               |  |  |
| 447.dealII    | 24     | <b><u>747</u></b>  | <b><u>368</u></b> | 749                | 367               | 742                | 370               | 24     | <b><u>761</u></b> | <b><u>361</u></b> | 726                | 378               | 762                | 360               |  |  |
| 450.soplex    | 24     | 1328               | 151               | <b><u>1307</u></b> | <b><u>153</u></b> | 1306               | 153               | 12     | 647               | 155               | 587                | 170               | <b><u>587</u></b>  | <b><u>170</u></b> |  |  |
| 453.povray    | 24     | <b><u>363</u></b>  | <b><u>351</u></b> | 362                | 353               | 363                | 351               | 24     | 309               | 413               | 299                | 428               | <b><u>302</u></b>  | <b><u>423</u></b> |  |  |
| 454.calculix  | 24     | <b><u>639</u></b>  | <b><u>310</u></b> | 640                | 310               | 638                | 310               | 24     | <b><u>639</u></b> | <b><u>310</u></b> | 640                | 310               | 638                | 310               |  |  |
| 459.GemsFDTD  | 24     | 2218               | 115               | <b><u>2010</u></b> | <b><u>127</u></b> | 2010               | 127               | 12     | <b><u>982</u></b> | <b><u>130</u></b> | 982                | 130               | 983                | 130               |  |  |
| 465.tonto     | 24     | 938                | 252               | 926                | 255               | <b><u>930</u></b>  | <b><u>254</u></b> | 24     | 856               | 276               | 885                | 267               | <b><u>878</u></b>  | <b><u>269</u></b> |  |  |
| 470.lbm       | 24     | <b><u>2638</u></b> | <b><u>125</u></b> | 2637               | 125               | 2640               | 125               | 12     | 1256              | 131               | 1254               | 132               | <b><u>1254</u></b> | <b><u>131</u></b> |  |  |
| 481.wrf       | 24     | 1122               | 239               | <b><u>1132</u></b> | <b><u>237</u></b> | 1136               | 236               | 24     | 1122              | 239               | <b><u>1132</u></b> | <b><u>237</u></b> | 1136               | 236               |  |  |
| 482.sphinx3   | 24     | 2133               | 219               | 2127               | 220               | <b><u>2129</u></b> | <b><u>220</u></b> | 24     | 2021              | 231               | <b><u>2017</u></b> | <b><u>232</u></b> | 2017               | 232               |  |  |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The config file option 'submit' was used.  
numactl was used to bind copies to the cores

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run

## Platform Notes

BIOS Settings:  
Power Management = Maximum Performance (Default = Active Power Controller)  
Data Reuse = Disabled (Default = Enabled)



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp\_rate2006 = 232

PowerEdge R610 (Intel Xeon X5650, 2.66 GHz)

SPECfp\_rate\_base2006 = 224

CPU2006 license: 55

Test date: Apr-2010

Test sponsor: Dell Inc.

Hardware Availability: Mar-2010

Tested by: Dell Inc.

Software Availability: Dec-2009

## General Notes

The Dell PowerEdge R610 and the Bull NovaScale R440 F2 models are electronically equivalent. The results have been measured on a Dell PowerEdge R610 model.

## Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static

C++ benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp\_rate2006 = 232

PowerEdge R610 (Intel Xeon X5650, 2.66 GHz)

SPECfp\_rate\_base2006 = 224

CPU2006 license: 55

Test date: Apr-2010

Test sponsor: Dell Inc.

Hardware Availability: Mar-2010

Tested by: Dell Inc.

Software Availability: Dec-2009

## Base Optimization Flags (Continued)

Fortran benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static

Benchmarks using both Fortran and C:

-xSSE4.2 -ipo -O3 -no-prec-div -static

## Peak Compiler Invocation

C benchmarks (except as noted below):

icc -m64

482.sphinx3: icc -m32

C++ benchmarks (except as noted below):

icpc -m64

450.soplex: icpc -m32

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

## Peak Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
 416.gamess: -DSPEC\_CPU\_LP64  
 433.milc: -DSPEC\_CPU\_LP64  
 434.zeusmp: -DSPEC\_CPU\_LP64  
 435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
 436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
 437.leslie3d: -DSPEC\_CPU\_LP64  
 444.namd: -DSPEC\_CPU\_LP64  
 447.dealII: -DSPEC\_CPU\_LP64  
 453.povray: -DSPEC\_CPU\_LP64  
 454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
 459.GemsFDTD: -DSPEC\_CPU\_LP64  
 465.tonto: -DSPEC\_CPU\_LP64  
 470.lbm: -DSPEC\_CPU\_LP64  
 481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp\_rate2006 = 232

PowerEdge R610 (Intel Xeon X5650, 2.66 GHz)

SPECfp\_rate\_base2006 = 224

CPU2006 license: 55

Test date: Apr-2010

Test sponsor: Dell Inc.

Hardware Availability: Mar-2010

Tested by: Dell Inc.

Software Availability: Dec-2009

## Peak Optimization Flags

### C benchmarks:

433.milc: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-fno-alias -opt-prefetch

470.lbm: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-opt-malloc-options=3 -ansi-alias -auto-ilp32

482.sphinx3: -xSSE4.2 -ipo -O3 -no-prec-div -static -unroll2

### C++ benchmarks:

444.namd: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-fno-alias -auto-ilp32

447.dealIII: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll2 -ansi-alias -scalar-rep-

450.soplex: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-opt-malloc-options=3

453.povray: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll4 -ansi-alias

### Fortran benchmarks:

410.bwaves: -xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch

416.gamess: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll2 -Ob0 -ansi-alias -scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: -xSSE4.2 -ipo -O3 -no-prec-div -static

459.GemsFDTD: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll2 -Ob0

465.tonto: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-unroll4 -auto -inline-calloc -opt-malloc-options=3

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp\_rate2006 = 232

PowerEdge R610 (Intel Xeon X5650, 2.66 GHz)

SPECfp\_rate\_base2006 = 224

CPU2006 license: 55

Test sponsor: Dell Inc.

Tested by: Dell Inc.

Test date: Apr-2010

Hardware Availability: Mar-2010

Software Availability: Dec-2009

## Peak Optimization Flags (Continued)

Benchmarks using both Fortran and C:

435.gromacs: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)  
-opt-prefetch -auto-ilp32

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.1-linux64-revE.20100330.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic11.1-linux64-revE.20100330.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.  
Report generated on Wed Jul 23 07:35:51 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 27 April 2010.