



SPEC[®] CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

SPECint[®]_rate2006 = 341

Express5800/A1080a-S/D (Intel Xeon E7520)

SPECint_rate_base2006 = 314

CPU2006 license: 9006


Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Jun-2010

Hardware Availability: Jul-2010

Software Availability: Mar-2010



Hardware

CPU Name: Intel Xeon E7520
 CPU Characteristics: 1867
 CPU MHz: 1867
 FPU: Integrated
 CPU(s) enabled: 16 cores, 4 chips, 4 cores/chip, 2 threads/core
 CPU(s) orderable: 1,2,3,4 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core
 L3 Cache: 18 MB I+D on chip per chip
 Other Cache: None
 Memory: 256 GB (64 x 4 GB PC3-8500R, 2 rank, CL7, ECC)
 Disk Subsystem: 1x300.0 GB SAS, 10000 RPM
 Other Hardware: None

Software

Operating System: Red Hat Enterprise Linux Server release 5.5, Kernel 2.6.18-194.el5 on an x86_64
 Compiler: Intel C++ Professional Compiler for IA32 and Intel 64, Version 11.1 Build 20091130 Package ID: 1_cproc_p_11.1.064
 Auto Parallel: No
 File System: ext2
 System State: Run level 5 (multi-user mode, with display manager as well as console logins)
 Base Pointers: 32-bit
 Peak Pointers: 32/64-bit
 Other Software: Microquill SmartHeap V8.1 Binutils 2.18.50.0.7.20080502



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

SPECint_rate2006 = 341

Express5800/A1080a-S/D (Intel Xeon E7520)

SPECint_rate_base2006 = 314

CPU2006 license: 9006

Test date: Jun-2010

Test sponsor: NEC Corporation

Hardware Availability: Jul-2010

Tested by: NEC Corporation

Software Availability: Mar-2010

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	32	<u>1230</u>	<u>254</u>	1228	255	1230	254	32	1047	299	<u>1036</u>	<u>302</u>	1036	302
401.bzip2	32	<u>1528</u>	<u>202</u>	1529	202	1527	202	32	1434	215	1430	216	<u>1431</u>	<u>216</u>
403.gcc	32	961	268	957	269	<u>961</u>	<u>268</u>	32	961	268	957	269	<u>961</u>	<u>268</u>
429.mcf	32	<u>769</u>	<u>380</u>	768	380	769	380	32	<u>766</u>	<u>381</u>	766	381	763	382
445.gobmk	32	1174	286	1176	285	<u>1176</u>	<u>286</u>	32	1074	313	<u>1075</u>	<u>312</u>	1076	312
456.hammer	32	760	393	<u>753</u>	<u>396</u>	746	400	32	571	523	<u>571</u>	<u>523</u>	572	522
458.sjeng	32	1468	264	<u>1467</u>	<u>264</u>	1464	264	32	1329	291	1331	291	<u>1331</u>	<u>291</u>
462.libquantum	32	619	1070	<u>618</u>	<u>1070</u>	617	1070	32	<u>614</u>	<u>1080</u>	617	1080	606	1090
464.h264ref	32	1960	361	1874	378	<u>1931</u>	<u>367</u>	32	1885	376	<u>1900</u>	<u>373</u>	1902	372
471.omnetpp	32	891	224	<u>892</u>	<u>224</u>	893	224	32	778	257	779	257	<u>778</u>	<u>257</u>
473.astar	32	1133	198	1125	200	<u>1133</u>	<u>198</u>	32	995	226	998	225	<u>995</u>	<u>226</u>
483.xalancbmk	32	652	339	655	337	<u>652</u>	<u>339</u>	32	652	339	655	337	<u>652</u>	<u>339</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The config file option 'submit' was used.
numactl was used to bind copies to the cores

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run

Platform Notes

Power Technology set to disabled in BIOS
Patrol Scrubbing set to disabled in Maintenance Console

Base Compiler Invocation

C benchmarks:
icc -m32

C++ benchmarks:
icpc -m32



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

SPECint_rate2006 = 341

Express5800/A1080a-S/D (Intel Xeon E7520)

SPECint_rate_base2006 = 314

CPU2006 license: 9006

Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Jun-2010

Hardware Availability: Jul-2010

Software Availability: Mar-2010

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch

C++ benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -Wl,-z,muldefs
-L/opt/SmartHeap_8.1/lib -lsmartheap

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):

icc -m32

401.bzip2: icc -m64

456.hmmer: icc -m64

458.sjeng: icc -m64

462.libquantum: icc -m64

C++ benchmarks (except as noted below):

icpc -m32

473.astar: icpc -m64

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
401.bzip2: -DSPEC_CPU_LP64

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

SPECint_rate2006 = 341

Express5800/A1080a-S/D (Intel Xeon E7520)

SPECint_rate_base2006 = 314

CPU2006 license: 9006

Test date: Jun-2010

Test sponsor: NEC Corporation

Hardware Availability: Jul-2010

Tested by: NEC Corporation

Software Availability: Mar-2010

Peak Portability Flags (Continued)

456.hmmcr: -DSPEC_CPU_LP64
 458.sjeng: -DSPEC_CPU_LP64
 462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
 473.astar: -DSPEC_CPU_LP64
 483.xalancbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

400.perlbench: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
 -O3(pass 2) -no-prec-div(pass 2) -static(pass 2)
 -prof-use(pass 2) -ansi-alias

401.bzip2: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
 -O3(pass 2) -no-prec-div(pass 2) -static(pass 2)
 -prof-use(pass 2) -opt-prefetch -ansi-alias -auto-ilp32

403.gcc: basepeak = yes

429.mcf: -xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch

445.gobmk: -xSSE4.2(pass 2) -prof-gen(pass 1) -prof-use(pass 2) -O2
 -ipo -no-prec-div -ansi-alias

456.hmmcr: -xSSE4.2 -ipo -O3 -no-prec-div -static -unroll2
 -ansi-alias -auto-ilp32

458.sjeng: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
 -O3(pass 2) -no-prec-div(pass 2) -static(pass 2)
 -prof-use(pass 2) -unroll4 -auto-ilp32

462.libquantum: -xSSE4.2 -ipo -O3 -no-prec-div -static -auto-ilp32
 -opt-prefetch

464.h264ref: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
 -O3(pass 2) -no-prec-div(pass 2) -static(pass 2)
 -prof-use(pass 2) -unroll2 -ansi-alias

C++ benchmarks:

471.omnetpp: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
 -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
 -ansi-alias -Wl,-z,muldefs
 -L/opt/SmartHeap_8.1/lib -lsmartheap

473.astar: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
 -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
 -ansi-alias -opt-ra-region-strategy=routine -Wl,-z,muldefs

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

SPECint_rate2006 = 341

Express5800/A1080a-S/D (Intel Xeon E7520)

SPECint_rate_base2006 = 314

CPU2006 license: 9006

Test date: Jun-2010

Test sponsor: NEC Corporation

Hardware Availability: Jul-2010

Tested by: NEC Corporation

Software Availability: Mar-2010

Peak Optimization Flags (Continued)

473.astar (continued):

`-L/opt/SmartHeap_8.1/lib64 -lsmartheap64`

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/NEC.Express5800.A1080a-S.Intel-ic11.1-linux64-revE.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/NEC.Express5800.A1080a-S.Intel-ic11.1-linux64-revE.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.

Report generated on Wed Jul 23 13:18:20 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 8 July 2010.