



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

ASUS TS300-E6 (P7F-E) server system (Intel Xeon X3440)

SPECfp®2006 = 34.3

SPECfp_base2006 = 32.6

CPU2006 license: 9016


Test sponsor: ASUSTeK Computer Inc.

Tested by: ASUSTeK Computer Inc.

Test date: Jul-2010

Hardware Availability: Mar-2010

Software Availability: Jan-2010



Hardware

CPU Name: Intel Xeon X3440
CPU Characteristics: Intel Turbo Boost Technology up to 2.93 GHz
CPU MHz: 2533
FPU: Integrated
CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip, 2 threads/core
CPU(s) orderable: 1 chips
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 256 KB I+D on chip per core

Software

Operating System: SUSE Linux Enterprise Server 11 (x86_64), Kernel 2.6.27.19-5-default
Compiler: Intel C++ and Fortran Professional Compiler for IA32 and Intel 64, Version 11.1 Build 20091130 Package ID: l_cproc_p_11.1.064, l_cprof_p_11.1.064
Auto Parallel: Yes
File System: ReiserFS
System State: Run level 3 (multi-user)

Continued on next page

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

ASUS TS300-E6 (P7F-E) server system (Intel Xeon X3440)

SPECfp2006 = 34.3

SPECfp_base2006 = 32.6

CPU2006 license: 9016

Test sponsor: ASUSTeK Computer Inc.

Tested by: ASUSTeK Computer Inc.

Test date: Jul-2010

Hardware Availability: Mar-2010

Software Availability: Jan-2010

L3 Cache: 8 MB I+D on chip per chip
 Other Cache: None
 Memory: 16 GB (4 x 4 GB PC3-10600R, CL=9)
 Disk Subsystem: HITACHI HDP725050GLA380 1 x 500 GB SATAII, 7200 RPM
 Other Hardware: None

Base Pointers: 64-bit
 Peak Pointers: 32/64-bit
 Other Software: None

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio										
410.bwaves	179	75.9	<u>179</u>	<u>75.9</u>	179	76.1	<u>179</u>	<u>75.9</u>	<u>179</u>	<u>75.7</u>	<u>179</u>	<u>75.9</u>
416.gamess	915	21.4	<u>916</u>	<u>21.4</u>	921	21.3	<u>858</u>	<u>22.8</u>	<u>849</u>	<u>23.1</u>	<u>858</u>	<u>22.8</u>
433.milc	205	44.8	<u>210</u>	<u>43.8</u>	215	42.7	<u>209</u>	<u>43.9</u>	<u>206</u>	<u>44.5</u>	<u>205</u>	<u>44.7</u>
434.zeusmp	271	33.6	272	33.5	<u>272</u>	<u>33.5</u>	<u>272</u>	<u>33.4</u>	<u>272</u>	<u>33.4</u>	<u>271</u>	<u>33.6</u>
435.gromacs	<u>359</u>	<u>19.9</u>	360	19.9	357	20.0	<u>348</u>	<u>20.5</u>	<u>352</u>	<u>20.3</u>	<u>348</u>	<u>20.5</u>
436.cactusADM	138	86.7	<u>137</u>	<u>87.2</u>	136	87.6	<u>125</u>	<u>95.6</u>	124	96.1	125	95.6
437.leslie3d	332	28.3	<u>332</u>	<u>28.3</u>	333	28.3	<u>332</u>	<u>28.3</u>	<u>332</u>	<u>28.3</u>	333	28.3
444.namd	<u>467</u>	<u>17.2</u>	467	17.2	463	17.3	<u>467</u>	<u>17.2</u>	467	17.2	463	17.3
447.dealII	359	31.9	<u>361</u>	<u>31.7</u>	361	31.7	<u>333</u>	<u>34.3</u>	338	33.9	<u>334</u>	<u>34.2</u>
450.soplex	328	25.5	<u>327</u>	<u>25.5</u>	323	25.8	<u>328</u>	<u>25.5</u>	<u>327</u>	<u>25.5</u>	323	25.8
453.povray	214	24.9	216	24.6	<u>214</u>	<u>24.8</u>	164	32.5	162	32.9	<u>163</u>	<u>32.6</u>
454.calculix	315	26.2	315	26.2	<u>315</u>	<u>26.2</u>	<u>311</u>	<u>26.5</u>	310	26.6	313	26.4
459.GemsFDTD	287	37.0	<u>287</u>	<u>37.0</u>	287	36.9	<u>275</u>	<u>38.6</u>	274	38.7	<u>274</u>	<u>38.7</u>
465.tonto	469	21.0	470	20.9	<u>470</u>	<u>21.0</u>	364	27.0	<u>364</u>	<u>27.0</u>	371	26.5
470.lbm	291	47.2	293	47.0	<u>292</u>	<u>47.0</u>	291	47.2	293	47.0	<u>292</u>	<u>47.0</u>
481.wrf	<u>308</u>	<u>36.3</u>	308	36.3	308	36.2	<u>309</u>	<u>36.2</u>	308	36.2	309	36.2
482.sphinx3	511	38.1	<u>511</u>	<u>38.2</u>	510	38.2	<u>511</u>	<u>38.1</u>	<u>511</u>	<u>38.2</u>	510	38.2

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The config file option 'submit' was used.

Operating System Notes

'ulimit -s unlimited' was used to set the stack size to unlimited prior to run
 OMP_NUM_THREADS set to number of cores
 KMP_AFFINITY set to granularity=fine,scatter
 KMP_STACKSIZE set to 200M



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

ASUS TS300-E6 (P7F-E) server system (Intel Xeon X3440)

SPECfp2006 = 34.3

SPECfp_base2006 = 32.6

CPU2006 license: 9016

Test date: Jul-2010

Test sponsor: ASUSTeK Computer Inc.

Hardware Availability: Mar-2010

Tested by: ASUSTeK Computer Inc.

Software Availability: Jan-2010

Component Notes

Tested system case compliance with Intel EEB 3.61 spec

SSI Server Power Supply 650W or higher

System was configured with ASPEED AST2050 VGA (on board VGA)

General Notes

Binaries were compiled on SLES 10 with Binutils 2.18.50.0.7.20080502

Base Compiler Invocation

C benchmarks:

`icc -m64`

C++ benchmarks:

`icpc -m64`

Fortran benchmarks:

`ifort -m64`

Benchmarks using both Fortran and C:

`icc -m64 ifort -m64`

Base Portability Flags

410.bwaves: `-DSPEC_CPU_LP64`
416.gamess: `-DSPEC_CPU_LP64`
 433.milc: `-DSPEC_CPU_LP64`
434.zeusmp: `-DSPEC_CPU_LP64`
435.gromacs: `-DSPEC_CPU_LP64 -nofor_main`
436.cactusADM: `-DSPEC_CPU_LP64 -nofor_main`
437.leslie3d: `-DSPEC_CPU_LP64`
 444.namd: `-DSPEC_CPU_LP64`
 447.dealII: `-DSPEC_CPU_LP64`
 450.soplex: `-DSPEC_CPU_LP64`
 453.povray: `-DSPEC_CPU_LP64`
 454.calculix: `-DSPEC_CPU_LP64 -nofor_main`
459.GemsFDTD: `-DSPEC_CPU_LP64`
 465.tonto: `-DSPEC_CPU_LP64`
 470.lbm: `-DSPEC_CPU_LP64`
 481.wrf: `-DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX`
482.sphinx3: `-DSPEC_CPU_LP64`



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

ASUS TS300-E6 (P7F-E) server system (Intel Xeon X3440)

SPECfp2006 = 34.3

SPECfp_base2006 = 32.6

CPU2006 license: 9016

Test sponsor: ASUSTeK Computer Inc.

Tested by: ASUSTeK Computer Inc.

Test date: Jul-2010

Hardware Availability: Mar-2010

Software Availability: Jan-2010

Base Optimization Flags

C benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch

C++ benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch

Fortran benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch -parallel

Benchmarks using both Fortran and C:

-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch -parallel

Peak Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

433.milc: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
-fno-alias

470.lbm: basepeak = yes

482.sphinx3: basepeak = yes

C++ benchmarks:

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

ASUS TS300-E6 (P7F-E) server system (Intel Xeon X3440)

SPECfp2006 = 34.3

SPECfp_base2006 = 32.6

CPU2006 license: 9016

Test date: Jul-2010

Test sponsor: ASUSTeK Computer Inc.

Hardware Availability: Mar-2010

Tested by: ASUSTeK Computer Inc.

Software Availability: Jan-2010

Peak Optimization Flags (Continued)

444.namd: basepeak = yes

447.dealII: -xsSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
-unroll12 -ansi-alias -scalar-rep -opt-prefetch

450.soplex: basepeak = yes

453.povray: -xsSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
-unroll14 -ansi-alias

Fortran benchmarks:

410.bwaves: -xsSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch
-parallel

416.gamess: -xsSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
-unroll12 -Ob0 -ansi-alias -scalar-rep-

434.zeusmp: Same as 410.bwaves

437.leslie3d: basepeak = yes

459.GemsFDTD: -xsSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
-unroll12 -Ob0 -opt-prefetch -parallel

465.tonto: -xsSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
-unroll14 -auto

Benchmarks using both Fortran and C:

435.gromacs: -xsSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
-opt-prefetch -auto-ilp32

436.cactusADM: -xsSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)
-unroll12 -opt-prefetch -parallel -auto-ilp32

454.calculix: -xsSE4.2 -ipo -O3 -no-prec-div -static -auto-ilp32

481.wrf: -xsSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch
-parallel -auto-ilp32



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

ASUS TS300-E6 (P7F-E) server system (Intel Xeon X3440)

SPECfp2006 = 34.3

SPECfp_base2006 = 32.6

CPU2006 license: 9016

Test date: Jul-2010

Test sponsor: ASUSTeK Computer Inc.

Hardware Availability: Mar-2010

Tested by: ASUSTeK Computer Inc.

Software Availability: Jan-2010

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.1-linux64-revF.20100609.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic11.1-linux64-revF.20100609.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.

Report generated on Wed Jul 23 10:31:30 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 3 August 2010.