



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECfp®_rate2006 = 978

IBM Power 750 Express (3.55 GHz, 32 core, RedHat)

SPECfp_rate_base2006 = 873

CPU2006 license: 11


Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: Oct-2010

Hardware Availability: Feb-2010

Software Availability: Nov-2010



Hardware

CPU Name: POWER7
CPU Characteristics: Intelligent Energy Optimization enabled, up to 3.86 GHz
CPU MHz: 3556
FPU: Integrated
CPU(s) enabled: 32 cores, 4 chips, 8 cores/chip, 4 threads/core
CPU(s) orderable: 8,16,24,32 cores
Primary Cache: 32 KB I + 32 KB D on chip per core

Software

Operating System: Red Hat Enterprise Linux Server release 6.0 (ppc64), Kernel 2.6.32-71.el6.ppc64
Compiler: IBM XL C/C++ for Linux, V11.1 Updated with the Nov2010 PTF
IBM XL Fortran for Linux, V13.1 Updated with the Nov2010 PTF
Auto Parallel: No
File System: ext2
System State: Run level 3 (multi-user)

Continued on next page

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

IBM Power 750 Express (3.55 GHz, 32 core, RedHat)

SPECfp_rate2006 = 978

SPECfp_rate_base2006 = 873

CPU2006 license: 11

Test date: Oct-2010

Test sponsor: IBM Corporation

Hardware Availability: Feb-2010

Tested by: IBM Corporation

Software Availability: Nov-2010

Secondary Cache: 256 KB I+D on chip per core
 L3 Cache: 4 MB I+D on chip per core
 Other Cache: None
 Memory: 256 GB (32x8 GB) DDR3 1066 MHz
 Disk Subsystem: 6x146.8 GB Software RAID-0 SAS SFF 15K RPM
 Other Hardware: None

Base Pointers: 32-bit
 Peak Pointers: 32/64-bit
 Other Software: -Post-Link Optimization for Linux on POWER, Version 5.5.0-3
 -MicroQuill SmartHeap 9
 -Apache C++ Standard Library 4.2.1

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	128	2143	812	2149	810	<u>2147</u>	<u>810</u>	128	2143	812	2149	810	<u>2147</u>	<u>810</u>
416.gamess	128	2500	1000	2493	1010	<u>2498</u>	<u>1000</u>	128	2304	1090	<u>2306</u>	<u>1090</u>	2307	1090
433.milc	128	1539	763	1550	758	<u>1546</u>	<u>760</u>	32	<u>370</u>	<u>794</u>	370	794	371	792
434.zeusmp	128	1083	1080	1095	1060	<u>1084</u>	<u>1070</u>	128	1083	1080	1095	1060	<u>1084</u>	<u>1070</u>
435.gromacs	128	1129	810	<u>1122</u>	<u>815</u>	1121	815	128	<u>853</u>	<u>1070</u>	845	1080	855	1070
436.cactusADM	128	<u>1156</u>	<u>1320</u>	1157	1320	1152	1330	64	<u>525</u>	<u>1460</u>	524	1460	528	1450
437.leslie3d	128	2333	516	2340	514	<u>2338</u>	<u>515</u>	32	<u>551</u>	<u>546</u>	550	547	551	546
444.namd	128	<u>778</u>	<u>1320</u>	782	1310	776	1320	128	<u>751</u>	<u>1370</u>	<u>751</u>	<u>1370</u>	753	1360
447.dealII	128	841	1740	852	1720	<u>847</u>	<u>1730</u>	128	<u>640</u>	<u>2290</u>	638	2290	642	2280
450.soplex	128	2037	524	2039	524	<u>2037</u>	<u>524</u>	64	964	554	<u>950</u>	<u>562</u>	948	563
453.povray	128	640	1060	<u>639</u>	<u>1070</u>	637	1070	128	487	1400	490	1390	<u>489</u>	<u>1390</u>
454.calculix	128	1072	985	1104	956	<u>1097</u>	<u>963</u>	128	1096	964	<u>1085</u>	<u>973</u>	1084	974
459.GemsFDTD	128	3153	431	<u>3148</u>	<u>431</u>	3147	431	128	3153	431	<u>3148</u>	<u>431</u>	3147	431
465.tonto	128	<u>1859</u>	<u>678</u>	1865	675	1856	679	128	1067	1180	<u>1067</u>	<u>1180</u>	1066	1180
470.lbm	128	1526	1150	1529	1150	<u>1526</u>	<u>1150</u>	128	1526	1150	1529	1150	<u>1526</u>	<u>1150</u>
481.wrf	128	1688	847	1692	845	<u>1690</u>	<u>846</u>	128	1652	865	<u>1650</u>	<u>867</u>	1645	869
482.sphinx3	128	<u>3228</u>	<u>773</u>	3233	772	3228	773	32	706	884	700	891	<u>704</u>	<u>886</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Peak Tuning Notes

IBM Post-Link Optimization tool with options "-O4 -nodp" used for
 433.milc 435.gromacs 450.soplex 482.sphinx3
 options "-O4 -vrox -nodp" used for
 434.zeusmp
 options "-O3 -lu -l -nodp -sdp 9" used for
 437.leslie3d 444.namd
 options "-O4" used for
 465.tonto



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECfp_rate2006 = 978

IBM Power 750 Express (3.55 GHz, 32 core, RedHat)

SPECfp_rate_base2006 = 873

CPU2006 license: 11

Test date: Oct-2010

Test sponsor: IBM Corporation

Hardware Availability: Feb-2010

Tested by: IBM Corporation

Software Availability: Nov-2010

Submit Notes

The config file option 'submit' was used.

Benchmarks bound to a processor using numactl on the submit command.

Operating System Notes

ulimit -s (stack) set to 1048576.

Large pages reserved as follows by root user:

```
echo 9000 > /proc/sys/vm/nr_hugepages
```

The following environment variables were set before the runspec command:

```
XLF RTE OPTS=intrin thd s=1
```

```
HUGETLB_VERBOSE=0
```

```
HUGETLB_MORECORE=yes
```

```
HUGETLB_ELFMAP=RW
```

447.dealII (peak): "apache_stdcxx_4_2_1" src.alt was used.

447.dealII (base): "apache_stdcxx_4_2_1" src.alt was used.

Base Compiler Invocation

C benchmarks:

```
xlc -qlanglvl=extc99
```

C++ benchmarks:

```
xlc
```

Fortran benchmarks:

```
xlf95
```

Benchmarks using both Fortran and C:

```
xlc -qlanglvl=extc99 xlf95
```

Base Portability Flags

```
410.bwaves: -qfixed  
416.gamess: -qfixed  
434.zeusmp: -qfixed  
435.gromacs: -qfixed -qextname  
436.cactusADM: -qfixed -qextname  
437.leslie3d: -qfixed  
454.calculix: -qfixed -qextname  
481.wrf: -DNOUNDERSCORE  
482.sphinx3: -qchars=signed
```



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECfp_rate2006 = 978

IBM Power 750 Express (3.55 GHz, 32 core, RedHat)

SPECfp_rate_base2006 = 873

CPU2006 license: 11

Test date: Oct-2010

Test sponsor: IBM Corporation

Hardware Availability: Feb-2010

Tested by: IBM Corporation

Software Availability: Nov-2010

Base Optimization Flags

C benchmarks:

```
-O5 -qarch=pwr7 -qtune=pwr7 -B/usr/share/libhugetlbfss/ -tl  
-Wl,--hugetlbfss-align
```

C++ benchmarks:

```
-O5 -qarch=pwr7 -qtune=pwr7 -gRTTI -B/usr/share/libhugetlbfss/ -tl  
-Wl,--hugetlbfss-align
```

Fortran benchmarks:

```
-O5 -qarch=pwr7 -qtune=pwr7 -qsmallstack=dynlenonheap -qalias=nostd  
-B/usr/share/libhugetlbfss/ -tl -Wl,--hugetlbfss-align
```

Benchmarks using both Fortran and C:

```
-O5 -qarch=pwr7 -qtune=pwr7 -B/usr/share/libhugetlbfss/ -tl  
-Wl,--hugetlbfss-align -qsmallstack=dynlenonheap -qalias=nostd
```

Base Other Flags

C benchmarks:

```
-qipa=threads
```

C++ benchmarks:

```
-qipa=threads
```

Fortran benchmarks:

```
-qipa=threads
```

Benchmarks using both Fortran and C:

```
-qipa=threads
```

Peak Compiler Invocation

C benchmarks:

```
xlc -qlanglvl=extc99
```

C++ benchmarks:

```
x1C
```

Fortran benchmarks:

```
xlf95
```

Benchmarks using both Fortran and C:

```
xlc -qlanglvl=extc99 xlf95
```



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

IBM Power 750 Express (3.55 GHz, 32 core, RedHat)

SPECfp_rate2006 = 978

SPECfp_rate_base2006 = 873

CPU2006 license: 11

Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: Oct-2010

Hardware Availability: Feb-2010

Software Availability: Nov-2010

Peak Portability Flags

```
410.bwaves: -qfixed
416.gamess: -qfixed
434.zeusmp: -qfixed
435.gromacs: -qfixed -qextname
436.cactusADM: -DSPEC_CPU_LP64 -qfixed -qextname
437.leslie3d: -qfixed
453.povray: -DSPEC_CPU_LP64
454.calculix: -qfixed -qextname
481.wrf: -DNOUNDERSCORE
482.sphinx3: -qchars=signed
```

Peak Optimization Flags

C benchmarks:

```
433.milc: -Wl,-q -O5 -qarch=pwr7 -qtune=pwr7 -lhugetlbfs
470.lbm: basepeak = yes
482.sphinx3: -Wl,-q -qpdf1(pass 1) -qpdf2(pass 2) -O4 -qarch=pwr7
               -qtune=pwr7 -lhugetlbfs
```

C++ benchmarks:

```
444.namd: -Wl,-q -qpdf1(pass 1) -qpdf2(pass 2) -O5 -qarch=pwr7
               -qtune=pwr7 -lhugetlbfs
447.dealII: -O4 -qarch=pwr7 -qtune=pwr7 -qrtti
               -qcpp_stdinc=/autobench/sources/stdcxx-4.2.1/dist/include/ansi:/autobench/sources/stdcxx-4.2.1/dist/include:/opt/ibmcpp/vacpp/11.1/include
               -lsmartheap -L/autobench/sources/stdcxx-4.2.1/dist/lib
               -R/autobench/sources/stdcxx-4.2.1/dist/lib -lstd8d
450.soplex: -Wl,-q -qpdf1(pass 1) -qpdf2(pass 2) -O3 -qarch=pwr7
               -qtune=pwr7 -q64 -lhugetlbfs
453.povray: -Wl,-q -qpdf1(pass 1) -qpdf2(pass 2) -O4 -qarch=pwr7
               -qtune=pwr7 -qsimd -q64 -lsmartheap64
```

Fortran benchmarks:

```
410.bwaves: basepeak = yes
416.gamess: -qpdf1(pass 1) -qpdf2(pass 2) -O5 -qarch=pwr7 -qtune=pwr7
               -qalias=nostd -lhugetlbfs
434.zeusmp: basepeak = yes
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECfp_rate2006 = 978

IBM Power 750 Express (3.55 GHz, 32 core, RedHat)

SPECfp_rate_base2006 = 873

CPU2006 license: 11

Test date: Oct-2010

Test sponsor: IBM Corporation

Hardware Availability: Feb-2010

Tested by: IBM Corporation

Software Availability: Nov-2010

Peak Optimization Flags (Continued)

437.leslie3d: -Wl,-q -O5 -qarch=pwr7 -qtune=pwr7 -q64
-B/usr/share/libhugetlbfs/ -tl -Wl,--hugetlbfs-align

459.GemsFDTD: basepeak = yes

465.tonto: -Wl,-q -qpdf1(pass 1) -qpdf2(pass 2) -O5 -qarch=pwr7
-qtune=pwr7 -qsimd -lhugetlbfs

Benchmarks using both Fortran and C:

435.gromacs: -Wl,-q -qpdf1(pass 1) -qpdf2(pass 2) -O4 -qarch=pwr7
-qtune=pwr7 -qsimd -lhugetlbfs

436.cactusADM: -O4 -qarch=pwr7 -qtune=pwr7 -qsimd -qnostrict -q64
-lhugetlbfs

454.calculix: -qpdf1(pass 1) -qpdf2(pass 2) -O5 -qarch=pwr7 -qtune=pwr7
-B/usr/share/libhugetlbfs/ -tl -Wl,--hugetlbfs-align

481.wrf: -O3 -qarch=pwr7 -qtune=pwr7 -q64 -lhugetlbfs

Peak Other Flags

C benchmarks:

-qipa=threads

C++ benchmarks (except as noted below):

-qipa=threads

Fortran benchmarks:

-qipa=threads

Benchmarks using both Fortran and C (except as noted below):

-qipa=threads

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/IBM-Linux-XL.20101123.01.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/IBM-Linux-XL.20101123.01.xml>



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECfp_rate2006 = 978

IBM Power 750 Express (3.55 GHz, 32 core, RedHat)

SPECfp_rate_base2006 = 873

CPU2006 license: 11

Test date: Oct-2010

Test sponsor: IBM Corporation

Hardware Availability: Feb-2010

Tested by: IBM Corporation

Software Availability: Nov-2010

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.

Report generated on Wed Jul 23 14:24:42 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 23 November 2010.