



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp®_rate2006 = 54.0

Intel DH57JG Motherboard (Intel Core i5-660)

SPECfp_rate_base2006 = 53.8

CPU2006 license: 13


Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Jul-2011

Hardware Availability: Jan-2010

Software Availability: Apr-2011



Hardware

CPU Name: Intel Core i5-660
 CPU Characteristics: Intel Turbo Boost Technology up to 3.60 GHz
 CPU MHz: 3333
 FPU: Integrated
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip, 2 threads/core
 CPU(s) orderable: 1 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

Software

Operating System: Windows 7 Ultimate (64-bit)
 Compiler: Intel C++ Compiler XE for Intel 64 Version 12.0.3.176 Build 20110309
 Intel Visual Fortran Compiler XE for Intel 64 Version 12.0.3.176 Build 20110309
 Microsoft Visual Studio 2008 Professional SP1 (for libraries)
 Auto Parallel: No
 File System: NTFS

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp_rate2006 = 54.0

Intel DH57JG Motherboard (Intel Core i5-660)

SPECfp_rate_base2006 = 53.8

CPU2006 license: 13

Test date: Jul-2011

Test sponsor: Intel Corporation

Hardware Availability: Jan-2010

Tested by: Intel Corporation

Software Availability: Apr-2011

L3 Cache: 4 MB I+D on chip per chip
 Other Cache: None
 Memory: 4 GB (2 x 2 GB 2Rx8 PC3-10600U-9)
 Disk Subsystem: Seagate 1 TB SATA, 7200 RPM
 Other Hardware: None

System State: Default
 Base Pointers: 32/64-bit
 Peak Pointers: 32/64-bit
 Other Software: SmartHeap Library Version 9.01 from <http://www.microquill.com/>

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	4	<u>1042</u>	<u>52.0</u>	1042	52.0	1034	52.4	4	<u>1042</u>	<u>52.0</u>	1042	52.0	1034	52.4
416.gamess	4	<u>1348</u>	<u>58.0</u>	1358	57.6	1348	58.0	4	<u>1348</u>	<u>58.0</u>	1358	57.6	1348	58.0
433.milc	4	<u>580</u>	<u>63.2</u>	581	63.2	579	63.6	4	<u>580</u>	<u>63.2</u>	581	63.2	579	63.6
434.zeusmp	4	627	58.0	<u>629</u>	<u>58.0</u>	631	57.6	4	627	58.0	<u>629</u>	<u>58.0</u>	631	57.6
435.gromacs	4	<u>530</u>	<u>54.0</u>	534	53.6	529	54.0	4	541	52.8	<u>539</u>	<u>53.2</u>	535	53.2
436.cactusADM	4	876	54.4	871	54.8	<u>875</u>	<u>54.8</u>	4	876	54.4	871	54.8	<u>875</u>	<u>54.8</u>
437.leslie3d	4	1187	31.6	<u>1154</u>	<u>32.4</u>	1139	33.2	4	1187	31.6	<u>1154</u>	<u>32.4</u>	1139	33.2
444.namd	4	634	50.4	634	50.8	<u>634</u>	<u>50.8</u>	4	<u>615</u>	<u>52.0</u>	616	52.0	615	52.0
447.dealII	4	756	60.4	751	60.8	<u>753</u>	<u>60.8</u>	4	749	61.2	<u>729</u>	<u>62.8</u>	707	64.8
450.soplex	4	<u>846</u>	<u>39.6</u>	845	39.6	846	39.6	2	479	34.8	<u>479</u>	<u>34.8</u>	480	34.8
453.povray	4	<u>288</u>	<u>73.6</u>	289	73.6	287	74.0	4	<u>246</u>	<u>86.4</u>	244	87.2	247	86.0
454.calculix	4	525	62.8	530	62.4	<u>525</u>	<u>62.8</u>	4	529	62.4	<u>529</u>	<u>62.4</u>	529	62.4
459.GemsFDTD	4	<u>1410</u>	<u>30.0</u>	1409	30.0	1411	30.0	4	<u>1410</u>	<u>30.0</u>	1409	30.0	1411	30.0
465.tonto	4	690	57.2	687	57.2	<u>690</u>	<u>57.2</u>	4	<u>677</u>	<u>58.0</u>	678	58.0	677	58.0
470.lbm	4	<u>775</u>	<u>70.8</u>	775	70.8	775	70.8	4	<u>775</u>	<u>70.8</u>	775	70.8	775	70.8
481.wrf	4	639	70.0	637	70.0	<u>638</u>	<u>70.0</u>	4	639	70.0	637	70.0	<u>638</u>	<u>70.0</u>
482.sphinx3	4	<u>1515</u>	<u>51.6</u>	1508	51.6	1518	51.2	4	1503	52.0	1513	51.6	<u>1505</u>	<u>51.6</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The config file option 'submit' was used.
The start command with the /affinity switch was used to bind processes to cores

General Notes

Tested systems can be used with Shin-G ATX case,
PC Power and Cooling 1200W power supply

Base Compiler Invocation

C benchmarks:
icl -Qvc9 -Qstd=c99

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp_rate2006 = 54.0

Intel DH57JG Motherboard (Intel Core i5-660)

SPECfp_rate_base2006 = 53.8

CPU2006 license: 13

Test date: Jul-2011

Test sponsor: Intel Corporation

Hardware Availability: Jan-2010

Tested by: Intel Corporation

Software Availability: Apr-2011

Base Compiler Invocation (Continued)

C++ benchmarks:

icl -Qvc9

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icl -Qvc9 -Qstd=c99 ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_P64 -names:lowercase
 416.gamess: -DSPEC_CPU_P64
 433.milc: -DSPEC_CPU_P64
 434.zeusmp: -DSPEC_CPU_P64
 435.gromacs: -DSPEC_CPU_P64
 436.cactusADM: -DSPEC_CPU_P64 -names:lowercase /assume:underscore
 437.leslie3d: -DSPEC_CPU_P64
 444.namd: -DSPEC_CPU_P64 /TP
 447.dealII: -DSPEC_CPU_P64 -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG
 450.soplex: -DSPEC_CPU_P64
 453.povray: -DSPEC_CPU_P64 -DSPEC_CPU_WINDOWS_ICL
 454.calculix: -DSPEC_CPU_P64 -DSPEC_CPU_NOZMODIFIER -names:lowercase
 459.GemsFDTD: -DSPEC_CPU_P64
 465.tonto: -DSPEC_CPU_P64
 470.lbm: -DSPEC_CPU_P64
 481.wrf: -DSPEC_CPU_P64 -DSPEC_CPU_WINDOWS_ICL
 482.sphinx3: -DSPEC_CPU_P64

Base Optimization Flags

C benchmarks:

-QxSSE4.2 -Qipo -O3 -Qprec-div- -Qansi-alias -Qauto-ilp32
/F1000000000 -link /FORCE:MULTIPLE

C++ benchmarks:

-QxSSE4.2 -Qipo -O3 -Qprec-div- -Qansi-alias -Qcxx-features
-Qauto-ilp32 /F1000000000 shlw64M.lib -link /FORCE:MULTIPLE

Fortran benchmarks:

-QxSSE4.2 -Qipo -O3 -Qprec-div- -Qansi-alias /F1000000000
-link /FORCE:MULTIPLE

Benchmarks using both Fortran and C:

-QxSSE4.2 -Qipo -O3 -Qprec-div- -Qansi-alias -Qauto-ilp32
/F1000000000 -link /FORCE:MULTIPLE



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp_rate2006 = 54.0

Intel DH57JG Motherboard (Intel Core i5-660)

SPECfp_rate_base2006 = 53.8

CPU2006 license: 13

Test date: Jul-2011

Test sponsor: Intel Corporation

Hardware Availability: Jan-2010

Tested by: Intel Corporation

Software Availability: Apr-2011

Peak Compiler Invocation

C benchmarks:

icl -Qvc9 -Qstd=c99

C++ benchmarks:

icl -Qvc9

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icl -Qvc9 -Qstd=c99 ifort

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

433.milc: basepeak = yes

470.lbm: basepeak = yes

482.sphinx3: -QxSSE4.2 -Qipo -O3 -Qprec-div- -Qunroll2 -Qansi-alias
-Qauto-ilp32 /F1000000000 -link /FORCE:MULTIPLE

C++ benchmarks:

444.namd: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Oa -Qauto-ilp32 /F1000000000
shlW64M.lib -link /FORCE:MULTIPLE

447.dealII: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qunroll2 -Qansi-alias
-Qscalar-rep- -Qauto-ilp32 /F1000000000 shlW64M.lib
-link /FORCE:MULTIPLE

450.soplex: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qauto-ilp32 /F1000000000 shlW64M.lib
-link /FORCE:MULTIPLE

453.povray: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qopt-prefetch -Qauto-ilp32
/F1000000000 shlW64M.lib -link /FORCE:MULTIPLE

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp_rate2006 = 54.0

Intel DH57JG Motherboard (Intel Core i5-660)

SPECfp_rate_base2006 = 53.8

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Jul-2011

Hardware Availability: Jan-2010

Software Availability: Apr-2011

Peak Optimization Flags (Continued)

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: basepeak = yes

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

465.tonto: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qunroll4 -Qauto /F1000000000
-link /FORCE:MULTIPLE

Benchmarks using both Fortran and C:

435.gromacs: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qopt-prefetch -Qauto-ilp32
/F1000000000 -link /FORCE:MULTIPLE

436.cactusADM: basepeak = yes

454.calculix: -QxSSE4.2 -Qipo -O3 -Qprec-div- -Qauto-ilp32 /F1000000000
-link /FORCE:MULTIPLE

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12-winx64-revC.html>

<http://www.spec.org/cpu2006/flags/Intel-Windows-Platform-Settings.20110719.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic12-winx64-revC.xml>

<http://www.spec.org/cpu2006/flags/Intel-Windows-Platform-Settings.20110719.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.

Report generated on Wed Jul 23 22:10:29 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 22 August 2011.