



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Itautec**

**SPECfp®\_rate2006 = 216**

Servidor Itautec MX214 (Intel Xeon E5645)

**SPECfp\_rate\_base2006 = 211**

CPU2006 license: 9001


**Test date:** Sep-2011

**Test sponsor:** Itautec

**Hardware Availability:** Jul-2011

**Tested by:** Itautec

**Software Availability:** Jan-2011



## Hardware

CPU Name: Intel Xeon E5645  
CPU Characteristics: Intel Turbo Boost Technology up to 2.80 GHz  
CPU MHz: 2400  
FPU: Integrated  
CPU(s) enabled: 12 cores, 2 chips, 6 cores/chip, 2 threads/core  
CPU(s) orderable: 1,2 chips  
Primary Cache: 32 KB I + 32 KB D on chip per core  
Secondary Cache: 256 KB I+D on chip per core

## Software

Operating System: SUSE Linux Enterprise Server 11 SP1 (x86\_64), Kernel 2.6.32.12-0.7-default  
Compiler: Intel C++ and Fortran Intel 64 Compiler XE for applications running on Intel 64 Version 12.0.2 Build 20110112  
Auto Parallel: No  
File System: ext3  
System State: Run level 3 (multi-user)  
Base Pointers: 64-bit

*Continued on next page*

*Continued on next page*



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Itautec**

**SPECfp\_rate2006 = 216**

**Servidor Itautec MX214 (Intel Xeon E5645)**

**SPECfp\_rate\_base2006 = 211**

**CPU2006 license:** 9001

**Test date:** Sep-2011

**Test sponsor:** Itautec

**Hardware Availability:** Jul-2011

**Tested by:** Itautec

**Software Availability:** Jan-2011

L3 Cache: 12 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 48 GB (12 x 4 GB 2Rx4 PC3-10600R-9, ECC)  
 Disk Subsystem: 1 x 500 GB SATA-2, 7200 RPM  
 Other Hardware: None

Peak Pointers: 32/64-bit  
 Other Software: None

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	24	<b>1917</b>	<b>170</b>	1917	170	1921	170	12	<b>959</b>	<b>170</b>	956	171	960	170
416.gamess	24	1853	254	1818	258	<b>1838</b>	<b>256</b>	24	1853	254	1818	258	<b>1838</b>	<b>256</b>
433.milc	24	<b>1232</b>	<b>179</b>	1232	179	1233	179	24	<b>1232</b>	<b>179</b>	1232	179	1233	179
434.zeusmp	24	<b>868</b>	<b>252</b>	872	251	866	252	24	<b>868</b>	<b>252</b>	872	251	866	252
435.gromacs	24	714	240	727	236	<b>724</b>	<b>237</b>	24	715	240	723	237	<b>719</b>	<b>238</b>
436.cactusADM	24	<b>1044</b>	<b>275</b>	1041	276	1055	272	24	<b>1044</b>	<b>275</b>	1041	276	1055	272
437.leslie3d	24	1891	119	1882	120	<b>1884</b>	<b>120</b>	12	915	123	915	123	<b>915</b>	<b>123</b>
444.namd	24	<b>868</b>	<b>222</b>	876	220	866	222	24	<b>855</b>	<b>225</b>	856	225	850	226
447.dealII	24	860	319	<b>816</b>	<b>336</b>	813	338	24	860	319	<b>816</b>	<b>336</b>	813	338
450.soplex	24	1696	118	<b>1600</b>	<b>125</b>	1592	126	12	<b>758</b>	<b>132</b>	760	132	696	144
453.povray	24	381	335	<b>379</b>	<b>337</b>	379	337	24	318	402	<b>321</b>	<b>398</b>	322	397
454.calculix	24	682	290	<b>685</b>	<b>289</b>	685	289	24	682	290	<b>685</b>	<b>289</b>	685	289
459.GemsFDTD	24	2288	111	<b>2284</b>	<b>111</b>	2283	112	24	2288	111	<b>2284</b>	<b>111</b>	2283	112
465.tonto	24	<b>1023</b>	<b>231</b>	1017	232	1051	225	24	1002	236	<b>1012</b>	<b>233</b>	1024	231
470.lbm	24	<b>1340</b>	<b>246</b>	1340	246	1341	246	12	<b>656</b>	<b>251</b>	657	251	<b>657</b>	<b>251</b>
481.wrf	24	1378	195	1368	196	<b>1376</b>	<b>195</b>	24	1378	195	1368	196	<b>1376</b>	<b>195</b>
482.sphinx3	24	2431	192	<b>2424</b>	<b>193</b>	2423	193	24	<b>2319</b>	<b>202</b>	2325	201	2314	202

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The config file option 'submit' was used.  
 numactl was used to bind copies to the cores

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run.  
 Large pages were not enabled for this run

## Platform Notes

Data Reuse disabled in BIOS.



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itaute

Servidor Itaute MX214 (Intel Xeon E5645)

**SPECfp\_rate2006 = 216**

CPU2006 license: 9001

Test date: Sep-2011

Test sponsor: Itaute

Hardware Availability: Jul-2011

Tested by: Itaute

Software Availability: Jan-2011

## Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static -ansi-alias

C++ benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static -ansi-alias

Fortran benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -static

Benchmarks using both Fortran and C:

-xSSE4.2 -ipo -O3 -no-prec-div -static -ansi-alias



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itautech

Servidor Itautech MX214 (Intel Xeon E5645)

**SPECfp\_rate2006 = 216**

CPU2006 license: 9001

Test date: Sep-2011

Test sponsor: Itautech

Hardware Availability: Jul-2011

Tested by: Itautech

Software Availability: Jan-2011

## Peak Compiler Invocation

C benchmarks (except as noted below):

icc -m64

482.sphinx3: icc -m32

C++ benchmarks (except as noted below):

icpc -m64

450.soplex: icpc -m32

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

## Peak Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

433.milc: basepeak = yes

470.lbm: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -opt-malloc-options=3  
-ansi-alias -opt-prefetch -static -auto-ilp32

482.sphinx3: -xSSE4.2 -ipo -O3 -no-prec-div -unroll2

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itautec

SPECfp\_rate2006 = 216

Servidor Itautec MX214 (Intel Xeon E5645)

SPECfp\_rate\_base2006 = 211

CPU2006 license: 9001

Test date: Sep-2011

Test sponsor: Itautec

Hardware Availability: Jul-2011

Tested by: Itautec

Software Availability: Jan-2011

## Peak Optimization Flags (Continued)

C++ benchmarks:

444.namd: -xsse4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -fno-alias  
-auto-ilp32

447.dealII: basepeak = yes

450.soplex: -xsse4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -opt-malloc-options=3  
-B /usr/share/libhugetlbfss/ -Wl,-hugetlbfss-link=BDT

453.povray: -xsse4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll14 -ansi-alias  
-B /usr/share/libhugetlbfss/ -Wl,-melf\_x86\_64 -Wl,-hugetlbfss-link=BDT

Fortran benchmarks:

410.bwaves: -xsse4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -static

416.gamess: basepeak = yes

434.zeusmp: basepeak = yes

437.leslie3d: -xsse4.2 -ipo -O3 -no-prec-div  
-B /usr/share/libhugetlbfss/ -Wl,-melf\_x86\_64 -Wl,-hugetlbfss-link=BDT

459.GemsFDTD: basepeak = yes

465.tonto: -xsse4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll14 -auto  
-inline-calloc -opt-malloc-options=3  
-B /usr/share/libhugetlbfss/ -Wl,-melf\_x86\_64 -Wl,-hugetlbfss-link=BDT

Benchmarks using both Fortran and C:

435.gromacs: -xsse4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -opt-prefetch  
-static -auto-ilp32

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: basepeak = yes



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itautech

SPECfp\_rate2006 = 216

Servidor Itautec MX214 (Intel Xeon E5645)

SPECfp\_rate\_base2006 = 211

CPU2006 license: 9001

Test date: Sep-2011

Test sponsor: Itautech

Hardware Availability: Jul-2011

Tested by: Itautech

Software Availability: Jan-2011

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Itautec-Intel-Linux64-Platform.html>

<http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Itautec-Intel-Linux64-Platform.xml>

<http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.

Report generated on Thu Jul 24 01:38:48 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 11 October 2011.