



# SPEC<sup>®</sup> CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu

SPECfp<sup>®</sup>2006 = **92.7**

PRIMERGY RX350 S7, Intel Xeon E5-2690, 2.90 GHz

SPECfp\_base2006 = **86.6**

CPU2006 license: 19


Test date: Feb-2012

Test sponsor: Fujitsu

Hardware Availability: Mar-2012

Tested by: Fujitsu

Software Availability: Feb-2012



**Hardware**

CPU Name: Intel Xeon E5-2690  
 CPU Characteristics: Intel Turbo Boost Technology up to 3.80 GHz  
 CPU MHz: 2900  
 FPU: Integrated  
 CPU(s) enabled: 16 cores, 2 chips, 8 cores/chip  
 CPU(s) orderable: 1,2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

**Software**

Operating System: Red Hat Enterprise Linux Server release 6.2 (Santiago)  
 2.6.32-220.el6.x86\_64  
 Compiler: C/C++: Version 12.1.2.273 of Intel C++ Studio XE for Linux;  
 Fortran: Version 12.1.2.273 of Intel Fortran Studio XE for Linux  
 Auto Parallel: Yes  
 File System: ext4

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu

SPECfp2006 = **92.7**

PRIMERGY RX350 S7, Intel Xeon E5-2690, 2.90 GHz

SPECfp\_base2006 = **86.6**

CPU2006 license: 19

Test sponsor: Fujitsu

Tested by: Fujitsu

Test date: Feb-2012

Hardware Availability: Mar-2012

Software Availability: Feb-2012

L3 Cache: 20 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 128 GB (16 x 8 GB 2Rx4 PC3L-12800R-11, ECC)  
 Disk Subsystem: 1 x SATA, 500 GB, 7200 RPM  
 Other Hardware: None

System State: Run level 3 (multi-user)  
 Base Pointers: 64-bit  
 Peak Pointers: 32/64-bit  
 Other Software: None

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	<b>42.6</b>	<b>319</b>	42.8	317	42.4	320	43.2	314	<b>42.6</b>	<b>319</b>	42.4	320
416.gamess	587	33.4	586	33.4	<b>587</b>	<b>33.4</b>	491	39.9	490	40.0	<b>490</b>	<b>39.9</b>
433.milc	129	71.0	130	70.9	<b>130</b>	<b>70.9</b>	128	71.6	<b>128</b>	<b>71.5</b>	128	71.5
434.zeusmp	<b>58.8</b>	<b>155</b>	58.6	155	58.8	155	<b>58.4</b>	<b>156</b>	58.4	156	58.4	156
435.gromacs	174	41.2	175	40.7	<b>174</b>	<b>41.1</b>	174	41.2	175	40.7	<b>174</b>	<b>41.1</b>
436.cactusADM	<b>25.0</b>	<b>478</b>	25.0	478	25.2	474	<b>25.0</b>	<b>478</b>	25.4	470	24.6	485
437.leslie3d	<b>49.6</b>	<b>189</b>	45.4	207	49.6	189	43.4	216	<b>42.6</b>	<b>221</b>	42.4	222
444.namd	310	25.9	310	25.9	<b>310</b>	<b>25.9</b>	304	26.4	305	26.3	<b>304</b>	<b>26.3</b>
447.dealII	184	62.1	185	61.8	<b>184</b>	<b>62.1</b>	<b>183</b>	<b>62.5</b>	183	62.5	183	62.5
450.soplex	174	48.0	<b>174</b>	<b>48.0</b>	174	48.0	174	48.0	<b>174</b>	<b>48.0</b>	174	48.0
453.povray	<b>110</b>	<b>48.6</b>	110	48.6	109	48.9	93.9	56.6	<b>93.1</b>	<b>57.2</b>	92.9	57.2
454.calculix	195	42.3	195	42.2	<b>195</b>	<b>42.3</b>	<b>175</b>	<b>47.2</b>	175	47.2	175	47.1
459.GemsFDTD	75.4	141	<b>75.8</b>	<b>140</b>	76.0	140	59.9	177	<b>59.9</b>	<b>177</b>	59.9	177
465.tonto	240	41.1	240	41.0	<b>240</b>	<b>41.0</b>	<b>202</b>	<b>48.7</b>	203	48.5	202	48.7
470.lbm	<b>35.6</b>	<b>386</b>	35.2	390	38.4	358	<b>32.8</b>	<b>419</b>	32.8	419	32.4	424
481.wrf	<b>156</b>	<b>71.5</b>	155	71.9	157	71.1	151	74.1	153	72.8	<b>152</b>	<b>73.3</b>
482.sphinx3	<b>246</b>	<b>79.3</b>	247	79.0	244	79.8	<b>246</b>	<b>79.3</b>	247	79.0	244	79.8

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The config file option 'submit' was used.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

## Platform Notes

BIOS configuration:  
 Intel HT Technology = Disable  
 Frequency Floor Override = Enable



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Fujitsu**

**SPECfp2006 = 92.7**

**PRIMERGY RX350 S7, Intel Xeon E5-2690, 2.90 GHz**

**SPECfp\_base2006 = 86.6**

**CPU2006 license:** 19

**Test sponsor:** Fujitsu

**Tested by:** Fujitsu

**Test date:** Feb-2012

**Hardware Availability:** Mar-2012

**Software Availability:** Feb-2012

## General Notes

Environment variables set by runspec before the start of the run:

```
KMP_AFFINITY = "granularity=fine,scatter"
LD_LIBRARY_PATH = "/SPECcpu2006/libs/32:/SPECcpu2006/libs/64"
OMP_NUM_THREADS = "16"
```

Binaries compiled on a system with  
Red Hat Enterprise Linux Server release 6.1 (Santiago)  
Added glibc-static-2.12-1.25.el6.x86\_64.rpm  
to enable static linking  
Transparent Huge Pages enabled with:  
echo always > /sys/kernel/mm/redhat\_transparent\_hugepage/enabled  
This result was measured on the PRIMERGY RX350 S7. The PRIMERGY RX350 S7  
and the PRIMERGY TX300 S7 are electronically equivalent.  
For information about Fujitsu please visit: <http://www.fujitsu.com>

## Base Compiler Invocation

C benchmarks:

```
icc -m64
```

C++ benchmarks:

```
icpc -m64
```

Fortran benchmarks:

```
ifort -m64
```

Benchmarks using both Fortran and C:

```
icc -m64 ifort -m64
```

## Base Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.lelie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.deallI: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
```

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

SPECfp2006 = 92.7

PRIMERGY RX350 S7, Intel Xeon E5-2690, 2.90 GHz

SPECfp\_base2006 = 86.6

CPU2006 license: 19  
Test sponsor: Fujitsu  
Tested by: Fujitsu

Test date: Feb-2012  
Hardware Availability: Mar-2012  
Software Availability: Feb-2012

## Base Portability Flags (Continued)

482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:

-xAVX -ipo -O3 -no-prec-div -static -parallel -opt-prefetch  
-ansi-alias

C++ benchmarks:

-xAVX -ipo -O3 -no-prec-div -static -opt-prefetch -ansi-alias

Fortran benchmarks:

-xAVX -ipo -O3 -no-prec-div -static -parallel -opt-prefetch

Benchmarks using both Fortran and C:

-xAVX -ipo -O3 -no-prec-div -static -parallel -opt-prefetch  
-ansi-alias

## Peak Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

433.milc: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -static -auto-ilp32  
-ansi-alias

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu

SPECfp2006 = 92.7

PRIMERGY RX350 S7, Intel Xeon E5-2690, 2.90 GHz

SPECfp\_base2006 = 86.6

CPU2006 license: 19

Test date: Feb-2012

Test sponsor: Fujitsu

Hardware Availability: Mar-2012

Tested by: Fujitsu

Software Availability: Feb-2012

## Peak Optimization Flags (Continued)

470.lbm: -xAVX -ipo -O3 -no-prec-div -static -parallel  
-opt-prefetch -ansi-alias

482.sphinx3: basepeak = yes

### C++ benchmarks:

444.namd: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -fno-alias  
-auto-ilp32

447.dealIII: -xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -ansi-alias  
-static

450.soplex: basepeak = yes

453.povray: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -ansi-alias

### Fortran benchmarks:

410.bwaves: -xAVX -ipo -O3 -no-prec-div -opt-prefetch -parallel  
-static

416.gamess: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2  
-inline-level=0 -scalar-rep- -static

434.zeusmp: -xAVX -ipo -O3 -no-prec-div -static -parallel  
-opt-prefetch

437.leslie3d: Same as 434.zeusmp

459.GemsFDTD: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2  
-inline-level=0 -opt-prefetch -parallel

465.tonto: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -inline-calloc  
-opt-malloc-options=3 -auto -unroll4

### Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: -xAVX -ipo -O3 -no-prec-div -static -parallel  
-opt-prefetch -ansi-alias

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Fujitsu**

**SPECfp2006 = 92.7**

PRIMERGY RX350 S7, Intel Xeon E5-2690, 2.90 GHz

**SPECfp\_base2006 = 86.6**

**CPU2006 license:** 19

**Test date:** Feb-2012

**Test sponsor:** Fujitsu

**Hardware Availability:** Mar-2012

**Tested by:** Fujitsu

**Software Availability:** Feb-2012

## Peak Optimization Flags (Continued)

454.calculix: -xAVX -ipo -O3 -no-prec-div -auto-ilp32 -ansi-alias

481.wrf: Same as 436.cactusADM

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-linux64.20111122.html>  
<http://www.spec.org/cpu2006/flags/Fujitsu-Platform.20120313.00.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-linux64.20111122.xml>  
<http://www.spec.org/cpu2006/flags/Fujitsu-Platform.20120313.00.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.  
Report generated on Thu Jul 24 03:47:33 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 13 March 2012.