



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro

SuperServer 6027AX-TRF
(X9DAX-iF, Intel Xeon E5-2697 v2, 2.70 GHz)

CPU2006 license: 001176

Test sponsor: Supermicro

Tested by: Supermicro

SPECint®2006 =

SPECint_base2006 = NC

Test date: Oct-2013

Hardware Availability: Sep-2013

Software Availability: Sep-2013

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, SPEC was notified that an attempt to reproduce the published result did not come within SPEC's requirements for run-to-run variation. Upon re-review, it was determined that the system configuration does not meet SPEC's requirements for documented and supported systems, and does not meet SPEC's requirements for general availability.

400.perlbench |

401.bzip2 |

403.gcc |

429.mcf |

445.gobmk |

456.hmmer |

458.sjeng |

462.libquantum |

464.h264ref |

471.xalancbmk |

473.atar |

483.xalancbmk |

Hardware

CPU Name: Intel Xeon E5-2697 v2
CPU Characteristics: Intel Turbo Boost Technology up to 3.50 GHz
CPU MHz: 2700

Continued on next page

Software

Operating System: Red Hat Enterprise Linux Server release 6.4,
Kernel 2.6.32-358.el6.x86_64

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro

SuperServer 6027AX-TRF
(X9DAX-iF, Intel Xeon E5-2697 v2, 2.70 GHz)

CPU2006 license: 001176

Test sponsor: Supermicro

Tested by: Supermicro

SPECint2006 =

SPECint_base2006

NC

Test date: Oct-2013

Hardware Availability: Sep-2013

Software Availability: Sep-2013

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, SPEC was notified that an attempt to reproduce the published result did not come within SPEC's requirements for run-to-run variation. Upon re-review, it was determined that the system configuration does not meet SPEC's requirements for documented and supported systems, and does not meet SPEC's requirements for general availability.

FPU:	Integrated	Compiler:	C/C++: Version 14.0.0.080 of Intel C++ Studio XE for Linux
CPU(s) enabled:	24 cores, 2 chips, 12 cores/chip	Auto Parallel:	Yes
CPU(s) orderable:	1,2 chips	File System:	ext4
Primary Cache:	32 KB I + 32 KB D on chip per core	System State:	Run level 3 (multi-user)
Secondary Cache:	256 KB I+D on chip per core	Base Pointers:	32/64-bit
L3 Cache:	30 MB I+D on chip per chip	Peak Pointers:	32/64-bit
Other Cache:	None	Other Software:	Microquill SmartHeap V10.0
Memory:	128 GB (16 x 8 GB 2Rx4 PC4-14900R-13, ECC)		
Disk Subsystem:	1 x 300 GB SATA II, 7200 RPM		
Other Hardware:	None		

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio										
400.perlbench	NC	NC										
401.bzip2	NC	NC										
403.gcc	NC	NC										
429.mcf	NC	NC										
445.gobmk	NC	NC										
456.hmmer	NC	NC										
458.sjeng	NC	NC										
462.libquantum	NC	NC										
464.h264ref	NC	NC										
471.omnetpp	NC	NC										
473.astar	NC	NC										
483.xalancbmk	NC	NC										

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro

SuperServer 6027AX-TRF
(X9DAX-iF, Intel Xeon E5-2697 v2, 2.70 GHz)

CPU2006 license: 001176

Test sponsor: Supermicro

Tested by: Supermicro

SPECint2006 =

SPECint_base2006

10

NC

Test date: Oct-2013

Hardware Availability: Sep-2013

Software Availability: Sep-2013

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, SPEC was notified that an attempt to reproduce the published result did not come within SPEC's requirements for run-to-run variation. Upon re-review, it was determined that the system configuration does not meet SPEC's requirements for documented and supported systems, and does not meet SPEC's requirements for general availability.

Submit Notes

The config file option 'submit' was us

Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

General Notes

Environment variables set by runspec before the start of the run:

LD_LIBRARY_PATH = "/usr/cpu2006/libs/32:/usr/cpu2006/libs/64:/usr/cpu2006/sh"
OMP_NUM_THREADS = "13"

Binaries compiled on a system with 1x Core i7-860 CPU + 8GB memory using Red Hat Enterprise Linux 6.4

Transparent Huge Pages enabled with:

echo always > /sys/kernel/mm/redhat_transparent_hugepage/enabled
runspec command invoked through numactl i.e.:
numactl --interleave=all runspec <etc>

Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro

SuperServer 6027AX-TRF
(X9DAX-iF, Intel Xeon E5-2697 v2, 2.70 GHz)

CPU2006 license: 001176

Test sponsor: Supermicro

Tested by: Supermicro

SPECint2006 =

SPECint_base2006

NC

Test date: Oct-2013

Hardware Availability: Sep-2013

Software Availability: Sep-2013

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, SPEC was notified that an attempt to reproduce the published result did not come within SPEC's requirements for run-to-run variation. Upon re-review, it was determined that the system configuration does not meet SPEC's requirements for documented and supported systems, and does not meet SPEC's requirements for general availability.

Base Portability Flags

400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
403.gcc: -DSPEC_CPU_LP64
429.mcf: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hmmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
464.h264ref: -DSPEC_CPU_LP64
471.omnetpp: -DSPEC_CPU_LP64
473.astar: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:
-xAVX -ipo -O3 -no-prec-div -parallel -opt-prefetch -auto-p32

-xAVX -ipo -O3 -no-prec-div -opt-prefetch -auto-p32 -Wl,-z,muldefs
-L/sh -lsmartheap64

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro

SuperServer 6027AX-TRF
(X9DAX-iF, Intel Xeon E5-2697 v2, 2.70 GHz)

CPU2006 license: 001176

Test sponsor: Supermicro

Tested by: Supermicro

SPECint2006 =

SPECint_base2006

NC

Test date: Oct-2013

Hardware Availability: Sep-2013

Software Availability: Sep-2013

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, SPEC was notified that an attempt to reproduce the published result did not come within SPEC's requirements for run-to-run variation. Upon re-review, it was determined that the system configuration does not meet SPEC's requirements for documented and supported systems, and does not meet SPEC's requirements for general availability.

Peak Compiler Invocation

C benchmarks (except as noted below):

icc -m64

400.perlbench: icc -m32

445.gobmk: icc -m32

464.h264ref: icc -m32

C++ benchmarks (except as noted below):

icpc -m32

473.astar: icpc -m64

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32

401.bzip2: -DSPEC_CPU_LP64

402.xalancbmk: -DSPEC_CPU_LP64

429.mcf: -DSPEC_CPU_LP64

456.hmmer: -DSPEC_CPU_LP64

458.sjeng: -DSPEC_CPU_LP64

462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX

473.astar: -DSPEC_CPU_LP64

483.xalancbmk: -DSPEC_CPU_LINUX



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro

SuperServer 6027AX-TRF
(X9DAX-iF, Intel Xeon E5-2697 v2, 2.70 GHz)

CPU2006 license: 001176

Test sponsor: Supermicro

Tested by: Supermicro

SPECint2006 =

SPECint_base2006

NC

Test date: Oct-2013

Hardware Availability: Sep-2013

Software Availability: Sep-2013

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, SPEC was notified that an attempt to reproduce the published result did not come within SPEC's requirements for run-to-run variation. Upon re-review, it was determined that the system configuration does not meet SPEC's requirements for documented and supported systems, and does not meet SPEC's requirements for general availability.

Peak Optimization Flags

C benchmarks:

400.perlbench: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -opt-prefetch
-ansi-alias

401.bzip2: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div -prof-use(pass 2) -auto-ilp32 -opt-prefetch
-ansi-alias

403.gcc: -xAVX -ipo -O3 -no-prec-div -inline-calloc
-opt-calloc options=3 -auto-ilp32

429.mcf: basepeak = yes

445.gobmk: -xAVX(pass 2) -prof-gen(pass 1) -prof-use(pass 2)
-ansi-alias

456.hmmer: -xAVX -ipo -O3 -no-prec-div -unroll12 -auto-ilp32
-ansi-alias

458.sjeng: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -unroll14

462.libquantum: basepeak = yes

464.h264ref: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -unroll12
-ansi-alias

C++ benchmarks:

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro

SuperServer 6027AX-TRF
(X9DAX-iF, Intel Xeon E5-2697 v2, 2.70 GHz)

CPU2006 license: 001176

Test sponsor: Supermicro

Tested by: Supermicro

SPECint2006 =

SPECint_base2006 = NC

Test date: Oct-2013

Hardware Availability: Sep-2013

Software Availability: Sep-2013

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, SPEC was notified that an attempt to reproduce the published result did not come within SPEC's requirements for run-to-run variation. Upon re-review, it was determined that the system configuration does not meet SPEC's requirements for documented and supported systems, and does not meet SPEC's requirements for general availability.

Peak Optimization Flags (Continued)

```
471.omnetpp: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
              -no-prec-div(pass 2) -prof-use(pass 2)
              -opt-ra-region-strategy=block           -ansi-alias
              -Wl,-z,muldefs -L/sh -lsmartheap

473.astar: -xAVX -ipo -O3 -no-prec-div -opt-prefetch -auto-p32
            -Wl,-z,muldefs -L/sh -lsmartheap64

483.xalancbmk: -xAVX -ipo -O3 -no-prec-div -opt-prefetch -ansi-alias
                -Wl,-z,loaders -L/sh -lsmartheap
```

Peak Other Flags

C benchmarks:

```
403.gcc -Dalloca=_alloca
```

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64.20140128.html>

<http://www.spec.org/cpu2006/flags/Supermicro-Platform-Settings-V1.2-revB.20130719.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64.20140128.xml>

<http://www.spec.org/cpu2006/flags/Supermicro-Platform-Settings-V1.2-revB.20130719.xml>



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro

SuperServer 6027AX-TRF
(X9DAX-iF, Intel Xeon E5-2697 v2, 2.70 GHz)

CPU2006 license: 001176

Test sponsor: Supermicro

Tested by: Supermicro

SPECint2006 =

SPECint_base2006 = NC

Test date: Oct-2013

Hardware Availability: Sep-2013

Software Availability: Sep-2013

SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, SPEC was notified that an attempt to reproduce the published result did not come within SPEC's requirements for run-to-run variation. Upon re-review, it was determined that the system configuration does not meet SPEC's requirements for documented and supported systems, and does not meet SPEC's requirements for general availability.

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.

Report generated on Wed Oct 1 12:23:44 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 25 February 2014.