



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

Intel DQ77MK motherboard (Intel Pentium G2120T)

SPECfp®_rate2006 = 61.9

SPECfp_rate_base2006 = 60.9

CPU2006 license: 13


Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Dec-2013

Hardware Availability: Jun-2013

Software Availability: Apr-2013



SPECfp_rate_base2006 = 60.9

SPECfp_rate2006 = 61.9

Hardware

CPU Name: Intel Pentium G2120T
 CPU Characteristics:
 CPU MHz: 2700
 FPU: Integrated
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
 CPU(s) orderable: 1 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core

Software

Operating System: Microsoft Windows 7 Enterprise 6.1.7601 Service Pack 1 Build 7601
 Compiler: C/C++: Version 13.1.1.171 of Intel C++ Studio XE for Windows;
 Fortran: Version 13.1.1.171 of Intel Fortran Studio XE for Windows;
 Libraries: Version 16.00.30319.01 of Microsoft Visual Studio 2010 Professional SP1
 Auto Parallel: No

Continued on next page

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp_rate2006 = 61.9

Intel DQ77MK motherboard (Intel Pentium G2120T)

SPECfp_rate_base2006 = 60.9

CPU2006 license: 13

Test date: Dec-2013

Test sponsor: Intel Corporation

Hardware Availability: Jun-2013

Tested by: Intel Corporation

Software Availability: Apr-2013

L3 Cache: 3 MB I+D on chip per chip
 Other Cache: None
 Memory: 4 GB (2 x 2 GB 1Rx8 PC3-12800U-11)
 Disk Subsystem: 250 GB Seagate SATA HDD, 7200 RPM
 Other Hardware: None

File System: NTFS
 System State: Default
 Base Pointers: 32/64-bit
 Peak Pointers: 32/64-bit
 Other Software: SmartHeap Library Version 10.0 from
<http://www.microquill.com/>

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	2	315	86.2	<u>314</u>	<u>86.6</u>	313	86.8	2	315	86.2	<u>314</u>	<u>86.6</u>	313	86.8
416.gamess	2	709	55.2	706	55.4	<u>708</u>	<u>55.4</u>	2	709	55.2	706	55.4	<u>708</u>	<u>55.4</u>
433.milc	2	<u>219</u>	<u>84.0</u>	219	83.8	219	84.0	2	<u>219</u>	<u>84.0</u>	219	83.8	219	84.0
434.zeusmp	2	284	64.0	<u>282</u>	<u>64.4</u>	282	64.4	2	284	64.0	<u>282</u>	<u>64.4</u>	282	64.4
435.gromacs	2	<u>241</u>	<u>59.2</u>	242	59.0	241	59.2	2	<u>241</u>	<u>59.2</u>	242	59.0	241	59.2
436.cactusADM	2	423	56.4	420	57.0	<u>421</u>	<u>56.8</u>	2	423	56.4	420	57.0	<u>421</u>	<u>56.8</u>
437.leslie3d	2	352	53.4	346	54.2	<u>347</u>	<u>54.2</u>	2	352	53.4	346	54.2	<u>347</u>	<u>54.2</u>
444.namd	2	<u>428</u>	<u>37.4</u>	428	37.4	428	37.4	2	427	37.6	427	37.6	<u>427</u>	<u>37.6</u>
447.dealII	2	<u>287</u>	<u>79.8</u>	287	79.8	287	79.6	2	<u>287</u>	<u>79.8</u>	287	79.8	287	79.6
450.soplex	2	344	48.4	<u>342</u>	<u>48.8</u>	342	48.8	2	<u>358</u>	<u>46.6</u>	358	46.6	357	46.8
453.povray	2	154	69.0	<u>154</u>	<u>69.0</u>	155	68.6	2	<u>128</u>	<u>83.0</u>	128	83.4	129	82.8
454.calculix	2	265	62.4	<u>265</u>	<u>62.2</u>	265	62.2	2	265	62.4	<u>265</u>	<u>62.2</u>	265	62.2
459.GemsFDTD	2	492	43.2	497	42.6	<u>496</u>	<u>42.8</u>	2	492	43.2	497	42.6	<u>496</u>	<u>42.8</u>
465.tonto	2	<u>397</u>	<u>49.6</u>	400	49.2	396	49.8	2	352	55.8	355	55.4	<u>354</u>	<u>55.6</u>
470.lbm	2	372	73.8	<u>372</u>	<u>73.8</u>	374	73.6	2	<u>372</u>	<u>73.8</u>	<u>372</u>	<u>73.8</u>	374	73.6
481.wrf	2	284	78.6	<u>277</u>	<u>80.8</u>	276	80.8	2	284	78.6	<u>277</u>	<u>80.8</u>	276	80.8
482.sphinx3	2	660	59.0	<u>661</u>	<u>59.0</u>	662	58.8	2	660	59.0	<u>661</u>	<u>59.0</u>	662	58.8

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

To compile these binaries, the Intel Compiler 13.1 was set up to generate 64-bit binaries with the command:

"ipsxe-comp-vars.bat intel64 vs2010" (shortcut provided in the Intel(r) Parallel Studio XE 2013 program folder)

Submit Notes

Processes were bound to specific processors using the start command with the /affinity switch. The config file option 'submit' was used to generate the affinity mask for each process.



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

Intel DQ77MK motherboard (Intel Pentium G2120T)

SPECfp_rate2006 = 61.9

CPU2006 license: 13

Test date: Dec-2013

Test sponsor: Intel Corporation

Hardware Availability: Jun-2013

Tested by: Intel Corporation

Software Availability: Apr-2013

Platform Notes

```
Sysinfo program C:\SPEC13.1/Docs/sysinfo
$Rev: 6775 $ $Date:: 2011-08-16 #\$ \8787f7622badcf24e01c368b1db4377c
running on Clt7054D218890C Sun Dec 8 05:49:16 2013
```

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:
<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

```
Trying 'systeminfo'
OS Name      : Microsoft Windows 7 Enterprise
OS Version   : 6.1.7601 Service Pack 1 Build 7601
System Manufacturer: INTEL_
System Model  : DQ77MK_
Processor(s) : 1 Processor(s) Installed.
[01]: Intel64 Family 6 Model 58 Stepping 9 GenuineIntel ~2700 Mhz
BIOS Version  : Intel Corp. MKQ7710H.86A.0054.2012.1120.1444, 11/20/2012
Total Physical Memory: 3,912 MB
```

```
Trying 'wmic cpu get /value'
DeviceID     : CPU0
L2CacheSize  : 512
L3CacheSize  : 3072
MaxClockSpeed: 2700
Name         : Intel(R) Pentium(R) CPU G2120T @ 2.70GHz
NumberOfCores: 2
NumberOfLogicalProcessors: 2
```

(End of data from sysinfo program)
BIOS: SATA mode set to RAID
Windows Disk Driver: Intel Rapid Storage Technology 12.5.0.1066
Windows Chipset Driver: Intel Chipset Driver 9.4.0.1027

Component Notes

Tested systems can be used with Shin-G ATX case,
PC Power and Cooling 1200W power supply
Micron MT8JTF25664AZ-1G6 Series Memory DIMMs

General Notes

Binaries compiled on a system with 1x Intel Core i7-860 CPU
+ 8GB memory using Windows 7 Enterprise 64-bit

Base Compiler Invocation

C benchmarks:

```
icl -Qvc10 -Qstd=c99
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

Intel DQ77MK motherboard (Intel Pentium G2120T)

SPECfp_rate2006 = 61.9

CPU2006 license: 13

Test date: Dec-2013

Test sponsor: Intel Corporation

Hardware Availability: Jun-2013

Tested by: Intel Corporation

Software Availability: Apr-2013

Base Compiler Invocation (Continued)

C++ benchmarks:

 icl -Qvc10

Fortran benchmarks:

 ifort

Benchmarks using both Fortran and C:

 icl -Qvc10 -Qstd=c99 ifort

Base Portability Flags

```
410.bwaves: -DSPEC_CPU_P64
416.games: -DSPEC_CPU_P64
  433.milc: -DSPEC_CPU_P64
434.zeusmp: -DSPEC_CPU_P64
435.gromacs: -DSPEC_CPU_P64
436.cactusADM: -DSPEC_CPU_P64 /names:lowercase /assume:underscore
437.leslie3d: -DSPEC_CPU_P64
  444.namd: -DSPEC_CPU_P64 /TP
447.dealII: -DSPEC_CPU_P64 -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG
  -Qoption,cpp,--ms_incompat_treatment_of_commas_in_macros
450.soplex: -DSPEC_CPU_P64
453.povray: -DSPEC_CPU_P64 -DSPEC_CPU_NEED_INvhyp -DNEED_INvhyp
454.calculix: -DSPEC_CPU_P64 -DSPEC_CPU_NOZMODIFIER /names:lowercase
459.GemsFDTD: -DSPEC_CPU_P64
465.tonto: -DSPEC_CPU_P64
470.lbm: -DSPEC_CPU_P64
  481.wrf: -DSPEC_CPU_P64 -DSPEC_CPU_WINDOWS_ICL
482.sphinx3: -DSPEC_CPU_P64
```

Base Optimization Flags

C benchmarks:

```
-QxSSE4.2 -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch
-Qauto-ilp32 /F100000000000 -link /FORCE:MULTIPLE
```

C++ benchmarks:

```
-QxSSE4.2 -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch
-Qcxx-features -Qauto-ilp32 /F100000000000 shlw64M.lib
  -link /FORCE:MULTIPLE
```

Fortran benchmarks:

```
-QxSSE4.2 -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch
/F100000000000 -link /FORCE:MULTIPLE
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

Intel DQ77MK motherboard (Intel Pentium G2120T)

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

SPECfp_rate2006 = 61.9

SPECfp_rate_base2006 = 60.9

Test date: Dec-2013

Hardware Availability: Jun-2013

Software Availability: Apr-2013

Base Optimization Flags (Continued)

Benchmarks using both Fortran and C:

```
-QxSSE4.2 -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch  
-Qauto-ilp32 /F1000000000 -link /FORCE:MULTIPLE
```

Peak Compiler Invocation

C benchmarks:

```
icl -Qvc10 -Qstd=c99
```

C++ benchmarks:

```
icl -Qvc10
```

Fortran benchmarks:

```
ifort
```

Benchmarks using both Fortran and C:

```
icl -Qvc10 -Qstd=c99 ifort
```

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

```
433.milc: basepeak = yes
```

```
470.lbm: basepeak = yes
```

```
482.sphinx3: basepeak = yes
```

C++ benchmarks:

```
444.namd: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)  
-Qipo -O3 -Qprec-div- -Oa -Qauto-ilp32 /F1000000000  
shlw64M.lib -link /FORCE:MULTIPLE
```

```
447.dealII: basepeak = yes
```

```
450.soplex: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)  
-Qipo -O3 -Qauto-ilp32 /F1000000000 shlw64M.lib  
-link /FORCE:MULTIPLE
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

Intel DQ77MK motherboard (Intel Pentium G2120T)

SPECfp_rate2006 = 61.9

CPU2006 license: 13

Test date: Dec-2013

Test sponsor: Intel Corporation

Hardware Availability: Jun-2013

Tested by: Intel Corporation

Software Availability: Apr-2013

Peak Optimization Flags (Continued)

```
453.povray: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
             -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qauto-ilp32
             /F10000000000 shlw64M.lib           -link /FORCE:MULTIPLE
```

Fortran benchmarks:

```
410.bwaves: basepeak = yes
416.gamess: basepeak = yes
434.zeusmp: basepeak = yes
437.leslie3d: basepeak = yes
459.GemsFDTD: basepeak = yes
```

```
465.tonto: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
             -Qipo -O3 -Qprec-div- -Qunroll14 -Qauto /F10000000000
             -link /FORCE:MULTIPLE
```

Benchmarks using both Fortran and C:

```
435.gromacs: basepeak = yes
436.cactusADM: basepeak = yes
454.calculix: basepeak = yes
481.wrf: basepeak = yes
```

The flags file that was used to format this result can be browsed at
<http://www.spec.org/cpu2006/flags/Intel-ic13.1-official-windows.html>

You can also download the XML flags source by saving the following link:
<http://www.spec.org/cpu2006/flags/Intel-ic13.1-official-windows.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Fri Jul 25 01:04:38 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 15 July 2014.