



# SPEC® CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.  
(Test Sponsor: Intel Corporation)

SPECfp®2006 = **91.0**

ASUS Z170MPLUS motherboard (Intel Core i5-6600)

SPECfp\_base2006 = **88.8**

CPU2006 license: 13


Test date: Oct-2015

Test sponsor: Intel Corporation

Hardware Availability: Sep-2015

Tested by: Intel Corporation

Software Availability: Aug-2015



### Hardware

CPU Name: Intel Core i5-6600  
 CPU Characteristics: Intel Turbo Boost Technology up to 3.90 GHz  
 CPU MHz: 3300  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip  
 CPU(s) orderable: 1 chip  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

### Software

Operating System: Microsoft Windows 10 Pro  
 10.0.10240 N/A Build 10240  
 Compiler: C/C++: Version 16.0.0.110 of Intel C++ Studio XE for Windows;  
 Fortran: Version 16.0.0.110 of Intel Fortran Studio XE for Windows;  
 Libraries: Version 18.00.30723 of Microsoft Visual Studio 2013  
 Auto Parallel: Yes

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.  
(Test Sponsor: Intel Corporation)

SPECfp2006 = **91.0**

ASUS Z170MPLUS motherboard (Intel Core i5-6600)

SPECfp\_base2006 = **88.8**

CPU2006 license: 13

Test date: Oct-2015

Test sponsor: Intel Corporation

Hardware Availability: Sep-2015

Tested by: Intel Corporation

Software Availability: Aug-2015

L3 Cache: 6 MB I+D on chip per chip  
Other Cache: None  
Memory: 8 GB (2 x 4 GB 2Rx4 PC4-2133P-U)  
Disk Subsystem: 1 TB Seagate SATA HDD, 7200 RPM  
Other Hardware: None

File System: NTFS  
System State: Default  
Base Pointers: 32/64-bit  
Peak Pointers: 32/64-bit  
Other Software: SmartHeap Library Version 11.0 from <http://www.microquill.com/>

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	102	134	100	136	<b>101</b>	<b>135</b>	102	134	100	136	<b>101</b>	<b>135</b>
416.gamess	413	47.4	412	47.5	<b>413</b>	<b>47.5</b>	<b>371</b>	<b>52.7</b>	371	52.7	371	52.7
433.milc	98.7	93.0	<b>98.7</b>	<b>93.0</b>	98.9	92.8	98.7	93.0	<b>98.7</b>	<b>93.0</b>	98.9	92.8
434.zeusmp	83.3	109	<b>48.3</b>	<b>188</b>	47.9	190	83.3	109	<b>48.3</b>	<b>188</b>	47.9	190
435.gromacs	<b>105</b>	<b>68.3</b>	105	68.3	104	68.4	<b>105</b>	<b>68.3</b>	105	68.3	104	68.4
436.cactusADM	33.8	354	<b>33.8</b>	<b>354</b>	36.5	327	33.8	354	<b>33.8</b>	<b>354</b>	36.5	327
437.leslie3d	<b>102</b>	<b>92.3</b>	98.3	95.6	102	91.9	<b>102</b>	<b>92.3</b>	98.3	95.6	102	91.9
444.namd	213	37.6	<b>213</b>	<b>37.6</b>	214	37.6	209	38.3	<b>209</b>	<b>38.3</b>	210	38.3
447.dealII	155	73.9	<b>155</b>	<b>73.9</b>	155	73.9	155	73.9	<b>155</b>	<b>73.9</b>	155	73.9
450.soplex	168	49.8	168	49.7	<b>168</b>	<b>49.8</b>	168	49.8	168	49.7	<b>168</b>	<b>49.8</b>
453.povray	75.5	70.5	<b>75.8</b>	<b>70.2</b>	75.8	70.2	64.2	82.9	<b>63.9</b>	<b>83.3</b>	63.8	83.4
454.calculix	<b>110</b>	<b>75.3</b>	110	75.3	109	75.4	<b>110</b>	<b>75.3</b>	110	75.3	109	75.4
459.GemsFDTD	146	72.5	<b>146</b>	<b>72.8</b>	146	72.9	146	72.5	<b>146</b>	<b>72.8</b>	146	72.9
465.tonto	175	56.2	174	56.5	<b>174</b>	<b>56.4</b>	155	63.5	154	63.8	<b>155</b>	<b>63.7</b>
470.lbm	<b>84.0</b>	<b>164</b>	84.1	163	83.0	166	<b>84.0</b>	<b>164</b>	84.1	163	83.0	166
481.wrf	<b>92.9</b>	<b>120</b>	92.8	120	93.1	120	<b>92.9</b>	<b>120</b>	92.8	120	93.1	120
482.sphinx3	215	90.6	216	90.3	<b>215</b>	<b>90.6</b>	215	90.6	216	90.3	<b>215</b>	<b>90.6</b>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Compiler Invocation Notes

To compile these binaries, the Intel Compiler 16.0 was set up to generate 64-bit binaries with the command:  
"psxevars.bat intel64" (shortcut provided in the Intel(r) Parallel Studio XE 2016 program folder)

## Platform Notes

Sysinfo program C:\SPEC16.0\Docs\sysinfo  
\$Rev: 6775 \$ \$Date:: 2011-08-16 #\$ \8787f7622badcf24e01c368b1db4377c  
running on Clt305A3A7B76F6 Wed Oct 14 05:27:13 2015

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

**ASUSTeK Computer Inc.**  
(Test Sponsor: Intel Corporation)

**SPECfp2006 = 91.0**

**ASUS Z170MPLUS motherboard (Intel Core i5-6600)**

**SPECfp\_base2006 = 88.8**

**CPU2006 license:** 13

**Test date:** Oct-2015

**Test sponsor:** Intel Corporation

**Hardware Availability:** Sep-2015

**Tested by:** Intel Corporation

**Software Availability:** Aug-2015

## Platform Notes (Continued)

<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

Trying 'systeminfo'

```
OS Name       : Microsoft Windows 10 Pro
OS Version    : 10.0.10240 N/A Build 10240
System Manufacturer: System manufacturer
System Model   : System Product Name
Processor(s)  : 1 Processor(s) Installed.
               [01]: Intel64 Family 6 Model 94 Stepping 3 GenuineIntel ~3301 Mhz
BIOS Version  : American Megatrends Inc. 0408, 8/28/2015
Total Physical Memory: 8,084 MB
```

Trying 'wmic cpu get /value'

```
DeviceID      : CPU0
L2CacheSize   : 1024
L3CacheSize   : 6144
MaxClockSpeed : 3301
Name          : Intel(R) Core(TM) i5-6600 CPU @ 3.30GHz
NumberOfCores : 4
NumberOfLogicalProcessors: 4
```

(End of data from sysinfo program)

## Component Notes

Tested systems can be used with Shin-G ATX case,  
PC Power and Cooling 1200W power supply

## General Notes

```
450.soplex (base): "getline_test" src.alt was used.
447.dealII (base): "max_prototype" src.alt was used.
447.dealII (base): "cxx11_make_pair" src.alt was used.
450.soplex (base): "getline_test" src.alt was used.
447.dealII (base): "max_prototype" src.alt was used.
447.dealII (base): "cxx11_make_pair" src.alt was used.

OMP_NUM_THREADS set to number of processors cores
KMP_AFFINITY set to granularity=fine,scatter
Binaries compiled on a system with 1x Intel Xeon E5-2699 v3 CPU
+ 64GB memory using Windows 8.1 Enterprise 64-bit
```



# SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.  
(Test Sponsor: Intel Corporation)

SPECfp2006 = 91.0

ASUS Z170MPLUS motherboard (Intel Core i5-6600)

SPECfp\_base2006 = 88.8

CPU2006 license: 13

Test date: Oct-2015

Test sponsor: Intel Corporation

Hardware Availability: Sep-2015

Tested by: Intel Corporation

Software Availability: Aug-2015

## Base Compiler Invocation

C benchmarks:

icl -Qvc12 -Qstd=c99

C++ benchmarks:

icl -Qvc12

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icl -Qvc12 -Qstd=c99 ifort

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_P64  
 416.gamess: -DSPEC\_CPU\_P64  
 433.milc: -DSPEC\_CPU\_P64  
 434.zeusmp: -DSPEC\_CPU\_P64  
 435.gromacs: -DSPEC\_CPU\_P64  
 436.cactusADM: -DSPEC\_CPU\_P64 -names:lowercase /assume:underscore  
 437.leslie3d: -DSPEC\_CPU\_P64  
 444.namd: -DSPEC\_CPU\_P64 /TP  
 447.dealII: -DSPEC\_CPU\_P64 -DDEAL\_II\_MEMBER\_VAR\_SPECIALIZATION\_BUG  
 -DSPEC\_CPU\_BOOST\_CONFIG\_MSC\_VER -DSPEC\_NEED\_ALGORITHM  
 450.soplex: -DSPEC\_CPU\_P64 -DSPEC\_GETLINE\_TEST  
 453.povray: -DSPEC\_CPU\_P64  
 454.calculix: -DSPEC\_CPU\_P64 -DSPEC\_CPU\_NOZMODIFIER -names:lowercase  
 459.GemsFDTD: -DSPEC\_CPU\_P64  
 465.tonto: -DSPEC\_CPU\_P64  
 470.lbm: -DSPEC\_CPU\_P64  
 481.wrf: -DSPEC\_CPU\_P64 -DSPEC\_CPU\_WINDOWS\_ICL  
 482.sphinx3: -DSPEC\_CPU\_P64

## Base Optimization Flags

C benchmarks:

-QxCORE-AVX2 -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias  
-Qopt-prefetch /F1000000000

C++ benchmarks:

-QxCORE-AVX2 -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias  
-Qopt-prefetch -Qcxx-features /F1000000000 shlw64M.lib  
-link /FORCE:MULTIPLE

Fortran benchmarks:

-QxCORE-AVX2 -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias  
-Qopt-prefetch /F1000000000

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.  
(Test Sponsor: Intel Corporation)

SPECfp2006 = 91.0

ASUS Z170MPLUS motherboard (Intel Core i5-6600)

SPECfp\_base2006 = 88.8

CPU2006 license: 13

Test date: Oct-2015

Test sponsor: Intel Corporation

Hardware Availability: Sep-2015

Tested by: Intel Corporation

Software Availability: Aug-2015

## Base Optimization Flags (Continued)

Benchmarks using both Fortran and C:

-QxCORE-AVX2 -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias  
-Qopt-prefetch /F1000000000

## Peak Compiler Invocation

C benchmarks:

icl -Qvc12 -Qstd=c99

C++ benchmarks:

icl -Qvc12

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icl -Qvc12 -Qstd=c99 ifort

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

433.milc: basepeak = yes

470.lbm: basepeak = yes

482.sphinx3: basepeak = yes

C++ benchmarks:

444.namd: -QxCORE-AVX2(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2)  
-Qipo -O3 -Qprec-div- -Oa /F1000000000 sh1W64M.lib  
-link /FORCE:MULTIPLE

447.dealIII: basepeak = yes

450.soplex: basepeak = yes

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

**ASUSTeK Computer Inc.**  
(Test Sponsor: Intel Corporation)

**SPECfp2006 = 91.0**

**ASUS Z170MPLUS motherboard (Intel Core i5-6600)**

**SPECfp\_base2006 = 88.8**

**CPU2006 license:** 13

**Test date:** Oct-2015

**Test sponsor:** Intel Corporation

**Hardware Availability:** Sep-2015

**Tested by:** Intel Corporation

**Software Availability:** Aug-2015

## Peak Optimization Flags (Continued)

```
453.povray: -QxCORE-AVX2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
            -Qipo -O3 -Qprec-div- -Qunroll4 -Qansi-alias /F1000000000
            shlW64M.lib -link /FORCE:MULTIPLE
```

Fortran benchmarks:

410.bwaves: basepeak = yes

```
416.gamess: -QxCORE-AVX2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
            -Qipo -O3 -Qprec-div- -Qunroll2 -Ob0 -Qansi-alias
            -Qscalar-rep- /F1000000000
```

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

```
465.tonto: -QxCORE-AVX2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
            -Qipo -O3 -Qprec-div- -Qunroll4 -Qauto -Qinline-alloc
            /F1000000000
```

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-windows.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-windows.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.  
Report generated on Tue Nov 17 19:17:45 2015 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 17 November 2015.