



# SPEC® CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

## NEC Corporation

### SPECint®\_rate2006 = 101

### Express5800/GT110h (Intel Pentium G4400)

### SPECint\_rate\_base2006 = 97.1

CPU2006 license: 9006


Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Jul-2016

Hardware Availability: Jul-2016

Software Availability: Feb-2016



#### Hardware

CPU Name: Intel Pentium G4400  
 CPU Characteristics:  
 CPU MHz: 3300  
 FPU: Integrated  
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip  
 CPU(s) orderable: 1 chip  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core  
 L3 Cache: 3 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 16 GB (2 x 8 GB 2Rx8 PC4-2133P-E)  
 Disk Subsystem: 1 x 1 TB SATA, 7200 RPM  
 Other Hardware: None

#### Software

Operating System: Red Hat Enterprise Linux Server release 7.2 (Maipo)  
 Kernel 3.10.0-327.4.5.el7.x86\_64  
 Compiler: C/C++: Version 16.0.0.101 of Intel C++ Studio XE for Linux  
 Auto Parallel: No  
 File System: ext4  
 System State: Run level 3 (multi-user)  
 Base Pointers: 32-bit  
 Peak Pointers: 32/64-bit  
 Other Software: Microquill SmartHeap V10.2



# SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

## NEC Corporation

SPECint\_rate2006 = 101

### Express5800/GT110h (Intel Pentium G4400)

SPECint\_rate\_base2006 = 97.1

CPU2006 license: 9006

Test date: Jul-2016

Test sponsor: NEC Corporation

Hardware Availability: Jul-2016

Tested by: NEC Corporation

Software Availability: Feb-2016

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	2	243	80.3	<b><u>243</u></b>	<b><u>80.4</u></b>	243	80.4	2	<b><u>216</u></b>	<b><u>90.3</u></b>	216	90.6	216	90.3
401.bzip2	2	445	43.3	<b><u>448</u></b>	<b><u>43.1</u></b>	448	43.0	2	<b><u>429</u></b>	<b><u>45.0</u></b>	430	44.9	429	45.0
403.gcc	2	204	78.7	205	78.6	<b><u>205</u></b>	<b><u>78.6</u></b>	2	204	78.7	205	78.4	<b><u>205</u></b>	<b><u>78.7</u></b>
429.mcf	2	<b><u>131</u></b>	<b><u>139</u></b>	131	139	131	139	2	<b><u>131</u></b>	<b><u>139</u></b>	131	139	131	139
445.gobmk	2	368	57.0	<b><u>369</u></b>	<b><u>56.8</u></b>	369	56.8	2	368	57.0	<b><u>369</u></b>	<b><u>56.8</u></b>	369	56.8
456.hammer	2	139	134	141	132	<b><u>141</u></b>	<b><u>132</u></b>	2	121	154	121	154	<b><u>121</u></b>	<b><u>154</u></b>
458.sjeng	2	365	66.4	364	66.4	<b><u>365</u></b>	<b><u>66.4</u></b>	2	353	68.6	<b><u>353</u></b>	<b><u>68.6</u></b>	353	68.6
462.libquantum	2	<b><u>59.9</u></b>	<b><u>691</u></b>	60.9	681	59.6	695	2	<b><u>59.9</u></b>	<b><u>691</u></b>	60.9	681	59.6	695
464.h264ref	2	<b><u>351</u></b>	<b><u>126</u></b>	350	126	351	126	2	349	127	<b><u>348</u></b>	<b><u>127</u></b>	348	127
471.omnetpp	2	<b><u>226</u></b>	<b><u>55.3</u></b>	227	55.2	225	55.5	2	212	58.9	209	59.9	<b><u>212</u></b>	<b><u>59.0</u></b>
473.astar	2	<b><u>255</u></b>	<b><u>55.0</u></b>	256	55.0	255	55.1	2	<b><u>255</u></b>	<b><u>55.0</u></b>	256	55.0	255	55.1
483.xalancbmk	2	98.6	140	98.8	140	<b><u>98.7</u></b>	<b><u>140</u></b>	2	98.6	140	98.8	140	<b><u>98.7</u></b>	<b><u>140</u></b>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The taskset mechanism was used to bind copies to processors. The config file option 'submit' was used to generate taskset commands to bind each copy to a specific processor. For details, please see the config file.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

## Platform Notes

BIOS Settings:  
Power Management Policy: Custom  
Energy Performance: Performance

## General Notes

Environment variables set by runspec before the start of the run:  
LD\_LIBRARY\_PATH = "/home/cpu2006/libs/32:/home/cpu2006/libs/64:/home/cpu2006/sh"

Binaries compiled on a system with 1x Intel Core i5-4670K CPU + 32GB memory using RedHat EL 7.1  
Transparent Huge Pages enabled with:  
echo always > /sys/kernel/mm/transparent\_hugepage/enabled



# SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

NEC Corporation

SPECint\_rate2006 = 101

Express5800/GT110h (Intel Pentium G4400)

SPECint\_rate\_base2006 = 97.1

CPU2006 license: 9006

Test date: Jul-2016

Test sponsor: NEC Corporation

Hardware Availability: Jul-2016

Tested by: NEC Corporation

Software Availability: Feb-2016

## Base Compiler Invocation

C benchmarks:

icc -m32 -L/opt/intel/compilers\_and\_libraries\_2016/linux/compiler/lib/ia32\_lin

C++ benchmarks:

icpc -m32 -L/opt/intel/compilers\_and\_libraries\_2016/linux/compiler/lib/ia32\_lin

## Base Portability Flags

400.perlbench: -D\_FILE\_OFFSET\_BITS=64 -DSPEC\_CPU\_LINUX\_IA32  
 401.bzip2: -D\_FILE\_OFFSET\_BITS=64  
 403.gcc: -D\_FILE\_OFFSET\_BITS=64  
 429.mcf: -D\_FILE\_OFFSET\_BITS=64  
 445.gobmk: -D\_FILE\_OFFSET\_BITS=64  
 456.hmmer: -D\_FILE\_OFFSET\_BITS=64  
 458.sjeng: -D\_FILE\_OFFSET\_BITS=64  
 462.libquantum: -D\_FILE\_OFFSET\_BITS=64 -DSPEC\_CPU\_LINUX  
 464.h264ref: -D\_FILE\_OFFSET\_BITS=64  
 471.omnetpp: -D\_FILE\_OFFSET\_BITS=64  
 473.astar: -D\_FILE\_OFFSET\_BITS=64  
 483.xalancbmk: -D\_FILE\_OFFSET\_BITS=64 -DSPEC\_CPU\_LINUX

## Base Optimization Flags

C benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -opt-mem-layout-trans=3

C++ benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -opt-mem-layout-trans=3  
-Wl,-z,muldefs -L/sh -lsmartheap

## Base Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

## Peak Compiler Invocation

C benchmarks (except as noted below):

icc -m32 -L/opt/intel/compilers\_and\_libraries\_2016/linux/compiler/lib/ia32\_lin

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

NEC Corporation

SPECint\_rate2006 = 101

Express5800/GT110h (Intel Pentium G4400)

SPECint\_rate\_base2006 = 97.1

CPU2006 license: 9006

Test date: Jul-2016

Test sponsor: NEC Corporation

Hardware Availability: Jul-2016

Tested by: NEC Corporation

Software Availability: Feb-2016

## Peak Compiler Invocation (Continued)

400.perlbench: icc -m64

401.bzip2: icc -m64

456.hmmer: icc -m64

458.sjeng: icc -m64

C++ benchmarks:

icpc -m32 -L/opt/intel/compilers\_and\_libraries\_2016/linux/compiler/lib/ia32\_lin

## Peak Portability Flags

400.perlbench: -D\_FILE\_OFFSET\_BITS=64 -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX\_X64  
 401.bzip2: -D\_FILE\_OFFSET\_BITS=64 -DSPEC\_CPU\_LP64  
 403.gcc: -D\_FILE\_OFFSET\_BITS=64  
 429.mcf: -D\_FILE\_OFFSET\_BITS=64  
 445.gobmk: -D\_FILE\_OFFSET\_BITS=64  
 456.hmmer: -D\_FILE\_OFFSET\_BITS=64 -DSPEC\_CPU\_LP64  
 458.sjeng: -D\_FILE\_OFFSET\_BITS=64 -DSPEC\_CPU\_LP64  
 462.libquantum: -D\_FILE\_OFFSET\_BITS=64 -DSPEC\_CPU\_LINUX  
 464.h264ref: -D\_FILE\_OFFSET\_BITS=64  
 471.omnetpp: -D\_FILE\_OFFSET\_BITS=64  
 473.astar: -D\_FILE\_OFFSET\_BITS=64  
 483.xalancbmk: -D\_FILE\_OFFSET\_BITS=64 -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

400.perlbench: -xSSE4.2(pass 2) -prof-gen:threadsafe(pass 1) -ipo(pass 2)  
 -O3(pass 2) -no-prec-div(pass 2) -par-num-threads=1(pass 1)  
 -prof-use(pass 2) -auto-ilp32

401.bzip2: -xSSE4.2(pass 2) -prof-gen:threadsafe(pass 1) -ipo(pass 2)  
 -O3(pass 2) -no-prec-div(pass 2) -par-num-threads=1(pass 1)  
 -prof-use(pass 2) -opt-prefetch -auto-ilp32 -ansi-alias

403.gcc: -xSSE4.2 -ipo -O3 -no-prec-div

429.mcf: basepeak = yes

445.gobmk: basepeak = yes

456.hmmer: -xSSE4.2 -ipo -O3 -no-prec-div -unroll2 -auto-ilp32

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

NEC Corporation

SPECint\_rate2006 = 101

Express5800/GT110h (Intel Pentium G4400)

SPECint\_rate\_base2006 = 97.1

CPU2006 license: 9006

Test date: Jul-2016

Test sponsor: NEC Corporation

Hardware Availability: Jul-2016

Tested by: NEC Corporation

Software Availability: Feb-2016

## Peak Optimization Flags (Continued)

458.sjeng: -xSSE4.2(pass 2) -prof-gen:threadsafe(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -par-num-threads=1(pass 1)  
-prof-use(pass 2) -unroll4 -auto-ilp32

462.libquantum: basepeak = yes

464.h264ref: -xSSE4.2(pass 2) -prof-gen:threadsafe(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -par-num-threads=1(pass 1)  
-prof-use(pass 2) -unroll2 -ansi-alias

C++ benchmarks:

471.omnetpp: -xSSE4.2(pass 2) -prof-gen:threadsafe(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -par-num-threads=1(pass 1)  
-prof-use(pass 2) -ansi-alias -opt-ra-region-strategy=block  
-Wl,-z,muldefs -L/sh -lsmartheap

473.astar: basepeak = yes

483.xalancbmk: basepeak = yes

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-linux64.html>

<http://www.spec.org/cpu2006/flags/NEC-Platform-Settings-V1.2-110h-RevA.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-linux64.xml>

<http://www.spec.org/cpu2006/flags/NEC-Platform-Settings-V1.2-110h-RevA.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.

Report generated on Tue Sep 6 16:55:19 2016 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 6 September 2016.