



SPEC[®] CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS A88X-PRO Motherboard (AMD A6-7400K with Radeon R5 Graphics)

SPECfp[®]_rate2006 = 38.2

SPECfp_rate_base2006 = 37.9

CPU2006 license: 13


Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Mar-2016

Hardware Availability: Jul-2014

Software Availability: Aug-2015



SPECfp_rate_base2006 = 37.9

SPECfp_rate2006 = 38.2

Hardware

CPU Name: AMD A6-7400K
 CPU Characteristics: AMD Turbo CORE technology up to 3.90 GHz
 CPU MHz: 3500
 FPU: Integrated
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
 CPU(s) orderable: 1 chip
 Primary Cache: 96 KB I on chip per chip; 16 KB D on chip per core
 Secondary Cache: 1 MB I+D on chip per chip

Continued on next page

Software

Operating System: Microsoft Windows 7 Enterprise 6.1.7601 Service Pack 1 Build 7601
 Compiler: C/C++: Version 16.0.0.110 of Intel C++ Studio XE for Windows;
 Fortran: Version 16.0.0.110 of Intel Fortran Studio XE for Windows;
 Libraries: Version 18.00.30723 of Microsoft Visual Studio 2013
 Auto Parallel: No

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS A88X-PRO Motherboard (AMD A6-7400K with Radeon R5 Graphics)

SPECfp_rate2006 = 38.2

SPECfp_rate_base2006 = 37.9

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Mar-2016

Hardware Availability: Jul-2014

Software Availability: Aug-2015

L3 Cache: None
Other Cache: None
Memory: 8 GB (2 x 4 GB 2Rx8 PC3-10600U-11)
Disk Subsystem: Seagate Barracuda 250 GB SATA, 7200 RPM
Other Hardware: None

File System: NTFS
System State: Default
Base Pointers: 32/64-bit
Peak Pointers: 32/64-bit
Other Software: SmartHeap Library Version 11.0 from <http://www.microquill.com/>

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	2	598	45.4	597	45.6	597	45.6	2	598	45.4	597	45.6	597	45.6
416.gamess	2	843	46.4	847	46.2	847	46.2	2	843	46.4	847	46.2	847	46.2
433.milc	2	456	40.2	456	40.2	457	40.2	2	456	40.2	456	40.2	457	40.2
434.zeusmp	2	441	41.2	440	41.4	440	41.4	2	441	41.2	440	41.4	440	41.4
435.gromacs	2	445	32.2	443	32.2	443	32.2	2	445	32.2	443	32.2	443	32.2
436.cactusADM	2	623	38.4	623	38.4	626	38.2	2	623	38.4	623	38.4	626	38.2
437.leslie3d	2	736	25.6	735	25.6	737	25.4	2	736	25.6	735	25.6	737	25.4
444.namd	2	558	28.8	557	28.8	557	28.8	2	552	29.0	552	29.0	552	29.0
447.dealII	2	436	52.4	445	51.4	446	51.4	2	436	52.4	445	51.4	446	51.4
450.soplex	2	667	25.0	667	25.0	670	25.0	2	649	25.6	650	25.6	651	25.6
453.povray	2	209	51.0	204	52.0	205	52.0	2	185	57.4	185	57.4	185	57.6
454.calculix	2	368	44.8	366	45.0	368	44.8	2	368	44.8	366	45.0	368	44.8
459.GemsFDTD	2	1044	20.4	1035	20.6	1026	20.6	2	1044	20.4	1035	20.6	1026	20.6
465.tonto	2	533	37.0	537	36.6	533	37.0	2	518	38.0	520	37.8	521	37.8
470.lbm	2	461	59.6	460	59.8	460	59.8	2	461	59.6	460	59.8	460	59.8
481.wrf	2	481	46.4	482	46.4	480	46.6	2	481	46.4	482	46.4	480	46.6
482.sphinx3	2	1164	33.4	1161	33.6	1161	33.6	2	1164	33.4	1161	33.6	1161	33.6

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

To compile these binaries, the Intel Compiler 16.0 was set up to generate 64-bit binaries with the command:
"psxevars.bat intel64" (shortcut provided in the Intel(r) Parallel Studio XE 2016 program folder)

Platform Notes

Sysinfo program C:\SPEC16.0\Docs\sysinfo
\$Rev: 6775 \$ \$Date:: 2011-08-16 #\$ \8787f7622badcf24e01c368b1db4377c
running on CltE03F49ACBFDE Fri Mar 18 23:00:53 2016

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS A88X-PRO Motherboard (AMD A6-7400K with Radeon R5 Graphics)

SPECfp_rate2006 = 38.2

SPECfp_rate_base2006 = 37.9

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Mar-2016

Hardware Availability: Jul-2014

Software Availability: Aug-2015

Platform Notes (Continued)

<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

Trying 'systeminfo'

```
OS Name       : Microsoft Windows 7 Enterprise
OS Version    : 6.1.7601 Service Pack 1 Build 7601
System Manufacturer: System manufacturer
System Model   : System Product Name
Processor(s)  : 1 Processor(s) Installed.
               [01]: AMD64 Family 21 Model 48 Stepping 1 AuthenticAMD ~3500 Mhz
BIOS Version  : American Megatrends Inc. 2502, 12/11/2015
Total Physical Memory: 7,108 MB
```

Trying 'wmic cpu get /value'

```
DeviceID      : CPU0
L2CacheSize   : 25359
L3CacheSize   : 0
MaxClockSpeed : 3500
Name          : AMD A6-7400K Radeon R5, 6 Compute Cores 2C+4G
NumberOfCores : 1
NumberOfLogicalProcessors: 2
```

(End of data from sysinfo program)

Component Notes

Tested systems can be used with Shin-G ATX case,
PC Power and Cooling 1200W power supply

General Notes

```
450.soplex (peak): "getline_test" src.alt was used.
447.dealIII (base): "max_prototype" src.alt was used.
447.dealIII (base): "cxx11_make_pair" src.alt was used.
450.soplex (base): "getline_test" src.alt was used.
447.dealIII (base): "max_prototype" src.alt was used.
447.dealIII (base): "cxx11_make_pair" src.alt was used.
```

Binaries compiled on a system with 1x Intel Xeon E5-2699 v3 CPU
+ 64GB memory using Windows 8.1 Enterprise 64-bit

Base Compiler Invocation

C benchmarks:

```
icl -Qvc12 -Qstd=c99
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS A88X-PRO Motherboard (AMD A6-7400K with Radeon R5 Graphics)

SPECfp_rate2006 = 38.2

SPECfp_rate_base2006 = 37.9

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Mar-2016

Hardware Availability: Jul-2014

Software Availability: Aug-2015

Base Compiler Invocation (Continued)

C++ benchmarks:

icl -Qvc12

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icl -Qvc12 -Qstd=c99 ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_P64
 416.gamess: -DSPEC_CPU_P64
 433.milc: -DSPEC_CPU_P64
 434.zeusmp: -DSPEC_CPU_P64
 435.gromacs: -DSPEC_CPU_P64
 436.cactusADM: -DSPEC_CPU_P64 /names:lowercase /assume:underscore
 437.leslie3d: -DSPEC_CPU_P64
 444.namd: -DSPEC_CPU_P64 /TP
 447.dealII: -DSPEC_CPU_P64 -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG
 -DSPEC_CPU_BOOST_CONFIG_MSC_VER -DSPEC_NEED_ALGORITHM
 450.soplex: -DSPEC_CPU_P64 -DSPEC_GETLINE_TEST
 453.povray: -DSPEC_CPU_P64
 454.calculix: -DSPEC_CPU_P64 -DSPEC_CPU_NOZMODIFIER /names:lowercase
 459.GemsFDTD: -DSPEC_CPU_P64
 465.tonto: -DSPEC_CPU_P64
 470.lbm: -DSPEC_CPU_P64
 481.wrf: -DSPEC_CPU_P64 -DSPEC_CPU_WINDOWS_ICL
 482.sphinx3: -DSPEC_CPU_P64

Base Optimization Flags

C benchmarks:

/arch:AVX -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch
-Qauto-ilp32 /F1000000000 -link /FORCE:MULTIPLE

C++ benchmarks:

/arch:AVX -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch
-Qcxx-features -Qauto-ilp32 /F1000000000 shlw64M.lib
-link /FORCE:MULTIPLE

Fortran benchmarks:

/arch:AVX -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch
/F1000000000 -link /FORCE:MULTIPLE

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS A88X-PRO Motherboard (AMD A6-7400K with Radeon R5 Graphics)

SPECfp_rate2006 = 38.2

SPECfp_rate_base2006 = 37.9

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Mar-2016

Hardware Availability: Jul-2014

Software Availability: Aug-2015

Base Optimization Flags (Continued)

Benchmarks using both Fortran and C:

```
/arch:AVX -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch
-Qauto-ilp32 /F1000000000 -link /FORCE:MULTIPLE
```

Peak Compiler Invocation

C benchmarks:

```
icl -Qvc12 -Qstd=c99
```

C++ benchmarks:

```
icl -Qvc12
```

Fortran benchmarks:

```
ifort
```

Benchmarks using both Fortran and C:

```
icl -Qvc12 -Qstd=c99 ifort
```

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

```
433.milc: basepeak = yes
```

```
470.lbm: basepeak = yes
```

```
482.sphinx3: basepeak = yes
```

C++ benchmarks:

```
444.namd: /arch:AVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Oa -Qauto-ilp32 /F1000000000
shlW64M.lib -link /FORCE:MULTIPLE
```

```
447.dealII: basepeak = yes
```

```
450.soplex: /arch:AVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qauto-ilp32 /F1000000000 shlW64M.lib
-link /FORCE:MULTIPLE
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS A88X-PRO Motherboard (AMD A6-7400K with Radeon R5 Graphics)

SPECfp_rate2006 = 38.2

SPECfp_rate_base2006 = 37.9

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Mar-2016

Hardware Availability: Jul-2014

Software Availability: Aug-2015

Peak Optimization Flags (Continued)

```
453.povray: /arch:AVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
           -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qauto-ilp32
           /F1000000000 shlw64M.lib -link /FORCE:MULTIPLE
```

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: basepeak = yes

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

```
465.tonto: /arch:AVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
           -Qipo -O3 -Qprec-div- -Qunroll4 -Qauto /F1000000000
           -link /FORCE:MULTIPLE
```

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-windows.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-windows.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Tue Sep 20 15:06:38 2016 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 20 September 2016.