



SPEC® CPU2017 Floating Point Speed Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL385 Gen10

(2.00 GHz, AMD EPYC 7401)

SPECSspeed2017_fp_base = 109

SPECSspeed2017_fp_peak = 113

CPU2017 License: 3


Test Sponsor: HPE

Tested by: HPE

Test Date: Jan-2019

Hardware Availability: Oct-2018

Software Availability: Nov-2018



Hardware

CPU Name: AMD EPYC 7401
 Max MHz.: 3000
 Nominal: 2000
 Enabled: 48 cores, 2 chips, 2 threads/core
 Orderable: 1, 2 chip(s)
 Cache L1: 64 KB I + 32 KB D on chip per core
 L2: 512 KB I+D on chip per core
 L3: 64 MB I+D on chip per chip, 8 MB shared / 3 cores
 Other: None
 Memory: 256 GB (16 x 16 GB 1Rx4 PC4-2667V-R)
 Storage: 2 x 600 GB 10 K SAS HDD, RAID 1
 Other: None

Software

OS: SUSE Linux Enterprise Server 12 (x86_64) SP3
 Kernel 4.4.162-94.72-default
 Compiler: C/C++: Version 1.2.1 of AOCC
 Fortran: Version 4.8.2 of GCC
 Parallel: Yes
 Firmware: HPE BIOS Version A40 10/02/2018 released Oct-2018
 File System: xfs
 System State: Run level 3 (multi-user)
 Base Pointers: 64-bit
 Peak Pointers: 64-bit
 Other: jemalloc memory allocator library V4.5.0



SPEC CPU2017 Floating Point Speed Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL385 Gen10

(2.00 GHz, AMD EPYC 7401)

SPECSpeed2017_fp_base = 109

SPECSpeed2017_fp_peak = 113

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Jan-2019

Hardware Availability: Oct-2018

Software Availability: Nov-2018

Results Table

Benchmark	Base							Peak						
	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
603.bwaves_s	48	129	457	129	456	129	458	48	129	459	128	462	131	450
607.cactuBSSN_s	48	110	151	104	161	110	152	48	105	159	108	154	108	154
619.lbm_s	48	103	50.7	104	50.3	103	50.6	48	103	50.7	104	50.3	103	50.6
621.wrf_s	48	153	86.7	153	86.6	151	87.4	48	152	87.0	151	87.4	152	86.9
627.cam4_s	48	94.5	93.8	95.4	92.9	94.4	93.9	96	82.4	108	83.3	106	82.1	108
628.pop2_s	48	310	38.3	313	38.0	310	38.3	48	310	38.3	313	38.0	310	38.3
638.imagick_s	48	128	113	138	104	139	104	48	121	119	137	105	131	110
644.nab_s	48	86.8	201	86.8	201	86.8	201	96	74.0	236	73.9	237	74.1	236
649.fotonik3d_s	48	132	68.9	130	69.9	128	71.1	48	132	68.9	130	69.9	128	71.1
654.roms_s	48	107	148	107	148	107	148	48	107	148	106	148	108	145
SPECSpeed2017_fp_base = 109														
SPECSpeed2017_fp_peak = 113														

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Notes

The AMD64 AOCC Compiler Suite is available at
<http://developer.amd.com/amd-aocc/>

The AOCC Gold Linker plugin was installed and used for the link stage.

The AOCC Fortran Plugin version 1.2 was used to leverage AOCC optimizers with gfortran. It is available here:
<http://developer.amd.com/amd-aocc/>

Operating System Notes

'ulimit -s unlimited' was used to set environment stack size
 'ulimit -l 2097152' was used to set environment locked pages in memory limit

runspec command invoked through numactl i.e.:
 numactl --interleave=all runspec <etc>

Set dirty_ratio=8 to limit dirty cache to 8% of memory
 Set swappiness=1 to swap only if necessary
 Set zone_reclaim_mode=1 to free local node memory and avoid remote memory sync then drop_caches=3 to reset caches before invoking runcpu

dirty_ratio, swappiness, zone_reclaim_mode and drop_caches were all set using privileged echo (e.g. echo 1 > /proc/sys/vm/swappiness).

Transparent huge pages were enabled for this run (OS default)



SPEC CPU2017 Floating Point Speed Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL385 Gen10

(2.00 GHz, AMD EPYC 7401)

SPECspeed2017_fp_base = 109

SPECspeed2017_fp_peak = 113

CPU2017 License: 3

Test Date: Jan-2019

Test Sponsor: HPE

Hardware Availability: Oct-2018

Tested by: HPE

Software Availability: Nov-2018

General Notes

Environment variables set by runcpu before the start of the run:

GOMP_CPU_AFFINITY = "0-95"

LD_LIBRARY_PATH = "/home/cpu2017/amd1806-speed-libs-revA/64:/home/cpu2017/amd1806-speed-libs-revA/32:"

OMP_PROC_BIND = "true"

OMP_STACKSIZE = "192M"

OMP_WAIT_POLICY = "active"

Binaries were compiled on a system with 2x AMD EPYC 7601 CPU + 512GB Memory using RHEL 7.4

NA: The test sponsor attests, as of date of publication, that CVE-2017-5754 (Meltdown) is mitigated in the system as tested and documented.

Yes: The test sponsor attests, as of date of publication, that CVE-2017-5753 (Spectre variant 1) is mitigated in the system as tested and documented.

Yes: The test sponsor attests, as of date of publication, that CVE-2017-5715 (Spectre variant 2) is mitigated in the system as tested and documented.

jemalloc: configured and built with GCC v4.8.2

in RHEL v7.2 under default conditions.

jemalloc: sources available from jemalloc.net or

<https://github.com/jemalloc/jemalloc/releases>

jemalloc uses environment variable MALLOC_CONF

with values narenas and lg_chunk:

narenas: sets the maximum number of arenas to use
for automatic multiplexing

of threads and arenas.

lg_chunk: set the virtual memory chunk size (log
base 2). For example,

lg_chunk:21 sets the default chunk size to 2^{21} =
2MiB.

Platform Notes

BIOS Configuration:

Thermal Configuration set to Maximum Cooling

Performance Determinism set to Power Deterministic

Memory Patrol Scrubbing set to Disabled

Workload Profile set to General Throughput Compute

Processor Power and Utilization Monitoring set to Disabled

Sysinfo program /home/cpu2017/bin/sysinfo

Rev: r5974 of 2018-05-19 9bcde8f2999c33d61f64985e45859ea9

running on linux-ubi7 Wed Jan 30 10:34:47 2019

SUT (System Under Test) info as seen by some common utilities.

For more information on this section, see

<https://www.spec.org/cpu2017/Docs/config.html#sysinfo>

From /proc/cpuinfo

model name : AMD EPYC 7401 24-Core Processor

(Continued on next page)



SPEC CPU2017 Floating Point Speed Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL385 Gen10

(2.00 GHz, AMD EPYC 7401)

SPECspeed2017_fp_base = 109

SPECspeed2017_fp_peak = 113

CPU2017 License: 3

Test Date: Jan-2019

Test Sponsor: HPE

Hardware Availability: Oct-2018

Tested by: HPE

Software Availability: Nov-2018

Platform Notes (Continued)

```
2 "physical id"s (chips)
96 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The following
excerpts from /proc/cpuinfo might not be reliable. Use with caution.)
cpu cores : 24
siblings : 48
physical 0: cores 0 1 2 4 5 6 8 9 10 12 13 14 16 17 18 20 21 22 24 25 26 28 29 30
physical 1: cores 0 1 2 4 5 6 8 9 10 12 13 14 16 17 18 20 21 22 24 25 26 28 29 30
```

From lscpu:

```
Architecture: x86_64
CPU op-mode(s): 32-bit, 64-bit
Byte Order: Little Endian
CPU(s): 96
On-line CPU(s) list: 0-95
Thread(s) per core: 2
Core(s) per socket: 24
Socket(s): 2
NUMA node(s): 8
Vendor ID: AuthenticAMD
CPU family: 23
Model: 1
Model name: AMD EPYC 7401 24-Core Processor
Stepping: 2
CPU MHz: 2000.000
CPU max MHz: 2000.0000
CPU min MHz: 1200.0000
BogoMIPS: 3992.22
Virtualization: AMD-V
L1d cache: 32K
L1i cache: 64K
L2 cache: 512K
L3 cache: 8192K
NUMA node0 CPU(s): 0-5,48-53
NUMA node1 CPU(s): 6-11,54-59
NUMA node2 CPU(s): 12-17,60-65
NUMA node3 CPU(s): 18-23,66-71
NUMA node4 CPU(s): 24-29,72-77
NUMA node5 CPU(s): 30-35,78-83
NUMA node6 CPU(s): 36-41,84-89
NUMA node7 CPU(s): 42-47,90-95
Flags: fpu vme de pse tsc msr pae mce cx8 apic sep mtrr pge mca cmov
pat pse36 clflush mmx fxsr sse sse2 ht syscall nx mmxext fxsr_opt pdpe1gb rdtscp lm
constant_tsc rep_good nopl nonstop_tsc extd_apicid amd_dcm aperfmpfperf eagerfpu dni
pclmulqdq monitor ssse3 fma cx16 sse4_1 sse4_2 movbe popcnt aes xsave avx f16c
rdrand lahf_lm cmp_legacy svm extapic cr8_legacy abm sse4a misalignsse 3dnowprefetch
osvw skinit wdt tce topoext perfctr_core perfctr_nb bpext perfctr_l2 mwaitx arat cpb
```

(Continued on next page)



SPEC CPU2017 Floating Point Speed Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL385 Gen10

(2.00 GHz, AMD EPYC 7401)

SPECspeed2017_fp_base = 109

SPECspeed2017_fp_peak = 113

CPU2017 License: 3

Test Date: Jan-2019

Test Sponsor: HPE

Hardware Availability: Oct-2018

Tested by: HPE

Software Availability: Nov-2018

Platform Notes (Continued)

```
hw_pstate ssbd ibpb npt lbrv svm_lock nrrip_save tsc_scale vmcbl_clean flushbyasid
decodeassists pausefilter pfthreshold vmmcall avic fsgsbase bmi1 avx2 smep bmi2
rdseed adx smap clflushopt sha_ni xsaveopt xsavec xgetbv1 clzero irperf amd_ibpb
overflow_recov succor smca
```

```
/proc/cpuinfo cache data
cache size : 512 KB
```

From numactl --hardware WARNING: a numactl 'node' might or might not correspond to a physical chip.

```
available: 8 nodes (0-7)
node 0 cpus: 0 1 2 3 4 5 48 49 50 51 52 53
node 0 size: 31998 MB
node 0 free: 31783 MB
node 1 cpus: 6 7 8 9 10 11 54 55 56 57 58 59
node 1 size: 32253 MB
node 1 free: 31993 MB
node 2 cpus: 12 13 14 15 16 17 60 61 62 63 64 65
node 2 size: 32253 MB
node 2 free: 32103 MB
node 3 cpus: 18 19 20 21 22 23 66 67 68 69 70 71
node 3 size: 32253 MB
node 3 free: 32115 MB
node 4 cpus: 24 25 26 27 28 29 72 73 74 75 76 77
node 4 size: 32253 MB
node 4 free: 32136 MB
node 5 cpus: 30 31 32 33 34 35 78 79 80 81 82 83
node 5 size: 32253 MB
node 5 free: 32147 MB
node 6 cpus: 36 37 38 39 40 41 84 85 86 87 88 89
node 6 size: 32253 MB
node 6 free: 32144 MB
node 7 cpus: 42 43 44 45 46 47 90 91 92 93 94 95
node 7 size: 32120 MB
node 7 free: 32014 MB
node distances:
node 0 1 2 3 4 5 6 7
 0: 10 16 16 16 32 32 32 32
 1: 16 10 16 16 32 32 32 32
 2: 16 16 10 16 32 32 32 32
 3: 16 16 16 10 32 32 32 32
 4: 32 32 32 32 10 16 16 16
 5: 32 32 32 32 16 10 16 16
 6: 32 32 32 32 16 16 10 16
 7: 32 32 32 32 16 16 16 10
```

From /proc/meminfo

(Continued on next page)



SPEC CPU2017 Floating Point Speed Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL385 Gen10

(2.00 GHz, AMD EPYC 7401)

SPECspeed2017_fp_base = 109

SPECspeed2017_fp_peak = 113

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Jan-2019

Hardware Availability: Oct-2018

Software Availability: Nov-2018

Platform Notes (Continued)

MemTotal: 263823852 kB

HugePages_Total: 0

Hugepagesize: 2048 kB

```
/usr/bin/lsb_release -d
SUSE Linux Enterprise Server 12 SP3
```

```
From /etc/*release* /etc/*version*
```

SuSE-release:

```
    SUSE Linux Enterprise Server 12 (x86_64)
```

```
    VERSION = 12
```

```
    PATCHLEVEL = 3
```

```
    # This file is deprecated and will be removed in a future service pack or release.
    # Please check /etc/os-release for details about this release.
```

os-release:

```
    NAME="SLES"
```

```
    VERSION="12-SP3"
```

```
    VERSION_ID="12.3"
```

```
    PRETTY_NAME="SUSE Linux Enterprise Server 12 SP3"
```

```
    ID="sles"
```

```
    ANSI_COLOR="0;32"
```

```
    CPE_NAME="cpe:/o:suse:sles:12:sp3"
```

uname -a:

```
Linux linux-ubi7 4.4.162-94.72-default #1 SMP Mon Nov 12 18:57:45 UTC 2018 (9de753f)
x86_64 x86_64 x86_64 GNU/Linux
```

Kernel self-reported vulnerability status:

CVE-2017-5754 (Meltdown): Not affected

CVE-2017-5753 (Spectre variant 1): Mitigation: __user pointer sanitization

CVE-2017-5715 (Spectre variant 2): Mitigation: Full AMD retpoline, IBPB, RSB filling

run-level 3 Jan 30 10:29

SPEC is set to: /home/cpu2017

Filesystem	Type	Size	Used	Avail	Use%	Mounted on
/dev/sda4	xfs	518G	5.2G	512G	1%	/home

Additional information from dmidecode follows. WARNING: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

BIOS HPE A40 10/02/2018

Memory:

16x HPE 840757-191 16 GB 1 rank 2666

16x UNKNOWN NOT AVAILABLE

(Continued on next page)



SPEC CPU2017 Floating Point Speed Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL385 Gen10

(2.00 GHz, AMD EPYC 7401)

SPECspeed2017_fp_base = 109

SPECspeed2017_fp_peak = 113

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Jan-2019

Hardware Availability: Oct-2018

Software Availability: Nov-2018

Platform Notes (Continued)

(End of data from sysinfo program)

Compiler Version Notes

```
=====
CC 619.lbm_s(base, peak) 638.imagick_s(base, peak) 644.nab_s(base, peak)
-----
AOCC.LLVM.1.2.1.B29.2018_05_14 clang version 6.0.0 (CLANG:
b6b3d31d6df08fb7da935a28842b39b7b3c2c55b) (llvm/cpu/llvm
18855c80ed252fc4ba4ac41e2086627ef2bdd04) (based on LLVM
AOCC.LLVM.1.2.1.B29.2018_05_14)
Target: x86_64-unknown-linux-gnu
Thread model: posix
InstalledDir: /root/work/compilers/aocc1.2.1/AOCC-1.2.1-Compiler/bin
-----

=====
FC 607.cactuBSSN_s(base, peak)
-----
AOCC.LLVM.1.2.1.B29.2018_05_14 clang version 6.0.0 (CLANG:
b6b3d31d6df08fb7da935a28842b39b7b3c2c55b) (llvm/cpu/llvm
18855c80ed252fc4ba4ac41e2086627ef2bdd04) (based on LLVM
AOCC.LLVM.1.2.1.B29.2018_05_14)
Target: x86_64-unknown-linux-gnu
Thread model: posix
InstalledDir: /root/work/compilers/aocc1.2.1/AOCC-1.2.1-Compiler/bin
AOCC.LLVM.1.2.1.B29.2018_05_14 clang version 6.0.0 (CLANG:
b6b3d31d6df08fb7da935a28842b39b7b3c2c55b) (llvm/cpu/llvm
18855c80ed252fc4ba4ac41e2086627ef2bdd04) (based on LLVM
AOCC.LLVM.1.2.1.B29.2018_05_14)
Target: x86_64-unknown-linux-gnu
Thread model: posix
InstalledDir: /root/work/compilers/aocc1.2.1/AOCC-1.2.1-Compiler/bin
GNU Fortran (GCC) 4.8.2
Copyright (C) 2013 Free Software Foundation, Inc.
GNU Fortran comes with NO WARRANTY, to the extent permitted by law.
You may redistribute copies of GNU Fortran
under the terms of the GNU General Public License.
For more information about these matters, see the file named COPYING
-----

=====
FC 603.bwaves_s(base, peak) 649.fotonik3d_s(base, peak) 654.roms_s(base,
peak)
-----
```

(Continued on next page)



SPEC CPU2017 Floating Point Speed Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL385 Gen10

(2.00 GHz, AMD EPYC 7401)

SPECspeed2017_fp_base = 109

SPECspeed2017_fp_peak = 113

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Jan-2019

Hardware Availability: Oct-2018

Software Availability: Nov-2018

Compiler Version Notes (Continued)

GNU Fortran (GCC) 4.8.2

Copyright (C) 2013 Free Software Foundation, Inc.

GNU Fortran comes with NO WARRANTY, to the extent permitted by law.

You may redistribute copies of GNU Fortran
under the terms of the GNU General Public License.

For more information about these matters, see the file named COPYING

=====
CC 621.wrf_s(base, peak) 627.cam4_s(base, peak) 628.pop2_s(base, peak)
=====

GNU Fortran (GCC) 4.8.2

Copyright (C) 2013 Free Software Foundation, Inc.

GNU Fortran comes with NO WARRANTY, to the extent permitted by law.

You may redistribute copies of GNU Fortran
under the terms of the GNU General Public License.

For more information about these matters, see the file named COPYING

AOCC.LLVM.1.2.1.B29.2018_05_14 clang version 6.0.0 (CLANG:

b6b3d31d6df08fb7da935a28842b39b7b3c2c55b) (llvm/cpu/llvm

18855c80ed252fc4ba4ac41e2086627ef2bdd04) (based on LLVM

AOCC.LLVM.1.2.1.B29.2018_05_14)

Target: x86_64-unknown-linux-gnu

Thread model: posix

InstalledDir: /root/work/compilers/aocc1.2.1/AOCC-1.2.1-Compiler/bin

Base Compiler Invocation

C benchmarks:

clang

Fortran benchmarks:

clang gfortran

Benchmarks using both Fortran and C:

clang gfortran

Benchmarks using Fortran, C, and C++:

clang++ clang gfortran

Base Portability Flags

603.bwaves_s: -DSPEC_LP64

(Continued on next page)



SPEC CPU2017 Floating Point Speed Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL385 Gen10

(2.00 GHz, AMD EPYC 7401)

SPECspeed2017_fp_base = 109

SPECspeed2017_fp_peak = 113

CPU2017 License: 3

Test Date: Jan-2019

Test Sponsor: HPE

Hardware Availability: Oct-2018

Tested by: HPE

Software Availability: Nov-2018

Base Portability Flags (Continued)

```
607.cactuBSSN_s: -DSPEC_LP64
619.lbm_s: -DSPEC_LP64
621.wrf_s: -DSPEC_CASE_FLAG -fconvert=big-endian -DSPEC_LP64
627.cam4_s: -DSPEC_CASE_FLAG -DSPEC_LP64
628.pop2_s: -DSPEC_CASE_FLAG -fconvert=big-endian -DSPEC_LP64
638.imagick_s: -DSPEC_LP64
644.nab_s: -DSPEC_LP64
649.fotonik3d_s: -DSPEC_LP64
654.roms_s: -DSPEC_LP64
```

Base Optimization Flags

C benchmarks:

```
-flto -fuse-ld=lld -Wl,-mllvm -Wl,-function-specialize -O3
-ffast-math -march=znver1 -fstruct-layout=3
-mllvm -unroll-threshold=50 -fremap-arrays -mno-avx2
-mllvm -inline-threshold=1000 -flv-function-specialization
-mllvm -enable-gvn-hoist -mllvm -function-specialize -z muldefs
-lamdlibm -DSPEC_OPENMP -fopenmp -fopenmp=libomp -lomp -ljemalloc
```

Fortran benchmarks:

```
-flto -fuse-ld=lld -Wl,-mllvm -Wl,-function-specialize -O3
-funroll-loops -ffast-math -z muldefs -lamdlibm -fplugin=dragonegg.so
-fplugin-arg-dragonegg-llvm-option=-inline-threshold:1000 -DSPEC_OPENMP
-fopenmp -fopenmp=libomp -lomp -ljemalloc -lgfortran
```

Benchmarks using both Fortran and C:

```
-flto -fuse-ld=lld -Wl,-mllvm -Wl,-function-specialize -O3
-ffast-math -march=znver1 -fstruct-layout=3
-mllvm -unroll-threshold=50 -fremap-arrays -mno-avx2
-mllvm -inline-threshold=1000 -flv-function-specialization
-mllvm -enable-gvn-hoist -mllvm -function-specialize -funroll-loops
-z muldefs -lamdlibm -fplugin=dragonegg.so
-fplugin-arg-dragonegg-llvm-option=-inline-threshold:1000 -DSPEC_OPENMP
-fopenmp -fopenmp=libomp -lomp -ljemalloc -lgfortran
```

Benchmarks using Fortran, C, and C++:

```
-Wl,-mllvm -Wl,-x86-use-vzeroupper=false -flto -fuse-ld=lld
-Wl,-mllvm -Wl,-function-specialize -O3 -ffast-math -march=znver1
-fstruct-layout=3 -mllvm -unroll-threshold=50 -fremap-arrays -mno-avx2
-mllvm -inline-threshold=1000 -flv-function-specialization
-mllvm -enable-gvn-hoist -mllvm -function-specialize
-mllvm -unroll-threshold=100 -mllvm -enable-partial-unswitch
-funroll-loops -z muldefs -lamdlibm -fplugin=dragonegg.so
```

(Continued on next page)



SPEC CPU2017 Floating Point Speed Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL385 Gen10

(2.00 GHz, AMD EPYC 7401)

SPECspeed2017_fp_base = 109

SPECspeed2017_fp_peak = 113

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Jan-2019

Hardware Availability: Oct-2018

Software Availability: Nov-2018

Base Optimization Flags (Continued)

Benchmarks using Fortran, C, and C++ (continued):

```
-fplugin-arg-dragonegg-llvm-option=-inline-threshold:1000 -DSPEC_OPENMP  
-fopenmp -fopenmp=libomp -lomp -ljemalloc
```

Base Other Flags

C benchmarks:

```
-Wno-return-type -DUSE_OPENMP
```

Fortran benchmarks:

```
-DUSE_OPENMP -Wno-return-type
```

Benchmarks using both Fortran and C:

```
-DUSE_OPENMP -Wno-return-type
```

Benchmarks using Fortran, C, and C++:

```
-Wno-return-type -DUSE_OPENMP
```

Peak Compiler Invocation

C benchmarks:

```
clang
```

Fortran benchmarks:

```
clang gfortran
```

Benchmarks using both Fortran and C:

```
clang gfortran
```

Benchmarks using Fortran, C, and C++:

```
clang++ clang gfortran
```

Peak Portability Flags

Same as Base Portability Flags



SPEC CPU2017 Floating Point Speed Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL385 Gen10

(2.00 GHz, AMD EPYC 7401)

SPECspeed2017_fp_base = 109

SPECspeed2017_fp_peak = 113

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Jan-2019

Hardware Availability: Oct-2018

Software Availability: Nov-2018

Peak Optimization Flags

C benchmarks:

```
619.lbm_s: basepeak = yes

638.imagick_s: -flto -fuse-lld=lld -Wl,-mllvm -Wl,-function-specialize
-Ofast -march=znver1 -mno-sse4a -fstruct-layout=5
-mllvm -vectorize-memory-aggressively -mno-avx2
-mllvm -unroll-threshold=50 -fremap-arrays
-mllvm -inline-threshold=1000 -mllvm -enable-gvn-hoist
-flv-function-specialization
-mllvm -enable-vectorize-compare -z muldefs -lamdlibm
-DSPEC_OPENMP -fopenmp -fopenmp=libomp -lomp -ljemalloc
```

644.nab_s: Same as 638.imagick_s

Fortran benchmarks:

```
603.bwaves_s: -flto -fuse-lld=lld -Wl,-mllvm -Wl,-function-specialize
-O3 -funroll-loops -ffast-math -z muldefs -lamdlibm
-fplugin=dragonegg.so
-fplugin-arg-dragonegg-llvm-option=-inline-threshold:1000
-DSPEC_OPENMP -fopenmp -fopenmp=libomp -lomp -ljemalloc
-lgfortran
```

649.fotonik3d_s: basepeak = yes

654.roms_s: Same as 603.bwaves_s

Benchmarks using both Fortran and C:

```
621.wrf_s: -flto -fuse-lld=lld -Wl,-mllvm -Wl,-function-specialize
-Ofast -march=znver1 -mno-sse4a -fstruct-layout=5
-mllvm -vectorize-memory-aggressively -mno-avx2
-mllvm -unroll-threshold=50 -fremap-arrays
-mllvm -inline-threshold=1000 -mllvm -enable-gvn-hoist
-flv-function-specialization
-mllvm -enable-vectorize-compare -O3 -funroll-loops
-ffast-math -z muldefs -lamdlibm -fplugin=dragonegg.so
-fplugin-arg-dragonegg-llvm-option=-inline-threshold:1000
-DSPEC_OPENMP -fopenmp -fopenmp=libomp -lomp -ljemalloc
-lgfortran
```

627.cam4_s: Same as 621.wrf_s

628.pop2_s: basepeak = yes

(Continued on next page)



SPEC CPU2017 Floating Point Speed Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL385 Gen10

(2.00 GHz, AMD EPYC 7401)

SPECspeed2017_fp_base = 109

SPECspeed2017_fp_peak = 113

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Jan-2019

Hardware Availability: Oct-2018

Software Availability: Nov-2018

Peak Optimization Flags (Continued)

Benchmarks using Fortran, C, and C++:

```
-Wl,-mllvm -Wl,-x86-use-vzeroupper=false -flto -fuse-lld=lld
-Wl,-mllvm -Wl,-function-specialize -Ofast -march=znver1 -mno-sse4a
-fstruct-layout=5 -mllvm -vectorize-memory-aggressively -mno-avx2
-mllvm -unroll-threshold=50 -fremap-arrays
-mllvm -inline-threshold=1000 -mllvm -enable-gvn-hoist
-flv-function-specialization -mllvm -enable-vectorize-compare
-mllvm -unroll-threshold=100 -O3 -funroll-loops -ffast-math
-z muldefs -lamlibm -fplugin=dragonegg.so
-fplugin-arg-dragonegg-llvm-option=-inline-threshold:1000 -DSPEC_OPENMP
-fopenmp -fopenmp=libomp -lomp -ljemalloc
```

Peak Other Flags

C benchmarks:

```
-Wno-return-type -DUSE_OPENMP
```

Fortran benchmarks:

```
-DUSE_OPENMP -Wno-return-type
```

Benchmarks using both Fortran and C:

```
-DUSE_OPENMP -Wno-return-type
```

Benchmarks using Fortran, C, and C++:

```
-Wno-return-type -DUSE_OPENMP
```

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2017/flags/aocc100-flags-revC-I.2018-11-13.html>

<http://www.spec.org/cpu2017/flags/gcc.2018-02-16.html>

<http://www.spec.org/cpu2017/flags/HPE-Platform-Flags-AMD-V1.2-EPYC-revD.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2017/flags/aocc100-flags-revC-I.2018-11-13.xml>

<http://www.spec.org/cpu2017/flags/gcc.2018-02-16.xml>

<http://www.spec.org/cpu2017/flags/HPE-Platform-Flags-AMD-V1.2-EPYC-revD.xml>

SPEC is a registered trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEC CPU2017 v1.0.5 on 2019-01-30 04:34:46-0500.

Report generated on 2019-02-19 13:56:54 by CPU2017 PDF formatter v6067.

Originally published on 2019-02-19.