



# SPEC CPU®2017 Floating Point Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

**Fujitsu**

PRIMEQUEST 3800E2, Intel Xeon Platinum 8260M,  
2.40GHz

**SPECrate®2017\_fp\_base = 971**

**SPECrate®2017\_fp\_peak = Not Run**

**CPU2017 License:** 19


**Test Sponsor:** Fujitsu

**Tested by:** Fujitsu

**Test Date:** Jul-2019

**Hardware Availability:** Apr-2019

**Software Availability:** Feb-2019



## Hardware

CPU Name: Intel Xeon Platinum 8260M  
 Max MHz: 3900  
 Nominal: 2400  
 Enabled: 192 cores, 8 chips, 2 threads/core  
 Orderable: 2,4,6,8 chips  
 Cache L1: 32 KB I + 32 KB D on chip per core  
 L2: 1 MB I+D on chip per core  
 L3: 35.75 MB I+D on chip per chip  
 Other: None  
 Memory: 3 TB (96 x 32 GB 2Rx4 PC4-2933Y-R)  
 Storage: 1 x SAS HDD, 600GB, 10.5K RPM, SAS HDD  
 Other: None

## Software

OS: SUSE Linux Enterprise Server 15  
 Compiler: 4.12.14-25.28-default  
 C/C++: Version 19.0.0.117 of Intel C/C++ Compiler for Linux;  
 Fortran: Version 19.0.0.117 of Intel Fortran Compiler for Linux  
 Parallel: No  
 Firmware: PRIMEQUEST 3800E2 Unified Firmware Version PB19043, Released Jun-2019  
 File System: xfs  
 System State: Run level 3 (multi-user)  
 Base Pointers: 64-bit  
 Peak Pointers: Not Applicable  
 Other: None  
 Power Management: --



# SPEC CPU®2017 Floating Point Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

**Fujitsu**

PRIMEQUEST 3800E2, Intel Xeon Platinum 8260M,  
2.40GHz

**SPECrate®2017\_fp\_base = 971**

**SPECrate®2017\_fp\_peak = Not Run**

CPU2017 License: 19

Test Sponsor: Fujitsu

Tested by: Fujitsu

Test Date: Jul-2019

Hardware Availability: Apr-2019

Software Availability: Feb-2019

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
503.bwaves_r	384	1820	2120	<b>1821</b>	<b>2120</b>	1824	2110							
507.cactusBSSN_r	384	<b>581</b>	<b>837</b>	581	837	582	835							
508.namd_r	384	475	768	473	772	<b>473</b>	<b>772</b>							
510.parest_r	384	<b>1974</b>	<b>509</b>	1978	508	1971	510							
511.povray_r	384	754	1190	<b>756</b>	<b>1190</b>	757	1180							
519.lbm_r	384	793	511	<b>793</b>	<b>510</b>	793	510							
521.wrf_r	384	933	922	927	928	<b>929</b>	<b>926</b>							
526.blender_r	384	507	1150	<b>509</b>	<b>1150</b>	509	1150							
527.cam4_r	384	563	1190	560	1200	<b>562</b>	<b>1200</b>							
538.imagick_r	384	<b>370</b>	<b>2580</b>	373	2560	370	2580							
544.nab_r	384	352	1840	<b>352</b>	<b>1840</b>	351	1840							
549.fotonik3d_r	384	2220	674	<b>2216</b>	<b>675</b>	2215	676							
554.roms_r	384	<b>1540</b>	<b>396</b>	1544	395	1540	396							

**SPECrate®2017\_fp\_base = 971**

**SPECrate®2017\_fp\_peak = Not Run**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The numactl mechanism was used to bind copies to processors. The config file option 'submit' was used to generate numactl commands to bind each copy to a specific processor. For details, please see the config file.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"  
Kernel Boot Parameter set with : nohz\_full=1-383

## General Notes

Environment variables set by runcpu before the start of the run:  
LD\_LIBRARY\_PATH = "/home/Benchmark/speccpu2017-fp/lib/intel64"

Binaries compiled on a system with 1x Intel Core i9-799X CPU + 32GB RAM

memory using Redhat Enterprise Linux 7.5

Transparent Huge Pages enabled by default

Prior to runcpu invocation

Filesystem page cache synced and cleared with:

sync; echo 3> /proc/sys/vm/drop\_caches

runcpu command invoked through numactl i.e.:

numactl --interleave=all runcpu <etc>

NA: The test sponsor attests, as of date of publication, that CVE-2017-5754 (Meltdown)

(Continued on next page)



# SPEC CPU®2017 Floating Point Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Fujitsu

PRIMEQUEST 3800E2, Intel Xeon Platinum 8260M,  
2.40GHz

SPECrate®2017\_fp\_base = 971

SPECrate®2017\_fp\_peak = Not Run

CPU2017 License: 19

Test Date: Jul-2019

Test Sponsor: Fujitsu

Hardware Availability: Apr-2019

Tested by: Fujitsu

Software Availability: Feb-2019

## General Notes (Continued)

is mitigated in the system as tested and documented.

Yes: The test sponsor attests, as of date of publication, that CVE-2017-5753 (Spectre variant 1) is mitigated in the system as tested and documented.

Yes: The test sponsor attests, as of date of publication, that CVE-2017-5715 (Spectre variant 2) is mitigated in the system as tested and documented.

## Platform Notes

BIOS configuration:

```
DCU Streamer Prefetcher = Disabled
DDR4 Write Data CRC Protection = Disabled
LLC Dead Line Alloc = Enabled
Sub Numa Clustering = Enabled
Uncore Frequency Scaling = Disabled
UPI Link L0p = Disabled
Fan Control = Full
Sysinfo program /home/Benchmark/speccpu2017-fp/bin/sysinfo
Rev: r5974 of 2018-05-19 9bcde8f2999c33d61f64985e45859ea9
running on linux-8r5c Thu Jul 11 22:52:34 2019
```

SUT (System Under Test) info as seen by some common utilities.

For more information on this section, see

<https://www.spec.org/cpu2017/Docs/config.html#sysinfo>

From /proc/cpuinfo

```
model name : Intel(R) Xeon(R) Platinum 8260M CPU @ 2.40GHz
  8 "physical id"s (chips)
  384 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The following
excerpts from /proc/cpuinfo might not be reliable. Use with caution.)
  cpu cores : 24
  siblings : 48
  physical 0: cores 0 1 2 3 4 5 6 8 9 10 11 12 13 16 17 18 19 20 21 25 26 27 28 29
  physical 1: cores 0 1 2 3 4 5 6 8 9 10 11 12 13 16 17 18 19 20 21 25 26 27 28 29
  physical 2: cores 0 1 3 4 5 6 8 9 10 11 12 13 16 17 18 19 20 21 24 25 26 27 28 29
  physical 3: cores 0 1 2 3 4 5 6 8 10 11 12 13 16 17 18 19 20 21 24 25 26 27 28 29
  physical 4: cores 0 1 2 3 4 5 6 8 9 10 11 12 13 16 17 18 19 20 21 25 26 27 28 29
  physical 5: cores 0 1 2 3 4 5 6 8 9 10 11 12 13 16 17 18 19 20 21 25 26 27 28 29
  physical 6: cores 0 1 2 3 4 5 6 8 9 10 11 12 13 16 17 18 19 20 21 25 26 27 28 29
  physical 7: cores 0 1 2 3 4 5 6 8 9 10 11 12 13 16 17 18 19 20 21 25 26 27 28 29
```

From lscpu:

```
Architecture:          x86_64
CPU op-mode(s):       32-bit, 64-bit
Byte Order:           Little Endian
CPU(s):               384
```

(Continued on next page)



# SPEC CPU®2017 Floating Point Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Fujitsu

PRIMEQUEST 3800E2, Intel Xeon Platinum 8260M,  
2.40GHz

SPECrate®2017\_fp\_base = 971

SPECrate®2017\_fp\_peak = Not Run

CPU2017 License: 19

Test Date: Jul-2019

Test Sponsor: Fujitsu

Hardware Availability: Apr-2019

Tested by: Fujitsu

Software Availability: Feb-2019

## Platform Notes (Continued)

On-line CPU(s) list: 0-383  
Thread(s) per core: 2  
Core(s) per socket: 24  
Socket(s): 8  
NUMA node(s): 16  
Vendor ID: GenuineIntel  
CPU family: 6  
Model: 85  
Model name: Intel(R) Xeon(R) Platinum 8260M CPU @ 2.40GHz  
Stepping: 6  
CPU MHz: 2400.000  
CPU max MHz: 3900.0000  
CPU min MHz: 1000.0000  
BogoMIPS: 4800.00  
Virtualization: VT-x  
L1d cache: 32K  
L1i cache: 32K  
L2 cache: 1024K  
L3 cache: 36608K  
NUMA node0 CPU(s): 0-3,7-9,13-15,19,20,192-195,199-201,205-207,211,212  
NUMA node1 CPU(s): 4-6,10-12,16-18,21-23,196-198,202-204,208-210,213-215  
NUMA node2 CPU(s): 24-27,31-33,37-39,43,44,216-219,223-225,229-231,235,236  
NUMA node3 CPU(s): 28-30,34-36,40-42,45-47,220-222,226-228,232-234,237-239  
NUMA node4 CPU(s): 48-50,54-56,60-62,66-68,240-242,246-248,252-254,258-260  
NUMA node5 CPU(s): 51-53,57-59,63-65,69-71,243-245,249-251,255-257,261-263  
NUMA node6 CPU(s): 72-75,79,80,84-86,90-92,264-267,271,272,276-278,282-284  
NUMA node7 CPU(s): 76-78,81-83,87-89,93-95,268-270,273-275,279-281,285-287  
NUMA node8 CPU(s): 96-99,103-105,109-111,115,116,288-291,295-297,301-303,307,308  
NUMA node9 CPU(s): 100-102,106-108,112-114,117-119,292-294,298-300,304-306,309-311  
NUMA node10 CPU(s): 120-123,127-129,133-135,139,140,312-315,319-321,325-327,331,332  
NUMA node11 CPU(s): 124-126,130-132,136-138,141-143,316-318,322-324,328-330,333-335  
NUMA node12 CPU(s): 144-147,151-153,157-159,163,164,336-339,343-345,349-351,355,356  
NUMA node13 CPU(s): 148-150,154-156,160-162,165-167,340-342,346-348,352-354,357-359  
NUMA node14 CPU(s): 168-171,175-177,181-183,187,188,360-363,367-369,373-375,379,380  
NUMA node15 CPU(s): 172-174,178-180,184-186,189-191,364-366,370-372,376-378,381-383  
Flags: fpu vme de pse tsc msr pae mce cx8 apic sep mtrr pge mca cmov  
pat pse36 clflush dts acpi mmx fxsr sse sse2 ss ht tm pbe syscall nx pdpe1gb rdtscp  
lm constant\_tsc art arch\_perfmon pebs bts rep\_good nopl xtopology nonstop\_tsc cpuid  
aperfmperf pni pclmulqdq dtes64 monitor ds\_cpl vmx smx est tm2 ssse3 sdbg fma cx16  
xtpr pdcm pcid dca sse4\_1 sse4\_2 x2apic movbe popcnt tsc\_deadline\_timer aes xsave  
avx f16c rdrand lahf\_lm abm 3dnowprefetch cpuid\_fault epb cat\_13 cdp\_13  
invpcid\_single intel\_ppin ssbd mba ibrs ibpb stibp ibrs\_enhanced tpr\_shadow vnmi  
flexpriority ept vpid fsgsbase tsc\_adjust bmi1 hle avx2 smep bmi2 erms invpcid rtm  
cqm mpk rdt\_a avx512f avx512dq rdseed adx smap clflushopt clwb intel\_pt avx512cd  
avx512bw avx512vl xsaveopt xsavec xgetbv1 xsaves cqm\_llc cqm\_occup\_llc cqm\_mbm\_total  
cqm\_mbm\_local dtherm ida arat pln pts hwp hwp\_act\_window hwp\_epp hwp\_pkg\_req pku  
ospke avx512\_vnni flush\_l1d arch\_capabilities

(Continued on next page)



# SPEC CPU®2017 Floating Point Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Fujitsu

PRIMEQUEST 3800E2, Intel Xeon Platinum 8260M,  
2.40GHz

SPECrate®2017\_fp\_base = 971

SPECrate®2017\_fp\_peak = Not Run

CPU2017 License: 19

Test Date: Jul-2019

Test Sponsor: Fujitsu

Hardware Availability: Apr-2019

Tested by: Fujitsu

Software Availability: Feb-2019

## Platform Notes (Continued)

```
/proc/cpuinfo cache data
cache size : 36608 KB
```

```
From numactl --hardware
WARNING: a numactl 'node' might or might not correspond to a
physical chip.
```

```
available: 16 nodes (0-15)
node 0 cpus: 0 1 2 3 7 8 9 13 14 15 19 20 192 193 194 195 199 200 201 205 206 207 211
212
node 0 size: 192269 MB
node 0 free: 191217 MB
node 1 cpus: 4 5 6 10 11 12 16 17 18 21 22 23 196 197 198 202 203 204 208 209 210 213
214 215
node 1 size: 193529 MB
node 1 free: 193194 MB
node 2 cpus: 24 25 26 27 31 32 33 37 38 39 43 44 216 217 218 219 223 224 225 229 230
231 235 236
node 2 size: 193529 MB
node 2 free: 193284 MB
node 3 cpus: 28 29 30 34 35 36 40 41 42 45 46 47 220 221 222 226 227 228 232 233 234
237 238 239
node 3 size: 193500 MB
node 3 free: 193241 MB
node 4 cpus: 48 49 50 54 55 56 60 61 62 66 67 68 240 241 242 246 247 248 252 253 254
258 259 260
node 4 size: 193529 MB
node 4 free: 193304 MB
node 5 cpus: 51 52 53 57 58 59 63 64 65 69 70 71 243 244 245 249 250 251 255 256 257
261 262 263
node 5 size: 193529 MB
node 5 free: 193324 MB
node 6 cpus: 72 73 74 75 79 80 84 85 86 90 91 92 264 265 266 267 271 272 276 277 278
282 283 284
node 6 size: 193529 MB
node 6 free: 193357 MB
node 7 cpus: 76 77 78 81 82 83 87 88 89 93 94 95 268 269 270 273 274 275 279 280 281
285 286 287
node 7 size: 193529 MB
node 7 free: 193342 MB
node 8 cpus: 96 97 98 99 103 104 105 109 110 111 115 116 288 289 290 291 295 296 297
301 302 303 307 308
node 8 size: 193529 MB
node 8 free: 193389 MB
node 9 cpus: 100 101 102 106 107 108 112 113 114 117 118 119 292 293 294 298 299 300
304 305 306 309 310 311
node 9 size: 193529 MB
node 9 free: 193355 MB
```

(Continued on next page)



# SPEC CPU®2017 Floating Point Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Fujitsu

PRIMEQUEST 3800E2, Intel Xeon Platinum 8260M,  
2.40GHz

SPECrate®2017\_fp\_base = 971

SPECrate®2017\_fp\_peak = Not Run

CPU2017 License: 19

Test Date: Jul-2019

Test Sponsor: Fujitsu

Hardware Availability: Apr-2019

Tested by: Fujitsu

Software Availability: Feb-2019

## Platform Notes (Continued)

```
node 10 cpus: 120 121 122 123 127 128 129 133 134 135 139 140 312 313 314 315 319 320  
321 325 326 327 331 332  
node 10 size: 193529 MB  
node 10 free: 193355 MB  
node 11 cpus: 124 125 126 130 131 132 136 137 138 141 142 143 316 317 318 322 323 324  
328 329 330 333 334 335  
node 11 size: 193529 MB  
node 11 free: 193359 MB  
node 12 cpus: 144 145 146 147 151 152 153 157 158 159 163 164 336 337 338 339 343 344  
345 349 350 351 355 356  
node 12 size: 193529 MB  
node 12 free: 193322 MB  
node 13 cpus: 148 149 150 154 155 156 160 161 162 165 166 167 340 341 342 346 347 348  
352 353 354 357 358 359  
node 13 size: 193529 MB  
node 13 free: 193303 MB  
node 14 cpus: 168 169 170 171 175 176 177 181 182 183 187 188 360 361 362 363 367 368  
369 373 374 375 379 380  
node 14 size: 193529 MB  
node 14 free: 193253 MB  
node 15 cpus: 172 173 174 178 179 180 184 185 186 189 190 191 364 365 366 370 371 372  
376 377 378 381 382 383  
node 15 size: 193326 MB  
node 15 free: 193154 MB  
node distances:  
node 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15  
0: 10 11 20 20 20 20 28 28 28 28 28 28 20 20 28 28  
1: 11 10 20 20 20 20 28 28 28 28 28 28 20 20 28 28  
2: 20 20 10 11 28 28 20 20 28 28 20 20 28 28 28 28  
3: 20 20 11 10 28 28 20 20 28 28 20 20 28 28 28 28  
4: 20 20 28 28 10 11 20 20 20 20 28 28 28 28 28 28  
5: 20 20 28 28 11 10 20 20 20 20 28 28 28 28 28 28  
6: 28 28 20 20 20 20 10 11 28 28 28 28 28 28 20 20  
7: 28 28 20 20 20 20 11 10 28 28 28 28 28 28 20 20  
8: 28 28 28 28 20 20 28 28 10 11 20 20 20 20 28 28  
9: 28 28 28 28 20 20 28 28 11 10 20 20 20 20 28 28  
10: 28 28 20 20 28 28 28 28 20 20 10 11 28 28 20 20  
11: 28 28 20 20 28 28 28 28 20 20 11 10 28 28 20 20  
12: 20 20 28 28 28 28 28 28 20 20 28 28 10 11 20 20  
13: 20 20 28 28 28 28 28 28 20 20 28 28 11 10 20 20  
14: 28 28 28 28 28 20 20 28 28 20 20 20 20 20 10 11  
15: 28 28 28 28 28 28 20 20 28 20 20 20 20 20 11 10
```

From /proc/meminfo

```
MemTotal: 3169264456 kB
HugePages_Total: 0
Hugepagesize: 2048 kB
```

(Continued on next page)



# SPEC CPU®2017 Floating Point Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Fujitsu

PRIMEQUEST 3800E2, Intel Xeon Platinum 8260M,  
2.40GHz

SPECrate®2017\_fp\_base = 971

SPECrate®2017\_fp\_peak = Not Run

CPU2017 License: 19

Test Date: Jul-2019

Test Sponsor: Fujitsu

Hardware Availability: Apr-2019

Tested by: Fujitsu

Software Availability: Feb-2019

## Platform Notes (Continued)

```
From /etc/*release* /etc/*version*
os-release:
  NAME="SLES"
  VERSION="15"
  VERSION_ID="15"
  PRETTY_NAME="SUSE Linux Enterprise Server 15"
  ID="sles"
  ID_LIKE="suse"
  ANSI_COLOR="0;32"
  CPE_NAME="cpe:/o:suse:sles:15"

uname -a:
Linux linux-8r5c 4.12.14-25.28-default #1 SMP Wed Jan 16 20:00:47 UTC 2019 (dd6077c)
x86_64 x86_64 x86_64 GNU/Linux
```

Kernel self-reported vulnerability status:

```
CVE-2017-5754 (Meltdown):           Not affected
CVE-2017-5753 (Spectre variant 1): Mitigation: __user pointer sanitization
CVE-2017-5715 (Spectre variant 2): Mitigation: Enhanced IBRS, IBPB: conditional, RSB
filling
```

run-level 3 Jul 11 22:49

```
SPEC is set to: /home/Benchmark/speccpu2017-fp
Filesystem      Type  Size  Used Avail Use% Mounted on
/dev/sda3        xfs   142G   55G   87G  39% /home
```

Additional information from dmidecode follows. WARNING: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

BIOS FUJITSU V1.0.0.0 R1.16.0 for D3858-B1x 04/24/2019

Memory:

```
 68x Micron 36ASF4G72PZ-2G9E2 32 GB 2 rank 2933
 28x Samsung M393A4K40CB2-CVF 32 GB 2 rank 2933
```

(End of data from sysinfo program)

## Compiler Version Notes

```
=====
C           | 519.lbm_r(base) 538.imagick_r(base) 544.nab_r(base)
-----
Intel(R) C Intel(R) 64 Compiler for applications running on Intel(R) 64,
```

(Continued on next page)



# SPEC CPU®2017 Floating Point Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Fujitsu

PRIMEQUEST 3800E2, Intel Xeon Platinum 8260M,  
2.40GHz

SPECrate®2017\_fp\_base = 971

SPECrate®2017\_fp\_peak = Not Run

CPU2017 License: 19

Test Date: Jul-2019

Test Sponsor: Fujitsu

Hardware Availability: Apr-2019

Tested by: Fujitsu

Software Availability: Feb-2019

## Compiler Version Notes (Continued)

Version 19.0.0.117 Build 20180804

Copyright (C) 1985-2018 Intel Corporation. All rights reserved.

=====

C++ | 508.namd\_r(base) 510.parest\_r(base)

=====

Intel(R) C++ Intel(R) 64 Compiler for applications running on Intel(R) 64,  
Version 19.0.0.117 Build 20180804

Copyright (C) 1985-2018 Intel Corporation. All rights reserved.

=====

C++, C | 511.povray\_r(base) 526.blender\_r(base)

=====

Intel(R) C++ Intel(R) 64 Compiler for applications running on Intel(R) 64,  
Version 19.0.0.117 Build 20180804

Copyright (C) 1985-2018 Intel Corporation. All rights reserved.

=====

Intel(R) C Intel(R) 64 Compiler for applications running on Intel(R) 64,  
Version 19.0.0.117 Build 20180804

Copyright (C) 1985-2018 Intel Corporation. All rights reserved.

=====

C++, C, Fortran | 507.cactusBSSN\_r(base)

=====

Intel(R) C++ Intel(R) 64 Compiler for applications running on Intel(R) 64,  
Version 19.0.0.117 Build 20180804

Copyright (C) 1985-2018 Intel Corporation. All rights reserved.

=====

Intel(R) C Intel(R) 64 Compiler for applications running on Intel(R) 64,  
Version 19.0.0.117 Build 20180804

Copyright (C) 1985-2018 Intel Corporation. All rights reserved.

=====

Intel(R) Fortran Intel(R) 64 Compiler for applications running on Intel(R)  
64, Version 19.0.0.117 Build 20180804

Copyright (C) 1985-2018 Intel Corporation. All rights reserved.

=====

Fortran | 503.bwaves\_r(base) 549.fotonik3d\_r(base) 554.roms\_r(base)

=====

Intel(R) Fortran Intel(R) 64 Compiler for applications running on Intel(R)  
64, Version 19.0.0.117 Build 20180804

Copyright (C) 1985-2018 Intel Corporation. All rights reserved.

=====

Fortran, C | 521.wrf\_r(base) 527.cam4\_r(base)

(Continued on next page)



# SPEC CPU®2017 Floating Point Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Fujitsu

PRIMEQUEST 3800E2, Intel Xeon Platinum 8260M,  
2.40GHz

SPECrate®2017\_fp\_base = 971

SPECrate®2017\_fp\_peak = Not Run

CPU2017 License: 19

Test Sponsor: Fujitsu

Tested by: Fujitsu

Test Date: Jul-2019

Hardware Availability: Apr-2019

Software Availability: Feb-2019

## Compiler Version Notes (Continued)

Intel(R) Fortran Intel(R) 64 Compiler for applications running on Intel(R)  
64, Version 19.0.0.117 Build 20180804

Copyright (C) 1985-2018 Intel Corporation. All rights reserved.

Intel(R) C Intel(R) 64 Compiler for applications running on Intel(R) 64,  
Version 19.0.0.117 Build 20180804

Copyright (C) 1985-2018 Intel Corporation. All rights reserved.

## Base Compiler Invocation

C benchmarks:

icc -m64 -std=c11

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

ifort -m64 icc -m64 -std=c11

Benchmarks using both C and C++:

icpc -m64 icc -m64 -std=c11

Benchmarks using Fortran, C, and C++:

icpc -m64 icc -m64 -std=c11 ifort -m64

## Base Portability Flags

503.bwaves\_r: -DSPEC\_LP64  
507.cactusBSSN\_r: -DSPEC\_LP64  
508.namd\_r: -DSPEC\_LP64  
510.parest\_r: -DSPEC\_LP64  
511.povray\_r: -DSPEC\_LP64  
519.llbm\_r: -DSPEC\_LP64  
521.wrf\_r: -DSPEC\_LP64 -DSPEC\_CASE\_FLAG -convert big\_endian  
526.blender\_r: -DSPEC\_LP64 -DSPEC\_LINUX -funsigned-char  
527.cam4\_r: -DSPEC\_LP64 -DSPEC\_CASE\_FLAG  
538.imagick\_r: -DSPEC\_LP64  
544.nab\_r: -DSPEC\_LP64  
549.fotonik3d\_r: -DSPEC\_LP64

(Continued on next page)



# SPEC CPU®2017 Floating Point Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Fujitsu

PRIMEQUEST 3800E2, Intel Xeon Platinum 8260M,  
2.40GHz

SPECrate®2017\_fp\_base = 971

SPECrate®2017\_fp\_peak = Not Run

CPU2017 License: 19

Test Sponsor: Fujitsu

Tested by: Fujitsu

Test Date: Jul-2019

Hardware Availability: Apr-2019

Software Availability: Feb-2019

## Base Portability Flags (Continued)

554.roms\_r: -DSPEC\_LP64

## Base Optimization Flags

C benchmarks:

```
-xCORE-AVX2 -ipo -O3 -no-prec-div -qopt-prefetch -ffinite-math-only  
-qopt-mem-layout-trans=3
```

C++ benchmarks:

```
-xCORE-AVX2 -ipo -O3 -no-prec-div -qopt-prefetch -ffinite-math-only  
-qopt-mem-layout-trans=3
```

Fortran benchmarks:

```
-xCORE-AVX2 -ipo -O3 -no-prec-div -qopt-prefetch -ffinite-math-only  
-qopt-mem-layout-trans=3 -auto -nostandard-realloc-lhs  
-align array32byte
```

Benchmarks using both Fortran and C:

```
-xCORE-AVX2 -ipo -O3 -no-prec-div -qopt-prefetch -ffinite-math-only  
-qopt-mem-layout-trans=3 -auto -nostandard-realloc-lhs  
-align array32byte
```

Benchmarks using both C and C++:

```
-xCORE-AVX2 -ipo -O3 -no-prec-div -qopt-prefetch -ffinite-math-only  
-qopt-mem-layout-trans=3
```

Benchmarks using Fortran, C, and C++:

```
-xCORE-AVX2 -ipo -O3 -no-prec-div -qopt-prefetch -ffinite-math-only  
-qopt-mem-layout-trans=3 -auto -nostandard-realloc-lhs  
-align array32byte
```

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2017/flags/Intel-ic19.0-official-linux64.2019-01-15.html>  
<http://www.spec.org/cpu2017/flags/Fujitsu-Platform-Settings-V1.0-CSL-RevE.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2017/flags/Intel-ic19.0-official-linux64.2019-01-15.xml>  
<http://www.spec.org/cpu2017/flags/Fujitsu-Platform-Settings-V1.0-CSL-RevE.xml>



# SPEC CPU®2017 Floating Point Rate Result

Copyright 2017-2019 Standard Performance Evaluation Corporation

Fujitsu

PRIMEQUEST 3800E2, Intel Xeon Platinum 8260M,  
2.40GHz

SPECrate®2017\_fp\_base = 971

SPECrate®2017\_fp\_peak = Not Run

CPU2017 License: 19

Test Sponsor: Fujitsu

Tested by: Fujitsu

Test Date: Jul-2019

Hardware Availability: Apr-2019

Software Availability: Feb-2019

SPEC CPU and SPECrate are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact [info@spec.org](mailto:info@spec.org).

Tested with SPEC CPU®2017 v1.0.5 on 2019-07-11 09:52:33-0400.

Report generated on 2019-10-15 14:45:02 by CPU2017 PDF formatter v6255.

Originally published on 2019-10-15.