



SPEC CPU®2017 Integer Rate Result

Copyright 2017-2022 Standard Performance Evaluation Corporation

Dell Inc.

SPECrate®2017_int_base = 1660

PowerEdge R7625 (AMD EPYC 9654 96-Core Processor)

SPECrate®2017_int_peak = Not Run

CPU2017 License: 55


Test Date: Oct-2022

Test Sponsor: Dell Inc.

Hardware Availability: Nov-2022

Tested by: Dell Inc.

Software Availability: Nov-2022



Hardware

CPU Name: AMD EPYC 9654
 Max MHz: 3700
 Nominal: 2400
 Enabled: 192 cores, 2 chips, 2 threads/core
 Orderable: 1,2 chips
 Cache L1: 32 KB I + 32 KB D on chip per core
 L2: 1 MB I+D on chip per core
 L3: 384 MB I+D on chip per chip, 32 MB shared / 8 cores
 Other: None
 Memory: 1536 GB (24 x 64 GB 2Rx4 PC5-4800B-R)
 Storage: 180 GB on tmpfs
 Other: None

Software

OS: SUSE Linux Enterprise Server 15 SP4 5.14.21-150400.22-default
 Compiler: C/C++/Fortran: Version 4.0.0 of AOCC
 Parallel: No
 Firmware: Version 1.0.0 released Sep-2022
 File System: tmpfs
 System State: Run level 3 (multi-user)
 Base Pointers: 64-bit
 Peak Pointers: Not Applicable
 Other: None
 Power Management: BIOS and OS set to prefer performance at the cost of additional power usage.



SPEC CPU®2017 Integer Rate Result

Copyright 2017-2022 Standard Performance Evaluation Corporation

Dell Inc.

SPECrate®2017_int_base = 1660

PowerEdge R7625 (AMD EPYC 9654 96-Core Processor)

SPECrate®2017_int_peak = Not Run

CPU2017 License: 55
Test Sponsor: Dell Inc.
Tested by: Dell Inc.

Test Date: Oct-2022
Hardware Availability: Nov-2022
Software Availability: Nov-2022

Results Table

| Benchmark | Base | | | | | | | | Peak | | | | | | | |
|-----------------|--------|-------------------|--------------------|-------------------|--------------------|---------|-------|--------|---------|-------|---------|-------|---------|-------|--|--|
| | Copies | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Copies | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | | |
| 500.perlbench_r | 384 | 474 | 1290 | <u>474</u> | <u>1290</u> | | | | | | | | | | | |
| 502.gcc_r | 384 | <u>465</u> | <u>1170</u> | 463 | 1170 | | | | | | | | | | | |
| 505.mcf_r | 384 | 268 | 2320 | <u>268</u> | <u>2320</u> | | | | | | | | | | | |
| 520.omnetpp_r | 384 | 638 | 790 | <u>643</u> | <u>784</u> | | | | | | | | | | | |
| 523.xalancbmk_r | 384 | 234 | 1740 | <u>234</u> | <u>1730</u> | | | | | | | | | | | |
| 525.x264_r | 384 | <u>161</u> | <u>4170</u> | 161 | 4190 | | | | | | | | | | | |
| 531.deepsjeng_r | 384 | <u>292</u> | <u>1510</u> | 290 | 1520 | | | | | | | | | | | |
| 541.leela_r | 384 | <u>424</u> | <u>1500</u> | 423 | 1500 | | | | | | | | | | | |
| 548.exchange2_r | 384 | <u>249</u> | <u>4040</u> | 249 | 4050 | | | | | | | | | | | |
| 557.xz_r | 384 | <u>477</u> | <u>870</u> | 475 | 873 | | | | | | | | | | | |

SPECrate®2017_int_base = 1660

SPECrate®2017_int_peak = Not Run

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Notes

The AMD64 AOCC Compiler Suite is available at
<http://developer.amd.com/amd-aocc/>

Submit Notes

The config file option 'submit' was used.
'numactl' was used to bind copies to the cores.
See the configuration file for details.

Operating System Notes

'ulimit -s unlimited' was used to set environment stack size limit
'ulimit -l 2097152' was used to set environment locked pages in memory limit

runcpu command invoked through numactl i.e.:
numactl --interleave=all runcpu <etc>

To limit dirty cache to 8% of memory, 'sysctl -w vm.dirty_ratio=8' run as root.
To limit swap usage to minimum necessary, 'sysctl -w vm.swappiness=1' run as root.
To free node-local memory and avoid remote memory usage,
'sysctl -w vm.zone_reclaim_mode=1' run as root.
To clear filesystem caches, 'sync; sysctl -w vm.drop_caches=3' run as root.
To disable address space layout randomization (ASLR) to reduce run-to-run
variability, 'sysctl -w kernel.randomize_va_space=0' run as root.

(Continued on next page)



SPEC CPU®2017 Integer Rate Result

Copyright 2017-2022 Standard Performance Evaluation Corporation

Dell Inc.

SPECrate®2017_int_base = 1660

PowerEdge R7625 (AMD EPYC 9654 96-Core Processor)

SPECrate®2017_int_peak = Not Run

CPU2017 License: 55

Test Sponsor: Dell Inc.

Tested by: Dell Inc.

Test Date: Oct-2022

Hardware Availability: Nov-2022

Software Availability: Nov-2022

Operating System Notes (Continued)

To enable Transparent Hugepages (THP) only on request for base runs,
'echo madvise > /sys/kernel/mm/transparent_hugepage/enabled' run as root.
To enable THP for all allocations for peak runs,
'echo always > /sys/kernel/mm/transparent_hugepage/enabled' and
'echo always > /sys/kernel/mm/transparent_hugepage/defrag' run as root.

Environment Variables Notes

Environment variables set by runcpu before the start of the run:

```
LD_LIBRARY_PATH =  
    "/mnt/ramdisk/cpu2017-1.1.8-aocc400-B1/amd_rate_aocc400_genoa_B_lib/lib:  
    /mnt/ramdisk/cpu2017-1.1.8-aocc400-B1/amd_rate_aocc400_genoa_B_lib/lib32  
    :"  
MALLOC_CONF = "retain:true"
```

General Notes

Binaries were compiled on a system with 2x AMD EPYC 9174F CPU + 1.5TiB Memory using RHEL 8.6

NA: The test sponsor attests, as of date of publication, that CVE-2017-5754 (Meltdown) is mitigated in the system as tested and documented.
Yes: The test sponsor attests, as of date of publication, that CVE-2017-5753 (Spectre variant 1) is mitigated in the system as tested and documented.
Yes: The test sponsor attests, as of date of publication, that CVE-2017-5715 (Spectre variant 2) is mitigated in the system as tested and documented.

Benchmark run from a 180 GB ramdisk created with the cmd: "mount -t tmpfs -o size=180G tmpfs /mnt/ramdisk"

Platform Notes

BIOS settings:

```
    DRAM Refresh Delay : Performance  
    DIMM Self Healing on  
Uncorrectable Memory Error : Disabled  
Virtualization Technology : Disabled  
    NUMA Nodes per Socket : 4  
    L3 Cache as NUMA Domain : Enabled
```

```
    System Profile : Custom  
    Memory Patrol Scrub : Disabled
```

(Continued on next page)



SPEC CPU[®]2017 Integer Rate Result

Copyright 2017-2022 Standard Performance Evaluation Corporation

Dell Inc.

SPECrate[®]2017_int_base = 1660

PowerEdge R7625 (AMD EPYC 9654 96-Core Processor)

SPECrate[®]2017_int_peak = Not Run

CPU2017 License: 55

Test Sponsor: Dell Inc.

Tested by: Dell Inc.

Test Date: Oct-2022

Hardware Availability: Nov-2022

Software Availability: Nov-2022

Platform Notes (Continued)

PCI ASPM L1 Link
Power Management : Disabled
Determinism Slider : Power Determinism

Sysinfo program /mnt/ramdisk/cpu2017-1.1.8-aocc400-B1/bin/sysinfo
Rev: r6622 of 2021-04-07 982a61ec0915b55891ef0e16acafc64d
running on localhost.localdomain Tue Oct 18 17:21:47 2022

SUT (System Under Test) info as seen by some common utilities.
For more information on this section, see
<https://www.spec.org/cpu2017/Docs/config.html#sysinfo>

From /proc/cpuinfo
model name : AMD EPYC 9654 96-Core Processor
2 "physical id"s (chips)
384 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The following excerpts from /proc/cpuinfo might not be reliable. Use with caution.)
cpu cores : 96
siblings : 192
physical 0: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24
25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52
53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80
81 82 83 84 85 86 87 88 89 90 91 92 93 94 95
physical 1: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24
25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52
53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80
81 82 83 84 85 86 87 88 89 90 91 92 93 94 95

From lscpu from util-linux 2.37.2:
Architecture: x86_64
CPU op-mode(s): 32-bit, 64-bit
Address sizes: 52 bits physical, 57 bits virtual
Byte Order: Little Endian
CPU(s): 384
On-line CPU(s) list: 0-383
Vendor ID: AuthenticAMD
Model name: AMD EPYC 9654 96-Core Processor
CPU family: 25
Model: 17
Thread(s) per core: 2
Core(s) per socket: 96
Socket(s): 2
Stepping: 1
Frequency boost: enabled
CPU max MHz: 3707.8120
CPU min MHz: 1500.0000

(Continued on next page)



SPEC CPU®2017 Integer Rate Result

Copyright 2017-2022 Standard Performance Evaluation Corporation

Dell Inc.

SPECrate®2017_int_base = 1660

PowerEdge R7625 (AMD EPYC 9654 96-Core Processor)

SPECrate®2017_int_peak = Not Run

CPU2017 License: 55

Test Date: Oct-2022

Test Sponsor: Dell Inc.

Hardware Availability: Nov-2022

Tested by: Dell Inc.

Software Availability: Nov-2022

Platform Notes (Continued)

```

BogoMIPS:                4801.60
Flags:                    fpu vme de pse tsc msr pae mce cx8 apic sep mtrr
pge mca cmov pat pse36 clflush mmx fxsr sse sse2 ht syscall nx mmxext fxsr_opt
pdpe1gb rdtscp lm constant_tsc rep_good nopl nonstop_tsc cpuid extd_apicid
aperfmpperf rapl pni pclmulqdq monitor ssse3 fma cx16 pcid sse4_1 sse4_2 x2apic movbe
popcnt aes xsave avx f16c rdrand lahf_lm cmp_legacy svm extapic cr8_legacy abm sse4a
misalignsse 3dnowprefetch osvw ibs skinit wdt tce topoext perfctr_core perfctr_nb
bpext perfctr_llc mwaitx cpb cat_l3 cdp_l3 invpcid_single hw_pstate ssbd mba ibrs
ibpb stibp vmmcall fsgsbase bmi1 avx2 smep bmi2 erms invpcid cqm rdt_a avx512f
avx512dq rdseed adx smap avx512ifma clflushopt clwb avx512cd sha_ni avx512bw
avx512vl xsaveopt xsavec xgetbv1 xsaves cqm_llc cqm_occup_llc cqm_mbm_total
cqm_mbm_local avx512_bf16 clzero irperf xsaveerptr rdpru wbnoinvd amd_ppin arat npt
lbrv svm_lock nrip_save tsc_scale vmcb_clean flushbyasid decodeassists pausefilter
pfthreshold avic v_vmsave_vmload vgif v_spec_ctrl avx512vbmi umip pku ospke
avx512_vbmi2 gfni vaes vpclmulqdq avx512_vnni avx512_bitalg avx512_vpopcntdq la57
rdpid overflow_recov succor smca fsrm flush_lld
Virtualization:          AMD-V
L1d cache:               6 MiB (192 instances)
L1i cache:               6 MiB (192 instances)
L2 cache:                192 MiB (192 instances)
L3 cache:                768 MiB (24 instances)
NUMA node(s):           24
NUMA node0 CPU(s):      0-7,192-199
NUMA node1 CPU(s):      8-15,200-207
NUMA node2 CPU(s):      16-23,208-215
NUMA node3 CPU(s):      24-31,216-223
NUMA node4 CPU(s):      32-39,224-231
NUMA node5 CPU(s):      40-47,232-239
NUMA node6 CPU(s):      48-55,240-247
NUMA node7 CPU(s):      56-63,248-255
NUMA node8 CPU(s):      64-71,256-263
NUMA node9 CPU(s):      72-79,264-271
NUMA node10 CPU(s):     80-87,272-279
NUMA node11 CPU(s):     88-95,280-287
NUMA node12 CPU(s):     96-103,288-295
NUMA node13 CPU(s):     104-111,296-303
NUMA node14 CPU(s):     112-119,304-311
NUMA node15 CPU(s):     120-127,312-319
NUMA node16 CPU(s):     128-135,320-327
NUMA node17 CPU(s):     136-143,328-335
NUMA node18 CPU(s):     144-151,336-343
NUMA node19 CPU(s):     152-159,344-351
NUMA node20 CPU(s):     160-167,352-359
NUMA node21 CPU(s):     168-175,360-367
NUMA node22 CPU(s):     176-183,368-375
NUMA node23 CPU(s):     184-191,376-383
Vulnerability Itlb multihit: Not affected

```

(Continued on next page)



SPEC CPU®2017 Integer Rate Result

Copyright 2017-2022 Standard Performance Evaluation Corporation

Dell Inc.

SPECrate®2017_int_base = 1660

PowerEdge R7625 (AMD EPYC 9654 96-Core Processor)

SPECrate®2017_int_peak = Not Run

CPU2017 License: 55

Test Date: Oct-2022

Test Sponsor: Dell Inc.

Hardware Availability: Nov-2022

Tested by: Dell Inc.

Software Availability: Nov-2022

Platform Notes (Continued)

Vulnerability L1tf: Not affected
 Vulnerability Mds: Not affected
 Vulnerability Meltdown: Not affected
 Vulnerability Spec store bypass: Mitigation; Speculative Store Bypass disabled via prctl and seccomp
 Vulnerability Spectre v1: Mitigation; usercopy/swapgs barriers and __user pointer sanitization
 Vulnerability Spectre v2: Mitigation; Retpolines, IBPB conditional, IBRS_FW, STIBP always-on, RSB filling
 Vulnerability Srbds: Not affected
 Vulnerability Tsx async abort: Not affected

From lscpu --cache:

| NAME | ONE-SIZE | ALL-SIZE | WAYS | TYPE | LEVEL | SETS | PHY-LINE | COHERENCY-SIZE |
|------|----------|----------|------|-------------|-------|-------|----------|----------------|
| L1d | 32K | 6M | 8 | Data | 1 | 64 | 1 | 64 |
| L1i | 32K | 6M | 8 | Instruction | 1 | 64 | 1 | 64 |
| L2 | 1M | 192M | 8 | Unified | 2 | 2048 | 1 | 64 |
| L3 | 32M | 768M | 16 | Unified | 3 | 32768 | 1 | 64 |

/proc/cpuinfo cache data
cache size : 1024 KB

From numactl --hardware

WARNING: a numactl 'node' might or might not correspond to a physical chip.

available: 24 nodes (0-23)
 node 0 cpus: 0 1 2 3 4 5 6 7 192 193 194 195 196 197 198 199
 node 0 size: 64053 MB
 node 0 free: 61895 MB
 node 1 cpus: 8 9 10 11 12 13 14 15 200 201 202 203 204 205 206 207
 node 1 size: 64507 MB
 node 1 free: 64184 MB
 node 2 cpus: 16 17 18 19 20 21 22 23 208 209 210 211 212 213 214 215
 node 2 size: 64507 MB
 node 2 free: 63768 MB
 node 3 cpus: 24 25 26 27 28 29 30 31 216 217 218 219 220 221 222 223
 node 3 size: 64507 MB
 node 3 free: 64239 MB
 node 4 cpus: 32 33 34 35 36 37 38 39 224 225 226 227 228 229 230 231
 node 4 size: 64507 MB
 node 4 free: 64285 MB
 node 5 cpus: 40 41 42 43 44 45 46 47 232 233 234 235 236 237 238 239
 node 5 size: 64507 MB
 node 5 free: 64282 MB
 node 6 cpus: 48 49 50 51 52 53 54 55 240 241 242 243 244 245 246 247
 node 6 size: 64507 MB
 node 6 free: 61845 MB
 node 7 cpus: 56 57 58 59 60 61 62 63 248 249 250 251 252 253 254 255

(Continued on next page)



SPEC CPU®2017 Integer Rate Result

Copyright 2017-2022 Standard Performance Evaluation Corporation

Dell Inc.

SPECrate®2017_int_base = 1660

PowerEdge R7625 (AMD EPYC 9654 96-Core Processor)

SPECrate®2017_int_peak = Not Run

CPU2017 License: 55

Test Date: Oct-2022

Test Sponsor: Dell Inc.

Hardware Availability: Nov-2022

Tested by: Dell Inc.

Software Availability: Nov-2022

Platform Notes (Continued)

```

node 7 size: 64507 MB
node 7 free: 64289 MB
node 8 cpus: 64 65 66 67 68 69 70 71 256 257 258 259 260 261 262 263
node 8 size: 64506 MB
node 8 free: 64305 MB
node 9 cpus: 72 73 74 75 76 77 78 79 264 265 266 267 268 269 270 271
node 9 size: 64455 MB
node 9 free: 64248 MB
node 10 cpus: 80 81 82 83 84 85 86 87 272 273 274 275 276 277 278 279
node 10 size: 64506 MB
node 10 free: 64002 MB
node 11 cpus: 88 89 90 91 92 93 94 95 280 281 282 283 284 285 286 287
node 11 size: 64506 MB
node 11 free: 64296 MB
node 12 cpus: 96 97 98 99 100 101 102 103 288 289 290 291 292 293 294 295
node 12 size: 64507 MB
node 12 free: 64163 MB
node 13 cpus: 104 105 106 107 108 109 110 111 296 297 298 299 300 301 302 303
node 13 size: 64507 MB
node 13 free: 64173 MB
node 14 cpus: 112 113 114 115 116 117 118 119 304 305 306 307 308 309 310 311
node 14 size: 64507 MB
node 14 free: 64296 MB
node 15 cpus: 120 121 122 123 124 125 126 127 312 313 314 315 316 317 318 319
node 15 size: 64507 MB
node 15 free: 64210 MB
node 16 cpus: 128 129 130 131 132 133 134 135 320 321 322 323 324 325 326 327
node 16 size: 64507 MB
node 16 free: 64240 MB
node 17 cpus: 136 137 138 139 140 141 142 143 328 329 330 331 332 333 334 335
node 17 size: 64507 MB
node 17 free: 64249 MB
node 18 cpus: 144 145 146 147 148 149 150 151 336 337 338 339 340 341 342 343
node 18 size: 64507 MB
node 18 free: 64263 MB
node 19 cpus: 152 153 154 155 156 157 158 159 344 345 346 347 348 349 350 351
node 19 size: 64507 MB
node 19 free: 64198 MB
node 20 cpus: 160 161 162 163 164 165 166 167 352 353 354 355 356 357 358 359
node 20 size: 64506 MB
node 20 free: 64244 MB
node 21 cpus: 168 169 170 171 172 173 174 175 360 361 362 363 364 365 366 367
node 21 size: 64404 MB
node 21 free: 64148 MB
node 22 cpus: 176 177 178 179 180 181 182 183 368 369 370 371 372 373 374 375
node 22 size: 64506 MB
node 22 free: 64254 MB

```

(Continued on next page)



SPEC CPU®2017 Integer Rate Result

Copyright 2017-2022 Standard Performance Evaluation Corporation

Dell Inc.

SPECrate®2017_int_base = 1660

PowerEdge R7625 (AMD EPYC 9654 96-Core Processor)

SPECrate®2017_int_peak = Not Run

CPU2017 License: 55

Test Sponsor: Dell Inc.

Tested by: Dell Inc.

Test Date: Oct-2022

Hardware Availability: Nov-2022

Software Availability: Nov-2022

Platform Notes (Continued)

```

node 23 cpus: 184 185 186 187 188 189 190 191 376 377 378 379 380 381 382 383
node 23 size: 64506 MB
node 23 free: 64075 MB
node distances:
node 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19
20 21 22 23
0: 10 12 12 12 11 12 12 12 11 12 12 12 32 32 32 32 32 32 32 32
32 32 32 32
1: 12 10 12 12 12 11 12 12 12 11 12 12 32 32 32 32 32 32 32 32
32 32 32 32
2: 12 12 10 12 12 12 11 12 12 12 11 12 32 32 32 32 32 32 32 32
32 32 32 32
3: 12 12 12 10 12 12 12 11 12 12 12 11 32 32 32 32 32 32 32 32
32 32 32 32
4: 11 12 12 12 10 12 12 12 11 12 12 12 32 32 32 32 32 32 32 32
32 32 32 32
5: 12 11 12 12 12 10 12 12 12 11 12 12 32 32 32 32 32 32 32 32
32 32 32 32
6: 12 12 11 12 12 12 10 12 12 12 11 12 32 32 32 32 32 32 32 32
32 32 32 32
7: 12 12 12 11 12 12 12 10 12 12 12 11 32 32 32 32 32 32 32 32
32 32 32 32
8: 11 12 12 12 11 12 12 12 10 12 12 12 32 32 32 32 32 32 32 32
32 32 32 32
9: 12 11 12 12 12 11 12 12 12 10 12 12 32 32 32 32 32 32 32 32
32 32 32 32
10: 12 12 11 12 12 12 11 12 12 12 10 12 32 32 32 32 32 32 32 32
32 32 32 32
11: 12 12 12 11 12 12 12 11 12 12 12 10 32 32 32 32 32 32 32 32
32 32 32 32
12: 32 32 32 32 32 32 32 32 32 32 32 32 10 12 12 12 11 12 12 12
11 12 12 12
13: 32 32 32 32 32 32 32 32 32 32 32 32 12 10 12 12 12 11 12 12
12 11 12 12
14: 32 32 32 32 32 32 32 32 32 32 32 32 12 12 10 12 12 12 11 12
12 12 11 12
15: 32 32 32 32 32 32 32 32 32 32 32 32 12 12 12 10 12 12 12 11
12 12 12 11
16: 32 32 32 32 32 32 32 32 32 32 32 32 11 12 12 12 10 12 12 12
11 12 12 12
17: 32 32 32 32 32 32 32 32 32 32 32 32 12 11 12 12 12 10 12 12
12 11 12 12
18: 32 32 32 32 32 32 32 32 32 32 32 32 12 12 11 12 12 12 10 12
12 12 11 12
19: 32 32 32 32 32 32 32 32 32 32 32 32 12 12 12 11 12 12 12 10
12 12 12 11
20: 32 32 32 32 32 32 32 32 32 32 32 32 11 12 12 12 11 12 12 12

```

(Continued on next page)



SPEC CPU®2017 Integer Rate Result

Copyright 2017-2022 Standard Performance Evaluation Corporation

Dell Inc.

SPECrate®2017_int_base = 1660

PowerEdge R7625 (AMD EPYC 9654 96-Core Processor)

SPECrate®2017_int_peak = Not Run

CPU2017 License: 55

Test Sponsor: Dell Inc.

Tested by: Dell Inc.

Test Date: Oct-2022

Hardware Availability: Nov-2022

Software Availability: Nov-2022

Platform Notes (Continued)

```

10  12  12  12
21:  32  32  32  32  32  32  32  32  32  32  32  32  32  12  11  12  12  12  11  12  12
12  10  12  12
22:  32  32  32  32  32  32  32  32  32  32  32  32  32  12  12  11  12  12  12  11  12
12  12  10  12
23:  32  32  32  32  32  32  32  32  32  32  32  32  32  12  12  12  11  12  12  12  11
12  12  12  10

```

From /proc/meminfo

```

MemTotal:      1584711364 kB
HugePages_Total:      0
Hugepagesize:    2048 kB

```

/sys/devices/system/cpu/cpu*/cpufreq/scaling_governor has performance

From /etc/*release* /etc/*version*

```

os-release:
NAME="SLES"
VERSION="15-SP4"
VERSION_ID="15.4"
PRETTY_NAME="SUSE Linux Enterprise Server 15 SP4"
ID="sles"
ID_LIKE="suse"
ANSI_COLOR="0;32"
CPE_NAME="cpe:/o:suse:sles:15:sp4"

```

uname -a:

```

Linux localhost.localdomain 5.14.21-150400.22-default #1 SMP PREEMPT_DYNAMIC Wed May 11 06:57:18 UTC 2022 (49db222) x86_64 x86_64 x86_64 GNU/Linux

```

Kernel self-reported vulnerability status:

```

CVE-2018-12207 (iTLB Multihit):          Not affected
CVE-2018-3620 (L1 Terminal Fault):       Not affected
Microarchitectural Data Sampling:       Not affected
CVE-2017-5754 (Meltdown):               Not affected
CVE-2018-3639 (Speculative Store Bypass): Mitigation: Speculative Store Bypass disabled via prctl and seccomp
CVE-2017-5753 (Spectre variant 1):       Mitigation: usercopy/swapgs barriers and __user pointer sanitization
CVE-2017-5715 (Spectre variant 2):       Mitigation: Retpolines, IBPB: conditional, IBRS_FW, STIBP: always-on, RSB filling
CVE-2020-0543 (Special Register Buffer Data Sampling): Not affected

```

(Continued on next page)



SPEC CPU®2017 Integer Rate Result

Copyright 2017-2022 Standard Performance Evaluation Corporation

Dell Inc.

SPECrate®2017_int_base = 1660

PowerEdge R7625 (AMD EPYC 9654 96-Core Processor)

SPECrate®2017_int_peak = Not Run

CPU2017 License: 55

Test Date: Oct-2022

Test Sponsor: Dell Inc.

Hardware Availability: Nov-2022

Tested by: Dell Inc.

Software Availability: Nov-2022

Platform Notes (Continued)

CVE-2019-11135 (TSX Asynchronous Abort): Not affected

run-level 3 Oct 18 17:19

SPEC is set to: /mnt/ramdisk/cpu2017-1.1.8-aocc400-B1

| Filesystem | Type | Size | Used | Avail | Use% | Mounted on |
|------------|-------|------|------|-------|------|--------------|
| tmpfs | tmpfs | 180G | 3.4G | 177G | 2% | /mnt/ramdisk |

From /sys/devices/virtual/dmi/id

```
Vendor: Dell Inc.
Product: PowerEdge R7625
Product Family: PowerEdge
Serial: 1234567
```

Additional information from dmidecode 3.2 follows. WARNING: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

Memory:

24x 80AD000080AD HMC94MEBRA109N 64 GB 2 rank 4800

BIOS:

```
BIOS Vendor: Dell Inc.
BIOS Version: 1.0.0
BIOS Date: 09/28/2022
BIOS Revision: 1.0
```

(End of data from sysinfo program)

Compiler Version Notes

```
=====  
C      | 500.perlbench_r(base) 502.gcc_r(base) 505.mcf_r(base)  
      | 525.x264_r(base) 557.xz_r(base)  
=====
```

AMD clang version 14.0.6 (CLANG: AOCC_4.0.0-Build#389 2022_10_07) (based on LLVM Mirror.Version.14.0.6)

Target: x86_64-unknown-linux-gnu

Thread model: posix

InstalledDir: /opt/AMD/aocc/aocc-compiler-rel-4.0-3206-389/bin

```
=====  
C++   | 520.omnetpp_r(base) 523.xalancbmk_r(base) 531.deepsjeng_r(base)  
     | 541.leela_r(base)  
=====
```

(Continued on next page)



SPEC CPU®2017 Integer Rate Result

Copyright 2017-2022 Standard Performance Evaluation Corporation

Dell Inc.

SPECrate®2017_int_base = 1660

PowerEdge R7625 (AMD EPYC 9654 96-Core Processor)

SPECrate®2017_int_peak = Not Run

CPU2017 License: 55

Test Date: Oct-2022

Test Sponsor: Dell Inc.

Hardware Availability: Nov-2022

Tested by: Dell Inc.

Software Availability: Nov-2022

Compiler Version Notes (Continued)

AMD clang version 14.0.6 (CLANG: AOCC_4.0.0-Build#389 2022_10_07) (based on LLVM Mirror.Version.14.0.6)

Target: x86_64-unknown-linux-gnu

Thread model: posix

InstalledDir: /opt/AMD/aocc/aocc-compiler-rel-4.0-3206-389/bin

Fortran | 548.exchange2_r(base)

AMD clang version 14.0.6 (CLANG: AOCC_4.0.0-Build#389 2022_10_07) (based on LLVM Mirror.Version.14.0.6)

Target: x86_64-unknown-linux-gnu

Thread model: posix

InstalledDir: /opt/AMD/aocc/aocc-compiler-rel-4.0-3206-389/bin

Base Compiler Invocation

C benchmarks:

clang

C++ benchmarks:

clang++

Fortran benchmarks:

flang

Base Portability Flags

500.perlbench_r: -DSPEC_LINUX_X64 -DSPEC_LP64

502.gcc_r: -DSPEC_LP64

505.mcf_r: -DSPEC_LP64

520.omnetpp_r: -DSPEC_LP64

523.xalancbmk_r: -DSPEC_LINUX -DSPEC_LP64

525.x264_r: -DSPEC_LP64

531.deepsjeng_r: -DSPEC_LP64

541.leela_r: -DSPEC_LP64

548.exchange2_r: -DSPEC_LP64

557.xz_r: -DSPEC_LP64



SPEC CPU®2017 Integer Rate Result

Copyright 2017-2022 Standard Performance Evaluation Corporation

Dell Inc.

SPECrate®2017_int_base = 1660

PowerEdge R7625 (AMD EPYC 9654 96-Core Processor)

SPECrate®2017_int_peak = Not Run

CPU2017 License: 55

Test Sponsor: Dell Inc.

Tested by: Dell Inc.

Test Date: Oct-2022

Hardware Availability: Nov-2022

Software Availability: Nov-2022

Base Optimization Flags

C benchmarks:

```
-m64 -flto -Wl,-mllvm -Wl,-align-all-nofallthru-blocks=6
-Wl,-mllvm -Wl,-reduce-array-computations=3
-Wl,-mllvm -Wl,-ldist-scalar-expand -fenable-aggressive-gather
-z muldefs -O3 -march=znver4 -fveclib=AMDLIBM -ffast-math
-fstruct-layout=7 -mllvm -unroll-threshold=50
-mllvm -inline-threshold=1000 -fremap-arrays -fstrip-mining
-mllvm -reduce-array-computations=3 -zopt -lamdlibm -lflang
-lamdalloc
```

C++ benchmarks:

```
-m64 -flto -Wl,-mllvm -Wl,-align-all-nofallthru-blocks=6
-Wl,-mllvm -Wl,-reduce-array-computations=3 -z muldefs -O3
-march=znver4 -fveclib=AMDLIBM -ffast-math
-mllvm -unroll-threshold=100 -finline-aggressive
-mllvm -loop-unswitch-threshold=200000
-mllvm -reduce-array-computations=3 -zopt
-fvirtual-function-elimination -fvisibility=hidden -lamdlibm -lflang
-lamdalloc-ext
```

Fortran benchmarks:

```
-m64 -flto -Wl,-mllvm -Wl,-align-all-nofallthru-blocks=6
-Wl,-mllvm -Wl,-reduce-array-computations=3
-Wl,-mllvm -Wl,-inline-recursion=4 -Wl,-mllvm -Wl,-lsr-in-nested-loop
-Wl,-mllvm -Wl,-enable-iv-split -z muldefs -O3 -march=znver4
-fveclib=AMDLIBM -ffast-math -fepilog-vectorization-of-inductions
-mllvm -optimize-strided-mem-cost -floop-transform
-mllvm -unroll-aggressive -mllvm -unroll-threshold=500 -lamdlibm
-lflang -lamdalloc
```

Base Other Flags

C benchmarks:

```
-Wno-unused-command-line-argument
```

C++ benchmarks:

```
-Wno-unused-command-line-argument
```

Fortran benchmarks:

```
-Wno-unused-command-line-argument
```



SPEC CPU®2017 Integer Rate Result

Copyright 2017-2022 Standard Performance Evaluation Corporation

Dell Inc.

SPECrate®2017_int_base = 1660

PowerEdge R7625 (AMD EPYC 9654 96-Core Processor)

SPECrate®2017_int_peak = Not Run

CPU2017 License: 55

Test Date: Oct-2022

Test Sponsor: Dell Inc.

Hardware Availability: Nov-2022

Tested by: Dell Inc.

Software Availability: Nov-2022

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2017/flags/aocc400-flags.html>

<http://www.spec.org/cpu2017/flags/Dell-Platform-Flags-PowerEdge-AMD-EPYC-v1.0.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2017/flags/aocc400-flags.xml>

<http://www.spec.org/cpu2017/flags/Dell-Platform-Flags-PowerEdge-AMD-EPYC-v1.0.xml>

SPEC CPU and SPECrate are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEC CPU®2017 v1.1.8 on 2022-10-18 18:21:47-0400.

Report generated on 2022-11-14 11:17:23 by CPU2017 PDF formatter v6442.

Originally published on 2022-11-11.