SPEC CINT95rate Results

©Copyright 1995, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Enterprise 3500

SPECint_rate95 = 1234

SPECint_rate_base95 = 1011

SPEC license # 6	Tested By: Sun, Palo Alto	Test Date: Sep-98	Hardware Avail: Dec-98	Software Avail: Oct-98



SPECrate

Hardware/Software Configuration for:
Sun Enterprise 3500

Hardware

Model Name:	Sun Enterprise 3500
CPU:	400MHz UltraSPARC II
FPU:	Integrated
Number of CPU(s):	8
Primary Cache:	16KBI+16KBD on chip
Secondary Cache:	4096KB(I+D) off chip
Other Cache:	None
Memory:	8192MB
Disk Subsystem:	2 x 9GB
Other Hardware:	FastEthernet

Software

Operating System:	Solaris 2.7
Compiler:	Sun C 5.0
File System:	UFS
System State:	Multi-User
Kernel Extensions:	

Benchmark # and Name	Base Copies	Base Run Time	Base SPEC Ratio	Copies	Run Time	SPEC Ratio
099.go	8	289	1147	8	283	1169
124.m88ksim	8	148	927	8	97	1412
126.gcc	8	118	1041	8	121	1013
129.compress	8	109	1192	8	100	1297
130.li	8	162	845	8	105	1298
132.ijpeg	8	166	1042	8	163	1062
134.perl	8	139	987	8	98	1400
147.vortex	8	204	952	8	152	1282
SPECint_rate_base95 (G. Mean)			1011			
SPECint_rate95 (G. Mean)						1234

Notes/Tuning Information

```
Baseline: -fast -xO5 -xarch=v8plusa -xprofile=use
099.go: -fast -xO4 -xarch=v8plus -xrestrict -xcrossfile -W2,-O4+ansi_alias+bopt -xprofile=use
124.m88ksim: -fast -xO5 -xsafe=mem -xarch=v8plus -xcrossfile -xrestrict
124 cont: -W2,-O4+cond_elim+pde,-Mt9000 -Wc,-Qiselect-sw_pf_tbl_th=20 -xprofile=use
126.gcc: -fast -xO4 -xarch=v8plus -W2,-O4+ansi_alias+cond_elim -xprofile=use
129.compress: -fast -xO4 -W2,-O4+ansi_alias+pde -xarch=v8plus -xprofile=use
130.li: PASS1=-fast -xO4 -xarch=v8plus -xcrossfile -xprofile=collect
130.li: PASS2=-fast -xO5 -xsafe=mem -xarch=v8plus -xcrossfile
130 PASS2 cont: -W2,-O4+ansi_alias+cond_elim+pde,-Mt350,-whole,-crit -xprofile=use
132.ijpeg: -fast -xO5 -xsafe=mem -xarch=v8plus -W2,-O4+ansi_alias+cond_elim -xprofile=use
134.perl: -fast -xO4 -xarch=v8plusa -xchip=ultra -xcrossfile -W2,-Mp1,-ANSI_S,-O4+cond_elim
134 cont: Wc,-Qiselect-sw_pf_tbl_th=30 -xprofile=use -lfast
147.vortex: PASS1=-fast -xO4 -xarch=v8plus -xcrossfile -xprofile=collect
147: PASS2=-fast -xO5 -xsafe=mem -xarch=v8plus -xcrossfile -xprofile=use
147 PASS2 cont: -W2,-O4+cond_elim,-Mt500,-Mr6000,crit
Portability: 124.m88ksim, 132.ijpeg: -DSYSV -Xc, 126.gcc: -Dalloca=__builtin_alloca -Xc
others: -Xc
Shell limits: # ulimit -n 1024  or % limit descriptors 1024
Config Version @(#)uds.cfg 1.0 98/09/03
```

For More Information Contact:
SPEC
10754 Ambassador Drive, Suite 201
Manassas, VA 20109
(703) 331-0180
info@specbench.org
http://www.specbench.org/

-- Prepared By: --