SPEC CFP95rate Results

©Copyright 1995, Standard Performance Evaluation Corporation

FUJITSU LIMITED
GP7000F Model600 275

SPECfp_rate95 = 821

SPECfp_rate_base95 = 754

SPEC license # 19	Tested By: FUJITSU LIMITED	Test Date: Dec-98	Hardware Avail: Dec-98	Software Avail: Feb-99



Hardware/Software Configuration for:
GP7000F Model600 275

Hardware

Model Name:	FUJITSU GP7000F Model600 275
CPU:	272MHz SPARC64 GP
FPU:	Integrated
Number of CPU(s):	4
Primary Cache:	64KBI+64KBD on chip, 4way
Secondary Cache:	8.0MB(I+D) off chip
Other Cache:	None
Memory:	4096MB
Disk Subsystem:	2 x 9.0GB
Other Hardware:	Ethernet

Software

Operating System:	Solaris 2.6 HW:5/98
Compiler:	Fujitsu Fortran V4.0.1
File System:	UFS
System State:	Single User
Kernel Extensions:	set consistent_coloring=1

Benchmark # and Name	Base Copies	Base Run Time	Base SPEC Ratio	Copies	Run Time	SPEC Ratio
101.tomcatv	4	94.2	1415	4	87	1525
102.swim	4	160	1930	4	145	2129
103.su2cor	4	109	462	4	110	456
104.hydro2d	4	124	699	4	121	716
107.mgrid	4	137	658	4	117	771
110.applu	4	210	378	4	208	380
125.turb3d	4	291	508	4	238	621
141.apsi	4	135	562	4	108	701
145.fpppp	4	319	1082	4	310	1113
146.wave5	4	122	882	4	117	923
SPECfp_rate_base95 (G. Mean)			754			
			SPECfp_rate95 (G. Mean)			821

Notes/Tuning Information

```
Baseline flags were: -Kfast,V8PFMADD,prefetch,gs
Nonbaseline: PEAKOPT=-X7 -Kfast,V8PFMADD,GREG,gs,prefetch; EXTRA_FFLAGS=-dn
101: ${PEAKOPT} -Kpreex,eval
102: ${PEAKOPT} -Koffset=160  -Ksp=0
103: ${PEAKOPT} -Knofuse,eval -x-
104: ${PEAKOPT} -Kpreex,eval
107: ${PEAKOPT} -Kcommonpad,eval
110: ${PEAKOPT} -Kauto,preex,eval
125: ${PEAKOPT} -Kcommonpad,eval -Ksp=0 -x-
141: -X7 ${PEAKOPT} -Kauto,preex,eval
145: ${PEAKOPT} -Keval
146: ${PEAKOPT} -Kauto,nofuse  -x10
Shell limits: ulimit -n 1024; ulimit -s 81920;
```

For More Information Contact:
SPEC
10754 Ambassador Drive, Suite 201
Manassas, VA 20109
(703) 331-0180
info@specbench.org
http://www.specbench.org/

-- Prepared By: --