SPEC CINT95 Results

©Copyright 1995, Standard Performance Evaluation Corporation

Sun Microsystems
Ultra 60 Model 1450

SPECint95 = 19.7

SPECint_base95 = 16.2

SPEC license # 6	Tested By: Sun, Palo Alto	Test Date: Apr-99	Hardware Avail: May-99	Software Avail: Feb-99



Hardware/Software Configuration for:
Ultra 60 Model 1450

Hardware

Model Name:	Ultra 60 Model 1450
CPU:	450 MHz UltraSPARC-II
FPU:	Integrated
Number of CPU(s):	1
Primary Cache:	16KBI+16KBD on chip
Secondary Cache:	4MB(I+D) off chip
Other Cache:	None
Memory:	512MB
Disk Subsystem:	2 x 9.1GB (7200 RPM)
Other Hardware:	Fast Ethernet System clock frequency: 112.5 MHz

Software

Operating System:	Solaris 7 (64bit)
Compiler:	Sun WorkShop C 5.0
File System:	UFS
System State:	Single User
Kernel Extensions:	consistent_coloring=1

Benchmark # and Name	Reference Time	Base Run Time	Base SPEC Ratio	Run Time	SPEC Ratio
099.go	4600	256	18.0	245	18.8
124.m88ksim	1900	126	15.1	83	22.9
126.gcc	1700	93.6	18.2	93	18.3
129.compress	1800	96.8	18.6	83	21.6
130.li	1900	145	13.1	98	19.3
132.ijpeg	2400	145	16.6	146	16.4
134.perl	1900	122	15.6	85	22.4
147.vortex	2700	175	15.4	143	18.9
SPECint_base95 (G. Mean)			16.2		
		SPECint95 (G. Mean)			19.7

Notes/Tuning Information

```
P1= -xprofile=collect:‘pwd‘/../feedback; P2= -xprofile=use:‘pwd‘/../feedback; FOPTION= -fast -xarch=v8plusa -s
Baseline: -fast -xO5 -xarch=v8plusa
Baseline: PASS1= ${P1}; PASS2= ${P2}
099.go: ${FOPTION} -xO4 -xrestrict -xcrossfile -W2,-O4+ansi_alias+bopt
099.go: PASS1= ${P1}; PASS2= ${P2} ${ALIGN} -dn
124.m88ksim: ${FOPTION} -xO5 -xsafe=mem  -xcrossfile -xrestrict -W2,-O4+cond_elim+pde,-ldstr,-Mt8500 -Wc,-Qiselect-sw_pf_tbl_th=20
124.m88ksim: PASS1= ${P1}; PASS2= ${P2} -dn
126.gcc: ${FOPTION} -xO4 -W2,-O4+ansi_alias+cond_elim
126.gcc: PASS1= ${P1}; PASS2= ${P2}
129.compress: ${FOPTION} -xO5 -xrestrict -W2,-O4+ansi_alias+pde -Wc,-Qms_pipe+unoovf
129.compress: PASS1= ${P1}; PASS2= ${P2} -dn
130.li: PASS1= -xO4 -xcrossfile ${P1}
130.li: PASS2= -xO5 -xsafe=mem -xcrossfile -W2,-O4+ansi_alias+cond_elim+pde,-Mt350,-whole,-crit ${P2} -dn
132.ijpeg: ${FOPTION} -xO5 -xsafe=mem  -W2,-O4+ansi_alias+cond_elim
132.ijpeg: PASS1= ${P1}; PASS2= ${P2} -dn
134.perl: ${FOPTION} -xO4  -xcrossfile -W2,-ANSI_S,-Mp1,-O4+cond_elim -Wc,-Qiselect-sw_pf_tbl_th=30
134.perl: EXTRA_LIBS= -lfast; PASS1= ${P1}; PASS2= ${P2} -dn
147.vortex: PASS1= -xO4 -xcrossfile ${P1}
147.vortex: PASS2= -xO5 -xsafe=mem -xcrossfile ${P2} -W2,-O4+cond_elim,-Mt500,-Mr6000,-crit -dn
Portability: 124.m88ksim, 132.ijpeg: -DSYSV -Xc, 126.gcc: -Dalloca=__builtin_alloca -Xc
others: -Xc
Shell limits: # ulimit -n 1024  or % limit descriptors 1024
Config file: ultrabest.cfg
```

For More Information Contact:
SPEC
10754 Ambassador Drive, Suite 201
Manassas, VA 20109
(703) 331-0180
info@spec.org
http://www.spec.org/

--

Prepared By: gnana