



SPEChpc™ 2021 Medium Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

Intel


SPEChpc 2021_med_base = 0.6819

SPEChpc 2021_med_peak = Not Run

Endeavour: Intel Server M50CYP2UR208 (Intel Xeon Platinum 8360Y)

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Sep-2021
Hardware Availability: Jul-2021
Software Availability: Jul-2021



Results Table

Benchmark	Base									Peak								
	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
705.lbm_m	OMP	192	6	1575	0.778	<u>1577</u>	<u>0.777</u>	1598	0.766									
718.tealeaf_m	OMP	192	6	<u>2465</u>	<u>0.548</u>	2459	0.549	2472	0.546									
719.clvleaf_m	OMP	192	6	2675	0.692	<u>2677</u>	<u>0.691</u>	2679	0.691									
728.pot3d_m	OMP	192	6	<u>3507</u>	<u>0.528</u>	3505	0.528	3519	0.526									
734.hpgmgfv_m	OMP	192	6	1719	0.582	1715	0.583	<u>1716</u>	<u>0.583</u>									
735.weather_m	OMP	192	6	2154	1.11	<u>2157</u>	<u>1.11</u>	2159	1.11									

SPEChpc 2021_med_base = **0.6819**

SPEChpc 2021_med_peak = **Not Run**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.



SPEChpc™ 2021 Medium Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

Intel

SPEChpc 2021_med_base = 0.6819

SPEChpc 2021_med_peak = Not Run

Endeavour: Intel Server M50CYP2UR208 (Intel Xeon Platinum 8360Y)

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Sep-2021
Hardware Availability: Jul-2021
Software Availability: Jul-2021

Hardware Summary

Type of System: Homogenous Cluster
Compute Node: Intel Server M50CYP2UR208 (Xeon 8360Y)
Interconnect: Mellanox HDR
File Server Node: LustreFS
Compute Nodes Used: 16
Total Chips: 32
Total Cores: 1152
Total Threads: 2304
Total Memory: 4 TB
Max. Peak Threads: --

Software Summary

Compiler: Intel oneAPI Compiler 2021.3.0
MPI Library: Intel MPI Library for Linux* OS, Version 2021.2 Build 20210302
Other MPI Info: None
Other Software: None
Base Parallel Model: OMP
Base Ranks Run: 192
Base Threads Run: 6
Peak Parallel Models: Not Run
Minimum Peak Ranks: --
Maximum Peak Ranks: --
Max. Peak Threads: --
Min. Peak Threads: --

Node Description: Intel Server M50CYP2UR208 (Xeon 8360Y)

Hardware

Number of nodes: 16
Uses of the node: Compute
Vendor: Intel
Model: Intel Server M50CYP2UR208 (Xeon 8360Y)
CPU Name: Intel Xeon Platinum 8360Y
CPU(s) orderable: 1, 2 chips
Chips enabled: 2
Cores enabled: 72
Cores per chip: 36
Threads per core: 2
CPU Characteristics: Turbo Boost Technology up to 3.5 GHz
CPU MHz: 2400
Primary Cache: 32 KB I + 48 KB D on chip per core
Secondary Cache: 1536 KB I+D on chip per core
L3 Cache: 54 MB I+D on chip per chip
Other Cache: None
Memory: 256 GB (16 x 16 GB 2Rx8 PC4-3200R)
Disk Subsystem: 1 x 960 GB SATA 2.5" SSD
Other Hardware: None
Accel Count: None
Accel Model: --
Accel Vendor: None
Accel Type: None
Accel Connection: None
Accel ECC enabled: None
Accel Description: None
Adapter: Mellanox ConnectX-6 HDR
Number of Adapters: 1
Slot Type: PCI-Express 4.0 x16
Data Rate: 200Gbit/s
Ports Used: 1

Software

Accelerator Driver: --
Adapter: Mellanox ConnectX-6 HDR
Adapter Driver: 5.1-2.5.8.0
Adapter Firmware: 20.29.2002
Operating System: CentOS Linux release 8.4.2105
4.18.0-240.22.1.el8_3.crt2.x86_64
Local File System: NFS
Shared File System: Lustre FS
System State: Multi-user
Other Software: --

(Continued on next page)



SPEChpc™ 2021 Medium Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

Intel

SPEChpc 2021_med_base = 0.6819

SPEChpc 2021_med_peak = Not Run

Endeavour: Intel Server M50CYP2UR208 (Intel Xeon Platinum 8360Y)

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Sep-2021
Hardware Availability: Jul-2021
Software Availability: Jul-2021

Node Description: Intel Server M50CYP2UR208 (Xeon 8360Y)

Hardware (Continued)

Interconnect Type: Mellanox HDR

Node Description: LustreFS

Hardware

Number of nodes: 1
Uses of the node: Fileserver
Vendor: Intel
Model: Inspur NF5280M5
CPU Name: Intel Xeon Gold 6244
CPU(s) orderable: 1-2 chips
Chips enabled: 2
Cores enabled: 16
Cores per chip: 8
Threads per core: 2
CPU Characteristics: Intel Xeon Gold
CPU MHz: 3600
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 512 KB I+D on chip per core
L3 Cache: 25344 KB I+D on chip per chip
Other Cache: None
Memory: 192 GB (12 x 16 GB 2Rx8 PC4-2666R)
Disk Subsystem: 1 x 1 TB 12 Gbps SAS 2.5" SSD
Other Hardware: None
Accel Count: --
Accel Model: --
Accel Vendor: --
Accel Type: --
Accel Connection: --
Accel ECC enabled: --
Accel Description: --
Adapter: Mellanox ConnectX-4 EDR
Number of Adapters: 1
Slot Type: PCI-Express 4.0 x16
Data Rate: 100 Gb/s
Ports Used: 2
Interconnect Type: Mellanox EDR

Software

Accelerator Driver: --
Adapter: Mellanox ConnectX-4 EDR
Adapter Driver: 5.1-2.5.8.0
Adapter Firmware: 20.29.2002
Operating System: CentOS Linux release 7.8.2003
4.18.0-240.22.1.el8_3.crt2.x86_64
Local File System: None
Shared File System: Lustre FS
System State: Multi-User
Other Software: None



SPEChpc™ 2021 Medium Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

Intel

SPEChpc 2021_med_base = 0.6819

SPEChpc 2021_med_peak = Not Run

Endeavour: Intel Server M50CYP2UR208 (Intel Xeon Platinum 8360Y)

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Sep-2021
Hardware Availability: Jul-2021
Software Availability: Jul-2021

Interconnect Description: Mellanox HDR

Hardware

Software

Vendor: Mellanox
Model: Mellanox HDR
Switch Model: Mellanox MQM8790-HS2F Quantum HDR InfiniBand Switch
Number of Switches: 18
Number of Ports: 40
Data Rate: 200 Gbit/s
Firmware: 20.29.2002
Topology: Fat-tree
Primary Use: MPI Traffic

: --

Submit Notes

The config file option 'submit' was used.

Compiler Version Notes

```
=====  
CC 705.lbm_m(base) 718.tealeaf_m(base) 734.hpgmgfv_m(base)  
-----
```

```
Intel(R) oneAPI DPC++/C++ Compiler 2021.3.0 (2021.3.0.20210619)  
Target: x86_64-unknown-linux-gnu  
Thread model: posix  
InstalledDir:  
  /global/panfs01/admin/opt/intel/oneAPI/2021.3.0.3219/compiler/2021.3.0/linux/bin  
-----
```

```
=====  
FC 719.clvleaf_m(base) 728.pot3d_m(base) 735.weather_m(base)  
-----
```

```
ifx (IFORT) 2021.3.0 Beta 20210619  
Copyright (C) 1985-2021 Intel Corporation. All rights reserved.  
-----
```

Base Compiler Invocation

C benchmarks:

```
mpicc -cc=icx -lstdc++(*)
```

Fortran benchmarks:

```
mpiifort -fc=ifx -lstdc++(*)
```

(Continued on next page)



SPEChpc™ 2021 Medium Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

Intel

SPEChpc 2021_med_base = 0.6819

SPEChpc 2021_med_peak = Not Run

Endeavour: Intel Server M50CYP2UR208 (Intel Xeon Platinum 8360Y)

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Sep-2021
Hardware Availability: Jul-2021
Software Availability: Jul-2021

Base Compiler Invocation (Continued)

(*) Indicates a compiler flag that was found in a non-compiler variable.

Base Optimization Flags

C benchmarks:

```
-Ofast -ipo -xCORE-AVX512 -mprefer-vector-width=512 -fiopenmp  
-ansi-alias
```

Fortran benchmarks:

```
-Ofast -ipo -xCORE-AVX512 -mprefer-vector-width=512 -fiopenmp  
-nostandard-realloc-lhs -align array64byte
```

The flags file that was used to format this result can be browsed at

<http://www.spec.org/hpc2021/flags/Intel-oneAPI-icx2021-official-linux64.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/hpc2021/flags/Intel-oneAPI-icx2021-official-linux64.xml>

SPEChpc is a trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEChpc2021 v1.0.2 on 2021-09-18 21:04:47-0400.
Report generated on 2023-08-25 18:59:12 by hpc2021 PDF formatter v1.0.3.
Originally published on 2021-10-20.