



SPEChpc™ 2021 Tiny Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

xFusion


SPEChpc 2021_tny_base = 15.0

xFusion FusionServer 2288H V7 (Intel Xeon Platinum 8490H)

SPEChpc 2021_tny_peak = Not Run

hpc2021 License: 6488
Test Sponsor: xFusion
Tested by: xFusion

Test Date: Apr-2023
Hardware Availability: Jan-2023
Software Availability: Nov-2022



Results Table

Benchmark	Base								Peak									
	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
505.lbm_t	MPI	360	1	<u>94.3</u>	<u>23.9</u>	89.2	25.2											
513.soma_t	MPI	360	1	<u>170</u>	<u>21.7</u>	170	21.7											
518.tealeaf_t	MPI	360	1	<u>93.3</u>	<u>17.7</u>	93.1	17.7											
519.clvleaf_t	MPI	360	1	<u>111</u>	<u>14.9</u>	111	14.9											
521.miniswp_t	MPI	360	1	123	13.0	<u>124</u>	<u>12.9</u>											
528.pot3d_t	MPI	360	1	<u>386</u>	<u>5.51</u>	366	5.81											
532.sph_exa_t	MPI	360	1	<u>59.1</u>	<u>33.0</u>	59.1	33.0											
534.hpgmgfv_t	MPI	360	1	<u>1042</u>	<u>1.13</u>	1041	1.13											
535.weather_t	MPI	360	1	<u>30.8</u>	<u>105</u>	29.0	111											

SPEChpc 2021_tny_base = 15.0

SPEChpc 2021_tny_peak = Not Run

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.



SPEChpc™ 2021 Tiny Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

xFusion

SPEChpc 2021_tny_base = 15.0

xFusion FusionServer 2288H V7 (Intel Xeon Platinum 8490H)

SPEChpc 2021_tny_peak = Not Run

hpc2021 License: 6488
Test Sponsor: xFusion
Tested by: xFusion

Test Date: Apr-2023
Hardware Availability: Jan-2023
Software Availability: Nov-2022

Hardware Summary

Type of System: Homogenous Cluster
Compute Node: xFusion FusionServer 2288H V7
Interconnect: Mellanox HDR
Node Node: xFusion FusionServer 2288H V7
Compute Nodes Used: 3
Total Chips: 6
Total Cores: 360
Total Threads: 360
Total Memory: 1536 GB
Max. Peak Threads: --

Software Summary

Compiler: C/C++/Fortran: Version 2022.2.1 of Intel oneAPI Compiler
MPI Library: Intel MPI Library for Linux* OS, Version 2022.2.1 Build 20221020
Other MPI Info: N/A
Other Software: N/A
Base Parallel Model: MPI
Base Ranks Run: 360
Base Threads Run: 1
Peak Parallel Models: Not Run
Minimum Peak Ranks: --
Maximum Peak Ranks: --
Max. Peak Threads: --
Min. Peak Threads: --

Node Description: xFusion FusionServer 2288H V7

Hardware

Number of nodes: 3
Uses of the node: Compute Node
Vendor: xFusion
Model: xFusion FusionServer 2288H V7
CPU Name: Intel Xeon Platinum 8490H
CPU(s) orderable: 2 chips
Chips enabled: 2
Cores enabled: 120
Cores per chip: 60
Threads per core: 1
CPU Characteristics: Turbo Boost Technology up to 3.5 GHz
CPU MHz: 1900
Primary Cache: 32 KB I + 48 KB D on chip per core
Secondary Cache: 2 MB I+D on chip per core
L3 Cache: 112.5 MB I+D on chip per chip
Other Cache: None
Memory: 512 GB (16 x 32 GB 2Rx4 PC5-4800B-R)
Disk Subsystem: 1 x 7.68 TB NVMe SSD
Other Hardware: None
Accel Count: N/A
Accel Model: N/A
Accel Vendor: N/A
Accel Type: N/A
Accel Connection: N/A
Accel ECC enabled: N/A
Accel Description: N/A
Adapter: MCX653105A-EFAT
Number of Adapters: 1
Slot Type: PCI-Express 4.0 x16
Data Rate: 100 Gb/s

Software

Accelerator Driver: N/A
Adapter: MCX653105A-EFAT
Adapter Driver: 5.4-3.1.0
Adapter Firmware: 20.32.1010
Operating System: CentOS Linux release 8.2.2004 4.18.0-193.el8.x86_644
Local File System: xfs
Shared File System: NFS
System State: Multi-user, run level 3
Other Software: N/A

(Continued on next page)



SPEChpc™ 2021 Tiny Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

xFusion

SPEChpc 2021_tny_base = 15.0

xFusion FusionServer 2288H V7 (Intel Xeon Platinum 8490H)

SPEChpc 2021_tny_peak = Not Run

hpc2021 License: 6488
Test Sponsor: xFusion
Tested by: xFusion

Test Date: Apr-2023
Hardware Availability: Jan-2023
Software Availability: Nov-2022

Node Description: xFusion FusionServer 2288H V7

Hardware (Continued)

Ports Used: 1
Interconnect Type: Mellanox HDR

Interconnect Description: Mellanox HDR

Hardware

Vendor: Mellanox
Model: Mellanox HDR
Switch Model: Mellanox MQM8790-HS2F
InfiniBand Switch
Number of Switches: 1
Number of Ports: 40
Data Rate: 200 Gbit/s
Firmware: 27.2010.1202
Topology: Mesh
Primary Use: MPI

Software

: --

Submit Notes

The config file option 'submit' was used.
export LD_PRELOAD="/usr/lib64/libhugetlbfs.so \$LD_PRELOAD"
export OMP_PROC_BIND=true
mpirun.hydra -bootstrap ssh --bind-to core -hostfile \${top}/\${hostfile} -np \$ranks -ppn \$ppn -genv OMP_NUM_THREADS=\$threads \$command

Compiler Version Notes

=====
CC 505.lbm_t(base) 513.soma_t(base) 518.tealeaf_t(base) 521.miniswp_t(base)
534.hpgmgfv_t(base)

Intel(R) oneAPI DPC++/C++ Compiler 2022.1.0 (2022.1.0.20220316)
Target: x86_64-unknown-linux-gnu
Thread model: posix
InstalledDir: /nfsshare/opt/intel/2022.2.0/compiler/latest/linux/bin-llvm

=====
CXXC 532.sph_exa_t(base)

Intel(R) oneAPI DPC++/C++ Compiler 2022.1.0 (2022.1.0.20220316)
Target: x86_64-unknown-linux-gnu
Thread model: posix

(Continued on next page)



SPEChpc™ 2021 Tiny Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

xFusion

SPEChpc 2021_tny_base = 15.0

xFusion FusionServer 2288H V7 (Intel Xeon Platinum 8490H)

SPEChpc 2021_tny_peak = Not Run

hpc2021 License: 6488
Test Sponsor: xFusion
Tested by: xFusion

Test Date: Apr-2023
Hardware Availability: Jan-2023
Software Availability: Nov-2022

Compiler Version Notes (Continued)

InstalledDir: /nfsshare/opt/intel/2022.2.0/compiler/latest/linux/bin-llvm

=====
FC 519.clvleaf_t(base) 535.weather_t(base)
=====

ifx (IFORT) 2022.1.0 20220316
Copyright (C) 1985-2022 Intel Corporation. All rights reserved.
=====

=====
FC 528.pot3d_t(base)
=====

ifx: command line warning #10157: ignoring option '-W'; argument is of wrong
type
ifx (IFORT) 2022.1.0 20220316
Copyright (C) 1985-2022 Intel Corporation. All rights reserved.
=====

Base Compiler Invocation

C benchmarks:
mpiicc -cc=icx

C++ benchmarks:
mpiicpc -cxx=icpx

Fortran benchmarks:
mpiifort -fc=ifx

Base Portability Flags

505.lbm_t: -lstdc++
513.soma_t: -lstdc++ -DSPEC_NO_VAR_ARRAY_REDUCE
518.tealeaf_t: -lstdc++
519.clvleaf_t: -lstdc++
521.miniswp_t: -lstdc++
528.pot3d_t: -lstdc++
532.sph_exa_t: -lstdc++
534.hpgmgfv_t: -lstdc++
535.weather_t: -lstdc++



SPEChpc™ 2021 Tiny Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

xFusion

SPEChpc 2021_tny_base = 15.0

xFusion FusionServer 2288H V7 (Intel Xeon Platinum 8490H)

SPEChpc 2021_tny_peak = Not Run

hpc2021 License: 6488
Test Sponsor: xFusion
Tested by: xFusion

Test Date: Apr-2023
Hardware Availability: Jan-2023
Software Availability: Nov-2022

Base Optimization Flags

C benchmarks:

-Ofast -ipo -xCORE-AVX512 -mprefer-vector-width=512 -ansi-alias

C++ benchmarks:

-Ofast -ipo -xCORE-AVX512 -mprefer-vector-width=512 -ansi-alias

Fortran benchmarks:

-Ofast -ipo -xCORE-AVX512 -mprefer-vector-width=512
-nostandard-realloc-lhs -align array64byte

Base Other Flags

C benchmarks (except as noted below):

-Ispecmpitime

521.miniswp_t: -Ispecmpitime/

534.hpgmgfv_t: -Ispecmpitime

C++ benchmarks:

-Ispecmpitime

Fortran benchmarks:

519.clvleaf_t: -Ispecmpitime

528.pot3d_t: -Wno-incompatible-function-pointer-types

535.weather_t: No flags used

The flags file that was used to format this result can be browsed at

http://www.spec.org/hpc2021/flags/Intel_compiler_flags.2023-02-09.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/hpc2021/flags/Intel_compiler_flags.2023-02-09.xml

SPEChpc is a trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEChpc2021 v1.1.7 on 2023-04-12 07:03:01-0400.

Report generated on 2023-05-11 20:27:44 by hpc2021 PDF formatter v1.0.3.

Originally published on 2023-05-10.