



SPEC® OMPG2012 Result

Copyright 2012-2017 Standard Performance Evaluation Corporation

Supermicro
(Test Sponsor: HZDR)


SPECompG_peak2012 = Not Run

Supermicro H8QGi+-F

SPECompG_base2012 = 3.14

OMP2012 license:65A
Test sponsor: HZDR
Tested by: HZDR

Test date: Jul-2017
Hardware Availability: Nov-2011
Software Availability: Sep-2016



Hardware

CPU Name: AMD Opteron 6276
 CPU Characteristics: AMD Turbo CORE technology up to 3.20 GHz
 CPU MHz: 2300
 CPU MHz Maximum: 3200
 FPU: Integrated
 CPU(s) enabled: 64 cores, 4 chips, 16 cores/chip
 CPU(s) orderable: 2,4 chips
 Primary Cache: 512 KB I on chip per chip,
 64 KB I shared / 2 cores;
 16 KB D on chip per core
 Secondary Cache: 16 MB I+D on chip per chip, 2 MB shared / 2 cores
 L3 Cache: 16 MB I+D on chip per chip, 8 MB shared / 8 cores
 Other Cache: None
 Memory: 256 GB (32 x 8 GB 2Rx4 PC3-10600R-9, ECC)
 Disk Subsystem: 500 GB (1 x 500 GB SATA 7200rpm)
 Other Hardware: --

Continued on next page

Software

Operating System: Ubuntu 14.04 LTS
 Kernel 4.4.0-38-generic
 Compiler: C/C++/Fortran: Version 6.2 of the GNU Compilers
 Auto Parallel: No
 File System: ext3
 System State: run-level 5
 Base Pointers: 64-bit
 Peak Pointers: Not Applicable
 Other Software: None



SPEC OMPG2012 Result

Copyright 2012-2017 Standard Performance Evaluation Corporation

Supermicro
(Test Sponsor: HZDR)

SPECompG_peak2012 = Not Run

Supermicro H8QGi+-F

SPECompG_base2012 = 3.14

OMP2012 license:65A
Test sponsor: HZDR
Tested by: HZDR

Test date: Jul-2017
Hardware Availability: Nov-2011
Software Availability: Sep-2016

Base Threads Run: 64
Minimum Peak Threads: --
Maximum Peak Threads: --

Results Table

| Benchmark | Base | | | | | | Peak | | | | | | | |
|--------------|---------|--------------|--------------|-------------|-------------|-------------|--------------|---------|---------|-------|---------|-------|---------|-------|
| | Threads | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Threads | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 350.md | 64 | 3368 | 1.37 | 3369 | 1.37 | 3367 | 1.38 | | | | | | | |
| 351.bwaves | 64 | 4756 | 0.953 | 4737 | 0.956 | 4749 | 0.954 | | | | | | | |
| 352.nab | 64 | 903 | 4.31 | 905 | 4.30 | 892 | 4.36 | | | | | | | |
| 357.bt331 | 64 | 785 | 6.04 | 780 | 6.08 | 740 | 6.40 | | | | | | | |
| 358.botsalgn | 64 | 619 | 7.03 | 616 | 7.06 | 613 | 7.09 | | | | | | | |
| 359.botsspar | 64 | 1167 | 4.50 | 1168 | 4.50 | 1180 | 4.45 | | | | | | | |
| 360.ilbdc | 64 | 31036 | 0.115 | 27818 | 0.128 | 33016 | 0.108 | | | | | | | |
| 362.fma3d | 64 | 1235 | 3.08 | 1225 | 3.10 | 1250 | 3.04 | | | | | | | |
| 363.swim | 64 | 1248 | 3.63 | 1269 | 3.57 | 1228 | 3.69 | | | | | | | |
| 367.imagick | 64 | 1124 | 6.26 | 1127 | 6.24 | 1126 | 6.24 | | | | | | | |
| 370.mgrid331 | 64 | 2045 | 2.16 | 1893 | 2.33 | 1773 | 2.49 | | | | | | | |
| 371.applu331 | 64 | 1278 | 4.74 | 1225 | 4.95 | 1497 | 4.05 | | | | | | | |
| 372.smithwa | 64 | 536 | 9.99 | 546 | 9.82 | 549 | 9.75 | | | | | | | |
| 376.kdtree | 64 | 479 | 9.40 | 474 | 9.49 | 479 | 9.39 | | | | | | | |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Platform Notes

Sysinfo program /tmp/spec/1.1/Docs/sysinfo
Revision 563 of 2016-06-10 (097295389cf6073d8c3b03fa376740a5)
running on laser084 Wed Jul 5 09:44:24 2017

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:
<http://www.spec.org/omp2012/Docs/config.html#sysinfo>

```

From /proc/cpuinfo
model name : AMD Opteron(TM) Processor 6276
 4 "physical id"s (chips)
 64 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The
following excerpts from /proc/cpuinfo might not be reliable. Use with
caution.)
cpu cores : 8
siblings : 16
physical 0: cores 0 1 2 3 4 5 6 7
physical 1: cores 0 1 2 3 4 5 6 7
physical 2: cores 0 1 2 3 4 5 6 7
physical 3: cores 0 1 2 3 4 5 6 7

```

Continued on next page



SPEC OMPG2012 Result

Copyright 2012-2017 Standard Performance Evaluation Corporation

Supermicro

(Test Sponsor: HZDR)

SPECompG_peak2012 = Not Run

Supermicro H8QGi+-F

SPECompG_base2012 = 3.14

OMP2012 license:65A

Test sponsor: HZDR

Tested by: HZDR

Test date: Jul-2017

Hardware Availability: Nov-2011

Software Availability: Sep-2016

Platform Notes (Continued)

cache size : 2048 KB

From /proc/meminfo

MemTotal: 264017344 kB

HugePages_Total: 0

Hugepagesize: 2048 kB

/usr/bin/lsb_release -d

Ubuntu 14.04.5 LTS

From /etc/*release* /etc/*version*

debian_version: jessie/sid

os-release:

NAME="Ubuntu"

VERSION="14.04.5 LTS, Trusty Tahr"

ID=ubuntu

ID_LIKE=debian

PRETTY_NAME="Ubuntu 14.04.5 LTS"

VERSION_ID="14.04"

HOME_URL="http://www.ubuntu.com/"

SUPPORT_URL="http://help.ubuntu.com/"

rh-release: Red Hat Enterprise Linux Server release 7.2 (Maipo)

uname -a:

Linux laser084 4.4.0-38-generic #57~14.04.1-Ubuntu SMP Tue Sep 6 17:20:43 UTC

2016 x86_64 x86_64 x86_64 GNU/Linux

run-level 5 Jul 5 09:38

SPEC is set to: /tmp/spec/1.1

Filesystem Type Size Used Avail Use% Mounted on

/dev/sdal ext3 37G 8.0G 27G 23% /

Cannot run dmidecode; consider saying 'chmod +s /usr/sbin/dmidecode'

(End of data from sysinfo program)

General Notes

Environment:

ENV_OMP_DYNAMIC=FALSE

ENV_OMP_NESTED=FALSE

Base Compiler Invocation

C benchmarks:

gcc

Continued on next page

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org/

Page 3



SPEC OMPG2012 Result

Copyright 2012-2017 Standard Performance Evaluation Corporation

Supermicro
(Test Sponsor: HZDR)

SPECompG_peak2012 = Not Run

Supermicro H8QGi+-F

SPECompG_base2012 = 3.14

OMP2012 license:65A
Test sponsor: HZDR
Tested by: HZDR

Test date: Jul-2017
Hardware Availability: Nov-2011
Software Availability: Sep-2016

Base Compiler Invocation (Continued)

C++ benchmarks:
g++

Fortran benchmarks:
gfortran

Base Portability Flags

350.md: -ffree-form -fno-range-check

Base Optimization Flags

C benchmarks:
-fopenmp -O3

C++ benchmarks:
-fopenmp -O3

Fortran benchmarks:
-fopenmp -O3

The flags file that was used to format this result can be browsed at
http://www.spec.org/omp2012/flags/gcc62_linux_flags.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/omp2012/flags/gcc62_linux_flags.xml

SPEC is a registered trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC OMP2012 v1.1.
Report generated on Wed Sep 6 18:01:44 2017 by SPEC OMP2012 PS/PDF formatter v541.
Originally published on 6 September 2017.