

SPECweb99_SSL Result

```

=====
IBM : eServer xSeries 335          ||
Zeus Technology Limited : Zeus V4.1R1 ||      CD SPECweb99_SSL
                                     ||
=====

```

SPEC has discovered a code defect in the SPECweb99_SSL test harness run on the client systems used in this result. The bug prevents these client systems from generating the correct SPECweb99_SSL workload. Specifically, the bug in the SPECweb99_SSL code results in the clients not generating any of the required SSL ClientKeyExchanges during the benchmark. Therefore, the results presented here are not comparable with any other SPECweb99_SSL results.

PERFORMANCE

Iteration	Conforming Simultaneous Connections
1	CD
2	CD
3	CD
Median	CD

Availability Dates

```

All Hardware          Sep-2002
HTTPS Software        Mar-2002
Operating System      Jul-2002
Supplemental System   May-2002

```

Hardware

```

Vendor                IBM
Model                 eServer xSeries 335
Processor              2.4 GHz Intel Xeon Processor
# Processors           2 cores, 2 chips, 1 core/chip
Primary Cache          12KBI+8KBD on chip
Secondary Cache        512KB
Other Cache            None
Memory                 4 GB
Disk Subsystem         2 x 36GB 15KRPM Ultra 320 SCSI Drives
Disk Controllers       1 LSI 1020 Ultra 320 SCSI LOM
Other Hardware         1 Extreme Networks Summit 7i Gb Switch

```

Software

```

Operating System      Red Hat 7.3 Linux
File System            ext2
Other Software         None

```

HTTPS Software

```

Vendor                Zeus Technology Limited
HTTPS Software        Zeus V4.1R1
API                   Zeus PEPP 0.6 ISAPI used for Dynamic content
Server Cache          None
Log Mode               Zeus Binary CLF

```

Test Sponsor

```

Test Date             Aug-2002
Tested By             IBM
SPEC License          11

```

Network

```

# of Controllers      1
Network Controllers   Broadcom NetXtreme GB
# of Nets              1
Type of Nets          Gigabit Ethernet
Network Speed          1 Gb/s
MSL (sec)              30 (Non RFC1122)
Time-Wait (sec)        60 (Non RFC1122)
MTU                    1500

```

Clients

```

# of Clients          5
Model                 IBM eServer xSeries 330
Processor              933Mhz Pentium III
# of Processors        1
Memory                 256MB
Network Controller     IBM Netfinity Gigabit Ethernet Adapter
Operating System       Microsoft Windows 2000 Professional w/SP2
Compiler               Microsoft VC++ v6.0

```

Benchmark Configuration

Requested Connections 870
Fileset Size (MB) 2903.6

=====
Notes/Tuning information

SUT Notes

2 disk software RAID0, using 64KB chunk size, for OS, webpages, and logs

Operating System Notes

Tuning parameters:

- net.ipv4.ip_forward=1, default 0
 - net.ipv4.conf.all.rp_filter = 1, enables source route verification, default 0
 - net.ipv4.tcp_timestamps = 0, turns TCP timestamp support off, default 1
 - net.ipv4.tcp_max_tw_buckets = 2000000, sets TCP time-wait buckets pool size, default 180000
 - net.core.rmem_max = 10000000, maximum receive socket buffer size, default 65535
 - net.core.rmem_default = 10000000, default receive socket buffer size, default 65535
 - net.core.wmem_max = 10000000, maximum send socket buffer size, default 65535
 - net.core.wmem_default = 10000000, default send socket buffer size, default 65535
 - net.core.optmem_max = 10000000, default 10240
 - net.core.hot_list_length = 10000, maximum number of skb-heads to be cached, default 128
 - net.ipv4.tcp_rmem = 30000000 30000000 30000000, maximum TCP read-buffer space allocatable, default 4096 87380 174760
 - net.ipv4.tcp_wmem = 30000000 30000000 30000000, maximum TCP write-buffer space allocatable, default 4096 16384 131072
 - net.ipv4.tcp_mem=30000000 30000000 30000000, maximum TCP buffer space, default 31744 32256 32768
 - fs.file-max = 81920, maximum number of open files, default 1024
- Kernel is standard default Red Hat Linux (2.4.18-3bigmem)

HTTPS Software Notes

Zeus Configuration

- tuning!bind_any yes
- tuning!cache_files 8192
- tuning!cache_flush_interval 31536000
- tuning!cache_large_file 1048576
- tuning!cache_max_bytes 0
- tuning!cache_small_file 4096
- tuning!cache_stat_expire 31536000
- tuning!num_children 16
- tuning!so_wbuff_size 1048576
- tuning!softservers no
- tuning!unique_bind no
- tuning!use_poll yes
- tuning!cache_cooling_time 0
- tuning!cbuff_size 65536
- tuning!ssl_sessioncache_size 5011
- tuning!ssl_sessioncache_expiry 120
- tuning!ssl_keepalive yes
- tuning!ssl_diskcache yes
- tuning!keepalive yes
- tuning!sendfile yes
- tuning!sendfile_minsize 1
- tuning!sendfile_maxsize 2147483647
- tuning!listen_queue_size 8192
- tuning!so_rbuff_size 0
- tuning!modules!cgi!cleansize 0

See Zeus-tuning.txt for a description of the Zeus tuning parameters

ISAPI Source code is available in the SPECweb99 support docs as IBM-20011019_1-API.tar.gz

=====
Test Run Details

Run Num	Conforming Connections	Percent Conform	Throughput ops/sec	Response msec	ops/sec/ loadgen	Kbits/sec
=> 1	CD	CD	CD	CD	CD	CD
2	CD	CD	CD	CD	CD	CD
3	CD	CD	CD	CD	CD	CD