



SPEC CPU®2017 Floating Point Speed Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL325 Gen11

(3.10 GHz, AMD EPYC 9554P)

SPECspeed®2017_base =

SPECspeed®2017_fp_peak =

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Dec-2022

Hardware Availability: Dec-2022

Software Availability: Nov-2022

SPEC has determined that this result does not comply with the SPEC CPU 2017 run and reporting rules. Specifically, the test sponsor notified SPEC that the results were measured on an unsupported configuration.

Threads

603.bwaves_s

607.cactuBSSN_s

619.lbm_s

621.wrf_s

627.cam4_s

628.pop2_s

638.imagick_s

644.nab_s

649.fotonik3d_s

654.roms_s

Hardware

CPU Name: AMD EPYC 9554P

Nominal: 3100

Enabled: 64 cores, 1 chip

Orderable: 1 chip

Cache L1: 32 KB I + 32 KB D on chip per core

L2: 1 MB I+D on chip per core

L3: 256 MB I+D on chip per chip,

32 MB shared / 8 cores

Other: None

Memory: 768 GB (12 x 64 GB 2Rx4 PC5-4800B-R)

Storage: 1 x 480 GB SATA SSD

Other: None

Software

OS:

Red Hat Enterprise Linux 9.0 (Plow)

Kernel 5.14.0-70.13.1.el9_0.x86_64

Compiler:

C/C++/Fortran: Version 4.0.0 of AOCC

Parallel:

Yes

Firmware:

HPE BIOS Version v1.12 11/24/2022 released

Nov-2022

File System:

xfs

System State:

Run level 3 (multi-user)

Base Pointers:

64-bit

Peak Pointers:

64-bit

Other:

None

Power Management: BIOS and OS set to prefer performance at the cost of additional power usage



SPEC CPU®2017 Floating Point Speed Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL325 Gen11

(3.10 GHz, AMD EPYC 9554P)

SPECspeed®2017_fp_base =

SPECspeed®2017_fp_peak =

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Dec-2022

Hardware Availability: Dec-2022

Software Availability: Nov-2022

SPEC has determined that this result does not comply with the SPEC CPU 2017 run and reporting rules. Specifically, the test sponsor notified SPEC that the results were measured on an unsupported configuration.

Results Table

Benchmark	Base								Peak							
	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio		
603.bwaves_s	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC		
607.cactuBSSN_s	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC		
619.lbm_s	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC		
621.wrf_s	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC		
627.cam4_s	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC		
628.pop2_s	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC		
638.imagick_s	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC		
644.nab_s	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC		
649.fotonik3d_s	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC		
654.roms_s	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC		

SPECspeed®2017_fp_base =

SPECspeed®2017_fp_peak =

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Notes

The AMD64 AOCC Compiler Suite is available at <http://developer.amd.com/amd-aocc/>

Submit Notes

The config file option 'submit' was used.
The option 'submit' was used to bind copies to the cores.
See the configuration file for details.

Operating System Notes

'ulimit -s unlimited' was used to set environment stack size limit
'ulimit -l 2097152' was used to set environment locked pages in memory limit

runcpu command invoked through numactl i.e.:
numactl --interleave=all runcpu <etc>

To limit dirty cache to 8% of memory, 'sysctl -w vm.dirty_ratio=8' run as root.
To limit swap usage to minimum necessary, 'sysctl -w vm.swappiness=1' run as root.
To free node-local memory and avoid remote memory usage,
'sysctl -w vm.zone_reclaim_mode=1' run as root.
To clear filesystem caches, 'sync; sysctl -w vm.drop_caches=3' run as root.

(Continued on next page)



SPEC CPU® 2017 Floating Point Speed Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL325 Gen11

(3.10 GHz, AMD EPYC 9554P)

SPECspeed® 2017 / fp base =

SPECspeed® 2017 / fp peak =

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Dec-2022

Hardware Availability: Dec-2022

Software Availability: Nov-2022

SPEC has determined that this result does not comply with the SPEC CPU 2017 run and reporting rules. Specifically, the test sponsor notified SPEC that the results were measured on an unsupported configuration.

Operating System Notes (Continued)

To disable address space layout randomization (ASLR) to reduce run-to-run variability, 'sysctl -w kernel.randomize_va_space=0' run as root.

To enable Transparent Hugepages (THP) for all allocations, and 'echo always > /sys/kernel/mm/transparent_hugepage/enabled' and 'echo always > /sys/kernel/mm/transparent_hugepage/defrag' run as root.

To always enable THP for peak runs of:

603.bwaves_s, 607.cactuBSSN_s, 619.lbm_s, 627.cam4_s, 638.pop2_s, 638.imagick_s, 644.nab_s, 649.fotonik3d_s:

'echo madvise > /sys/kernel/mm/transparent_hugepage/enabled; echo always > /sys/kernel/mm/transparent_hugepage/defrag' run as root.

To disable THP for peak runs of 641.wrf_s:

'echo never > /sys/kernel/mm/transparent_hugepage/enabled; echo always > /sys/kernel/mm/transparent_hugepage/defrag' run as root.

To enable THP only on request for peak runs of 654.roms_s:

'echo madvise > /sys/kernel/mm/transparent_hugepage/enabled; echo madvise > /sys/kernel/mm/transparent_hugepage/defrag' run as root.

Environment Variables Notes

Environment variables set by runcpu before the start of the run:

```
GOMP_CPU_AFFINITY = "0-63"
LD_LIBRARY_PATH = "/hpc/cpu2017/compd_speed_aocc400_genoa_B_lib/lib:"
LIBOMP_NUM_HIDDEN_HELPERS_THREADS = "0"
MALLOC_CONF = "oversize_threshold:0,retain:true"
OMP_DYNAMIC = "false"
OMP_SCHEDULE = "static"
OMP_STACKSIZE = "128M"
OMP_THREAD_LIMIT = "64"
```

Environment variables set by runcpu during the 621.wrf_s peak run:

```
GOMP_CPU_AFFINITY = "0-63"
```

Environment variables set by runcpu during the 628.pop2_s peak run:

```
GOMP_CPU_AFFINITY = "0-63"
```

Environment variables set by runcpu during the 649.fotonik3d_s peak run:

```
GOMP_CPU_AFFINITY = "0-63"
PGHPF_ZME = "yes"
```

Environment variables set by runcpu during the 654.roms_s peak run:

```
GOMP_CPU_AFFINITY = "0 32 1 33 2 34 3 35 4 36 5 37 6 38 7 39 8 40 9 41 10 42 11 43 12 44 13 45 14 46 15 47
16 48 17 49 18 50 19 51 20 52 21 53 22 54 23 55 24 56 25 57 26 58 27 59 28 60 29 61 30 62 31 63"
```

General Notes

Binaries were compiled on a system with 2x AMD EPYC 9174F CPU + 1.5TiB Memory using RHEL 8.6

(Continued on next page)



SPEC CPU®2017 Floating Point Speed Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL325 Gen11

(3.10 GHz, AMD EPYC 9554P)

SPECspeed®2017_base =

SPECspeed®2017_fp_peak =

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Dec-2022

Hardware Availability: Dec-2022

Software Availability: Nov-2022

SPEC has determined that this result does not comply with the SPEC CPU 2017 rules and reporting rules. Specifically, the test sponsor notified SPEC that the results were measured on an unsupported configuration.

General Notes (Continued)

NA: The test sponsor attests, as of date of publication, that CVE-2017-5754 (Meltdown) is mitigated in the system as tested and documented.

Yes: The test sponsor attests, as of date of publication, that CVE-2017-5753 (Spectre variant 1) is mitigated in the system as tested and documented.

Yes: The test sponsor attests, as of date of publication, that CVE-2017-5715 (Spectre variant 2) is mitigated in the system as tested and documented.

Platform Notes

BIOS Configuration

Workload Profile set to General Peak Frequency Compute
 Determinism Control set to Manual
 Performance Determinism set to Power Deterministic
 AMD SMT Option set to Disabled
 Last-Level Cache (LLC) as NUMA Node 0 Enabled
 ACPI CST C2 Latency set to 18 microseconds
 Memory PStates set to Disabled
 Thermal Configuration set to Maximum Cooling
 Workload Profile set to Manual
 Power Regulator set to OS Control Mode

The system ROM used for this result contains microcode version 0xa10110e for the AMD EPYC 9nn4X family of processors. The reference code/AGESA version used in this ROM is version Gen 1.0.1.1-L6

```
Sysinfo program /home/cpu2017/bin/sysinfo
Revision 622 of 2021-04-09 982a61ec0915b55891ef0e16acafc64d
running on localhost.localdomain Thu Dec  8 12:07:13 2022
```

SUT (System Under Test) info as seen by some common utilities.
 For more information on this section, see
<https://www.spec.org/cpu2017/Docs/config.html#sysinfo>

From /proc/cpuinfo

```
model name : AMD EPYC 9554P 64-Core Processor
1 "physical id"s (chips)
64 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The following
excerpts from /proc/cpuinfo might not be reliable. Use with caution.)
cpu cores : 64
siblings  : 64
physical 0: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24
25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52
53 54 55 56 57 58 59 60 61 62 63
```

From lscpu from util-linux 2.37.4:

```
Architecture:          x86_64
CPU op-mode(s):        32-bit, 64-bit
Address sizes:         52 bits physical, 57 bits virtual
```

(Continued on next page)



SPEC CPU® 2017 Floating Point Speed Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL325 Gen11

(3.10 GHz, AMD EPYC 9554P)

SPECspeed® 2017_base =

SPECspeed® 2017_peak =

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Dec-2022

Hardware Availability: Dec-2022

Software Availability: Nov-2022

SPEC has determined that this result does not comply with the SPEC CPU 2017 run and reporting rules. Specifically, the test sponsor notified SPEC that the results were measured on an unsupported configuration.

Platform Notes (Continued)

```

Byte Order: Little Endian
CPU(s): 64
On-line CPU(s) list: 0-63
Vendor ID: AuthenticAMD
BIOS Vendor ID: Advanced Micro Devices, Inc.
Model name: AMD EPYC 9554P 64-Core Processor
BIOS Model name: AMD EPYC 9554P 64-Core Processor
CPU family: 25
Model: 7
Thread(s) per core: 1
Core(s) per socket: 64
Socket(s): 1
Stepping: 1
Frequency boost: enabled
CPU max MHz: 3762.9880
CPU min MHz: 1500.0000
BogoMIPS: 83
Flags: fpu vme de pse tsc msr pae mce cx8 apic sep mtrr
pge mca cmov pat pse36 clflush mmx fxsr sse sse2 ht syscall nx mmxext fxsr_opt
pdpelgb rdtscp lm constant_tsc rep_good nopl nonstop_tsc cpuid extd_apicid
aperfperf rapl pstate tsc_evt drand48 rdtscp rdpru rdpru_wbnoinvd amd_ppin arat npt
aperfperf rapl pstate tsc_evt drand48 rdtscp rdpru rdpru_wbnoinvd amd_ppin arat npt
popcnt aes xsave avx102 rdpru rdpru_wbnoinvd amd_ppin arat npt
misalignsse 3dnowprefetch osvw ibs skinit wdt tce topoext perfctr_core perfctr_nb
bpext perfctr_llc waitx opb cat_l3 cdp_l3 invpcid_single hw_pstate ssbd mba ibrs
ibpb stibp vmxcall vmsave bml avx2 smep bmi2 erms invpcid cqm rdt_a avx512f
avx512dq rdpru rdpru_wbnoinvd amd_ppin arat npt
avx512vlnvml avx512vbmi avx512vbmi2 vaes vpclmulqdq avx512_vnni avx512_bitalg avx512_vpoptdq la57
rdpru rdpru_wbnoinvd amd_ppin arat npt
Virtualization: AMD-V
2 MiB (64 instances)
L1i cache: 2 MiB (64 instances)
L2 cache: 64 MiB (64 instances)
L3 cache: 256 MiB (8 instances)
NUMA node(s): 8
NUMA node0 CPU(s): 0-7
NUMA node1 CPU(s): 32-39
NUMA node2 CPU(s): 16-23
NUMA node3 CPU(s): 48-55
NUMA node4 CPU(s): 24-31
NUMA node5 CPU(s): 56-63
NUMA node6 CPU(s): 8-15
NUMA node7 CPU(s): 40-47
Vulnerability Itlb multihit: Not affected
Vulnerability L1tf: Not affected
Vulnerability Mds: Not affected
Vulnerability Meltdown: Not affected
Vulnerability Spec store bypass: Mitigation; Speculative Store Bypass disabled via

```

(Continued on next page)



SPEC CPU®2017 Floating Point Speed Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL325 Gen11

(3.10 GHz, AMD EPYC 9554P)

SPECspeed®2017_base =

SPECspeed®2017_fp_peak =

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Dec-2022

Hardware Availability: Dec-2022

Software Availability: Nov-2022

SPEC has determined that this result does not comply with the SPEC CPU 2017 rules and reporting rules. Specifically, the test sponsor notified SPEC that the results were measured on an unsupported configuration.

Platform Notes (Continued)

proctl

Vulnerability Spectre v1: Mitigation: usercopy/swapgs barriers and __user

pointer sanitization

Vulnerability Spectre v2: Mitigation: Retpolines, BSB conditional, IBRS_FW,

STIBP disabled, RSB filling

Vulnerability Srbds: Not affected

Vulnerability Tsx async abort: Not affected

From lscpu --cache:

NAME	ONE-SIZE	ALL-SIZE	WAYS	TYPE	LEVEL	SETS	PHY-LINE	COHERENCY-SIZE
L1d	32K	2M	8	Data	1	64	1	64
L1i	32K	2M	1	Instruction	1	64	1	64
L2	1M	64M	1	Unified	2	2048	1	64
L3	32M	256M	1	Unified	3	32768	1	64

/proc/cpuinfo cache data
cache size : 1024 KB

From numactl --hardware

WARNING: a numactl 'node' might or might not correspond to a physical chip.

```

available: 8 nodes (0 cpus)
node 0 cpus: 0 1 2 3 4 5 6 7
node 0 size: 96519 MB
node 0 free: 96115 MB
node 1 cpus: 32 33 34 35 36 37 38 39
node 1 size: 96766 MB
node 1 free: 96330 MB
node 2 cpus: 16 17 18 19 20 21 22 23
node 2 size: 96766 MB
node 2 free: 96552 MB
node 3 cpus: 40 41 42 43 44 45 46 47
node 3 size: 96766 MB
node 3 free: 96529 MB
node 4 cpus: 24 25 26 27 28 29 30 31
node 4 size: 96766 MB
node 4 free: 96593 MB
node 5 cpus: 56 57 58 59 60 61 62 63
node 5 size: 96717 MB
node 5 free: 96490 MB
node 6 cpus: 8 9 10 11 12 13 14 15
node 6 size: 96766 MB
node 6 free: 96375 MB
node 7 cpus: 40 41 42 43 44 45 46 47
node 7 size: 96766 MB
node 7 free: 96555 MB
node distances:
node  0  1  2  3  4  5  6  7
0:  10  11  11  11  11  11  11  11
1:  11  10  11  11  11  11  11  11
2:  11  11  10  11  11  11  11  11
3:  11  11  11  10  11  11  11  11

```

(Continued on next page)



SPEC CPU®2017 Floating Point Speed Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL325 Gen11

(3.10 GHz, AMD EPYC 9554P)

SPECspeed®2017_base =

SPECspeed®2017_peak =

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Dec-2022

Hardware Availability: Dec-2022

Software Availability: Nov-2022

SPEC has determined that this result does not comply with the SPEC CPU 2017 run and reporting rules. Specifically, the test sponsor notified SPEC that the results were measured on an unsupported configuration.

Platform Notes (Continued)

```

4: 11 11 11 11 10 11 11 11
5: 11 11 11 11 11 10 11 11
6: 11 11 11 11 11 11 10 11
7: 11 11 11 11 11 11 11 10

```

From /proc/meminfo

MemTotal: 792369040 kB

HugePages_Total: 0

Hugepagesize: 2048 kB

/sbin/tuned-adm active

Current active profile: throughput-performance

/sys/devices/system/cpu/cpu*/cpu*/cpufreq/scaling_governor has performance

From /etc/*release* /etc/*version*

os-release:

NAME="Red Hat Enterprise Linux"

VERSION="9.0 (Plow)"

ID="rhel"

ID_LIKE="fedora"

VERSION_ID="9.0"

PLATFORM_ID="platform:el9"

PRETTY_NAME="Red Hat Enterprise Linux 9.0 (Plow)"

ANSI_COLOR="0;31"

redhat-release: Red Hat Enterprise Linux release 9.0 (Plow)

system-release: Red Hat Enterprise Linux release 9.0 (Plow)

system-release-cpe: cpe:/o:redhat:enterprise_linux:9::baseos

uname -a:

Linux localhost.localdomain 5.14.0-70.13.1.el9_0.x86_64 #1 SMP PREEMPT Thu Apr 14

12:42:28 EDT 2022 x86_64 x86_64 x86_64 GNU/Linux

Kernel self-reported vulnerability status:

CVE-2018-12207 (iTLB Multihit):	Not affected
CVE-2018-3620 (L1 Terminal Fault):	Not affected
Microarchitectural Data Sampling:	Not affected
CVE-2017-5754 (Meltdown):	Not affected
CVE-2018-3639 (Speculative Store Bypass):	Mitigation: Speculative Store Bypass disabled via prctl
CVE-2017-5753 (Spectre variant 1):	Mitigation: usercopy/swappgs barriers and __user pointer sanitization
CVE-2017-5715 (Spectre variant 2):	Mitigation: Retpolines, IBPB: conditional, IBRS_FW, STIBP: disabled, RSB filling
CVE-2020-0543 (Special Register Buffer Data Sampling):	Not affected
CVE-2019-11135 (TSX Asynchronous Abort):	Not affected

(Continued on next page)



SPEC CPU®2017 Floating Point Speed Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL325 Gen11

(3.10 GHz, AMD EPYC 9554P)

SPECspeed®2017_base =

SPECspeed®2017_fp_peak =

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Dec-2022

Hardware Availability: Dec-2022

Software Availability: Nov-2022

SPEC has determined that this result does not comply with the SPEC CPU 2017 run and reporting rules. Specifically, the test sponsor notified SPEC that the results were measured on an unsupported configuration.

Platform Notes (Continued)

run-level 3 Dec 8 12:06

SPEC is set to: /home/cpu2017

Filesystem	Type	Size	Used	Avail	Use%	Mounted on
/dev/mapper/rhel-home	xfs	372G	17G	356G	5%	/home

From /sys/devices/virtual/dmi/id

Vendor: HPE
 Product: ProLiant DL325 Gen11
 Product Family: ProLiant
 Serial: DL325GEN11-002

Additional information from dmi code 3.3 follows. WARNING: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

Memory:

12x Hynix HMC94MEBRA121N 64 GB 2 rank 4800

BIOS:

BIOS Vendor: HPE
 BIOS Version: 1.12
 BIOS Date: 11/24/2022
 BIOS Revision: 1.12
 Firmware Revision: 1.12

(End of data from sysinfo program)

Compiler Version Notes

=====
619.lbm_s(base, peak) 638.imagick_s(base, peak) 644.nab_s(base, peak)
=====

AMD clang version 14.0.6 (CLANG: AOCC_4.0.0-Build#389 2022_10_07) (based on LLVM Mirror.Version.14.0.6)

Target: x86_64-unknown-linux-gnu

Thread model: posix

InstalledDir: /opt/AMD/aocc/aocc-compiler-rel-4.0-3206-389/bin
=====

=====
C++, C, Fortran | 607.cactuBSSN_s(base, peak)
=====

AMD clang version 14.0.6 (CLANG: AOCC_4.0.0-Build#389 2022_10_07) (based on LLVM Mirror.Version.14.0.6)

Target: x86_64-unknown-linux-gnu

Thread model: posix

InstalledDir: /opt/AMD/aocc/aocc-compiler-rel-4.0-3206-389/bin

AMD clang version 14.0.6 (CLANG: AOCC_4.0.0-Build#389 2022_10_07) (based on LLVM Mirror.Version.14.0.6)

Target: x86_64-unknown-linux-gnu

Thread model: posix

InstalledDir: /opt/AMD/aocc/aocc-compiler-rel-4.0-3206-389/bin
=====

(Continued on next page)



SPEC CPU®2017 Floating Point Speed Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL325 Gen11

(3.10 GHz, AMD EPYC 9554P)

SPECspeed®2017_fp_base =

SPECspeed®2017_fp_peak =

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Dec-2022

Hardware Availability: Dec-2022

Software Availability: Nov-2022

SPEC has determined that this result does not comply with the SPEC CPU 2017 run and reporting rules. Specifically, the test sponsor notified SPEC that the results were measured on an unsupported configuration.

Compiler Version Notes (Continued)

AMD clang version 14.0.6 (CLANG: AOCCL4.0.0-Build#389 2022_10_07) (based on LLVM Mirror.Version.14.0.6)
Target: x86_64-unknown-linux-gnu
Thread model: posix
InstalledDir: /opt/AMD/aocc/aocc-compiler-rel-4.0-3206-389/bin

Fortran | 603.bwaves_s(base, peak) 64.fotoniks_s(base, peak) 654.roms_s(base, peak)

AMD clang version 14.0.6 (CLANG: AOCCL4.0.0-Build#389 2022_10_07) (based on LLVM Mirror.Version.14.0.6)
Target: x86_64-unknown-linux-gnu
Thread model: posix
InstalledDir: /opt/AMD/aocc/aocc-compiler-rel-4.0-3206-389/bin

Fortran, C | 621.wrf_s(base, peak) cam4_s(base, peak) 628.pop2_s(base, peak)

AMD clang version 14.0.6 (CLANG: AOCCL4.0.0-Build#389 2022_10_07) (based on LLVM Mirror.Version.14.0.6)
Target: x86_64-unknown-linux-gnu
Thread model: posix
InstalledDir: /opt/AMD/aocc/aocc-compiler-rel-4.0-3206-389/bin

AMD clang version 14.0.6 (CLANG: AOCCL4.0.0-Build#389 2022_10_07) (based on LLVM Mirror.Version.14.0.6)
Target: x86_64-unknown-linux-gnu
Thread model: posix
InstalledDir: /opt/AMD/aocc/aocc-compiler-rel-4.0-3206-389/bin

Base Compiler Invocation

Clang compiler:

clang

Fortran benchmarks:

flang

Benchmarks using both Fortran and C:

flang clang

Benchmarks using Fortran, C, and C++:

clang++ clang flang



SPEC CPU® 2017 Floating Point Speed Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL325 Gen11

(3.10 GHz, AMD EPYC 9554P)

SPECspeed® 2017 / fp base =

SPECspeed® 2017 / fp peak =

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Dec-2022

Hardware Availability: Dec-2022

Software Availability: Nov-2022

SPEC has determined that this result does not comply with the SPEC CPU 2017 run and reporting rules. Specifically, the test sponsor notified SPEC that the results were measured on an unsupported configuration.

Base Portability Flags

```

603.bwaves_s: -DSPEC_LP64
607.cactuBSSN_s: -DSPEC_LP64
619.lbm_s: -DSPEC_LP64
621.wrf_s: -DSPEC_CASE_FLAG -Mbyteswapio -DSPEC_LP64
627.cam4_s: -DSPEC_CASE_FLAG -DSPEC_LP64
628.pop2_s: -DSPEC_CASE_FLAG -Mbyteswapio -DSPEC_LP64
638.imagick_s: -DSPEC_LP64
644.nab_s: -DSPEC_LP64
649.fotonik3d_s: -DSPEC_LP64
654.roms_s: -DSPEC_LP64

```

Base Optimization Flags

C benchmarks:

```

-m64 -Wl,-mllvm -Wl,-align-all-nofallthru-blocks=6
-Wl,-mllvm -Wl,-reduce-array-computations=3 -O3 -march=znver4
-fveclib=AMDLIBM -ffast-math -fopenmp -flto -fstruct-layout=7
-mllvm -unroll-loops -mllvm -inline-threshold=1000
-fremap-arrays -fskip-mining -mllvm -reduce-array-computations=3
-DSPEC_OPENMP -zopt -fopenmp=libomp -lomp -lamdlibm -lamdalloc
-lflang

```

Fortran benchmarks:

```

-m64 -Wl,-mllvm -Wl,-align-all-nofallthru-blocks=6
-Wl,-mllvm -Wl,-reduce-array-computations=3
-Wl,-mllvm -Wl,-enable-X86-prefetching -DSPEC_OPENMP -O3 -march=znver4
-fveclib=AMDLIBM -ffast-math -fopenmp -flto -Mrecursive
-funroll-loops -mllvm -lsr-in-nested-loop
-mllvm -reduce-array-computations=3 -zopt -fopenmp=libomp -lomp
-lamdlibm -lamdalloc -lflang

```

Benchmarks using both Fortran and C:

```

-m64 -Wl,-mllvm -Wl,-align-all-nofallthru-blocks=6
-Wl,-mllvm -Wl,-reduce-array-computations=3
-Wl,-mllvm -Wl,-enable-X86-prefetching -O3 -march=znver4
-fveclib=AMDLIBM -ffast-math -fopenmp -flto -fstruct-layout=7
-mllvm -unroll-threshold=50 -mllvm -inline-threshold=1000

```

(Continued on next page)



SPEC CPU®2017 Floating Point Speed Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL325 Gen11

(3.10 GHz, AMD EPYC 9554P)

SPECspeed®2017_base =

SPECspeed®2017_peak =

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Dec-2022

Hardware Availability: Dec-2022

Software Availability: Nov-2022

SPEC has determined that this result does not comply with the SPEC CPU 2017 rules and reporting rules. Specifically, the test sponsor notified SPEC that the results were measured on an unsupported configuration.

Base Optimization Flags (Continued)

Benchmarks using both Fortran and C (continued):

`-fremap-arrays -fstrip-mining -mllvm -reduce-array-computations=3
-DSPEC_OPENMP -zopt -Mrecursive -funroll-loops
-mllvm -lsr-in-nested-loop -fopenmp=libomp -lomp -lamdlibm -lamdalloc
-lflang`

Benchmarks using Fortran, C, and C++:

`-m64 -Wl,-mllvm -Wl,-align-all-nofallthrough -mllvm -blocks=6
-Wl,-mllvm -Wl,-reduce-array-computations=3
-Wl,-mllvm -Wl,-x86-use-vector-grouper=false -O3 -march=znver4
-fveclib=AMDLIBM -ffast-math -fopenmp=flto -fstruct-layout=7
-mllvm -unroll-threshold=500000 -mllvm -inline-threshold=1000
-fremap-arrays -fstrip-mining -mllvm -reduce-array-computations=3
-DSPEC_OPENMP -zopt -mllvm -unroll-threshold=100 -finline-aggressive
-mllvm -loop-unswitch-threshold=200000 -Mrecursive -funroll-loops
-mllvm -lsr-in-nested-loop -fopenmp=libomp -lomp -lamdlibm -lamdalloc
-lflang`

Base Other Flags

C benchmarks:

`-Wno-return-type -Wno-unused-command-line-argument
-Wno-unused-command-line-argument`

Benchmarks using both Fortran and C:

`-Wno-return-type -Wno-unused-command-line-argument`

Benchmarks using Fortran, C, and C++:

`-Wno-return-type -Wno-unused-command-line-argument`



SPEC CPU®2017 Floating Point Speed Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL325 Gen11

(3.10 GHz, AMD EPYC 9554P)

SPECspeed®2017_base =

SPECspeed®2017_fp_peak =

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Dec-2022

Hardware Availability: Dec-2022

Software Availability: Nov-2022

SPEC has determined that this result does not comply with the SPEC CPU 2017 rules and reporting rules. Specifically, the test sponsor notified SPEC that the results were measured on an unsupported configuration.

Peak Compiler Invocation

C benchmarks:

clang

Fortran benchmarks:

flang

Benchmarks using both Fortran and C:

flang clang

Benchmarks using Fortran, C, and C++:

clang++ clang flang

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

619.lbm_s: basepeak = yes

638.imagick_s: basepeak = yes

644.nab_s: basepeak = yes

Fortran benchmarks:

603.bwaves_s: basepeak = yes

649.fotonik3d_s: -m64 -Wl,-mllvm -Wl,-align-all-nofallthru-blocks=6

-Wl,-mllvm -Wl,-reduce-array-computations=3

-Wl,-mllvm -Wl,-enable-X86-prefetching -DSPEC_OPENMP

-Ofast -march=znver4 -fveclib=AMDLIBM -ffast-math

-fopenmp -fltto -Mrecursive

(Continued on next page)



SPEC CPU® 2017 Floating Point Speed Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL325 Gen11

(3.10 GHz, AMD EPYC 9554P)

SPECspeed® 2017 / fp base =

SPECspeed® 2017 / fp peak =

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Dec-2022

Hardware Availability: Dec-2022

Software Availability: Nov-2022

SPEC has determined that this result does not comply with the SPEC CPU 2017 run and reporting rules. Specifically, the test sponsor notified SPEC that the results were measured on an unsupported configuration.

Peak Optimization Flags (Continued)

649.fotonik3d_s (continued):

```
-mllvm -reduce-array-computations=3 -zopt -fopenmp -libomp
-lomp -lamdlibm -lamdalloc -lflang
```

654.roms_s: -m64 -Wl,-mllvm -Wl,-align-all-nofallthru-blocks=6

```
-Wl,-mllvm -Wl,-reduce-array-computations=3
-Wl,-mllvm -Wl,-enable-X86-prefetching -DSPEC_OPENMP
-Ofast -march=znver4 -fveclib=AMDLIBM -ffast-math
-fopenmp -Mrecursive -mllvm -reduce-array-computations=3
-fvector-transform -fscalar-transform -fopenmp=libomp
-lomp -lamdlibm -lamdalloc -lflang
```

Benchmarks using both Fortran and C:

621.wrf_s: -m64 -Wl,-mllvm -Wl,-align-all-nofallthru-blocks=6

```
-Wl,-mllvm -Wl,-reduce-array-computations=3
-Wl,-mllvm -Wl,-enable-X86-prefetching -Ofast
-march=znver4 -fveclib=AMDLIBM -ffast-math -fopenmp
-flto -fstruct-layout=9 -mllvm -unroll-threshold=50
-fremap-array -fstrip-mining
-mllvm -inline-threshold=1000
-mllvm -reduce-array-computations=3 -DSPEC_OPENMP -zopt
-O3 -Mrecursive -funroll-loops -mllvm -lsr-in-nested-loop
-fopenmp=libomp -lomp -lamdlibm -lamdalloc -lflang
```

peak = yes

626.top2_s: -m64 -Wl,-mllvm -Wl,-align-all-nofallthru-blocks=6

```
-Wl,-mllvm -Wl,-reduce-array-computations=3
-Wl,-mllvm -Wl,-enable-X86-prefetching -Ofast
-march=znver4 -fveclib=AMDLIBM -ffast-math -fopenmp
-flto -fstruct-layout=9 -mllvm -unroll-threshold=50
-fremap-arrays -fstrip-mining
-mllvm -inline-threshold=1000
-mllvm -reduce-array-computations=3 -DSPEC_OPENMP -zopt
-Mrecursive -fvector-transform -fscalar-transform
-fopenmp=libomp -lomp -lamdlibm -lamdalloc -lflang
```

(Continued on next page)



SPEC CPU®2017 Floating Point Speed Result

Copyright 2017-2023 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

ProLiant DL325 Gen11

(3.10 GHz, AMD EPYC 9554P)

SPECspeed®2017_base =

SPECspeed®2017_fp_peak =

CPU2017 License: 3

Test Sponsor: HPE

Tested by: HPE

Test Date: Dec-2022

Hardware Availability: Dec-2022

Software Availability: Nov-2022

SPEC has determined that this result does not comply with the SPEC CPU 2017 rules and reporting rules. Specifically, the test sponsor notified SPEC that the results were measured on an unsupported configuration.

Peak Optimization Flags (Continued)

Benchmarks using Fortran, C, and C++:

607.cactuBSSN_s: basepeak = yes

Peak Other Flags

C benchmarks:

-Wno-return-type -Wno-unused-command-line-argument

Fortran benchmarks:

-Wno-unused-command-line-argument

Benchmarks using both Fortran and C:

-Wno-return-type -Wno-unused-command-line-argument

Benchmarks using Fortran, C, and C++:

-Wno-return-type -Wno-unused-command-line-argument

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2017/flags/HPE-Platform-Flags-AMD-Genoa-rev2.1.html>

<http://www.spec.org/cpu2017/flags/aocc400-flags.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2017/flags/HPE-Platform-Flags-AMD-Genoa-rev2.1.xml>

<http://www.spec.org/cpu2017/flags/aocc400-flags.xml>

SPEC CPU and SPECspeed are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEC CPU®2017 v1.1.8 on 2022-12-08 01:37:13-0500.

Report generated on 2023-09-12 17:54:22 by CPU2017 PDF formatter v6716.

Originally published on 2023-02-01.