



SPEChpc™ 2021 Small Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

Intel


Endeavour: Intel Server D50DNP2MFALACB (Intel Xeon Platinum 8480+)

SPEChpc 2021_sml_base = 48.8

SPEChpc 2021_sml_peak = 54.7

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Jul-2023
Hardware Availability: Jan-2023
Software Availability: Apr-2023



Results Table

Benchmark	Base								Peak									
	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
605.lbm_s	OMP	1024	14	29.1	53.3	23.1	67.0	23.5	66.0	OMP	512	28	16.5	93.7	18.9	82.2	19.0	81.5
613.soma_s	OMP	1024	14	62.0	25.8	64.4	24.8	63.9	25.0	OMP	512	28	48.1	33.3	51.8	30.9	52.3	30.6
618.tealeaf_s	OMP	1024	14	23.3	87.8	27.0	76.1	27.4	74.8	OMP	512	28	19.9	103	23.2	88.2	24.1	84.9
619.civleaf_s	OMP	1024	14	35.3	46.7	40.2	41.0	39.6	41.6	OMP	512	28	29.3	56.3	32.5	50.7	32.7	50.5
621.miniswp_s	OMP	1024	14	33.5	32.8	38.1	28.8	38.2	28.8	OMP	512	28	30.3	36.3	32.6	33.8	32.8	33.5
628.pot3d_s	OMP	1024	14	15.5	108	20.1	83.2	20.2	83.0	OMP	1024	14	14.6	115	19.4	86.5	19.5	86.0
632.sph_exa_s	OMP	1024	14	51.4	44.7	56.1	41.0	56.3	40.9	OMP	512	28	50.7	45.4	53.6	42.9	53.8	42.8
634.hpgmgfv_s	OMP	1024	14	31.7	30.7	36.2	27.0	36.2	26.9	OMP	1024	14	31.7	30.7	36.2	27.0	36.2	26.9
635.weather_s	OMP	1024	14	18.2	143	22.9	113	22.9	114	OMP	1024	14	18.2	143	22.9	113	22.9	114

SPEChpc 2021_sml_base = 48.8

SPEChpc 2021_sml_peak = 54.7

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.



SPEChpc™ 2021 Small Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

Intel

Endeavour: Intel Server D50DNP2MFALACB (Intel Xeon Platinum 8480+)

SPEChpc 2021_sml_base = 48.8

SPEChpc 2021_sml_peak = 54.7

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Jul-2023
Hardware Availability: Jan-2023
Software Availability: Apr-2023

Hardware Summary

Type of System: Homogenous Cluster
Compute Node: Intel Server D50DNP2MFALACB (Xeon 8480+)
Interconnect: Mellanox HDR
Compute Nodes Used: 128
Total Chips: 256
Total Cores: 14336
Total Threads: 28672
Total Memory: 64 TB
Max. Peak Threads: 28

Software Summary

Compiler: Intel oneAPI Compiler 2023.1.0
MPI Library: Intel MPI Library 2021.9 for Linux OS
Other MPI Info: None
Other Software: None
Base Parallel Model: OMP
Base Ranks Run: 1024
Base Threads Run: 14
Peak Parallel Models: OMP
Minimum Peak Ranks: 512
Maximum Peak Ranks: 1024
Max. Peak Threads: 28
Min. Peak Threads: 14

Node Description: Intel Server D50DNP2MFALACB (Xeon 8480+)

Hardware

Number of nodes: 128
Uses of the node: Compute
Vendor: Intel
Model: Intel Server D50DNP2MFALACB (Xeon 8480+)
CPU Name: Intel Xeon Platinum 8480+
CPU(s) orderable: 1, 2 chips
Chips enabled: 2
Cores enabled: 112
Cores per chip: 56
Threads per core: 2
CPU Characteristics: Turbo Boost Technology up to 3.8 GHz
CPU MHz: 2000
Primary Cache: 32 KB I + 48 KB D on chip per core
Secondary Cache: 2 MB I+D on chip per core
L3 Cache: 105 MB I+D on chip per chip
Other Cache: None
Memory: 512 GB (16 x 32 GB 2Rx8 PC5-4800B)
Disk Subsystem: 1 x 1 TB NVMe U.2 2.5" SSD
Other Hardware: None
Accel Count: None
Accel Model: None
Accel Vendor: None
Accel Type: None
Accel Connection: None
Accel ECC enabled: None
Accel Description: None
Adapter: Mellanox ConnectX-6 HDR
Number of Adapters: 1
Slot Type: PCI-Express 4.0 x16
Data Rate: 200Gbit/s
Ports Used: 1
Interconnect Type: Mellanox HDR

Software

Accelerator Driver: None
Adapter: Mellanox ConnectX-6 HDR
Adapter Driver: 5.9-0.5.5
Adapter Firmware: 20.36.1010
Operating System: Rocky Linux 8.7 (Green Obsidian)
4.18.0-372.32.1.el8_6.crt3.x86_64
Local File System: NFS
Shared File System: PANASAS FS
System State: Multi-user
Other Software: None



SPEChpc™ 2021 Small Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

Intel

Endeavour: Intel Server D50DNP2MFALACB (Intel Xeon Platinum 8480+)

SPEChpc 2021_sml_base = 48.8

SPEChpc 2021_sml_peak = 54.7

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Jul-2023
Hardware Availability: Jan-2023
Software Availability: Apr-2023

Interconnect Description: Mellanox HDR

Hardware

Software

Vendor: Mellanox
Model: Mellanox HDR
Switch Model: Mellanox MQM8790-HS2F Quantum HDR InfiniBand Switch
Number of Switches: 18
Number of Ports: 40
Data Rate: 200 Gbit/s
Firmware: 20.36.1010
Topology: Fat-tree
Primary Use: MPI Traffic

: --

Submit Notes

The config file option 'submit' was used.

General Notes

The PANASAS filesystem as described on this result page was formerly generally available. At the time of this publication, it may not be shipping, and/or may not be supported, and/or may fail to meet other tests of General Availability described in the SPEC HPG Policy document, <http://www.spec.org/hpg/policy.html>

Compiler Version Notes

=====
CXXC 632.sph_exa_s(base, peak)

Intel(R) oneAPI DPC++/C++ Compiler 2023.1.0 (2023.1.0.20230320)
Target: x86_64-unknown-linux-gnu
Thread model: posix
InstalledDir:
/global/panfs01/admin/opt/intel/oneAPI/2023.1.0.46401/compiler/2023.1.0/linux/bin-llvm
Configuration file:
/global/panfs01/admin/opt/intel/oneAPI/2023.1.0.46401/compiler/2023.1.0/linux/bin-llvm/./bin/icpx.cfg

=====
CC 605.lbm_s(base, peak) 613.soma_s(base, peak) 618.tealeaf_s(base, peak)
621.miniswp_s(base) 634.hpgmgfv_s(base, peak)

Intel(R) oneAPI DPC++/C++ Compiler 2023.1.0 (2023.1.0.20230320)
Target: x86_64-unknown-linux-gnu

(Continued on next page)



SPEChpc™ 2021 Small Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

Intel

Endeavour: Intel Server D50DNP2MFALACB (Intel Xeon Platinum 8480+)

SPEChpc 2021_sml_base = 48.8

SPEChpc 2021_sml_peak = 54.7

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Jul-2023
Hardware Availability: Jan-2023
Software Availability: Apr-2023

Compiler Version Notes (Continued)

Thread model: posix
InstalledDir:
 /global/panfs01/admin/opt/intel/oneAPI/2023.1.0.46401/compiler/2023.1.0/linux/bin-llvm
Configuration file:
 /global/panfs01/admin/opt/intel/oneAPI/2023.1.0.46401/compiler/2023.1.0/linux/bin-llvm/./bin/icx.cfg

=====
CC 621.miniswp_s(peak)
=====

icc: remark #10441: The Intel(R) C++ Compiler Classic (ICC) is deprecated and will be removed from product release in the second half of 2023. The Intel(R) oneAPI DPC++/C++ Compiler (ICX) is the recommended compiler moving forward. Please transition to use this compiler. Use '-diag-disable=10441' to disable this message.

icc: command line warning #10148: option '-Wno-incompatible-function-pointer-types' not supported

icc (ICC) 2021.9.0 20230302
Copyright (C) 1985-2023 Intel Corporation. All rights reserved.

=====
FC 619.clvleaf_s(peak) 628.pot3d_s(peak)
=====

ifort (IFORT) 2021.9.0 20230302
Copyright (C) 1985-2023 Intel Corporation. All rights reserved.

=====
FC 619.clvleaf_s(base) 628.pot3d_s(base) 635.weather_s(base, peak)
=====

ifx (IFX) 2023.1.0 20230320
Copyright (C) 1985-2023 Intel Corporation. All rights reserved.

Base Compiler Invocation

C benchmarks:
mpiicc -cc=icx

C++ benchmarks:
mpicpc -cxx=icpx

Fortran benchmarks:
mpiifort -fc=ifx



SPEChpc™ 2021 Small Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

Intel

Endeavour: Intel Server D50DNP2MFALACB (Intel Xeon Platinum 8480+)

SPEChpc 2021_sml_base = 48.8

SPEChpc 2021_sml_peak = 54.7

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Jul-2023
Hardware Availability: Jan-2023
Software Availability: Apr-2023

Base Portability Flags

```
605.lbm_s: -lstdc++ -std=c++14
613.soma_s: -lstdc++ -std=c++14
618.tealeaf_s: -lstdc++ -std=c++14
621.miniswp_s: -lstdc++ -std=c++14
634.hpgmgfv_s: -lstdc++ -std=c++14
```

Base Optimization Flags

C benchmarks:

```
-O3 -Ofast -xCORE-AVX512 -mprefer-vector-width=512
-qopt-multiple-gather-scatter-by-shuffles -fiopenmp -ffast-math -flto
-funroll-loops
```

C++ benchmarks:

```
-O3 -Ofast -xCORE-AVX512 -mprefer-vector-width=512
-qopt-multiple-gather-scatter-by-shuffles -fiopenmp -ffast-math -flto
-funroll-loops
```

Fortran benchmarks:

```
-O3 -Ofast -xCORE-AVX512 -mprefer-vector-width=512
-qopt-multiple-gather-scatter-by-shuffles -fiopenmp -ffast-math -flto
-funroll-loops -nostandard-realloc-lhs -align array64byte
```

Base Other Flags

C benchmarks:

```
-Ispecmpitime -Wno-incompatible-function-pointer-types
```

C++ benchmarks:

```
-Ispecmpitime
```

Fortran benchmarks:

```
619.clvleaf_s: -Ispecmpitime
```

Peak Compiler Invocation

C benchmarks (except as noted below):

```
mpicc -cc=icx
```

(Continued on next page)



SPEChpc™ 2021 Small Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

Intel

Endeavour: Intel Server D50DNP2MFALACB (Intel Xeon Platinum 8480+)

SPEChpc 2021_sml_base = 48.8

SPEChpc 2021_sml_peak = 54.7

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Jul-2023
Hardware Availability: Jan-2023
Software Availability: Apr-2023

Peak Compiler Invocation (Continued)

621.miniswp_s: mpiicc

C++ benchmarks:

mpiicpc -cxx=icpx

Fortran benchmarks (except as noted below):

mpiifort

635.weather_s: mpiifort -fc=ifx

Peak Portability Flags

605.lbm_s: -lstdc++ -std=c++14
613.soma_s: -lstdc++ -std=c++14
618.tealeaf_s: -lstdc++ -std=c++14
621.miniswp_s: -lstdc++ -std=c++14
634.hpgmgfv_s: -lstdc++ -std=c++14

Peak Optimization Flags

C benchmarks:

605.lbm_s: -O3 -Ofast -xCORE-AVX512 -mprefer-vector-width=512
-qopt-multiple-gather-scatter-by-shuffles -fiopenmp
-ffast-math -flto -funroll-loops

613.soma_s: -O3 -Ofast -xCORE-AVX512 -mprefer-vector-width=512
-qopt-multiple-gather-scatter-by-shuffles -fiopenmp
-ffast-math -flto -funroll-loops
-qopt-streaming-stores=always

618.tealeaf_s: Same as 605.lbm_s

621.miniswp_s: -O3 -Ofast -xCORE-AVX512 -ansi-alias -qopenmp -ipo
-qopt-zmm-usage=high
-qopt-multiple-gather-scatter-by-shuffles

634.hpgmgfv_s: basepeak = yes

C++ benchmarks:

-O3 -Ofast -xCORE-AVX512 -ansi-alias -qopenmp -ipo
-qopt-zmm-usage=high -qopt-multiple-gather-scatter-by-shuffles

(Continued on next page)



SPEChpc™ 2021 Small Result

Copyright 2021-2023 Standard Performance Evaluation Corporation

Intel

Endeavour: Intel Server D50DNP2MFALACB (Intel Xeon Platinum 8480+)

SPEChpc 2021_sml_base = 48.8

SPEChpc 2021_sml_peak = 54.7

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Jul-2023
Hardware Availability: Jan-2023
Software Availability: Apr-2023

Peak Optimization Flags (Continued)

Fortran benchmarks:

```
619.clvleaf_s: -O3 -Ofast -xCORE-AVX512 -ansi-alias -qopenmp -ipo  
-qopt-zmm-usage=high  
-qopt-multiple-gather-scatter-by-shuffles  
-nostandard-realloc-lhs -align array64byte
```

628.pot3d_s: Same as 619.clvleaf_s

635.weather_s: basepeak = yes

Peak Other Flags

C benchmarks:

```
-Ispecmpitime -Wno-incompatible-function-pointer-types
```

C++ benchmarks:

```
-Ispecmpitime
```

Fortran benchmarks:

```
619.clvleaf_s: -Ispecmpitime
```

The flags file that was used to format this result can be browsed at

http://www.spec.org/hpc2021/flags/Intel_compiler_flags.2023-08-16.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/hpc2021/flags/Intel_compiler_flags.2023-08-16.xml

SPEChpc is a trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEChpc2021 v1.1.7 on 2023-07-11 21:07:37-0400.
Report generated on 2023-08-16 15:02:26 by hpc2021 PDF formatter v1.0.3.
Originally published on 2023-08-16.